ISO/IEC 14776-326:2015-09 (E)

Information technology - Small Computer System Interface (SCSI) - Part 326: Reduced Block Commands (RBC)

Contents

Page

FOREWORD 5
1 Scope 6
2 Normative references 6
3 Terms, definitions, abbreviations, keywords, and conventions 7
3.1 Terms and definitions 7
3.2 Abbreviations 8
3.3 Keywords 8
3.4 Conventions 9
3.4.1 Non-numeric values 9
3.4.2 Numeric values 10
4 RBC device model 10
4.1 General 10
4.2 Removable medium device 10
4.3 Command usage 11
4.3.1 General 11
4.3.2 Using the INQUIRY command 11
4.3.3 Using the REQUEST SENSE command 11
4.3.4 FORMAT UNIT command progress determination 11
4.4 Using the PREVENT ALLOW MEDIUM REMOVAL command 12
4.4.1 General 12
4.4.2 START STOP UNIT command state restrictions 12
4.5 Logical Blocks 12
4.6 Reservations 13
5 Reduced Block Commands 14
5.1 General 14
5.2 FORMAT UNIT command 16
5.3 READ(10) Command 17
5.4 READ CAPACITY command 17
5.5 START STOP UNIT command 18
5.5.1 General 18
5.5.2 Power conditions 19
5.5.3 Enable/Disable bits 20
5.6 SYNCHRONIZE CACHE command 21
5.7 VERIFY command 21
5.8 WRITE(10) command 22
5.9 Mode parameters 23
5.9.1 General 23
5.9.2 Mode parameter list 23
5.9.3 Mode Parameter header 23
5.9.4 RBC Device Parameter's page 23

6 SPC-2 implementation requirements for RBC devices 25
6.1 General 25
6.2 INQUIRY command 25
6.2.1 Standard INQUIRY data 25
6.2.2 INQUIRY vital product data pages 26
6.3 MODE SELECT(6) command 27
6.4 MODE SENSE(6) command 27
6.5 PREVENT ALLOW MEDIUM REMOVAL 28
6.6 REQUEST SENSE command 28
6.7 TEST UNIT READY command 28
6.8 WRITE BUFFER Command 29
6.8.1 General 29
6.8.2 Download microcode and save mode (101b) 30
6.8.3 Download microcode with offsets and save mode (111b) 30
7 Asynchronous event notification for RBC devices 30
7.1 General 30
7.2 Unit attention 31
7.2.1 General 31
7.2.2 Power condition change notification 31
7.3 Deferred errors 31
7.4 Information exception condition notification 31
7.5 Event status notification 31
7.5.1 General 31
7.5.2 Event Status sense information 32
7.5.3 Power Management CLASS event INFORMATION field 32
7.5.4 MEDIA CLASS EVENT INFORMATION field 33
7.5.5 DEVICE BUSY CLASS EVENT INFORMATION field 34
7.5.6 Event status retention 35
7.5.7 Removable medium device initial response 35
Annex A (normative) RBC device implementation requirements for SBP-2 36
A.1 SBP-2 terms and definitions 36
A.1.1 Terms and definitions 36
A.1.2 Abbreviations 38
A.2 SBP-2 storage model 38
A.2.1 General 38
A.2.2 Model configuration 38
A.2.3 Reconnect/Power reset support 40
A.3 Configuration ROM support 40
A.3.1 General 40
A.3.2 Unit Directory – Command_Set_Spec_ID 40
A.3.3 Unit Directory – Command_Set 41
A.3.4 Unit Directory – Logical_Unit_Number 41
A.4 Security support 41
A.5 Status block support 41
A.6 Unsolicited Status support 42
A.6.1 General 42
A.6.2 Unit attention condition 42
A.6.3 Event Status retention 42

Figure A.1 – Mass storage interface block diagram 39
Figure A.2 – Status block for RBC 42

Table 1 – RBC direct access commands that are allowed in the presence of various reservations 14
Table 2 – Reduced Block Command set 15
Table 3 – FORMAT UNIT command 16
Table 4 – READ (10) Command Descriptor Block 17
Table 5 – READ CAPACITY Command Descriptor Block 18
Table 6 – READ CAPACITY data 18
Table 7 – START STOP UNIT Command Descriptor Block 19
Table 8 – POWER CONDITIONS 19
Table 9 – START STOP control bit definitions 21
Table 10 – SYNCHRONIZE CACHE Command Descriptor Block 21
Table 11 – VERIFY Command Descriptor Block 22
Table 12 – WRITE(10) Command Descriptor Block 22
Table 13 – Mode parameter list 23
Table 14 – RBC Device Parameters page format 24
Table 15 – Required SPC-2 commands 25
Table 16 – Standard Inquiry data format 26
Table 17 – MODE SELECT(6) Command Descriptor Block 27
Table 18 – MODE SENSE(6) Command Descriptor Block 28
Table 19 – FAILURE PREDICTION ASCQ XY definitions 29
Table 20 – WRITE BUFFER Command Descriptor Block 29
Table 21 – Asynchronous Event conditions 30
Table 22 – Power condition sense code and qualifier values 31
Table 23 – Event status ASCQ values 32
Table 24 – Event Status INFORMATION field format 32
Table 25 – POWER MANAGEMENT CLASS EVENT INFORMATION field format 32
Table 26 – POWER MANAGEMENT CLASS EVENT EVENT field 33
Table 27 – POWER MANAGEMENT CLASS EVENT STATUS field 33
Table 28 – MEDIA CLASS EVENT INFORMATION field format 33
Table 29 – MEDIA CLASS EVENT EVENT field 34
Table 30 – DEVICE BUSY CLASS EVENT information field format 34
Table 31 – DEVICE BUSY CLASS EVENT EVENT field 34
Table 32 – DEVICE BUSY CLASS STATUS field 35