

# ISO/IEC 14776-326:2015-09 (E)

## Information technology - Small Computer System Interface (SCSI) - Part 326: Reduced Block Commands (RBC)

---

Contents	Page
FOREWORD.....	5
1 Scope.....	6
2 Normative references .....	6
3 Terms, definitions, abbreviations, keywords, and conventions .....	7
3.1 Terms and definitions.....	7
3.2 Abbreviations.....	8
3.3 Keywords.....	8
3.4 Conventions.....	9
3.4.1 Non-numeric values.....	9
3.4.2 Numeric values.....	10
4 RBC device model.....	10
4.1 General.....	10
4.2 Removable medium device .....	10
4.3 Command usage.....	11
4.3.1 General .....	11
4.3.2 Using the INQUIRY command.....	11
4.3.3 Using the REQUEST SENSE command.....	11
4.3.4 FORMAT UNIT command progress determination.....	11
4.4 Using the PREVENT ALLOW MEDIUM REMOVAL command.....	12
4.4.1 General .....	12
4.4.2 START STOP UNIT command state restrictions.....	12
4.5 Logical Blocks.....	12
4.6 Reservations.....	13
5 Reduced Block Commands .....	14
5.1 General.....	14
5.2 FORMAT UNIT command.....	16
5.3 READ(10) Command.....	17
5.4 READ CAPACITY command .....	17
5.5 START STOP UNIT command .....	18
5.5.1 General .....	18
5.5.2 Power conditions .....	19
5.5.3 Enable/Disable bits.....	20
5.6 SYNCHRONIZE CACHE command .....	21
5.7 VERIFY command.....	21
5.8 WRITE(10) command.....	22
5.9 Mode parameters.....	23
5.9.1 General .....	23
5.9.2 Mode parameter list.....	23
5.9.3 Mode Parameter header .....	23
5.9.4 RBC Device Parameter's page.....	23

6	SPC-2 implementation requirements for RBC devices.....	25
6.1	General.....	25
6.2	INQUIRY command.....	25
6.2.1	Standard INQUIRY data.....	25
6.2.2	INQUIRY vital product data pages .....	26
6.3	MODE SELECT(6) command .....	27
6.4	MODE SENSE(6) command .....	27
6.5	PREVENT ALLOW MEDIUM REMOVAL.....	28
6.6	REQUEST SENSE command .....	28
6.7	TEST UNIT READY command .....	28
6.8	WRITE BUFFER Command.....	29
6.8.1	General .....	29
6.8.2	Download microcode and save mode (101b).....	30
6.8.3	Download microcode with offsets and save mode (111b) .....	30
7	Asynchronous event notification for RBC devices .....	30
7.1	General.....	30
7.2	Unit attention .....	31
7.2.1	General .....	31
7.2.2	Power condition change notification.....	31
7.3	Deferred errors .....	31
7.4	Information exception condition notification.....	31
7.5	Event status notification .....	31
7.5.1	General .....	31
7.5.2	Event Status sense information .....	32
7.5.3	Power Management CLASS event INFORMATION field .....	32
7.5.4	MEDIA CLASS EVENT INFORMATION field.....	33
7.5.5	DEVICE BUSY CLASS EVENT INFORMATION field .....	34
7.5.6	Event status retention.....	35
7.5.7	Removable medium device initial response.....	35
Annex A (normative)	RBC device implementation requirements for SBP-2 .....	36
A.1	SBP-2 terms and definitions.....	36
A.1.1	Terms and definitions .....	36
A.1.2	Abbreviations.....	38
A.2	SBP-2 storage model .....	38
A.2.1	General .....	38
A.2.2	Model configuration .....	38
A.2.3	Reconnect/Power reset support .....	40
A.3	Configuration ROM support.....	40
A.3.1	General .....	40
A.3.2	Unit Directory – Command_Set_Spec_ID.....	40
A.3.3	Unit Directory – Command_Set.....	41
A.3.4	Unit Directory – Logical_Unit_Number .....	41
A.4	Security support.....	41
A.5	Status block support .....	41
A.6	Unsolicited Status support .....	42
A.6.1	General .....	42
A.6.2	Unit attention condition .....	42
A.6.3	Event Status retention .....	42

Figure A.1 – Mass storage interface block diagram .....	39
Figure A.2 – Status block for RBC.....	42
Table 1 – RBC direct access commands that are allowed in the presence of various reservations .....	14
Table 2 – Reduced Block Command set.....	15
Table 3 – FORMAT UNIT command .....	16
Table 4 – READ (10) Command Descriptor Block.....	17
Table 5 – READ CAPACITY Command Descriptor Block.....	18
Table 6 – READ CAPACITY data .....	18
Table 7 – START STOP UNIT Command Descriptor Block.....	19
Table 8 – POWER CONDITIONS .....	19
Table 9 – START STOP control bit definitions.....	21
Table 10 – SYNCHRONIZE CACHE Command Descriptor Block.....	21
Table 11 – VERIFY Command Descriptor Block .....	22
Table 12 – WRITE(10) Command Descriptor Block .....	22
Table 13 – Mode parameter list.....	23
Table 14 – RBC Device Parameters page format .....	24
Table 15 – Required SPC-2 commands.....	25
Table 16 – Standard Inquiry data format .....	26
Table 17 – MODE SELECT(6) Command Descriptor Block.....	27
Table 18 – MODE SENSE(6) Command Descriptor Block .....	28
Table 19 – FAILURE PREDICTION ASCQ XY definitions.....	29
Table 20 – WRITE BUFFER Command Descriptor Block.....	29
Table 21 – Asynchronous Event conditions .....	30
Table 22 – Power condition sense code and qualifier values .....	31
Table 23 – Event status ASCQ values.....	32
Table 24 – Event Status INFORMATION field format .....	32
Table 25 – POWER MANAGEMENT CLASS EVENT INFORMATION field format .....	32
Table 26 – POWER MANAGEMENT CLASS EVENT EVENT field .....	33
Table 27 – POWER MANAGEMENT CLASS EVENT STATUS field.....	33
Table 28 – MEDIA CLASS EVENT INFORMATION field format .....	33
Table 29 – MEDIA CLASS EVENT EVENT field .....	34
Table 30 – DEVICE BUSY CLASS EVENT information field format .....	34
Table 31 – DEVICE BUSY CLASS EVENT EVENT field .....	34
Table 32 – DEVICE BUSY CLASS STATUS field .....	35