

# ISO/IEC TR 11801-9902:2017-06 (E)

## Information technology - Generic cabling for customer premises - Part 9902: Specifications for End-to-end link configurations

---

<b>Contents</b>	<b>Page</b>
FOREWORD.....	5
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references .....	7
3 Terms, definitions, abbreviated terms and symbols.....	7
3.1 Terms and definitions.....	7
3.2 Abbreviated terms.....	8
3.3 Symbols.....	8
4 Specifications .....	9
5 Examples of end-to-end link configurations.....	10
6 Performance specifications when using end-to-end link limits .....	11
6.1 General.....	11
6.2 Worst case limits.....	12
6.3 Insertion loss limits .....	13
6.4 Return loss .....	14
6.5 NEXT limits.....	16
6.6 PSNEXT limits .....	17
6.7 ACR-F Limits .....	18
6.8 PSACR-F .....	19
6.9 TCL specifications .....	19
6.10 ELTCTL specifications .....	20
6.11 Coupling attenuation specifications .....	20
6.12 DC loop resistance.....	20
6.13 Propagation delay.....	21
6.14 Delay skew .....	21
6.15 DC resistance unbalance within a pair .....	21
7 E2E link performance .....	21
7.1 General.....	21
7.2 Reference performance testing .....	22
7.3 Installation performance testing .....	22
7.4 Installation performance testing of E2E links.....	22
8 Testing of end-to-end links .....	23
Annex A (informative) CP cords .....	24
A.1 Specifications for Class D and Class E CP cords .....	24
A.2 Specifications for Class E <sub>A</sub> CP cords .....	24
A.2.1 General .....	24
A.2.2 Insertion loss .....	24
A.2.3 Return loss .....	24
A.2.4 NEXT.....	25
A.2.5 PSNEXT .....	25
A.2.6 ACR-F .....	25
A.2.7 PSACR-F.....	25
A.2.8 TCL .....	26
A.2.9 ELTCTL.....	26

A.2.10	Propagation delay.....	26
A.2.11	Delay skew .....	26
A.2.12	DC resistance unbalance within a pair .....	26
	Bibliography.....	27
Figure 1	– Symbols for bulkhead connections .....	9
Figure 2	– One-segment, two-connections, E2E link .....	10
Figure 3	– Two-segments, three-connections, E2E link .....	10
Figure 4	– Three-segments, one-connection bulkheads, four-connections, E2E link .....	10
Figure 5	– Three-segments, six-connections, E2E link .....	10
Figure 6	– Three-segments, four-connections, E2E link .....	11
Figure 7	– Three-segments, four-connections, E2E link .....	11
Figure 8	– Four-segments, five-connections, E2E link .....	11
Figure 9	– Five-segments, six-connections, E2E link.....	11
Figure A.1	– One-segment, two-connection, CP cord .....	24
Table 1	– Worst case Class D E2E link performance at key frequencies .....	12
Table 2	– Worst case Class E E2E link performance at key frequencies .....	13
Table 3	– Class D E2E link insertion loss limits .....	13
Table 4	– Class E E2E link insertion loss limits .....	14
Table 5	– Class D E2E link return loss limits .....	14
Table 6	– Class E E2E link return loss limits .....	15
Table 7	– Class D E2E link NEXT limits .....	16
Table 8	– Class E E2E link NEXT limits .....	16
Table 9	– Class D E2E link PSNEXT limits.....	17
Table 10	– Class E E2E link PSNEXT limits .....	17
Table 11	– Class D E2E Link ACR-F limits .....	18
Table 12	–Class E E2E Link ACR-F limits .....	18
Table 13	– Class D E2E link PSACR-F limits .....	19
Table 14	– Class E E2E link PSACR-F limits.....	19
Table 15	– E2E link TCL .....	19
Table 16	– E2E link segment ELTCTL.....	20
Table 17	– Minimum E2E link coupling attenuation .....	20
Table 18	– E2E link segment DC loop resistance .....	20
Table 19	– E2E link delay .....	21
Table 20	– E2E link delay skew .....	21
Table 21	– E2E link DC resistance unbalance .....	21
Table 22	– Test regime for reference performance and installation performance – Balanced cabling of Classes D to E .....	23
Table A.1	– Class E <sub>A</sub> insertion loss specifications .....	24
Table A.2	– Class E <sub>A</sub> return loss specifications .....	25

Table A.3 – Class $E_A$ NEXT specifications.....	25
Table A.4 – Class $E_A$ PSNEXT specifications .....	25
Table A.5 – Class $E_A$ ACR-F specifications .....	25
Table A.6 – Class $E_A$ PSACR-F specifications .....	26
Table A.7 – Class $E_A$ propagation delay specifications .....	26
Table A.8 – Class $E_A$ delay skew specifications.....	26
Table A.9 – E2E link DC resistance unbalance .....	26