

ISO/IEC 29341-24-1:2017-09 (E)

Information technology - UPnP Device Architecture - Part 24-1: Internet gateway device control protocol - Level 2 - Internet gateway device

Contents		Page
Introduction		1
1	Scope	1
2	Normative references	2
3	Terms, definitions, symbols and abbreviated terms	3
4	Device Model	4
4.1	Device Type	4
4.2	Requirements for an Internet Gateway Device	4
4.3	Device Architecture	5
4.3.1	Device Requirements	6
4.3.2	Relationships Between Services	7
4.4	Security policies	8
4.4.1	Access control and user roles	8
4.4.2	General policies	8
4.4.3	WANIPConnection:2	8
4.4.4	WANPPPConnection:1	10
4.4.5	WANIPv6FirewallControl:1	12
4.4.6	LANHostConfigManagement:1	13
4.4.7	Layer3Forwarding:1	13
4.4.8	WANEthernetLinkConfig:1	13
4.4.9	WANCableLinkConfig:1	14
4.4.10	WANDSLLinkConfig:1	14
4.4.11	WANCommonInterfaceConfig:1	14
4.4.12	WANPOTSLinkConfig:1	15
5	XML Device Description	16
6	Test	18
Annex A Theory of Operation		19
Figure 1 -- InternetGatewayDevice with LAN and WAN Interfaces		2
Figure 2 -- InternetGatewayDevice Devices and Services Hierarchy		5
Table 1 -- Device Requirements		5
Table 2 -- Service Descriptions		6
Table 3 -- Recommended access levels for WANIPConnection:2 actions		8
Table 4 -- Recommended access levels for WANPPPConnection:1 actions		10
Table 5 -- Recommended access levels for WANIPv6FirewallControl:1 actions		12
Table 6 -- Recommended access levels for LANHostConfigManagement:1 actions		13
Table 7 -- Recommended access levels for Layer3Forwarding:1 actions		13

Table 8 -- Recommended access levels for WANEthernetLinkConfig:1 actions	13
Table 9 -- Recommended access levels for WANCableLinkConfig:1 actions	14
Table 10 -- Recommended access levels for WANDSLLinkConfig:1 actions	14
Table 11 -- Recommended access levels for WANCommonInterfaceConfig:1 actions	14
Table 12 -- Recommended access levels for WANPOTSLinkConfig:1 actions	15