ISO/IEC 29341-26-1:2017-09 (E)

Information technology - UPnP Device Architecture - Part 26-1: Telephony device control protocol - Level 2 - Telephony architecture

Contents

Page

1 Scope v

2 Normative references 1

3 Terms, definitions and abbreviated terms 1
3.1 Provisioning terms 1
3.2 Symbols 1
3.3 General telephony terms 2

4 Text conventions 2

5 Introduction 2

6 Telephony Reference Architecture 3
6.1 Telephony Basic Architecture Paradigm 3
6.2 Telephony Components Overview 5
6.2.1 Call Management Service 6
6.2.2 Media Management Service 7
6.2.3 Interaction of Media and Call Management Service 7
6.2.4 Messaging Service 8
6.2.5 Presence Service 9
6.2.6 Calendar Service 9
6.2.7 Address Book Service 10
6.2.8 Phone Management via Data Model 10
6.2.9 InputConfig Service 11
6.2.10 Security 12

Annex A (informative) Deployment Scenarios 13

Annex B (informative) Bibliography 20

Figure 1 -- UPnP Telephony Basic Architecture 3

Figure 2 -- Architecture with a Telephny Control Point (TelCP) on an independent Device (3-Box Model) 4

Figure 3 -- Service Level Architectural View 4

Figure 4 -- UPnP Devices and Services for Telephony Architecture 5

Figure 5 -- A Deployment Scenario with Two Telephony Server Devices in a Single Physical Box 6

Figure 6 -- Call Management Service 7

Figure 7 -- Media Management Service 7

Figure 8 -- Architecture for Media Management Service 8

Figure 9 -- Messaging Service Interaction Diagram 8

Figure 10 -- Architecture for Presence Service 9

Figure 11 -- Architecture for Calendar Service 10

Figure 12 -- Architecture for Address Book Service 10

Figure 13 -- Phone Management via Data Model Interaction Diagram 11

Figure 14 -- Architecture for InputConfig Service (IS) 11

Figure 15 -- Architecture for Security Service 12

Figure A.1 -- Architecture with Telephony Control Point on a TV 13

Figure A.2 -- Deployment with a TelCP on a TC - Multiple TV Model 13

Figure A.3 -- Deployment with a TelCP on a TV - Multiple Phone Model 14

Figure A.4 -- An Architecture with a Telephony Control Point (TelCP) and a Telephony Client (TC) on a TV (2-Box Model) 14

Figure A.5 -- Deployment model with a Telephony Control Point (TelCP) and a Telephony Client (TC) on a TV (2-Box Model) - Multiple TV Model 15

Figure A.6 -- Deployment model with a Telephony Control Point (TelCP) and a Telephony Server (TS) on a Phone (2-Box Physical Model) 15

Figure A.7 -- Deployment with a phone having a Telephony Server (TS) and a Telephony Control Point (TelCP) - Multiple TV Model 16

Figure A.8 -- Deployment with a Telephony Control Point (TelCP) on a Phone 16

Figure A.9 -- Deployment with a Telephony Control Point (TelCP) on a Phone - Multiple TV Model ... 17

Figure A.10 -- Deployment with an independent Telephony Control point (TelCP) -3 Box Scenario .. 17

Figure A.11 -- Deployment with an independent Telephony Control Point (TelCP) - 3- Box with Multiple TV Model 18

Figure A.12 -- Messaging Service Deployment with Phone as the Messaging Aggregator 18

Figure A.13 -- Multiple Telephony Servers in a telephone 19