ISO/IEC 11801-4:2017-11 (E)

Information technology - Generic cabling for customer premises - Part 4: Single-tenant homes

CONTENTS

FOREWORD 5
INTRODUCTION 7
1 Scope 9
2 Normative references 9
3 Terms, definitions and abbreviated terms 9
3.1 Terms and definitions 9
3.2 Abbreviated terms 10
4 Conformance 11
5 Structure of the generic cabling system 11
5.1 General 11
5.2 Functional elements 12
5.3 Cabling subsystems for ICT and BCT 12
5.3.1 General 12
5.3.2 Primary home cabling subsystem 14
5.3.3 Secondary home cabling subsystem 14
5.4 Cabling structure 14
5.5 Interfaces 15
5.5.1 Equipment interfaces and test interfaces 15
5.5.2 Channel and permanent link 16
5.5.3 Network access cabling 17
5.5.4 External network interface 18
5.6 Accommodation of functional elements 18
5.6.1 General 18
5.6.2 Coverage areas 19
5.6.3 Dimensioning and configuring 20
5.6.4 Connecting hardware 21
5.6.5 Application outlets 21
5.6.6 Equipment cords 21
6 Channel performance requirements 22
6.1 General 22
6.2 Environmental performance 22
6.3 Transmission performance 22
6.3.1 Channel construction 22
6.3.2 Balanced cabling 22
6.3.3 Coaxial cabling 23
6.3.4 Optical fibre cabling 23
7 Link performance requirements 23
7.1 General 23
7.2 Balanced cabling 23
7.3 Coaxial cabling 23
7.4 Optical fibre cabling 23

8 Reference implementations 23
8.1 General 23
8.2 Channel construction 24
8.3 Balanced cabling 24
8.3.1 General 24
8.3.2 ICT channels 25
8.3.3 BCT channels 25
8.4 Coaxial cabling 26
8.5 Optical fibre cabling 26
8.5.1 General 26
8.5.2 Component selection 26
8.5.3 Dimensions 26
9 Cable requirements 26
9.1 General 26
9.2 Balanced cables 27
9.2.1 ICT cabling 27
9.2.2 BCT cabling 27
9.3 Coaxial cables 27
9.4 Optical fibre cables 27
10 Connecting hardware requirements 27
10.1 General requirements 27
10.2 Connecting hardware for balanced cabling 27
10.2.1 General requirements 27
10.2.2 Electrical, mechanical and environmental performance 27
10.3 Connecting hardware for coaxial cabling 28
10.3.1 General requirements 28
10.3.2 Electrical, mechanical and environmental performance 28
10.4 Connecting hardware for optical fibre cabling 28
10.4.1 General requirements 28
10.4.2 Optical, mechanical and environmental performance 28
11 Cords 28
11.1 Jumpers 28
11.2 Balanced cords 28
11.3 Coaxial cords 28
11.4 Optical fibre cords 28
Annex A (informative) Reference implementation of TV and radio applications – use of baluns 29
A.1 Types and locations of baluns 29
A.1.1 General 29
A.1.2 Baluns at the ENI and baluns at the equipment interface toward the PHD 29
A.1.3 Baluns near or in the BO 30
A.1.4 Baluns in the cord between BO and the terminal equipment 31
A.2 Home network interface 31
Bibliography 33

Figure 1 – Relationships between the generic cabling documents produced by ISO/IEC JTC 1/SC 25 7
Figure 2 – Structure of the generic cabling system 12
Figure 3 – Interconnect and cross-connect models 13
Figure 4 – Interconnect and cross-connects at the PHD 13
Figure 5 – Hierarchical structure of a generic cabling system in support of ICT and BCT applications 14
Figure 6 – Equipment and test interfaces in support of ICT and BCT applications 16
Figure 7 – Channels and permanent links within the home 17
Figure 8 – Examples of interconnection of home and network access cabling 18
Figure 9 – Overview of a generic cabling for home 19
Figure 10 – Interconnection of home cabling subsystems 20
Figure 11 – Reference implementations for ICT and BCT channels (PHD/SHD to TO/BO) 24
Figure A.1 – Balun at the ENI 29
Figure A.2 – Baluns in the PHD 30
Figure A.3 – Balun built into the system outlet 30
Figure A.4 – Balun in the cord between BO and the TE 31
Figure A.5 – Types of HNI 32

Table 1 – Maximum channel lengths for reference implementations of ICT/BCT channels 21
Table 2 – Link length equations 25
Table A.1 – Insertion loss and total sectional slope 32