

ISO/IEC 11801-1:2017-11 (E)

Information technology - Generic cabling for customer premises - Part 1: General requirements

CONTENTS

FOREWORD.....	11
INTRODUCTION.....	13
1 Scope.....	15
2 Normative references	15
3 Terms, definitions, abbreviations and symbols.....	20
3.1 Terms and definitions.....	20
3.2 Abbreviations.....	27
3.3 Symbols.....	29
3.3.1 Variables	29
3.3.2 Indices.....	30
4 Conformance.....	30
5 Structure of generic cabling.....	31
5.1 Functional elements.....	31
5.2 Interfaces.....	32
5.3 Cabling subsystems.....	32
5.3.1 Cabling subsystem 1	32
5.3.2 Cabling subsystems $n \geq 2$	33
5.3.3 Common subsystems.....	33
5.3.4 Tie cabling.....	34
5.3.5 Channel and permanent link.....	34
6 Channel performance requirements	34
6.1 General.....	34
6.2 Environmental performance	34
6.2.1 General	34
6.2.2 Environmental classification.....	35
6.3 Balanced cabling transmission performance	37
6.3.1 General	37
6.3.2 Component choice.....	38
6.3.3 Channel parameters	38
6.4 Coaxial cabling transmission performance	64
6.4.1 General	64
6.4.2 Component choice.....	65
6.4.3 Channel parameters	65
6.5 Optical fibre cabling transmission performance	67
6.5.1 Component choice.....	67
6.5.2 Channel parameters	67
7 Link performance requirements	67
7.1 General.....	67
7.2 Balanced cabling	68
7.2.1 General	68
7.2.2 Return loss	69
7.2.3 Insertion loss/attenuation.....	70
7.2.4 NEXT.....	72
7.2.5 Attenuation to crosstalk ratio at the near-end.....	76
7.2.6 Attenuation to crosstalk ratio at the far-end	78
7.2.7 Direct current loop resistance	82

7.2.8	Direct current resistance unbalance.....	83
7.2.9	Propagation delay.....	83
7.2.10	Delay skew.....	84
7.2.11	Unbalance attenuation and coupling attenuation.....	86
7.2.12	Alien crosstalk.....	89
7.3	Coaxial cabling.....	94
7.3.1	General.....	94
7.3.2	Return loss.....	94
7.3.3	Insertion loss.....	94
7.3.4	Direct current loop resistance.....	95
7.3.5	DC current carrying capacity.....	95
7.3.6	Screening attenuation.....	95
7.4	Optical fibre cabling.....	95
8	Reference implementation for backbone cabling subsystems.....	96
8.1	General.....	96
8.2	Balanced cabling.....	96
8.2.1	Component choice.....	96
8.2.2	Dimensions.....	96
8.3	Optical fibre cabling.....	97
8.3.1	General.....	97
8.3.2	Component selection.....	98
8.3.3	Dimensions.....	98
9	Cable requirements.....	98
9.1	General.....	98
9.2	Operating environment.....	98
9.3	Balanced cables.....	98
9.3.1	Basic requirements.....	98
9.3.2	Balanced cables of Category 5 through 7 _A , 8.1 and 8.2.....	99
9.3.3	Balanced cables of Category BCT-B.....	101
9.4	Coaxial cables.....	103
9.4.1	General.....	103
9.4.2	Environmental characteristics.....	103
9.4.3	Mechanical characteristics.....	103
9.4.4	Electrical characteristics.....	104
9.5	Optical fibre cable (cabled optical fibres).....	104
9.5.1	Mechanical and environmental characteristics.....	104
9.5.2	Cabled optical fibre Categories.....	105
10	Connecting hardware requirements.....	106
10.1	General requirements.....	106
10.1.1	Overview.....	106
10.1.2	Location.....	106
10.1.3	Design.....	106
10.1.4	Operating environment.....	107
10.1.5	Mounting.....	109
10.1.6	Installation practices.....	109
10.1.7	Marking and colour coding.....	110
10.2	Category 5 through 7 _A , 8.1, and 8.2 connecting hardware for balanced cabling.....	110

10.2.1	General	110
10.2.2	Performance marking.....	110
10.2.3	Mechanical characteristics.....	110
10.2.4	Electrical characteristics	112
10.2.5	Additional requirements	124
10.3	BCT-B connecting hardware	125
10.4	Connecting hardware for use with coaxial cabling for BCT applications.....	125
10.4.1	General requirements	125
10.4.2	Performance marking.....	125
10.4.3	Electrical characteristics	125
10.5	Optical fibre connecting hardware	126
10.5.1	General requirements	126
10.5.2	Marking and colour coding.....	127
10.5.3	Mechanical and optical characteristics.....	127
10.6	Connecting hardware in accordance with IEC 60603-7 series	128
10.7	Connecting hardware in accordance with IEC 61076-3-104.....	129
10.8	Connecting hardware in accordance with IEC 61076-2-101 (Type D, 4 poles).....	129
10.9	Connecting hardware in accordance with IEC 61076-2-109 (Type X, 8 poles).....	129
10.10	Connecting hardware in accordance with IEC 61169-2 and IEC 61169-24 (Type F).....	130
10.11	Connecting hardware for two optical fibres.....	130
10.12	Connecting hardware for twelve and twenty-four optical fibres	130
11	Cord requirements	131
11.1	General.....	131
11.2	Operating environment.....	131
11.3	Balanced cords of Category 5 through 7 _A , 8.1, 8.2 and BCT-B	131
11.3.1	General	131
11.3.2	Identification	131
11.3.3	Operating environment	132
11.3.4	Return loss	132
11.3.5	NEXT.....	132
11.4	Coaxial cords.....	135
11.5	Optical fibre cords.....	135
11.5.1	General	135
11.5.2	Identification	136
11.5.3	Performance requirements for patch cords	136
Annex A (normative) Conformance testing procedures for balanced cabling of Classes A to F _A , I and II and optical fibre cabling		137
A.1	General.....	137
A.2	Channel and link performance testing	137
A.2.1	General	137
A.2.2	Conformance testing of balanced cabling channels, and links.....	137
A.2.3	Installation conformance testing of optical fibre cabling channels	138
A.3	Overview of test schedules	138
Annex B (normative) Mechanical and environmental performance testing of connecting hardware for balanced cabling		141
B.1	Overview.....	141
B.2	Solderless connections	141
B.3	Free and fixed connectors (modular plugs and jacks).....	142

B.4	Other connecting hardware	143
Annex C (informative)	Electromagnetic characteristics	145
Annex D (informative)	Acronyms for balanced cables	146
Annex E (informative)	Supported applications	148
E.1	Supported applications for balanced cabling	148
E.2	Supported applications for optical fibre cabling	151
E.3	Supported applications for coaxial cabling	154
E.4	Supported industrial applications for optical fibre cabling	155
Annex F (informative)	Optical fibre cable OM1, OM2 and OS1	156
Bibliography	157
Figure 1 – Relationships between the generic cabling documents produced by ISO/IEC JTC 1/SC 25		14
Figure 2 – General functional elements		31
Figure 3 – Interconnect models		31
Figure 4 – Cross-connect models		32
Figure 5 – Equipment and test interfaces		32
Figure 6 – Link options		68
Figure 7 – Link designations		68
Figure 8 – Backbone cabling model		96
Figure 9 – Pin grouping and pair assignments for IEC 60603-7 series interface for Categories 5, 6, 6 _A and 8.1 (front view of fixed connector (jack), not to scale)		128
Figure 10 – Pin grouping and pair assignment for the IEC 60603-7 series interface for Categories 7, 7 _A , 8.2 and BCT-B (front view of fixed connector (jack), not to scale)		129
Figure 11 – Pin grouping and pair assignments for the IEC 61076-3-104 interface for Categories 7, 7 _A , 8.2 and BCT-B (front view of fixed connector (jack), not to scale)		129
Figure 12 – Four position jack pin and pair grouping assignments for IEC 61076-2-101 connecting hardware (front view of connector)		129
Figure 13 – Eight position jack pin and pair grouping assignments for IEC 61076-2-109 connecting hardware (front view of connector)		130
Figure 14 – Conductor assignment of IEC 61169-2 and IEC 61169-24 (Type F) connector		130
Figure 15 – Optical fibre assignments for connecting hardware for two optical fibres		130
Figure 16 – Optical fibre assignments for connecting hardware for 12 and 24 optical fibres (front view of fixed or free connector)		131
Figure D.1 – Cable naming schema		146
Figure D.2 – Cable types		147
Table 1 – Channel environments		35
Table 2 – Details of environmental classification		36
Table 3 – Return loss for a channel		39
Table 4 – Informative return loss values for a channel at key frequencies		40
Table 5 – Insertion loss for a channel		41
Table 6 – Informative insertion loss values for a channel at key frequencies		42
Table 7 – NEXT for a channel		43
Table 8 – Informative NEXT values for a channel at key frequencies		44

Table 9 – PS NEXT for a channel	45
Table 10 – Informative PS NEXT values for a channel at key frequencies	46
Table 11 – Informative ACR-N values for a channel at key frequencies	47
Table 12 – Informative PS ACR-N values for a channel at key frequencies	48
Table 13 – ACR-F for a channel.....	49
Table 14 – Informative ACR-F values for a channel at key frequencies	50
Table 15 – PS ACR-F for a channel	51
Table 16 – Informative PS ACR-F values for a channel at key frequencies.....	52
Table 17 – DC loop resistance for a channel.....	52
Table 18 – Propagation delay for a channel	53
Table 19 – Informative propagation delay values for a channel at key frequencies	54
Table 20 – Delay skew for a channel	55
Table 21 – TCL for channel for unscreened systems.....	56
Table 22 – Informative TCL values for unscreened channels at key frequencies	56
Table 23 – TCL for Class I and II screened channels	56
Table 24 – Informative TCL values for Class I and II screened channels at key frequencies.....	57
Table 25 – ELTCTL for channel for unscreened systems.....	57
Table 26 – Informative ELTCTL values for unscreened channels at key frequencies	58
Table 27 – ELTCTL for Class I and II channels	58
Table 28 – Informative ELTCTL values for Class I and II channels at key frequencies	58
Table 29 – Coupling attenuation for a channel for screened systems	59
Table 30 – PS ANEXT for a channel	60
Table 31 – Informative PS ANEXT values for a channel at key frequencies.....	60
Table 32 – PS ANEXT _{avg} for a channel.....	61
Table 33 – Informative PS ANEXT _{avg} values for a channel at key frequencies	61
Table 34 – PS AACR-F for a channel.....	62
Table 35 – Informative PS AACR-F values for a channel at key frequencies	63
Table 36 – PS AACR-F _{avg} for a channel	63
Table 37 – Informative PS AACR-F _{avg} values for a channel at key frequencies.....	64
Table 38 – Alien crosstalk and coupling attenuation for screened channels.....	64
Table 39 – Return loss for a channel.....	65
Table 40 – Insertion loss for a channel	65
Table 41 – Informative insertion loss values for a channel at key frequencies	66
Table 42 – DC loop resistance for a channel.....	66
Table 43 – DC current carrying capacity for a channel	66
Table 44 – Operating voltage for a channel.....	66
Table 45 – Screening attenuation for a channel	67
Table 46 – Return loss for 2-connection or 3-connection link	69
Table 47 – Informative return loss values for links at key frequencies	70
Table 48 – Insertion loss for 2-connection or 3-connection link	71
Table 49 – Informative insertion loss values for links with maximum implementation at key frequencies	72

Table 50 – NEXT for 2-connection or 3-connection link.....	72
Table 51 – Informative NEXT values for links with maximum implementation at key frequencies.....	74
Table 52 – PS NEXT for 2-connection or 3-connection link.....	75
Table 53 – Informative PS NEXT values for links with maximum implementation at key frequencies.....	76
Table 54 – Informative ACR-N values for links with maximum implementation at key frequencies.....	77
Table 55 – Informative PS ACR-N values for links with maximum implementation at key frequencies.....	78
Table 56 – ACR-F for 2-connection or 3-connection link.....	79
Table 57 – Informative ACR-F values for links with maximum implementation at key frequencies.....	80
Table 58 – PS ACR-F for 2-connection or 3-connection link.....	81
Table 59 – Informative PS ACR-F values for links with maximum implementation at key frequencies.....	82
Table 60 – DC loop resistance for 2-connection or 3-connection link.....	82
Table 61 – Informative DC loop resistance for links with maximum implementation.....	83
Table 62 – Propagation delay for 2-connection or 3-connection link.....	84
Table 63 – Informative propagation delay values for links with maximum implementation at key frequencies.....	84
Table 64 – Delay skew for 2-connection or 3-connection link.....	85
Table 65 – Informative delay skew for links with maximum implementation.....	86
Table 66 – TCL for Class I and II screened permanent links.....	87
Table 67 – Informative TCL values for Class I and II screened permanent links at key frequencies.....	87
Table 68 – ELTCTL for Class I and II permanent links.....	88
Table 69 – Informative ELTCTL values for Class I and II permanent links at key frequencies.....	88
Table 70 – Coupling attenuation for a screened permanent link.....	89
Table 71 – Informative coupling attenuation values for screened permanent links at key frequencies.....	89
Table 72 – PS ANEXT for 2-connection or 3-connection link.....	90
Table 73 – Informative PS ANEXT values for links at key frequencies.....	91
Table 74 – PS ANEXT _{avg} for 2-connection or 3-connection link.....	91
Table 75 – Informative PS ANEXT _{avg} values for links at key frequencies.....	92
Table 76 – PS AACR-F for 2-connection or 3-connection link.....	92
Table 77 – Informative PS AACR-F values for links at key frequencies.....	93
Table 78 – PS AACR-F _{avg} for a 2-connection or 3-connection link.....	93
Table 79 – Informative PS AACR-F _{avg} values for links at key frequencies.....	94
Table 80 – Alien crosstalk and coupling attenuation for screened links.....	94
Table 81 – Insertion loss for link.....	95
Table 82 – Informative insertion loss values for link at key frequencies.....	95
Table 83 – DC loop resistance for link.....	95
Table 84 – Backbone link length equations.....	97

Table 85 – Basic requirements of balanced cables.....	99
Table 86 – Mechanical characteristics of balanced cables of Category 5, 6, 6A, 7 and 7A	99
Table 87 – Mechanical characteristics of balanced cables of Category BCT-B	102
Table 88 – Minimum transmission performance requirements BCT-B balanced pairs	102
Table 89 – Basic requirements of coaxial cables	103
Table 90 – Mechanical performance requirements for coaxial BCT cables	103
Table 91 – Minimum electrical performance requirements for cables of Category BCT-C	104
Table 92 – Cabled optical fibre attenuation (maximum), dB/km	105
Table 93 – Multimode optical fibre modal bandwidth	105
Table 94 – Environmental performance specifications for balanced cabling connecting hardware	107
Table 95 – Environmental performance specifications for coaxial cabling connecting hardware	108
Table 96 – Environmental performance specifications for optical fibre cabling connecting hardware.....	109
Table 97 – Mechanical characteristics of connecting hardware for use with balanced cabling.....	111
Table 98 – Matrix of backward compatible mated free and fixed connector (plug and jack) performance	113
Table 99 – Return loss	113
Table 100 – Informative return loss values for connector at key frequencies	114
Table 101 – Insertion loss.....	114
Table 102 – Informative insertion loss values for connector at key frequencies	115
Table 103 – Near-end crosstalk (NEXT).....	115
Table 104 – Informative NEXT values for connector at key frequencies	116
Table 105 – Power sum near-end crosstalk (PS NEXT) (for information only)	116
Table 106 – Informative PS NEXT values for connector at key frequencies	117
Table 107 – Far-end crosstalk (FEXT)	117
Table 108 – Informative FEXT values for connector at key frequencies.....	118
Table 109 – Power sum far-end crosstalk (PS FEXT) (for information only).....	118
Table 110 – Informative PS FEXT values for connector at key frequencies	119
Table 111 – Input to output resistance	119
Table 112 – Input to output resistance unbalance	119
Table 113 – DC current carrying capacity	119
Table 114 – Propagation delay	120
Table 115 – Delay skew.....	120
Table 116 – Transverse conversion loss (TCL)	120
Table 117 – Informative TCL values for connector at key frequencies	121
Table 118 – Transverse conversion transfer loss (TCTL)	121
Table 119 – Informative TCTL values for connector at key frequencies	121
Table 120 – Transfer impedance (screened connectors only).....	122
Table 121 – Informative transfer impedance values (screened connectors only) at key frequencies.....	122

Table 122 – Coupling attenuation (screened connectors only)	122
Table 123 – Informative coupling attenuation values (screened connectors only) at key frequencies	122
Table 124 – Insulation resistance	123
Table 125 – Voltage proof	123
Table 126 – Power sum alien near-end crosstalk (PS ANEXT)	123
Table 127 – Informative PS ANEXT values at key frequencies	123
Table 128 – Power sum alien far-end crosstalk (PS AFEXT)	124
Table 129 – Informative PS AFEXT values at key frequencies	124
Table 130 – Coupling attenuation for BCT-B connecting hardware	125
Table 131 – Formulae for return loss limits for BCT-C connecting hardware	125
Table 132 – Return loss limits for BCT-C connecting hardware at key frequencies	126
Table 133 – Formulae for insertion loss limits for BCT-C connecting hardware	126
Table 134 – Insertion loss limits for BCT-C connecting hardware at key frequencies	126
Table 135 – Screening attenuation limits for BCT-C connecting hardware	126
Table 136 – Attenuation of connecting hardware for optical fibre	127
Table 137 – Return loss of optical fibre connecting hardware	127
Table 138 – Electrical characteristics of terminal equipment outlets intended for use with balanced cabling	128
Table 139 – Minimum return loss for balanced cords	132
Table 140 – Informative values of return loss for balanced cords at key frequencies	132
Table 141 – Assumptions for cabling components used in the calculation of NEXT informative values	134
Table 142 – Informative values of NEXT for 2 m balanced cords at key frequencies	134
Table 143 – Informative values of NEXT for 5 m balanced cords at key frequencies	135
Table 144 – Informative values of NEXT for 10 m balanced cords at key frequencies	135
Table A.1 – Test regime for reference conformance and installation conformance – Balanced cabling of Classes A through F _A , BCT-B, I and II	139
Table A.2 – Test regime for reference conformance and installation conformance – Optical fibre cabling	140
Table B.1 – Standards for solderless connections	141
Table B.2 – Standards for free and fixed connectors (modular plugs and jacks)	142
Table B.3 – Standards for M12 style connectors	142
Table B.4 – Free and fixed connectors (modular plugs and jacks) operations matrix	143
Table B.5 – Reference for reliability testing of other connecting hardware	143
Table B.6 – Other connecting hardware operations matrix	144
Table E.1 – Applications using balanced cabling	149
Table E.2 – Industrial applications using balanced cabling	150
Table E.3 – Modular connector pin assignment for applications	151
Table E.4 – Maximum channel attenuation for supported applications using optical fibre cabling	152
Table E.5 – Maximum channel lengths supported by optical fibre applications for multimode optical fibre	153
Table E.6 – Maximum channel length supported by optical fibre applications for single-mode optical fibre	154

Table E.7 – Supported BCT applications using balanced cabling	154
Table E.8 – Supported BCT applications using coaxial cabling	155
Table E.9 – Supported applications and maximum channel lengths with cabled multimode optical fibres	155
Table E.10 – Supported applications and maximum channel lengths with cabled all-silica single-mode optical fibres	155
Table F.1 – Grandfathered OM1, OM2 and OS1 specifications.....	156
Table F.2 – Supported applications and maximum channel lengths with cabled all-silica multimode optical fibres	156
Table F.3 – Supported applications and maximum channel lengths with cabled all-silica singlemode optical fibres	156