

# ISO/IEC 14776-154:2017-12 (E)

## Information technology - Small Computer System Interface (SCSI) - Part 154: Serial Attached SCSI - 3 (SAS-3)

---

### CONTENTS

FOREWORD.....	14
INTRODUCTION.....	16
1 Scope.....	18
2 Normative references.....	18
3 Terms, definitions, symbols, abbreviations, keywords, and conventions.....	20
3.1 Terms and definitions.....	20
3.2 Symbols and abbreviations.....	33
3.2.1 Abbreviations.....	33
3.2.2 Symbols.....	36
3.2.2.1 Units.....	36
3.2.2.2 Mathematical operators.....	36
3.2.2.3 Other symbols.....	37
3.3 Keywords.....	38
3.4 Editorial conventions.....	39
3.5 Numeric and character conventions.....	40
3.5.1 Numeric conventions.....	40
3.5.2 Units of measure.....	40
3.5.3 Byte encoded character strings conventions.....	41
4 General.....	42
4.1 Physical links and phys.....	42
4.2 Phy test functions.....	42
5 Physical layer.....	43
5.1 Physical layer overview.....	43
5.2 Conventions for defining maximum limits for S-parameters.....	43
5.3 Compliance points.....	44
5.3.1 Compliance points overview.....	44
5.3.2 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s compliance points.....	45
5.3.3 12 Gbit/s compliance points.....	53
5.4 Interconnects.....	55
5.4.1 SATA connectors and cable assemblies.....	55
5.4.2 SAS connectors and cables.....	56
5.4.3 Connectors.....	60
5.4.3.1 Connectors overview.....	60
5.4.3.2 Connector categories.....	62
5.4.3.3 Recommended electrical performance limits for mated connector pairs supporting rates of 12 Gbit/s.....	63
5.4.3.4 SAS internal connectors.....	64
5.4.3.4.1 SAS Drive connectors.....	64
5.4.3.4.1.1 SAS Drive plug connector.....	64
5.4.3.4.1.2 SAS Drive cable receptacle connector.....	65
5.4.3.4.1.3 SAS Drive backplane receptacle connector.....	66
5.4.3.4.1.4 SAS Drive connector pin assignments.....	67
5.4.3.4.1.5 SAS MultiLink Drive plug connector.....	69
5.4.3.4.1.6 SAS MultiLink Drive cable receptacle connector.....	69
5.4.3.4.1.7 SAS MultiLink Drive backplane receptacle connector.....	70
5.4.3.4.1.8 SAS MultiLink Drive connector pin assignments.....	70
5.4.3.4.1.9 Micro SAS plug connector.....	74
5.4.3.4.1.10 Micro SAS receptacle connector.....	74
5.4.3.4.1.11 Micro SAS connector pin assignments.....	75
5.4.3.4.2 SAS 4i connectors.....	76
5.4.3.4.2.1 SAS 4i cable receptacle connector.....	76

5.4.3.4.2.2 SAS 4i plug connector.....	76
5.4.3.4.2.3 SAS 4i connector pin assignments .....	77
5.4.3.4.3 Mini SAS 4i connectors.....	79
5.4.3.4.3.1 Mini SAS 4i cable plug connector .....	79
5.4.3.4.3.2 Mini SAS 4i receptacle connector .....	79
5.4.3.4.3.3 Mini SAS 4i connector pin assignments.....	80
5.4.3.4.4 Mini SAS HD internal connectors .....	82
5.4.3.4.4.1 Mini SAS HD 4i cable plug connector .....	82
5.4.3.4.4.2 Mini SAS HD 8i cable plug connector .....	83
5.4.3.4.4.3 Mini SAS HD 4i receptacle connector .....	84
5.4.3.4.4.4 Mini SAS HD 8i receptacle connector .....	85
5.4.3.4.4.5 Mini SAS HD 16i receptacle connector.....	86
5.4.3.4.4.6 Mini SAS HD 4i connector pin assignments.....	87
5.4.3.5 SAS external connectors.....	90
5.4.3.5.1 Mini SAS 4x connectors.....	90
5.4.3.5.1.1 Mini SAS 4x cable plug connector .....	90
5.4.3.5.1.2 Mini SAS 4x receptacle connector .....	97
5.4.3.5.1.3 Mini SAS 4x connector pin assignments.....	103
5.4.3.5.1.4 Mini SAS 4x active connector pin assignments .....	104
5.4.3.5.1.5 Mini SAS 4x active cable power requirements.....	105
5.4.3.5.2 Mini SAS HD external connectors .....	106
5.4.3.5.2.1 Mini SAS HD 4x cable plug connector .....	106
5.4.3.5.2.2 Mini SAS HD 8x cable plug connector .....	107
5.4.3.5.2.3 Mini SAS HD 4x receptacle connector .....	108
5.4.3.5.2.4 Mini SAS HD 8x receptacle connector .....	109
5.4.3.5.2.5 Mini SAS HD 16x receptacle connector.....	110
5.4.3.5.2.6 Mini SAS HD 4x connector pin assignments.....	111
5.4.3.5.2.7 Mini SAS HD external connector management interface.....	112
5.4.3.5.2.8 Mini SAS HD external connector memory map.....	113
5.4.3.5.3 QSFP+ connectors .....	113
5.4.3.5.3.1 QSFP+ cable plug.....	113
5.4.3.5.3.2 QSFP+ receptacle.....	114
5.4.3.5.3.3 QSFP+ connector pin assignments .....	115
5.4.3.5.3.4 QSFP+ memory map .....	116
5.4.4 Cable assemblies.....	117
5.4.4.1 SAS internal cable assemblies.....	117
5.4.4.1.1 SAS Drive cable assemblies.....	117
5.4.4.1.2 SAS internal symmetric cable assemblies.....	119
5.4.4.1.2.1 SAS internal symmetric cable assemblies overview .....	119
5.4.4.1.2.2 SAS internal symmetric cable assembly - SAS 4i.....	120
5.4.4.1.2.3 SAS internal symmetric cable assembly - Mini SAS 4i .....	121
5.4.4.1.2.4 SAS internal symmetric cable assembly - Mini SAS HD 4i.....	122
5.4.4.1.2.5 SAS internal symmetric cable assembly - Mini SAS HD 8i.....	123
5.4.4.1.2.6 SAS internal symmetric cable assembly - SAS 4i to Mini SAS 4i with vendor-specific sidebands.....	124
5.4.4.1.2.7 SAS internal symmetric cable assembly - SAS 4i controller to Mini SAS 4i backplane with SGPIO.....	125
5.4.4.1.2.8 SAS internal symmetric cable assembly - Mini SAS 4i controller to SAS 4i backplane with SGPIO.....	126
5.4.4.1.2.9 SAS internal symmetric cable assembly - Mini SAS 4i to Mini SAS HD 4i .....	127
5.4.4.1.3 SAS internal fanout cable assemblies .....	128
5.4.4.1.3.1 SAS internal fanout cable assemblies overview .....	128
5.4.4.1.3.2 SAS internal controller-based fanout cable assemblies.....	129
5.4.4.1.3.3 SAS internal backplane-based fanout cable assemblies .....	132
5.4.4.2 SAS external cable assemblies.....	135
5.4.4.2.1 SAS external cable assemblies overview .....	135
5.4.4.2.2 SAS external cable assembly - Mini SAS 4x.....	136
5.4.4.2.3 SAS external cable assembly - Mini SAS HD 4x.....	139

5.4.4.2.4 SAS external cable assembly - Mini SAS HD 8x .....	141
5.4.4.2.5 SAS external cable assembly - Mini SAS HD 8x to Mini SAS HD 4x .....	143
5.4.4.2.6 SAS external cable assembly - Mini SAS HD 4x to Mini SAS 4x .....	145
5.4.4.2.7 SAS external cable assembly - QSFP+ .....	146
5.4.5 Backplanes .....	146
5.5 TxRx connection characteristics .....	147
5.5.1 TxRx connection characteristics overview .....	147
5.5.2 TxRx connection general characteristics .....	148
5.5.3 Passive TxRx connection S-parameter limits .....	149
5.5.4 Passive TxRx connection characteristics for untrained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s .....	151
5.5.5 Passive TxRx connection characteristics for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s .....	152
5.5.6 Passive TxRx connection characteristics for trained 12 Gbit/s .....	153
5.5.7 TxRx connection characteristics for active cable assemblies .....	157
5.5.7.1 Active cable assembly electrical characteristics for trained 6 Gbit/s overview .....	157
5.5.7.2 Active cable assembly output electrical characteristics for trained 6 Gbit/s .....	157
5.5.7.3 Active cable assembly S-parameter limits for trained 6 Gbit/s and trained 12 Gbit/s .....	158
5.5.7.4 Active cable assembly electrical characteristics overview for 12 Gbit/s .....	159
5.5.7.5 Active cable assembly electrical characteristics for 12 Gbit/s .....	160
5.6 Test loads .....	161
5.6.1 Test loads overview .....	161
5.6.2 Zero-length test load .....	162
5.6.3 TCTF test load .....	163
5.6.4 Low-loss TCTF test load .....	168
5.6.5 Trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s reference transmitter test load .....	169
5.7 End to end simulation for trained 12 Gbit/s .....	173
5.7.1 End to end simulation for trained 12 Gbit/s overview .....	173
5.7.2 Usage models for end to end simulation for trained 12 Gbit/s .....	174
5.7.3 Reference transmitter equalization for trained 12 Gbit/s .....	175
5.7.4 Crosstalk measurement for end to end simulations and 12 Gbit/s jitter tolerance .....	177
5.8 Transmitter device and receiver device electrical characteristics .....	178
5.8.1 General electrical characteristics .....	178
5.8.2 Transmitter device and receiver device transients .....	179
5.8.3 Eye masks and the JTF .....	180
5.8.3.1 Eye masks overview .....	180
5.8.3.2 JTF .....	180
5.8.3.3 Transmitter device eye mask for untrained 1.5 Gbit/s and 3 Gbit/s .....	181
5.8.3.4 Receiver device eye mask for untrained 1.5 Gbit/s and 3 Gbit/s .....	182
5.8.3.5 Receiver device jitter tolerance eye mask for untrained 1.5 Gbit/s and 3 Gbit/s .....	182
5.8.4 Transmitter device characteristics .....	184
5.8.4.1 Transmitter device characteristics overview .....	184
5.8.4.2 Transmitter device coupling requirements .....	184
5.8.4.3 Transmitter device general electrical characteristics .....	184
5.8.4.4 Transmitter device signal output characteristics for untrained 1.5 Gbit/s and 3 Gbit/s as measured with the zero-length test load .....	186
5.8.4.5 Transmitter device signal output characteristics for untrained 1.5 Gbit/s and 3 Gbit/s as measured with each test load .....	187
5.8.4.6 Transmitter device signal output characteristics for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s ..	189
5.8.4.6.1 Transmitter device signal output characteristics for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s overview .....	189
5.8.4.6.2 Trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s transmitter device test procedure .....	190
5.8.4.6.3 Trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s Transmitter device S-parameter limits .....	191
5.8.4.6.4 Recommended trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s transmitter device settings for interoperability .....	192
5.8.4.6.5 Trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s reference transmitter device characteristics .....	193
5.8.4.6.6 Trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s Transmitter equalization, VMA, and $V_{P,P}$ measurement .....	194
5.8.4.7 Transmitter device signal output characteristics for trained 12 Gbit/s .....	196
5.8.4.7.1 Transmitter device signal output characteristics for trained 12 Gbit/s overview .....	196

5.8.4.7.2 12 Gbit/s Transmitter device S-parameter limits.....	203
5.8.4.7.3 12 Gbit/s reference transmitter device.....	205
5.8.4.7.4 Transmitter device end to end simulation characteristics for trained 12 Gbit/s .....	207
5.8.4.7.5 Transmitter device signal output characteristics at CTS for 12 Gbit/s when an active cable is connected.....	208
5.8.4.8 Transmitter device signal output characteristics for OOB signals .....	208
5.8.5 Receiver device characteristics .....	210
5.8.5.1 Receiver device characteristics overview.....	210
5.8.5.2 Receiver device coupling requirements .....	210
5.8.5.3 Receiver device general electrical characteristics.....	211
5.8.5.4 Delivered signal characteristics for untrained 1.5 Gbit/s and 3 Gbit/s.....	213
5.8.5.5 Maximum delivered jitter for untrained 1.5 Gbit/s and 3 Gbit/s .....	214
5.8.5.6 Receiver device jitter tolerance for untrained 1.5 Gbit/s and 3 Gbit/s .....	215
5.8.5.7 Receiver device and delivered signal characteristics for trained 1.5 Gbit/s, 3 Gbit/s, 6 Gbit/s, and 12 Gbit/s .....	216
5.8.5.7.1 Delivered signal characteristics for trained 1.5 Gbit/s, 3 Gbit/s, 6 Gbit/s, and 12 Gbit/s .....	216
5.8.5.7.2 Receiver device S-parameter limits .....	216
5.8.5.7.3 Reference receiver device characteristics .....	218
5.8.5.7.3.1 Reference receiver device overview .....	218
5.8.5.7.3.2 Reference receiver device DFE .....	219
5.8.5.7.3.3 Reference receiver device equalization for trained 12 Gbit/s.....	219
5.8.5.7.4 Reference receiver device termination characteristics for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s .....	220
5.8.5.7.5 Reference receiver device termination characteristics for trained 12 Gbit/s.....	220
5.8.5.7.6 Stressed receiver device jitter tolerance test .....	221
5.8.5.7.6.1 Stressed receiver device jitter tolerance test overview for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s .....	221
5.8.5.7.6.2 Stressed receiver device jitter tolerance test procedure for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s .....	223
5.8.5.7.6.3 Test equipment calibration and ISI generator calibration for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s .....	224
5.8.5.7.6.4 Crosstalk source calibration for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s.....	224
5.8.5.7.6.5 Stressed receiver device jitter tolerance test procedure for trained 12 Gbit/s.....	225
5.8.5.7.6.6 ISI generator calibration for trained 12 Gbit/s .....	225
5.8.5.7.6.7 Crosstalk calibration for the trained 12 Gbit/s stressed receiver device jitter tolerance test .....	228
5.8.5.7.6.8 Applied RJ for trained 12 Gbit/s stressed receiver device jitter tolerance test .....	228
5.8.5.7.6.9 Applied SJ.....	228
5.8.5.8 Delivered signal characteristics for OOB signals .....	230
5.8.6 Spread spectrum clocking (SSC).....	230
5.8.6.1 SSC overview.....	230
5.8.6.2 Transmitter SSC modulation .....	231
5.8.6.3 Receiver SSC modulation tolerance .....	232
5.8.6.4 Expander device center-spreading tolerance buffer.....	233
5.8.7 Non-tracking clock architecture.....	234
5.9 READY LED signal electrical characteristics.....	234
5.10 POWER DISABLE signal electrical characteristics .....	235
5.11 Out of band (OOB) signals .....	237
5.11.1 OOB signals overview.....	237
5.11.2 Transmitting OOB signals.....	238
5.11.3 Receiving OOB signals.....	240
5.11.4 Transmitting the SATA port selection signal.....	241
Annex A (normative) Jitter tolerance pattern (JTPAT) .....	242
Annex B (normative) SASWDP .....	244
B.1 SASWDP introduction .....	244
B.2 SASWDP.m.....	244

B.3 SASWDP_testcase.m .....	251
Annex C (informative) StatEye .....	253
C.1 StatEye introduction .....	253
C.2 analysis.py .....	253
C.3 cdr.py .....	254
C.4 extractJitter.py .....	255
C.5 penrose.py .....	257
C.6 portlocker.py .....	259
C.7 stateye.py .....	262
C.8 touchstone.py .....	277
C.9 testcase.py .....	285
C.10 testall.py .....	290
C.11 File StatEye_readme.pdf .....	293
C.11.1 How to install and run the SAS-2.1 StatEye .....	293
Annex D (normative) End to end simulation for trained 12 Gbit/s .....	294
D.1 Detailed end to end simulation procedure description for trained 12 Gbit/s .....	294
D.2 Trained 12 Gbit/s usage models, S-parameter files, and crosstalk amplitude .....	296
D.2.1 Transmitter device connected to a separable passive TxRx connection segment .....	296
D.2.2 Transmitter device connected to a non-separable passive TxRx connection segment .....	298
D.2.3 TxRx connection segment .....	301
D.2.4 Stressed Receiver device delivered signal calibration end to end simulation diagram .....	302
Annex E (informative) 12 Gbit/s S-parameters and end to end simulation .....	304
E.1 S-parameters for 12 Gbit/s simulation .....	304
E.1.1 Measurement procedure .....	304
E.1.2 Multiple channel segments .....	305
E.2 End to end simulation using SAS3_EYEOPENING .....	306
Annex F (informative) Signal performance measurements .....	307
F.1 Signal performance measurements overview .....	307
F.2 Glossary .....	307
F.3 Simple physical link .....	307
F.3.1 Simple physical link overview .....	307
F.3.2 Assumptions for the structure of the transmitter device and the receiver device .....	308
F.3.3 Definition of receiver sensitivity and receiver device sensitivity .....	309
F.4 Signal measurement architecture .....	310
F.4.1 General .....	310
F.4.2 Relationship between signal compliance measurements at interoperability points and operation in systems .....	310
F.5 De-embedding connectors in test fixtures .....	311
F.6 De-embedding test fixture for 12 Gbit/s transmitter compliance .....	311
F.7 Measurement conditions for signal output at the transmitter device .....	312
F.8 Measurement conditions for signal tolerance at the transmitter device .....	313
F.9 Measurement conditions for signal output at the receiver device .....	315
F.10 Measurement conditions for signal tolerance at the receiver device .....	315
F.11 S-parameter measurements .....	316
F.11.1 S-parameter overview .....	316
F.11.2 S-parameter naming conventions .....	316
F.11.3 Use of single ended instrumentation in differential applications .....	317
F.11.4 Measurement configurations for physical link elements .....	319
F.11.4.1 Measurement configuration overview .....	319
F.11.4.2 Transmitter device $S_{22}$ measurements .....	319
F.11.4.3 Receiver device $S_{11}$ measurements .....	320
F.11.4.4 TxRx connection $S_{11}$ measurements at IT or CT .....	320
F.11.4.5 TxRx connection $S_{22}$ measurements at IR or CR .....	321
F.12 Calibration of JMDs .....	322

F.12.1 Calibration of JMDs overview .....	322
F.12.1.1 Purpose of JMD calibration .....	322
F.12.1.2 Overview of low frequency calibration for SSC configurations .....	322
F.12.1.3 Overview of low frequency calibration for non-SSC configurations .....	324
F.12.1.4 High frequency calibration .....	324
F.12.2 JMD calibration procedure .....	325
F.12.2.1 General characteristics and equipment .....	325
F.12.2.2 Calibration of the JMD for testing SSC configurations .....	326
F.12.2.3 Calibration of the JMD for testing non-SSC configurations .....	327
 Annex G (informative) Description of the included Touchstone models for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s .....	 329
G.1 Description of included Touchstone models for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s overview ...	329
G.2 Reference transmitter device termination model for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s .....	329
G.3 Reference receiver device termination model for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s .....	330
G.4 Generic return loss circuit model for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s .....	331
G.5 Reference transmitter test load for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s .....	332
 Annex H (informative) Mini SAS 4x active cable assembly power supply and voltage detection circuitry ....	 335
 Annex I (informative) SAS icons .....	 336
 Annex J (informative) Standards bodies contact information .....	 338
Bibliography .....	339

Figure 1 – SCSI document relationships .....	16
Figure 2 – ATA document relationships .....	17
Figure 3 – Physical links and phys .....	42
Figure 4 – Maximum limits for S-parameters definitions .....	44
Figure 5 – 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s External cable assembly CT compliance points and CR compliance points .....	46
Figure 6 – Backplane with SAS Drive connector 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s IT compliance points and IR compliance points .....	47
Figure 7 – Backplane with SAS Drive connector 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s compliance points with SATA phy attached .....	48
Figure 8 – SAS multilane internal cable assembly 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s IT compliance points and IR compliance points .....	49
Figure 9 – SAS multilane internal cable assembly and backplane 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s IT compliance points and IR compliance points .....	50
Figure 10 – SAS multilane internal cable assembly and backplane 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s IT compliance points and IR compliance points with SATA device attached .....	51
Figure 11 – SAS Drive cable assembly 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s IT compliance points and IR compliance points .....	52
Figure 12 – 12 Gbit/s TxRx connection and compliance points .....	53
Figure 13 – Simulated 12 Gbit/s TxRx connection and compliance points .....	53
Figure 14 – 12 Gbit/s CTS and CR compliance points .....	54
Figure 15 – SATA connectors and cables .....	55
Figure 16 – SAS Drive cable environments .....	56
Figure 17 – SAS Drive backplane environment .....	57
Figure 18 – SAS external cable environment .....	57
Figure 19 – SAS internal symmetric cable environment - controller to backplane .....	58
Figure 20 – SAS internal symmetric cable environment - controller to controller .....	58
Figure 21 – SAS internal controller-based fanout cable environment .....	59
Figure 22 – SAS internal backplane-based fanout cable environment .....	59
Figure 23 – Recommended $ S_{DD21} $ , $ S_{CC22} $ , $ S_{DD22} $ , NEXT, and FEXT limits for connector mated pairs supporting rates of 12 Gbit/s .....	64
Figure 24 – SAS Drive plug connector .....	65
Figure 25 – Single-port SAS Drive cable receptacle connector .....	65
Figure 26 – Dual-port SAS Drive cable receptacle connector .....	66
Figure 27 – SAS Drive backplane receptacle connector .....	66
Figure 28 – SAS MultiLink Drive plug connector .....	69
Figure 29 – SAS MultiLink Drive cable receptacle connector .....	69
Figure 30 – SAS MultiLink Drive backplane receptacle connector .....	70
Figure 31 – Micro SAS plug connector .....	74
Figure 32 – Micro SAS receptacle connector .....	74
Figure 33 – SAS 4i cable receptacle connector .....	76
Figure 34 – SAS 4i plug connector .....	76
Figure 35 – Mini SAS 4i cable plug connector .....	79
Figure 36 – Mini SAS 4i receptacle connector .....	79
Figure 37 – Mini SAS HD 4i cable plug connector .....	82
Figure 38 – Mini SAS HD 8i cable plug connector .....	83
Figure 39 – Mini SAS HD 4i receptacle connector .....	84
Figure 40 – Mini SAS HD 8i receptacle connector .....	85
Figure 41 – Mini SAS HD 16i receptacle connector .....	86
Figure 42 – Mini SAS 4x cable plug connector .....	90
Figure 43 – Mini SAS 4x cable plug connector for untrained 1.5 Gbit/s and 3 Gbit/s that attaches to an enclosure out port or an enclosure in port .....	92
Figure 44 – Mini SAS 4x cable plug connector for untrained 1.5 Gbit/s and 3 Gbit/s that attaches to an enclosure out port .....	92
Figure 45 – Mini SAS 4x cable plug connector for untrained 1.5 Gbit/s and 3 Gbit/s that attaches to an enclosure in port .....	93
Figure 46 – Mini SAS 4x cable plug connector for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s that attaches to an enclosure out port or an enclosure in port .....	93

Figure 47 – Mini SAS 4x cable plug connector for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s that attaches to an enclosure out port .....	94
Figure 48 – Mini SAS 4x cable plug connector for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s that attaches to an enclosure in port .....	94
Figure 49 – Mini SAS 4x active cable plug connector for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s that attaches to an enclosure out port or an enclosure in port .....	95
Figure 50 – Mini SAS 4x active cable plug connector for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s that attaches to an enclosure out port .....	95
Figure 51 – Mini SAS 4x active cable plug connector for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s that attaches to an enclosure in port .....	96
Figure 52 – Mini SAS 4x receptacle connector .....	97
Figure 53 – Mini SAS 4x receptacle connector - end device or enclosure universal port for untrained 1.5 Gbit/s and 3 Gbit/s .....	98
Figure 54 – Mini SAS 4x receptacle connector - enclosure out port for untrained 1.5 Gbit/s and 3 Gbit/s .....	99
Figure 55 – Mini SAS 4x receptacle connector - enclosure in port for untrained 1.5 Gbit/s and 3 Gbit/s .....	99
Figure 56 – Mini SAS 4x receptacle connector - end device or enclosure universal port for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s and for untrained 1.5 Gbit/s and 3 Gbit/s .....	100
Figure 57 – Mini SAS 4x receptacle connector - enclosure out port for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s and for untrained 1.5 Gbit/s and 3 Gbit/s .....	100
Figure 58 – Mini SAS 4x receptacle connector - enclosure in port for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s and for untrained 1.5 Gbit/s and 3 Gbit/s .....	101
Figure 59 – Mini SAS 4x active receptacle connector - end device or enclosure universal port .....	101
Figure 60 – Mini SAS 4x active receptacle connector - enclosure out port .....	102
Figure 61 – Mini SAS 4x active receptacle connector - enclosure in port .....	102
Figure 62 – Mini SAS HD 4x cable plug connector .....	106
Figure 63 – Mini SAS HD 8x cable plug connector .....	107
Figure 64 – Mini SAS HD 4x receptacle connector .....	108
Figure 65 – Mini SAS HD 8x receptacle connector .....	109
Figure 66 – Mini SAS HD 16x receptacle connector .....	110
Figure 67 – QSFP+ cable plug connector .....	113
Figure 68 – QSFP+ receptacle connector .....	114
Figure 69 – Single-port SAS Drive cable assembly .....	117
Figure 70 – Dual-port SAS Drive cable assembly .....	118
Figure 71 – MultiLink SAS Drive cable assembly .....	119
Figure 72 – SAS internal symmetric cable assembly - SAS 4i .....	120
Figure 73 – SAS internal symmetric cable assembly - Mini SAS 4i .....	121
Figure 74 – SAS internal symmetric cable assembly - Mini SAS HD 4i .....	122
Figure 75 – SAS internal symmetric cable assembly - Mini SAS HD 8i .....	123
Figure 76 – SAS internal symmetric cable assembly - SAS 4i to Mini SAS 4i with vendor-specific sideband signals .....	124
Figure 77 – SAS internal symmetric cable assembly - SAS 4i controller to Mini SAS 4i backplane with SGPIO connections .....	125
Figure 78 – SAS internal symmetric cable assembly - Mini SAS 4i controller to SAS 4i backplane with SGPIO connections .....	126
Figure 79 – SAS internal symmetric cable assembly - Mini SAS 4i to Mini SAS HD 4i .....	127
Figure 80 – SAS internal controller-based fanout cable assembly - SAS 4i .....	129
Figure 81 – SAS internal controller-based fanout cable assembly - Mini SAS 4i .....	130
Figure 82 – SAS internal controller-based fanout cable assembly - Mini SAS HD 4i .....	131
Figure 83 – SAS internal backplane-based fanout cable assembly - SAS 4i .....	132
Figure 84 – SAS internal backplane-based fanout cable assembly - Mini SAS 4i .....	133
Figure 85 – SAS internal backplane-based fanout cable assembly - Mini SAS HD 4i .....	134
Figure 86 – Mini SAS 4x external cable assembly .....	136
Figure 87 – Mini SAS 4x active external cable assembly .....	137
Figure 88 – SAS external cable assembly with Mini SAS 4x cable plug connectors .....	138
Figure 89 – SAS external cable assembly - Mini SAS HD 4x .....	139
Figure 90 – SAS external cable assembly with Mini SAS HD 4x cable plug connectors .....	140
Figure 91 – SAS external cable assembly - Mini SAS HD 8x .....	141
Figure 92 – SAS external cable assembly with Mini SAS HD 8x cable plug connectors .....	142

Figure 93 – SAS external cable assembly - Mini SAS HD 8x to Mini SAS HD 4x .....	143
Figure 94 – SAS external cable assembly with a Mini SAS HD 8x cable plug connector and two Mini SAS HD 4x cable plug connectors .....	144
Figure 95 – SAS external cable assembly - Mini SAS HD 4x to Mini SAS 4x .....	145
Figure 96 – SAS external cable assembly with a Mini SAS HD 4x cable plug connector and a Mini SAS 4x cable plug connector .....	146
Figure 97 – Passive TxRx connection $ S_{DD22} $ , $ S_{CD22} $ , $ S_{CD21} $ , and NEXT limits .....	151
Figure 98 – Example of a passive TxRx connection compliance testing for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s .....	152
Figure 99 – Example passive TxRx connection compliance testing for trained 12 Gbit/s .....	154
Figure 100 – Passive TxRx connection segment between CTS and CR or ITS and IR end to end simulation diagram for trained 12 Gbit/s .....	155
Figure 101 – Active cable S-parameter limits .....	159
Figure 102 – Active cable eye mask for 12 Gbit/s .....	160
Figure 103 – Zero-length test load for transmitter device compliance point .....	162
Figure 104 – Zero-length test load for receiver device compliance point .....	162
Figure 105 – Zero-length test load $ S_{DD21}(f) $ requirements .....	163
Figure 106 – TCTF test load .....	163
Figure 107 – TCTF test load $ S_{DD21}(f) $ and ISI loss requirements at IT for untrained 3 Gbit/s .....	164
Figure 108 – TCTF test load $ S_{DD21}(f) $ and ISI loss requirements at CT for untrained 3 Gbit/s .....	165
Figure 109 – TCTF test load $ S_{DD21}(f) $ and ISI loss requirements at IT for untrained 1.5 Gbit/s .....	166
Figure 110 – TCTF test load $ S_{DD21}(f) $ and ISI loss requirements at CT for untrained 1.5 Gbit/s .....	167
Figure 111 – Low-loss TCTF test load .....	168
Figure 112 – Low-loss TCTF test load $ S_{DD21}(f) $ and ISI loss requirements .....	169
Figure 113 – Trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s reference transmitter with a test load $ S_{DD21}(f) $ up to 6 GHz .....	170
Figure 114 – Trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s reference transmitter test load pulse response .....	171
Figure 115 – Trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s reference transmitter test load impulse response for 6 Gbit/s .....	172
Figure 116 – Trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s reference transmitter test load D24.3 response .....	173
Figure 117 – NEXT and FEXT measurement definition .....	174
Figure 118 – Reference sampling point and reference pulse response cursor .....	175
Figure 119 – Reference transmitter coefficient error computation .....	176
Figure 120 – Convergence of reference transmitter equalization .....	177
Figure 121 – Transmitter device transient test circuit .....	179
Figure 122 – Receiver device transient test circuit .....	179
Figure 123 – Transmitter device eye mask .....	181
Figure 124 – Receiver device eye mask .....	182
Figure 125 – Deriving a receiver device jitter tolerance eye mask for untrained 1.5 Gbit/s and 3 Gbit/s .....	183
Figure 126 – Transmitter device common mode voltage limit .....	190
Figure 127 – Transmitter device $ S_{CC22} $ , $ S_{DD22} $ , and $ S_{CD22} $ limits .....	192
Figure 128 – Trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s reference transmitter device .....	193
Figure 129 – Trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s reference transmitter device termination S-parameters model .....	194
Figure 130 – Transmitter equalization measurement .....	195
Figure 131 – Minimum and maximum coefficient ranges at maximum peak to peak voltage .....	198
Figure 132 – 12 Gbit/s transmitter device common mode voltage limit .....	199
Figure 133 – Transmitter circuit compliance test configuration .....	201
Figure 134 – 12 Gbit/s transmitter circuit output waveform .....	202
Figure 135 – 12 Gbit/s transmitter device $ S_{CC22} $ , $ S_{DD22} $ , and $ S_{CD22} $ limits .....	204
Figure 136 – 12 Gbit/s reference transmitter device .....	205
Figure 137 – 12 Gbit/s reference transmitter .....	205
Figure 138 – Simulation of the reference transmitter from a captured signal .....	208
Figure 139 – Applied SJ for untrained 1.5 Gbit/s and 3 Gbit/s .....	215
Figure 140 – Receiver device $ S_{CC11} $ , $ S_{DD11} $ , and $ S_{CD11} $ limits .....	217
Figure 141 – Reference receiver device for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s .....	218
Figure 142 – Reference receiver device for trained 12 Gbit/s .....	218

Figure 143 – Reference receiver device termination S-parameters for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s .....	220
Figure 144 – Stressed receiver device jitter tolerance test block diagram for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s .....	221
Figure 145 – Stressed receiver device jitter tolerance test D24.3 eye opening for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s .....	223
Figure 146 – Stressed receiver transmitter equalization adjustment for 12 Gbit/s .....	225
Figure 147 – Simulation of the reference transmitter from a captured signal .....	226
Figure 148 – Applied SJ for trained 1.5 Gbit/s, 3 Gbit/s, 6 Gbit/s, and 12 Gbit/s without SSC support .....	228
Figure 149 – Applied SJ for trained 1.5 Gbit/s, 3 Gbit/s, 6 Gbit/s and 12 Gbit/s with SSC support .....	229
Figure 150 – Center-spreading tolerance buffer .....	234
Figure 151 – OOB signal transmission .....	239
Figure 152 – SATA port selection signal .....	241
Figure C.1 – Reference channel eye opening .....	293
Figure D.1 – Trained 12 Gbit/s die to die insertion loss model .....	294
Figure D.2 – Transmitter device end to end simulation diagram that includes a separable TxRx connection segment .....	297
Figure D.3 – End to end simulation diagram from target device usage model for a transmitter device connected to a non-separable TxRx connection segment .....	299
Figure D.4 – End to end simulation diagram of the target device usage model for a transmitter device connected to a non-separable TxRx connection segment .....	300
Figure D.5 – Stressed receiver device delivered signal calibration end to end simulation diagram .....	302
Figure E.1 – S-parameter measurement connections for a four port VNA .....	304
Figure E.2 – Example of a SAS three TxRx connection segment .....	305
Figure F.1 – A simple physical link .....	307
Figure F.2 – Transmitter device details .....	308
Figure F.3 – Receiver device details .....	309
Figure F.4 – De-embedding of connectors in test fixtures .....	311
Figure F.5 – De-embedding to ET for 12 Gbit/s transmitter compliance .....	312
Figure F.6 – De-embedding calibration test structure .....	312
Figure F.7 – Measurement conditions for signal output at the transmitter device .....	313
Figure F.8 – Transmitter device signal output measurement test fixture details .....	313
Figure F.9 – Measurement conditions for signal tolerance at the transmitter device .....	314
Figure F.10 – Calibration of test fixture for signal tolerance at the transmitter device .....	314
Figure F.11 – Measurement conditions for signal output at the receiver device .....	315
Figure F.12 – Measurement conditions for signal tolerance at the receiver device .....	315
Figure F.13 – Calibration of test fixture for signal tolerance at the receiver device .....	316
Figure F.14 – S-parameter port naming conventions .....	317
Figure F.15 – Four single ended port or two differential port element .....	318
Figure F.16 – S-parameters for single ended and differential systems .....	318
Figure F.17 – Measurement conditions for $S_{22}$ at the transmitter device connector .....	319
Figure F.18 – Measurement conditions for $S_{11}$ at the receiver device connector .....	320
Figure F.19 – Measurement conditions for $S_{11}$ at IT or CT .....	321
Figure F.20 – Measurement conditions for $S_{22}$ at IR or CR .....	322
Figure G.1 – Reference transmitter device and reference receiver device termination circuit model .....	329
Figure G.2 – Generic return loss circuit model .....	331
Figure G.3 – Generic return loss model $ S_{11} $ .....	332
Figure G.4 – Reference transmitter test load measurement setup .....	333
Figure G.5 – Reference transmitter test load $ S_{DD21}(f) $ up to 20 GHz .....	334
Figure H.1 – Dual comparator design for active cable assembly detection .....	335
Figure I.1 – SAS primary icon .....	336
Figure I.2 – SAS alternate icon .....	336
Figure I.3 – MultiLink SAS icon .....	337

Table 1 – Numbering conventions .....	40
Table 2 – Comparison of decimal prefixes and binary prefixes .....	41
Table 3 – Compliance points.....	45
Table 4 – Connectors.....	60
Table 5 – Connector categories.....	62
Table 6 – Recommended electrical performance limits for the mated connector pairs that support rates of 12 Gbit/s.....	63
Table 7 – SAS Drive connector pin assignments.....	67
Table 8 – SAS MultiLink connector pin assignments.....	71
Table 9 – Micro SAS connector pin assignments .....	75
Table 10 – Controller SAS 4i connector pin assignments and physical link usage.....	77
Table 11 – Backplane SAS 4i connector pin assignments and physical link usage .....	78
Table 12 – Controller Mini SAS 4i connector pin assignments and physical link usage .....	80
Table 13 – Backplane Mini SAS 4i connector pin assignments and physical link usage.....	81
Table 14 – Controller Mini SAS HD 4i connector pin assignments and physical link usage.....	87
Table 15 – Backplane Mini SAS HD 4i connector pin assignments and physical link usage.....	88
Table 16 – Mini SAS 4x cable plug connector and Mini SAS 4x active cable plug connector icons, key slot positions, and key positions .....	91
Table 17 – Mini SAS 4x receptacle connector icons, key positions, and key slot positions.....	98
Table 18 – Mini SAS 4x connector pin assignments and physical link usage.....	103
Table 19 – Mini SAS 4x active connector pin assignments and physical link usage .....	104
Table 20 – Mini SAS 4x active cable supplied power requirements .....	105
Table 21 – Mini SAS HD 4x connector pin assignments and physical link usage .....	111
Table 22 – Management interface connection requirements .....	112
Table 23 – QSFP+ connector pin assignments .....	115
Table 24 – TxRx connection general characteristics .....	148
Table 25 – Maximum limits for S-parameters of the passive TxRx connection between ITS and IR or CTS and CR.....	150
Table 26 – Passive TxRx connection characteristics for trained 6 Gbit/s .....	152
Table 27 – Passive TxRx connection characteristics for trained 12 Gbit/s at ET and ER.....	156
Table 28 – Active cable assembly output electrical characteristics for trained 6 Gbit/s.....	157
Table 29 – Maximum limits for S-parameters for active cable assemblies .....	158
Table 30 – Active cable assembly electrical characteristics for 12 Gbit/s.....	160
Table 31 – General electrical characteristics .....	178
Table 32 – JTF parameters.....	181
Table 33 – Transmitter device general electrical characteristics .....	184
Table 34 – Transmitter device termination characteristics.....	185
Table 35 – Transmitter device signal output characteristics for untrained 1.5 Gbit/s and 3 Gbit/s as measured with the zero-length test load at IT and CT .....	186
Table 36 – Transmitter device signal output characteristics for untrained 1.5 Gbit/s and 3 Gbit/s as measured with each test load at IT and CT .....	188
Table 37 – Transmitter device signal output characteristics for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s at IT and CT.....	189
Table 38 – Transmitter device common mode voltage limit characteristics.....	190
Table 39 – Maximum limits for S-parameters at IT <sub>S</sub> or CT <sub>S</sub> .....	191
Table 40 – Recommended trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s transmitter device settings at IT and CT compliance point .....	192
Table 41 – Trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s reference transmitter device characteristics at IT and CT compliance point .....	193
Table 42 – Transmitter device signal output characteristics for trained 12 Gbit/s at ET, IT, and CT .....	196
Table 43 – 12 Gbit/s transmitter device common mode voltage limit characteristics.....	199
Table 44 – Transmitter coefficient requests and corresponding transmitter circuit response .....	200
Table 45 – Transmitter circuit coefficient presets at ET.....	203
Table 46 – 12 Gbit/s maximum limits for S-parameters at IT <sub>S</sub> or CT <sub>S</sub> .....	204
Table 47 – 12 Gbit/s reference transmitter device characteristics at ET.....	206
Table 48 – Transmitter device characteristics for trained 12 Gbit/s at ET and ER .....	207
Table 49 – Transmitter device signal output characteristics for 12 Gbit/s at CTS when an active cable is connected.....	208

Table 50 – Transmitter device signal output characteristics for OOB signals .....	209
Table 51 – Receiver device general electrical characteristics .....	211
Table 52 – Recommended receiver device common mode tolerance for 6 Gbit/s, and 12 Gbit/s .....	211
Table 53 – Receiver device termination characteristics .....	212
Table 54 – Delivered signal characteristics for untrained 1.5 Gbit/s and 3 Gbit/s as measured with the zero-length test load at IR and CR.....	213
Table 55 – Maximum delivered jitter for untrained 1.5 Gbit/s and 3 Gbit/s at IR and CR .....	214
Table 56 – Receiver device jitter tolerance for untrained 1.5 Gbit/s and 3 Gbit/s at IR and CR .....	215
Table 57 – $f_{\min}$ , $f_c$ , and $f_{\max}$ for untrained 1.5 Gbit/s and 3 Gbit/s.....	216
Table 58 – Delivered signal characteristics for trained 1.5 Gbit/s, 3 Gbit/s, 6 Gbit/s, and 12 Gbit/s at IR and CR compliance point.....	216
Table 59 – Maximum limits for S-parameters at IR or CR .....	217
Table 60 – Reference receiver equalization stage characteristics for trained 12 Gbit/s .....	219
Table 61 – Stressed receiver device jitter tolerance test characteristics for trained 1.5 Gbit/s, 3 Gbit/s, and 6 Gbit/s.....	222
Table 62 – Number of bits received per number of errors for desired BER.....	224
Table 63 – ISI generator characteristics for trained 12 Gbit/s at ET and ER .....	227
Table 64 – RJ characteristics for trained 12 Gbit/s stressed receiver device tolerance test.....	228
Table 65 – $f_{\min}$ , $f_c$ , and $f_{\max}$ for trained 1.5 Gbit/s, 3 Gbit/s, 6 Gbit/s, and 12 Gbit/s without SSC support ...	229
Table 66 – $f_{\min}$ , $f_c$ , $f_{\max}$ , and $SJ_{lf}$ for trained 1.5 Gbit/s, 3 Gbit/s, 6 Gbit/s, and 12 Gbit/s with SSC support.....	229
Table 67 – Delivered signal characteristics for OOB signals .....	230
Table 68 – SSC modulation types.....	230
Table 69 – SAS phy transmitter SSC modulation types.....	231
Table 70 – Expander phy transmitter SSC modulation types .....	232
Table 71 – Receiver SSC modulation types tolerance.....	232
Table 72 – Expander device center-spreading tolerance buffer .....	233
Table 73 – Output characteristics of the READY LED signal.....	235
Table 74 – Characteristics of the POWER DISABLE signal applied to the SAS target device.....	236
Table 75 – OOB signal timing specifications.....	237
Table 76 – OOB signal transmitter device requirements .....	238
Table 77 – OOB signal receiver device burst time detection requirements .....	240
Table 78 – OOB signal receiver device idle time detection requirements.....	240
Table 79 – OOB signal receiver device negation time detection requirements .....	240
Table 80 – SATA port selection signal transmitter device requirements.....	241
Table A.1 – JTPAT for RD+ .....	242
Table A.2 – JTPAT for RD- .....	243
Table D.1 – Crosstalk transmitter characteristics.....	295
Table D.2 – S-parameter files for transmitter devices connected to separable TxRx connection segment..	296
Table D.3 – The S-parameter files for a transmitter device connected to a non-separable TxRx connection segment.....	298
Table D.4 – S-parameter files for a TxRx connection segment .....	301
Table D.5 – S-parameter files for stressed receiver device delivered signal calibration.....	303
Table F.1 – High frequency jitter source amplitudes.....	325
Table F.2 – Low frequency jitter source calibration amplitudes .....	327
Table F.3 – Low frequency jitter attenuation targets .....	328
Table J.1 – Standards bodies .....	338