

ISO/IEC 14763-4:2018-02 (E)

Information technology - Implementation and operation of customer premises cabling - Part 4: Measurement of end-to-end (E2E)-Links

CONTENTS

- FOREWORD.....3
- INTRODUCTION.....4
- 1 Scope.....5
- 2 Normative references5
- 3 Terms, definitions and abbreviated terms6
 - 3.1 Terms and definitions.....6
 - 3.2 Abbreviated terms.....6
- 4 Conformance.....6
- 5 Configuration and limits of performance of E2E link.....6
- 6 Test configuration of E2E link7
- 7 E2E link testing7
- 8 Laboratory testing of E2E link.....7
- 9 Field testing of E2E link.....8
 - 9.1 Visual inspection.....8
 - 9.2 Requirements of field test equipment.....8
 - 9.3 Field test measurement parameters8
- 10 Test head requirements8
 - 10.1 General.....8
 - 10.2 Test head requirements according to the IEC 60603-7 series.....8
 - 10.3 Test head requirements of IEC 61076-2-1019
 - 10.4 Test head requirements of IEC 61076-2-1099
- Annex A (normative) Additional requirements for test head designs10
 - A.1 General.....10
 - A.2 Outline of additional NEXT requirements.....10
 - A.3 Additional test head requirements10
 - A.3.1 Category 5 test head requirements10
 - A.3.2 Category 6 test head requirements11
- Bibliography.....12

- Figure 1 – Reference planes and configuration of E2E link7

- Table A.1 – Category 5 E2E link test head de-embedded NEXT performance in the range of frequency of $50 \text{ MHz} \leq f < 100 \text{ MHz}$ 11
- Table A.2 – Category 6 E2E link test head de-embedded NEXT performance in the range of frequency of $50 \text{ MHz} \leq f < 250 \text{ MHz}$ 11