ISO/IEC 14776-263:2018-10 (E)

Information technology - Small computer system interface (SCSI) - Part 263: SAS protocol layer - 3 (SPL-3)

FOREWORD ... 39
INTRODUCTION ... 41
SCSI standards family ... 42

1 Scope ... 44

2 Normative references ... 45

3 Terms, definitions, symbols, abbreviations, keywords, and conventions ... 46
3.1 Terms and definitions ... 46
3.2 Symbols and abbreviations ... 75
3.2.1 Abbreviations ... 75
3.2.2 Units ... 77
3.2.3 Symbols ... 77
3.2.4 Mathematical operators ... 78
3.3 Keywords ... 78
3.4 Editorial conventions ... 79
3.5 Numeric and character conventions ... 80
3.5.1 Numeric conventions ... 80
3.5.2 Units of measure ... 81
3.5.3 Byte encoded character strings conventions ... 82
3.6 UML notation conventions ... 82
3.6.1 Notation conventions overview ... 82
3.6.2 Constraint and note conventions ... 82
3.6.3 Class diagram conventions ... 83
3.6.4 Object diagram conventions ... 88
3.7 State machine conventions ... 90
3.7.1 State machine conventions overview ... 90
3.7.2 Transitions ... 91
3.7.3 Messages, requests, indications, confirmations, responses, and event notifications ... 91
3.7.4 State machine counters, timers, and variables ... 91
3.7.5 State machine arguments ... 92
3.8 Bit and byte ordering ... 92
3.9 Notation for procedures and functions ... 93

4 General ... 94
4.1 Architecture ... 94
4.1.1 Architecture overview ... 94
4.1.2 Physical links and phys ... 96
4.1.3 Logical links ... 100
4.1.4 Narrow ports and wide ports ... 100
4.1.5 Application clients and device servers ... 104
4.1.6 SAS devices ... 104
4.1.7 Expander devices ... 105
4.1.8 Service delivery subsystem ... 106
4.1.9 Domains ... 107
4.1.10 Expander device topologies ... 110
4.1.10.1 Expander device topology overview ... 110
4.1.10.2 Expander device topologies ... 111
4.1.11 Pathways ... 113
4.1.12 Connections ... 113
4.1.13 Persistent connections ... 115
4.1.13.1 Persistent connection operation ... 115
4.1.13.2 Persistent connection support ... 116
4.1.14 Advancing credit ... 116
4.1.15 Broadcasts ... 116
4.2 Names and identifiers ... 118

4.2.1 Names and identifiers overview 118
4.2.2 NAA IEEE Registered format identifier 120
4.2.3 NAA Locally Assigned format identifier 121
4.2.4 SAS address 121
4.2.5 Hashed SAS addresses 121
4.2.6 Device names and expander device SAS addresses 122
4.2.7 Device names for SATA devices with world wide names 123
4.2.8 Port names 123
4.2.9 Port identifiers and SAS port SAS addresses 123
4.2.10 Phy identifiers 124
4.3 State machines 125
4.3.1 State machine overview 125
4.3.2 Transmit data path 126
4.3.3 Receive data path 131
4.3.4 State machines and SAS Device, SAS Port, and SAS Phy classes 135
4.4 Events 137
4.4.1 Reset sequences 137
4.4.2 Hard reset 139
4.4.2.1 Hard reset overview 139
4.4.2.2 Additional hard reset processing by SAS ports 139
4.4.2.3 Additional hard reset processing by expander ports 139
4.4.3 I_T nexus loss 139
4.4.4 Power loss expected 140
4.5 Expander device model 141
4.5.1 Expander device model overview 141
4.5.2 Expander ports 142
4.5.3 Expander connection manager (ECM) 143
4.5.4 Expander connection router (ECR) 143
4.5.5 Broadcast propagation processor (BPP) 144
4.5.6 Expander device interfaces 144
4.5.6.1 Expander device interface overview 144
4.5.6.2 Expander device interfaces detail 146
4.5.6.3 ECM interface 147
4.5.6.4 ECR interface 149
4.5.6.5 BPP interface 151
4.5.7 Expander device routing 152
4.5.7.1 Routing attributes and routing methods 152
4.5.7.2 Expander device topology routing attribute restrictions 153
4.5.7.3 Connection request routing 153
4.5.7.4 Expander route table 153
4.5.7.4.1 Expander route table overview 153
4.5.7.4.2 Phy-based expander route table 154
4.5.7.4.3 Expander-based expander route table 155
4.5.8 Expander device reduced functionality 155
4.5.9 Broadcast (Expander) handling 156
4.6 Discover process 156
4.6.1 Discover process overview 156
4.6.2 Starting the discover process (Broadcast (Change) handling) 156
4.6.3 Discover process traversal 157
4.6.4 Discover process in a self-configuring expander device 159
4.6.5 Enabling multiplexing 160
4.7 Configuration subprocess 160
4.7.1 Configuration subprocess overview 160
4.7.2 Allowed expander device topologies 161
4.7.3 Externally configurable expander device route table optimization 162
4.7.4 Externally configurable expander device expander route index order 163
4.8 Zoning 170

4.8.1 Zoning overview ... 170
4.8.2 Zoning expander device requirements ... 174
4.8.3 Zoning operation ... 177
4.8.3.1 Zone phy information ... 177
4.8.3.2 Zone groups ... 179
4.8.3.3 Zone permission table ... 180
4.8.3.4 Zoning expander route table ... 182
4.8.3.5 Source zone group and destination zone group determination ... 183
4.8.4 Zone phy information and link reset sequences ... 184
4.8.5 Broadcast processing in a zoning expander device with zoning enabled ... 187
4.8.6 Zone configuration ... 188
4.8.6.1 Zone configuration overview ... 188
4.8.6.2 Lock step ... 188
4.8.6.3 Load step ... 189
4.8.6.4 Activate step ... 190
4.8.6.5 Unlock step ... 190
4.8.6.6 Zone lock inactivity timer ... 191
4.8.6.7 Enable a zoning expander device ... 191
4.9 SAS device and expander device power conditions ... 191
4.10 Phy power conditions ... 192
4.10.1 Low phy power conditions ... 192
4.10.1.1 Low phy power conditions overview ... 192
4.10.1.2 Active phy power condition ... 192
4.10.1.3 Partial phy power condition ... 192
4.10.1.4 Slumber phy power condition ... 192
4.10.1.5 End device low phy power conditions ... 193
4.10.1.6 Expander device low phy power conditions ... 193
4.10.2 SATA phy power conditions ... 194
4.11 Phy test functions ... 194
4.11.1 Phy test functions overview ... 194
4.11.2 Transmit pattern phy test function ... 195
4.12 Phy events ... 195
4.13 Using POWER DISABLE signal to create a power on event ... 200
4.13.1 Using POWER DISABLE signal to create a power on event overview ... 200
4.13.2 Discovering POWER DISABLE signal support ... 200
4.13.3 Using a management device server to control the POWER DISABLE signal ... 201

5 Phy layer ... 202
5.1 Phy layer overview ... 202
5.2 8b10b coding ... 202
5.2.1 8b10b coding overview ... 202
5.2.2 8b10b coding notation conventions ... 202
5.3 Character encoding and decoding ... 203
5.3.1 Character encoding and decoding overview ... 203
5.3.2 Bit transmission order ... 203
5.3.3 Character transmission order ... 203
5.3.4 Frame transmission order ... 204
5.3.5 Running disparity (RD) ... 204
5.3.6 Data characters ... 204
5.3.7 Control characters ... 210
5.3.8 Encoding characters in the transmitter ... 211
5.3.9 Decoding characters in the receiver ... 211
5.4 Dwords, primitives, data dwords, and invalid dwords ... 212
5.5 Bit order ... 212
5.6 Out of band (OOB) signals ... 214
5.6.1 OOB signals overview ... 214
5.6.2 Transmission of OOB signals ... 215

5.6.3 Receiver detection of OOB signals 216
5.6.4 SATA port selection signal 218
5.6.5 Phy power conditions 218
5.7 Phy capabilities bits 218
5.8 BMC coding 222
5.8.1 BMC coding overview 222
5.8.2 TTIU bit cell encoding in the transmitter 223
5.8.3 TTIU bit transmission order 224
5.8.4 TTIU bit cell decoding in the receiver 224
5.9 Train_Tx-SNW TTIUs 225
5.9.1 Train_Tx-SNW TTIU format 225
5.9.2 Control/Status TTIU 226
5.9.3 Error Response TTIU 230
5.10 Phy reset sequences 233
5.10.1 Phy reset sequences overview 233
5.10.2 SATA phy reset sequence 234
5.10.2.1 SATA OOB sequence 234
5.10.2.2 SATA speed negotiation sequence 234
5.10.3 SAS to SATA phy reset sequence 235
5.10.4 SAS to SAS phy reset sequence 236
5.10.4.1 SAS OOB sequence 236
5.10.4.2 SAS speed negotiation sequence 239
5.10.4.2.1 SAS speed negotiation sequence overview 239
5.10.4.2.2 SAS speed negotiation sequence timing specifications 240
5.10.4.2.3 Speed negotiation window (SNW) definitions 241
5.10.4.2.3.1 SNW definitions overview 241
5.10.4.2.3.2 SNW-1, SNW-2, and Final-SNW 242
5.10.4.2.3.3 SNW-3 243
5.10.4.2.3.4 Train_Tx-SNW 245
5.10.4.2.3.4.1 Phy's transmitter initial condition 245
5.10.4.2.3.4.2 Transmitter training 245
5.10.4.2.3.4.3 Pattern marker 246
5.10.4.2.3.5 Train_Rx-SNW 248
5.10.4.2.4 SAS speed negotiation sequence 251
5.10.4.2.5 SAS speed negotiation sequence examples 252
5.10.4.2.6 Train_Tx pattern sequence 260
5.10.4.2.6.1 Train_Tx pattern sequence overview 260
5.10.4.2.6.2 Train_Tx pattern initial sequence 261
5.10.4.2.6.3 Train_Tx pattern handshake sequence 264
5.10.4.2.6.3.1 Train_Tx pattern handshake sequence overview 264
5.10.4.2.6.3.2 Attached phy's receiver increment or decrement request 264
5.10.4.2.6.3.3 Attached phy's receiver reference_1, reference_2, or no_equalization request 267
5.10.4.2.6.4 Train_Tx pattern completion sequence 269
5.10.4.2.6.5 Invalid TTIU sequence 272
5.10.4.3 Multiplexing sequence 273
5.10.5 Phy reset sequence after devices are attached 274
5.11 Phy power condition sequences 275
5.11.1 Transitioning from the active phy power condition to a low phy power condition 275
5.11.2 Transitioning from a low phy power condition to the active phy power condition 276
5.11.3 Events during low phy power condition 276
5.12 SP (phy layer) state machine 278
5.12.1 SP state machine overview 278
5.12.2 SP transmitter and SP receiver 280
5.12.3 OOB sequence states 283
5.12.3.1 OOB sequence states overview 283
5.12.3.2 SP0:OOB_COMINIT state 284
5.12.3.2.1 State description 284

5.12.3.2.2 Transition SP0:OOB_COMINIT to SP1:OOB_AwaitCOMX 285
5.12.3.2.3 Transition SP0:OOB_COMINIT to SP3:OOB_AwaitCOMINIT_Sent 285
5.12.3.2.4 Transition SP0:OOB_COMINIT to SP4:OOB_COMSAS 285
5.12.3.3 SP1:OOB_AwaitCOMX state 285
5.12.3.3.1 State description 285
5.12.3.3.2 Transition SP1:OOB_AwaitCOMX to SP0:OOB_COMINIT 285
5.12.3.3.3 Transition SP1:OOB_AwaitCOMX to SP4:OOB_COMSAS 285
5.12.3.4 SP2:OOB_NoCOMSASTimeout state 286
5.12.3.4.1 State description 286
5.12.3.4.2 Transition SP2:OOB_NoCOMSASTimeout to SP0:OOB_COMINIT 286
5.12.3.4.3 Transition SP2:OOB_NoCOMSASTimeout to SP4:OOB_COMSAS 286
5.12.3.5 SP3:OOB_AwaitCOMINIT_Sent state 286
5.12.3.5.1 State description 286
5.12.3.5.2 Transition SP3:OOB_AwaitCOMINIT_Sent to SP4:OOB_COMSAS 286
5.12.3.6 SP4:OOB_COMSAS state 286
5.12.3.6.1 State description 286
5.12.3.6.2 Transition SP4:OOB_COMSAS to SP5:OOB_AwaitCOMSAS_Sent 287
5.12.3.6.3 Transition SP4:OOB_COMSAS to SP6:OOB_AwaitNoCOMSAS 287
5.12.3.6.4 Transition SP4:OOB_COMSAS to SP7:OOB_AwaitCOMSAS 287
5.12.3.7 SP5:OOB_AwaitCOMSAS_Sent state 287
5.12.3.7.1 State description 287
5.12.3.7.2 Transition SP5:OOB_AwaitCOMSAS_Sent to SP6:OOB_AwaitNoCOMSAS 287
5.12.3.8 SP6:OOB_AwaitNoCOMSAS state 287
5.12.3.8.1 State description 287
5.12.3.8.2 Transition SP6:OOB_AwaitNoCOMSAS to SP0:OOB_COMINIT 287
5.12.3.8.3 Transition SP6:OOB_AwaitNoCOMSAS to SP8:SAS_Start 288
5.12.3.9 SP7:OOB_AwaitCOMSAS state 288
5.12.3.9.1 State description 288
5.12.3.9.2 Transition SP7:OOB_AwaitCOMSAS to SP2:OOB_NoCOMSASTimeout 288
5.12.3.9.3 Transition SP7:OOB_AwaitCOMSAS to SP6:OOB_AwaitNoCOMSAS 288
5.12.3.9.4 Transition SP7:OOB_AwaitCOMSAS to SP16:SATA_COMWAKE 288
5.12.3.9.5 Transition SP7:OOB_AwaitCOMSAS to SP26:SATA _SpinupHold 288
5.12.4 SAS speed negotiation states 289
5.12.4.1 SAS speed negotiation states overview 289
5.12.4.2 Negotiation idle 289
5.12.4.3 SP8:SAS_Start state 292
5.12.4.3.1 State description 292
5.12.4.3.2 Transition SP8:SAS_Start to SP0:OOB_COMINIT 292
5.12.4.3.3 Transition SP8:SAS_Start to SP1:OOB_AwaitCOMX 293
5.12.4.3.4 Transition SP8:SAS_Start to SP9:SAS_WindowNotSupported 293
5.12.4.3.5 Transition SP8:SAS_Start to SP10:SAS_AwaitALIGN 293
5.12.4.3.6 Transition SP8:SAS_Start to SP27:SAS_Settings 293
5.12.4.4 SP9:SAS_WindowNotSupported state 293
5.12.4.4.1 State description 293
5.12.4.4.2 Transition SP9:SAS_WindowNotSupported to SP0:OOB_COMINIT 293
5.12.4.4.3 Transition SP9:SAS_WindowNotSupported to SP14:SAS_Fail 293
5.12.4.5 SP10:SAS_AwaitALIGN state 293
5.12.4.5.1 State description 293
5.12.4.5.2 Transition SP10:SAS_AwaitALIGN to SP0:OOB_COMINIT 294
5.12.4.5.3 Transition SP10:SAS_AwaitALIGN to SP11:SAS_AwaitALIGN1 294
5.12.4.5.4 Transition SP10:SAS_AwaitALIGN to SP12:SAS_AwaitSNW 294
5.12.4.5.5 Transition SP10:SAS_AwaitALIGN to SP14:SAS_Fail 294
5.12.4.6 SP11:SAS_AwaitALIGN1 state 294
5.12.4.6.1 State description 294
5.12.4.6.2 Transition SP11:SAS_AwaitALIGN1 to SP0:OOB_COMINIT 294
5.12.4.6.3 Transition SP11:SAS_AwaitALIGN1 to SP12:SAS_AwaitSNW 294
5.12.4.6.4 Transition SP11:SAS_AwaitALIGN1 to SP14:SAS_Fail 294

5.12.4.7 SP12:SAS_AwaitSNW state 295
5.12.4.7.1 State description 295
5.12.4.7.2 Transition SP12:SAS_AwaitSNW to SP0:OOB_COMINIT 295
5.12.4.7.3 Transition SP12:SAS_AwaitSNW to SP13:SAS_Pass 295
5.12.4.8 SP13:SAS_Pass state 295
5.12.4.8.1 State description 295
5.12.4.8.2 Transition SP13:SAS_Pass to SP0:OOB_COMINIT 295
5.12.4.8.3 Transition SP13:SAS_Pass to SP8:SAS_Start 295
5.12.4.8.4 Transition SP13:SAS_Pass to SP15:SAS_PHY_Ready 296
5.12.4.9 SP14:SAS_Fail state 296
5.12.4.9.1 State description 296
5.12.4.9.2 Transition SP14:SAS_Fail to SP1:OOB_AwaitCOMX 296
5.12.4.9.3 Transition SP14:SAS_Fail to SP8:SAS_Start 296
5.12.4.10 SP15:SAS_PHY_Ready state 296
5.12.4.10.1 State description 296
5.12.4.10.2 Transition SP15:SAS_PHY_Ready to SP0:OOB_COMINIT 297
5.12.4.10.3 Transition SP15:SAS_PHY_Ready to SP31:SAS_PS_Low_Phy_Power 297
5.12.4.11 SP27:SAS_Settings state 297
5.12.4.11.1 State description 297
5.12.4.11.2 Transition SP27:SAS_Settings to SP0:OOB_COMINIT 297
5.12.4.11.3 Transition SP27:SAS_Settings to SP1:OOB_AwaitCOMX 298
5.12.4.11.4 Transition SP27:SAS_Settings to SP8:SAS_Start 298
5.12.4.11.5 Transition SP27:SAS_Settings to SP28:SAS_TrainSetup 298
5.12.4.12 SP28:SAS_TrainSetup 298
5.12.4.12.1 State description 298
5.12.4.12.2 Transition SP28:SAS_TrainSetup to SP0:OOB_COMINIT 299
5.12.4.12.3 Transition SP28:SAS_TrainSetup to SP29:SAS_Train_Rx 299
5.12.4.12.4 Transition SP28:SAS_TrainSetup to SP34:SAS_Train_Tx 299
5.12.4.13 SP34:SAS_Train_Tx state 299
5.12.4.13.1 State description 299
5.12.4.13.2 Transition SP34:SAS_Train_Tx to SP1:OOB_AwaitCOMX 299
5.12.4.13.3 Transition SP34:SAS_Train_Tx to SP28:SAS_TrainSetup 299
5.12.4.13.4 Transition SP34:SAS_Train_Tx to SP29:SAS_Train_Rx 300
5.12.4.14 SP29:SAS_Train_Rx state 300
5.12.4.14.1 State description 300
5.12.4.14.2 Transition SP29:SAS_Train_Rx to SP0:OOB_COMINIT 300
5.12.4.14.3 Transition SP29:SAS_Train_Rx to SP1:OOB_AwaitCOMX 300
5.12.4.14.4 Transition SP29:SAS_Train_Rx to SP28:SAS_TrainSetup 301
5.12.4.14.5 Transition SP29:SAS_Train_Rx to SP30:SAS_TrainingDone 301
5.12.4.15 SP30:SAS_TrainingDone state 301
5.12.4.15.1 State description 301
5.12.4.15.2 Transition SP30:SAS_TrainingDone to SP0:OOB_COMINIT 301
5.12.4.15.3 Transition SP30:SAS_TrainingDone to SP1:OOB_AwaitCOMX 302
5.12.4.15.4 Transition SP30:SAS_TrainingDone to SP28:SAS_TrainSetup 302
5.12.4.15.5 Transition SP30:SAS_TrainingDone to SP15:SAS_PHY_Ready 302
5.12.5 SAS phy power conditions states 302
5.12.5.1 SAS phy power conditions states overview 302
5.12.5.2 SP31:SAS_PS_Low_Phy_Power state 303
5.12.5.2.1 State description 303
5.12.5.2.2 Transition SP31:SAS_PS_Low_Phy_Power to SP0:OOB_COMINIT 304
5.12.5.2.3 Transition SP31:SAS_PS_Low_Phy_Power to SP32:SAS_PS_ALIGN0 304
5.12.5.3 SP32:SAS_PS_ALIGN0 state 304
5.12.5.3.1 State description 304
5.12.5.3.2 Transition SP32:SAS_PS _ALIGN0 state to SP0:OOB_COMINIT 304
5.12.5.3.3 Transition SP32:SAS_PS _ALIGN0 to SP33:SAS_PS _ALIGN1 305
5.12.5.4 SP33:SAS_PS_ALIGN1 state 305
5.12.5.4.1 State description 305

5.12.5.4.2 Transition SP33:SAS_PS_ALIGN1 state to SP0:OOB_COMINIT 305
5.12.5.4.3 Transition SP33:SAS_PS_ALIGN1 state to SP15:SAS_PHY_Ready 305
5.12.6 SATA host emulation states 305
5.12.6.1 SATA host emulation states overview 305
5.12.6.2 SP16:SATA_COMWAKE state 307
5.12.6.2.1 State description 307
5.12.6.2.2 Transition SP16:SATA_COMWAKE to SP0:OOB_COMINIT 307
5.12.6.2.3 Transition SP16:SATA_COMWAKE to SP17:SATA_AwaitCOMWAKE 307
5.12.6.3 SP17:SATA_AwaitCOMWAKE state 307
5.12.6.3.1 State description 307
5.12.6.3.2 Transition SP17:SATA_AwaitCOMWAKE to SP0:OOB_COMINIT 307
5.12.6.3.3 Transition SP17:SATA_AwaitCOMWAKE to SP18:SATA_AwaitNoCOMWAKE 307
5.12.6.4 SP18:SATA_AwaitNoCOMWAKE state 307
5.12.6.4.1 State description 307
5.12.6.4.2 Transition SP18:SATA_AwaitNoCOMWAKE to SP0:OOB_COMINIT 307
5.12.6.4.3 Transition SP18:SATA_AwaitNoCOMWAKE to SP19:SATA_AwaitALIGN 307
5.12.6.5 SP19:SATA_AwaitALIGN state 308
5.12.6.5.1 State description 308
5.12.6.5.2 Transition SP19:SATA_AwaitALIGN to SP0:OOB_COMINIT 308
5.12.6.5.3 Transition SP19:SATA_AwaitALIGN to SP20:SATA_AdjustSpeed 308
5.12.6.6 SP20:SATA_AdjustSpeed state 308
5.12.6.6.1 State description 308
5.12.6.6.2 Transition SP20:SATA_AdjustSpeed to SP0:OOB_COMINIT 308
5.12.6.6.3 Transition SP20:SATA_AdjustSpeed to SP21:SATA_TransmitALIGN 309
5.12.6.7 SP21:SATA_TransmitALIGN state 309
5.12.6.7.1 State description 309
5.12.6.7.2 Transition SP21:SATA_TransmitALIGN to SP0:OOB_COMINIT 309
5.12.6.7.3 Transition SP21:SATA_TransmitALIGN to SP22:SATA_PHY_Ready 309
5.12.6.8 SP22:SATA_PHY_Ready state 309
5.12.6.8.1 State description 309
5.12.6.8.2 Transition SP22:SATA_PHY_Ready to SP0:OOB_COMINIT 309
5.12.6.8.3 Transition SP22:SATA_PHY_Ready to SP23:SATA_PM_Partial 310
5.12.6.8.4 Transition SP22:SATA_PHY_Ready to SP24:SATA_PM_Slumber 310
5.12.6.9 SP23:SATA_PM_Partial state 310
5.12.6.9.1 State description 310
5.12.6.9.2 Transition SP23:SATA_PM_Partial to SP0:OOB_COMINIT 310
5.12.6.9.3 Transition SP23:SATA_PM_Partial to SP16:SATA_COMWAKE 310
5.12.6.9.4 Transition SP23:SATA_PM_Partial to SP19:SATA_AwaitALIGN 310
5.12.6.10 SP24:SATA_PM_Slumber state 310
5.12.6.10.1 State description 310
5.12.6.10.2 Transition SP24:SATA_PM_Slumber to SP0:OOB_COMINIT 310
5.12.6.10.3 Transition SP24:SATA_PM_Slumber to SP16:SATA_COMWAKE 311
5.12.6.10.4 Transition SP24:SATA_PM_Slumber to SP19:SATA_AwaitALIGN 311
5.12.7 SATA port selector state SP25:SATA_PortSel 311
5.12.7.1 State description 311
5.12.7.2 Transition SP25:SATA_PortSel to SP1:OOB_AwaitCOMX 311
5.12.8 SATA spinup hold state SP26:SATA_SpinupHold 312
5.12.8.1 State description 312
5.12.8.2 Transition SP26:SATA_SpinupHold to SP0:OOB_COMINIT 312
5.13 SP_DWS (phy layer dword synchronization) state machine 312
5.13.1 SP_DWS state machine overview 312
5.13.2 SP_DWS receiver 314
5.13.3 SP_DWS0:AcquireSync state 315
5.13.3.1 State description 315
5.13.3.2 Transition SP_DWS0:AcquireSync to SP_DWS1:Valid1 315
5.13.4 SP_DWS1:Valid1 state 316
5.13.4.1 State description 316

5.13.4.2 Transition SP_DWS1:Valid1 to SP_DWS0:AcquireSync 316
5.13.4.3 Transition SP_DWS1:Valid1 to SP_DWS2:Valid2 316
5.13.5 SP_DWS2:Valid2 state 316
5.13.5.1 State description 316
5.13.5.2 Transition SP_DWS2:Valid2 to SP_DWS0:AcquireSync 316
5.13.5.3 Transition SP_DWS2:Valid2 to SP_DWS3:SyncAcquired 316
5.13.6 SP_DWS3:SyncAcquired state 316
5.13.6.1 State description 316
5.13.6.2 Transition SP_DWS3:SyncAcquired to SP_DWS0:AcquireSync 317
5.13.6.3 Transition SP_DWS3:SyncAcquired to SP_DWS4:Lost1 317
5.13.7 SP_DWS4:Lost1 state 317
5.13.7.1 State description 317
5.13.7.2 Transition SP_DWS4:Lost1 to SP_DWS0:AcquireSync 317
5.13.7.3 Transition SP_DWS4:Lost1 to SP_DWS5:Lost1Recovered 317
5.13.7.4 Transition SP_DWS4:Lost1 to SP_DWS6:Lost2 317
5.13.8 SP_DWS5:Lost1Recovered state 317
5.13.8.1 State description 317
5.13.8.2 Transition SP_DWS5:Lost1Recovered to SP_DWS0:AcquireSync 317
5.13.8.3 Transition SP_DWS5:Lost1Recovered to SP_DWS3:SyncAcquired 318
5.13.8.4 Transition SP_DWS5:Lost1Recovered to SP_DWS6:Lost2 318
5.13.9 SP_DWS6:Lost2 state 318
5.13.9.1 State description 318
5.13.9.2 Transition SP_DWS6:Lost2 to SP_DWS0:AcquireSync 318
5.13.9.3 Transition SP_DWS6:Lost2 to SP_DWS7:Lost2Recovered 318
5.13.9.4 Transition SP_DWS6:Lost2 to SP_DWS8:Lost3 318
5.13.10 SP_DWS7:Lost2Recovered state 318
5.13.10.1 State description 318
5.13.10.2 Transition SP_DWS7:Lost2Recovered to SP_DWS0:AcquireSync 318
5.13.10.3 Transition SP_DWS7:Lost2Recovered to SP_DWS4:Lost1 319
5.13.10.4 Transition SP_DWS7:Lost2Recovered to SP_DWS8:Lost3 319
5.13.11 SP_DWS8:Lost3 state 319
5.13.11.1 State description 319
5.13.11.2 Transition SP_DWS8:Lost3 to SP_DWS0:AcquireSync 319
5.13.11.3 Transition SP_DWS8:Lost3 to SP_DWS9:Lost3Recovered 319
5.13.12 SP_DWS9:Lost3Recovered state 319
5.13.12.1 State description 319
5.13.12.2 Transition SP_DWS9:Lost3Recovered to SP_DWS0:AcquireSync 319
5.13.12.3 Transition SP_DWS9:Lost3Recovered to SP_DWS6:Lost2 320
5.14 PTT (phy layer transmitter training) state machines 320
5.14.1 PTT state machines overview 320
5.14.2 SP transmitter additions for transmitter training 320
5.14.2.1 SP transmitter additions for transmitter training overview 320
5.14.2.2 TTIU transmit setup 321
5.14.2.3 No_equalization, reference_1, and reference_2 coefficient settings request 321
5.14.2.4 Coefficient limits 321
5.14.2.5 Coefficient request result of update complete 321
5.14.2.5.1 Coefficient request processing 321
5.14.2.5.2 Coefficient adjustment completes 322
5.14.2.5.3 No coefficient adjustment 322
5.14.2.6 Coefficient request result of maximum 322
5.14.2.6.1 Coefficient request processing 322
5.14.2.6.2 Coefficient adjustment completes 323
5.14.2.6.3 No coefficient adjustment 323
5.14.2.7 Coefficient request result of minimum 323
5.14.2.7.1 Coefficient request processing 323
5.14.2.7.2 Coefficient adjustment completes 323
5.14.2.7.3 No coefficient adjustment 323

5.14.3 SP receiver additions for transmitter training 324
5.14.4 PTT_T (phy layer transmitter training transmit pattern) state machine 325
5.14.4.1 PTT_T state machine overview 325
5.14.4.2 PTT_T0:Idle state 327
5.14.4.2.1 State description 327
5.14.4.2.2 Transition PTT_T0:Idle to PTT_T1:Initialize 327
5.14.4.3 PTT_T1:Initialize state 327
5.14.4.3.1 State description 327
5.14.4.3.2 Transition PTT_T1:Initialize to PTT_T0:Idle 327
5.14.4.3.3 Transition PTT_T1:Initialize to PTT_T2:Tx_Training 328
5.14.4.4 PTT_T2:Tx_Training state 328
5.14.4.4.1 State description 328
5.14.4.4.2 Entry conditions 328
5.14.4.4.3 Control word and status word mappings 329
5.14.4.4.4 Error message handling 330
5.14.4.4.5 Resetting attached phy's transmitter 330
5.14.4.4.6 Local phy's transmitter and attached phy's transmitter training completed 331
5.14.4.4.7 Transition PTT_T2:Tx_Training to PTT_T0:Idle 331
5.14.4.4.8 Transition PTT_T2:Tx_Training to PTT_T3:Local_Tx_Training 332
5.14.4.5 PTT_T3:Local_Tx_Training state 332
5.14.4.5.1 State description 332
5.14.4.5.2 Entry conditions 332
5.14.4.5.3 Status word mappings 332
5.14.4.5.4 Local phy's transmitter and attached phy's transmitter training completed 332
5.14.4.5.5 Error message handling 333
5.14.4.5.6 Transition PTT_T3:Local_Tx_Training to PTT_T0:Idle 333
5.14.5 PTT_R (phy layer transmitter training receive pattern) state machine 333
5.14.5.1 PTT_R state machine overview 333
5.14.5.2 PTT_R0:Idle state 335
5.14.5.2.1 State description 335
5.14.5.2.2 Transition PTT_R0:Idle to PTT_R1:Initialize 335
5.14.5.3 PTT_R1:Initialize state 335
5.14.5.3.1 State description 335
5.14.5.3.2 Transition PTT_R1:Initialize to PTT_R0:Idle 335
5.14.5.3.3 Transition PTT_R1:Initialize to PTT_R2:Receive_Train_Tx_Pattern 335
5.14.5.4 PTT_R2:Receive_Train_Tx_Pattern state 335
5.14.5.4.1 State description 335
5.14.5.4.2 Transition PTT_R2:Receive_Train_Tx_Pattern to PTT_R0:Idle 341
5.14.5.4.3 Transition PTT_R2:Receive_Train_Tx_Pattern to PTT_R1:Initialize 341
5.14.6 PTT_SC (phy layer transmitter training set transmitter coefficient) state machines 341
5.14.6.1 PTT_SC (phy layer transmitter training set transmitter coefficient) state machines overview 341
5.14.6.2 PTT_SC1 state machine overview 343
5.14.6.3 PTT_SC1_0:Idle state 343
5.14.6.3.1 State description 343
5.14.6.3.2 Transition PTT_SC1_0:Idle to PTT_SC1_1:Wait_Inc_Dec 343
5.14.6.4 PTT_SC1_1:Wait_Inc_Dec state 343
5.14.6.4.1 State description 343
5.14.6.4.2 Transition PTT_SC1_1:Wait_Inc_Dec to PTT_SC1_0:Idle 343
5.14.6.4.3 Transition PTT_SC1_1:Wait_Inc_Dec to PTT_SC1_2:Set_Coefficient 343
5.14.6.5 PTT_SC1_2:Set_Coefficient state 344
5.14.6.5.1 State description 344
5.14.6.5.2 Transition PTT_SC1_2:Set_Coefficient to PTT_SC1_0:Idle 345
5.14.6.5.3 Transition PTT_SC1_2:Set_Coefficient to PTT_SC1_3:Wait_Hold 345
5.14.6.6 PTT_SC1_3:Wait_Hold state 345
5.14.6.6.1 State description 345
5.14.6.6.2 Transition PTT_SC1_3:Wait_Hold to PTT_SC1_0:Idle 345
5.14.6.6.3 Transition PTT_SC1_3:Wait_Hold to PTT_SC1_1:Wait_Inc_Dec 345

5.14.7 PTT_SC2 (phy layer transmitter training set transmitter coefficient 2) state machine 345
5.14.8 PTT_SC3 (phy layer transmitter training set transmitter coefficient 3) state machine 346
5.14.9 PTT_GC (phy layer transmitter training get transmitter coefficient) state machines 346
5.14.9.1 PTT_GC (phy layer transmitter training get transmitter coefficient) state machines overview 346
5.14.9.2 PTT_GC1 state machine 347
5.14.9.3 PTT_GC1_0:Idle state 348
5.14.9.3.1 State description 348
5.14.9.3.2 Transition PTT_GC1_0:Idle to PTT_GC1_1:Get_Coefficient 348
5.14.9.4 PTT_GC1_1:Get_Coefficient state 348
5.14.9.4.1 State description 348
5.14.9.4.2 Transition PTT_GC1_1:Get_Coefficient to PTT_GC1_0:Idle 348
5.14.9.4.3 Transition PTT_GC1_1:Get_Coefficient to PTT_GC1_2:Wait_Restart 348
5.14.9.5 PTT_GC1_2:Wait_Restart state 349
5.14.9.5.1 State description 349
5.14.9.5.2 Transition PTT_GC1_2:Wait_Restart to PTT_GC1_0:Idle 349
5.14.10 PTT_GC2 (phy layer transmitter training get transmitter coefficient 2) state machine 349
5.14.11 PTT_GC3 (phy layer transmitter training get transmitter coefficient 3) state machine 349
5.14.12 PTT_PL (phy layer transmitter training pattern lock) state machine 350
5.14.12.1 PTT_PL state machine overview 350
5.14.12.2 PTT_PL0:Idle state 351
5.14.12.2.1 State description 351
5.14.12.2.2 Transition PTT_PL0:Idle to PTT_PL1:Acquire_Lock 352
5.14.12.3 PTT_PL1:Acquire_Lock state 352
5.14.12.3.1 State description 352
5.14.12.3.2 Transition PTT_PL1:Acquire_Lock to PTT_PL2:Valid 352
5.14.12.4 PTT_PL2:Valid state 352
5.14.12.4.1 State description 352
5.14.12.4.2 Transition PTT_PL2:Valid to PTT_PL1:Acquire_Lock 352
5.14.12.4.3 Transition PTT_PL2:Valid to PTT_PL3:Lock_Acquired 352
5.14.12.5 PTT_PL3:Lock_Acquired state 352
5.14.12.5.1 State description 352
5.14.12.5.2 Transition PTT_PL3:Lock_Acquired to PTT_PL4:Lost1 352
5.14.12.6 PTT_PL4:Lost1 state 353
5.14.12.6.1 State description 353
5.14.12.6.2 Transition PTT_PL4:Lost1 to PTT_PL3:Lock_Acquired 353
5.14.12.6.3 Transition PTT_PL4:Lost1 to PTT_PL5:Lost2 353
5.14.12.7 PTT_PL5:Lost2 state 353
5.14.12.7.1 State description 353
5.14.12.7.2 Transition PTT_PL5:Lost2 to PTT_PL3:Lock_Acquired 353
5.14.12.7.3 Transition PTT_PL5:Lost2 to PTT_PL6:Lost3 353
5.14.12.8 PTT_PL6:Lost3 state 353
5.14.12.8.1 State description 353
5.14.12.8.2 Transition PTT_PL6:Lost3 to PTT_PL3:Lock_Acquired 353
5.14.12.8.3 Transition PTT_PL6:Lost3 to PTT_PL7:Lost4 353
5.14.12.9 PTT_PL7:Lost4 state 353
5.14.12.9.1 State description 353
5.14.12.9.2 Transition PTT_PL7:Lost4 to PTT_PL3:Lock_Acquired 354
5.14.12.9.3 Transition PTT_PL7:Lost4 to PTT_PL1:Acquire_Lock 354
5.15 Multiplexing 354
5.16 Spinup 355

6 Link layer 356
6.1 Link layer overview 356
6.2 Primitives 356
6.2.1 Primitives overview 356
6.2.2 Primitive summary 357
6.2.3 Primitive encodings 366

6.2.4 Primitive sequences 371
6.2.4.1 Primitive sequences overview 371
6.2.4.2 Single primitive sequence 371
6.2.4.3 Repeated primitive sequence 371
6.2.4.4 Continued primitive sequence 372
6.2.4.5 Extended primitive sequence 372
6.2.4.6 Triple primitive sequence 373
6.2.4.7 Redundant primitive sequence 374
6.2.5 Deletable primitives 375
6.2.5.1 ALIGN 375
6.2.5.2 MUX (Multiplex) 376
6.2.5.3 NOTIFY 377
6.2.5.3.1 NOTIFY overview 377
6.2.5.3.2 NOTIFY (ENABLE SPINUP) 377
6.2.5.3.3 NOTIFY (POWER LOSS EXPECTED) 378
6.2.5.4 OOB_IDLE 379
6.2.6 Primitives not specific to type of connections 379
6.2.6.1 AIP (Arbitration in progress) 379
6.2.6.2 BREAK 379
6.2.6.3 BREAK_REPLY 380
6.2.6.4 BROADCAST 380
6.2.6.5 CLOSE 380
6.2.6.6 EOAF (End of address frame) 381
6.2.6.7 ERROR 381
6.2.6.8 HARD_RESET 381
6.2.6.9 OPEN_ACCEPT 381
6.2.6.10 OPEN_REJECT 381
6.2.6.11 PS_ACK 384
6.2.6.12 PS_NAK 384
6.2.6.13 PS_REQ 384
6.2.6.14 PWR_ACK 384
6.2.6.15 PWR_DONE 384
6.2.6.16 PWR_GRANT 384
6.2.6.17 PWR_REQ 384
6.2.6.18 SOAF (Start of address frame) 385
6.2.6.19 TRAIN 385
6.2.6.20 TRAIN_DONE 385
6.2.7 Primitives used only inside SSP and SMP connections 385
6.2.7.1 ACK (Acknowledge) 385
6.2.7.2 CREDIT_BLOCKED 385
6.2.7.3 DONE 385
6.2.7.4 EOF (End of frame) 386
6.2.7.5 EXTEND_CONNECTION 386
6.2.7.6 NAK (Negative acknowledgement) 386
6.2.7.7 RRDY (Receiver ready) 387
6.2.7.8 SOF (Start of frame) 387
6.2.8 Primitives used only inside STP connections and on SATA physical links 387
6.2.8.1 SATA_ERROR 387
6.2.8.2 SATA_PMACK, SATA_PMNAK, SATA_PMREQ_P, and SATA_PMREQ_S (Power management acknowledgements and requests) 388
6.2.8.3 SATA_HOLD and SATA_HOLDA (Hold and hold acknowledge) 388
6.2.8.4 SATA_R_RDY and SATA_X_RDY (Receiver ready and transmitter ready) 388
6.2.8.5 Other primitives used inside STP connections and on SATA physical links 388
6.3 Physical link rate tolerance management 388
6.3.1 Physical link rate tolerance management overview 388
6.3.2 Phys originating dwords 389
6.3.3 Expander phys forwarding dwords 390

6.4 Idle physical links ... 391
6.5 CRC ... 391
6.5.1 CRC overview ... 391
6.5.2 CRC generation ... 393
6.5.3 CRC checking ... 395
6.6 Scrambling ... 396
6.7 Bit order of CRC and scrambler ... 398
6.8 Address frames ... 401
6.8.1 Address frames overview ... 401
6.8.2 IDENTIFY address frame ... 403
6.8.3 OPEN address frame ... 407
6.9 Link reset sequence ... 411
6.9.1 Link reset sequence overview ... 411
6.9.2 Expander device handling of link reset sequences ... 414
6.10 SL_IR (link layer identification and hard reset) state machines ... 414
6.10.1 SL_IR state machines overview ... 414
6.10.2 SL_IR transmitter and receiver ... 416
6.10.3 SL_IR_TIR (transmit IDENTIFY or HARD_RESET) state machine ... 416
6.10.3.1 SL_IR_TIR state machine overview ... 416
6.10.3.2 SL_IR_TIR1:Idle state ... 417
6.10.3.2.1 State description ... 417
6.10.3.2.2 Transition SL_IR_TIR1:Idle to SL_IR_TIR2:Transmit_Identify ... 417
6.10.3.2.3 Transition SL_IR_TIR1:Idle to SL_IR_TIR3:Transmit_Hard_Reset ... 417
6.10.3.3 SL_IR_TIR2:Transmit_Identify state ... 417
6.10.3.3.1 State description ... 417
6.10.3.3.2 Transition SL_IR_TIR2:Transmit_Identify to SL_IR_TIR4:Completed ... 417
6.10.3.4 SL_IR_TIR3:Transmit_Hard_Reset state ... 417
6.10.3.4.1 State description ... 417
6.10.3.4.2 Transition SL_IR_TIR3:Transmit_Hard_Reset to SL_IR_TIR4:Completed ... 417
6.10.3.5 SL_IR_TIR4:Completed state ... 418
6.10.4 SL_IR_RIF (receive IDENTIFY address frame) state machine ... 418
6.10.4.1 SL_IR_RIF state machine overview ... 418
6.10.4.2 SL_IR_RIF1:Idle state ... 418
6.10.4.2.1 State description ... 418
6.10.4.2.2 Transition SL_IR_RIF1:Idle to SL_IR_RIF2:Receive_Identify_Frame ... 418
6.10.4.3 SL_IR_RIF2:Receive_Identify_Frame state ... 418
6.10.4.3.1 State description ... 418
6.10.4.3.2 Transition SL_IR_RIF2:Receive_Identify_Frame to SL_IR_RIF3:Completed ... 419
6.10.4.4 SL_IR_RIF3:Completed state ... 419
6.10.5 SL_IR_IRC (identification and hard reset control) state machine ... 419
6.10.5.1 SL_IR_IRC state machine overview ... 419
6.10.5.2 SL_IR_IRC1:Idle state ... 419
6.10.5.2.1 State description ... 419
6.10.5.2.2 Transition SL_IR_IRC1:Idle to SL_IR_IRC2:Wait ... 419
6.10.5.3 SL_IR_IRC2:Wait state ... 419
6.10.5.3.1 State description ... 419
6.10.5.3.2 Transition SL_IR_IRC2:Wait to SL_IR_IRC3:Completed ... 420
6.10.5.4 SL_IR_IRC3:Completed state ... 420
6.11 Entering a low phy power condition ... 421
6.12 Power control and SL_P (link layer power control) state machines ... 421
6.12.1 Power source device ... 421
6.12.2 Power consumer device ... 422
6.12.3 NOTIFY (ENABLE SPINUP) usage ... 422
6.12.4 SL_P_S (link layer power source device) state machine ... 423
6.12.4.1 SL_P_S state machine overview ... 423
6.12.4.2 SL_P_S transmitter and SL_P_S receiver ... 424
6.12.4.3 SL_P_S_1:Idle state ... 425

6.12.4.3.1 State description 425
6.12.4.3.2 Transition SL_P_S_1:Idle to SL_P_S_2:Wait_Grant 425
6.12.4.4 SL_P_S_2:Wait_Grant state 425
6.12.4.4.1 State description 425
6.12.4.4.2 Transition SL_P_S_2:Wait_Grant to SL_P_S_1:Idle 426
6.12.4.4.3 Transition SL_P_S_2:Wait_Grant to SL_P_S_3:Wait_Done 426
6.12.4.5 SL_P_S_3:Wait_Done state 426
6.12.4.5.1 State description 426
6.12.4.5.2 Transition SL_P_S_3:Wait_Done to SL_P_S_1:Idle 427
6.12.5 SL_P_C (link layer power consumer device) state machine 427
6.12.5.1 SL_P_C state machine overview 427
6.12.5.2 SL_P_C receiver 429
6.12.5.3 SL_P_C_1:Idle state 429
6.12.5.3.1 State description 429
6.12.5.3.2 Transition SL_P_C_1:Idle to SL_P_C_2:Request_Power 429
6.12.5.4 SL_P_C_2:Request_Power state 429
6.12.5.4.1 State description 429
6.12.5.4.2 Transition SL_P_C_2:Request_Power to SL_P_C_1:Idle 430
6.12.5.4.3 Transition SL_P_C_2:Request_Power to SL_P_C_3:Wait_Grant 430
6.12.5.4.4 Transition SL_P_C_2:Request_Power to SL_P_C_4:Wait_Done 430
6.12.5.5 SL_P_C_3:Wait_Grant state 430
6.12.5.5.1 State description 430
6.12.5.5.2 Transition SL_P_C_3:Wait_Grant to SL_P_C_1:Idle 431
6.12.5.5.3 Transition SL_P_C_3:Wait_Grant to SL_P_C_4:Wait_Done 431
6.12.5.6 SL_P_C_4:Wait_Done state 431
6.12.5.6.1 State description 431
6.12.5.6.2 Transition SL_P_C_4:Wait_Done to SL_P_C_1:Idle 431
6.13 SAS domain changes (Broadcast (Change) usage) 432
6.14 Connections 433
6.14.1 Connections overview 433
6.14.2 Opening a connection 433
6.14.2.1 Connection request 433
6.14.2.2 Results of a connection request 435
6.14.3 Arbitration fairness 435
6.14.4 Arbitration inside an expander device 436
6.14.4.1 Expander logical phy arbitration requirements 436
6.14.4.2 ECM arbitration requirements 437
6.14.4.2.1 ECM arbitration requirements overview 437
6.14.4.2.2 Arbitrating confirmations 438
6.14.4.2.3 Arb Won confirmation 438
6.14.4.2.4 Arb Lost confirmation 439
6.14.4.2.5 Arb Reject confirmation 439
6.14.4.3 Arbitration status 440
6.14.4.4 Partial Pathway Timeout timer 440
6.14.4.5 Pathway recovery 441
6.14.5 BREAK handling 441
6.14.6 Aborting a connection request 442
6.14.7 Expander device request for an SSP connection close 444
6.14.8 Closing a connection 444
6.14.9 Breaking a connection 445
6.15 Rate matching 446
6.16 SL (link layer for SAS logical phys) state machines 449
6.16.1 SL state machines overview 449
6.16.2 SL transmitter and receiver 452
6.16.3 SL_RA (receive OPEN address frame) state machine 454
6.16.4 SL_CC (connection control) state machine 454
6.16.4.1 SL_CC state machine overview 454

6.16.4.2 SL_CC0:Idle state ... 456
6.16.4.2.1 State description ... 456
6.16.4.2.2 Transition SL_CC0:Idle to SL_CC1:ArbSel ... 458
6.16.4.2.3 Transition SL_CC0:Idle to SL_CC2:Selected ... 458
6.16.4.2.4 Transition SL_CC0:Idle to SL_CC8:PS_Request ... 459
6.16.4.2.5 Transition SL_CC0:Idle to SL_CC9:PS_Quiet ... 459
6.16.4.3 SL_CC1:ArbSel state ... 459
6.16.4.3.1 State description ... 459
6.16.4.3.2 Transition SL_CC1:ArbSel to SL_CC0:Idle ... 461
6.16.4.3.3 Transition SL_CC1:ArbSel to SL_CC2:Selected ... 461
6.16.4.3.4 Transition SL_CC1:ArbSel to SL_CC3:Connected ... 461
6.16.4.3.5 Transition SL_CC1:ArbSel to SL_CC5:BreakWait ... 462
6.16.4.3.6 Transition SL_CC1:ArbSel to SL_CC6:Break ... 462
6.16.4.4 SL_CC2:Selected state ... 462
6.16.4.4.1 State description ... 462
6.16.4.4.2 Transition SL_CC2:Selected to SL_CC0:Idle ... 463
6.16.4.4.3 Transition SL_CC2:Selected to SL_CC3:Connected ... 463
6.16.4.4.4 Transition SL_CC2:Selected to SL_CC5:BreakWait ... 463
6.16.4.4.5 Transition SL_CC2:Selected to SL_CC6:Break ... 464
6.16.4.5 SL_CC3:Connected state ... 464
6.16.4.5.1 State description ... 464
6.16.4.5.2 Transition SL_CC3:Connected to SL_CC4:DisconnectWait ... 464
6.16.4.5.3 Transition SL_CC3:Connected to SL_CC5:BreakWait ... 465
6.16.4.5.4 Transition SL_CC3:Connected to SL_CC6:Break ... 465
6.16.4.5.5 Transition SL_CC3:Connected to SL_CC7:CloseSTP ... 465
6.16.4.6 SL_CC4:DisconnectWait state ... 465
6.16.4.6.1 State description ... 465
6.16.4.6.2 Transition SL_CC4:DisconnectWait to SL_CC0:Idle ... 465
6.16.4.6.3 Transition SL_CC4:DisconnectWait to SL_CC5:BreakWait ... 466
6.16.4.6.4 Transition SL_CC4:DisconnectWait to SL_CC6:Break ... 466
6.16.4.7 SL_CC5:BreakWait state ... 466
6.16.4.7.1 State description ... 466
6.16.4.7.2 Transition SL_CC5:BreakWait to SL_CC0:Idle ... 466
6.16.4.8 SL_CC6:Break state ... 466
6.16.4.8.1 State description ... 466
6.16.4.8.2 Transition SL_CC6:Break to SL_CC0:Idle ... 467
6.16.4.9 SL_CC7:CloseSTP state ... 467
6.16.4.9.1 State description ... 467
6.16.4.9.2 Transition SL_CC7:CloseSTP to SL_CC0:Idle ... 467
6.16.4.10 SL_CC8:PS_Request state ... 467
6.16.4.10.1 State description ... 467
6.16.4.10.2 Transition SL_CC8:PS_Request to SL_CC9:PS_Quiet ... 468
6.16.4.10.3 Transition SL_CC8:PS_Request to SL_CC0:Idle ... 468
6.16.4.10.4 Transition SL_CC8:PS_Request to SL_CC2:Selected ... 469
6.16.4.11 SL_CC9:PS_Quiet state ... 469
6.16.4.11.1 State description ... 469
6.16.4.11.2 Transition SL_CC9:PS_Quiet to SL_CC0:Idle ... 469
6.16.4.11.3 Transition SL_CC9:PS_Quiet to SL_CC1:ArbSel ... 469
6.17 XL (link layer for expander logical phys) state machine ... 470
6.17.1 XL state machine overview ... 470
6.17.2 XL transmitter and receiver ... 476
6.17.3 XL0:Idle state ... 478
6.17.3.1 State description ... 478
6.17.3.2 Transition XL0:Idle to XL1:Request_Path ... 479
6.17.3.3 Transition XL0:Idle to XL5:Forward_Open ... 479
6.17.3.3.1 Transition XL0:Idle to XL11:PS_Request ... 479
6.17.3.3.2 Transition XL0:Idle to XL12:PS_Quiet ... 480

6.17.4 XL1:Request_Path state 480
6.17.4.1 State description 480
6.17.4.2 Transition XL1:Request_Path to XL0:Idle 481
6.17.4.3 Transition XL1:Request_Path to XL2:Request_Open 481
6.17.4.4 Transition XL1:Request_Path to XL4:Open_Reject 481
6.17.4.5 Transition XL1:Request_Path to XL5:Forward_Open 481
6.17.4.6 Transition XL1:Request_Path to XL9:Break 482
6.17.5 XL2:Request_Open state 482
6.17.5.1 State description 482
6.17.5.2 Transition XL2:Request_Open to XL3:Open_Confirm_Wait 482
6.17.6 XL3:Open_Confirm_Wait state 482
6.17.6.1 State description 482
6.17.6.2 Transition XL3:Open_Confirm_Wait to XL0:Idle 483
6.17.6.3 Transition XL3:Open_Confirm_Wait to XL1:Request_Path 483
6.17.6.4 Transition XL3:Open_Confirm_Wait to XL5:Forward_Open 483
6.17.6.5 Transition XL3:Open_Confirm_Wait to XL7:Connected 484
6.17.6.6 Transition XL3:Open_Confirm_Wait to XL9:Break 484
6.17.6.7 Transition XL3:Open_Confirm_Wait to XL10:Break_Wait 484
6.17.7 XL4:Open_Reject state 484
6.17.7.1 State description 484
6.17.7.2 Transition XL4:Open_Reject to XL0:Idle 484
6.17.7.3 Transition XL4:Open_Reject to XL5:Forward_Open 484
6.17.8 XL5:Forward_Open state 484
6.17.8.1 State description 484
6.17.8.2 Transition XL5:Forward_Open to XL6:Open_Response_Wait 485
6.17.9 XL6:Open_Response_Wait state 485
6.17.9.1 State description 485
6.17.9.2 Transition XL6:Open_Response_Wait to XL0:Idle 486
6.17.9.3 Transition XL6:Open_Response_Wait to XL1:Request_Path 486
6.17.9.4 Transition XL6:Open_Response_Wait to XL2:Request_Open 486
6.17.9.5 Transition XL6:Open_Response_Wait to XL7:Connected 487
6.17.9.6 Transition XL6:Open_Response_Wait to XL9:Break 487
6.17.9.7 Transition XL6:Open_Response_Wait to XL10:Break_Wait 487
6.17.10 XL7:Connected state 487
6.17.10.1 State description 487
6.17.10.2 Transition XL7:Connected to XL8:Close_Wait 488
6.17.10.3 Transition XL7:Connected to XL9:Break 488
6.17.10.4 Transition XL7:Connected to XL10:Break_Wait 488
6.17.11 XL8:Close_Wait state 489
6.17.11.1 State description 489
6.17.11.2 Transition XL8:Close_Wait to XL0:Idle 489
6.17.11.3 Transition XL8:Close_Wait to XL9:Break 489
6.17.11.4 Transition XL8:Close_Wait to XL10:Break_Wait 490
6.17.12 XL9:Break state 490
6.17.12.1 State description 490
6.17.12.2 Transition XL9:Break to XL0:Idle 490
6.17.13 XL10:Break_Wait state 490
6.17.13.1 State description 490
6.17.13.2 Transition XL10:Break_Wait to XL0:Idle 490
6.17.14 XL11:PS_Request state 490
6.17.14.1 State description 490
6.17.14.2 Transition XL11:PS_Request to XL12:PS_Quiet 491
6.17.14.3 Transition XL11:PS_Request to XL0:Idle 492
6.17.14.4 Transition XL11:PS_Request to XL1:Request_Path 492
6.17.15 XL12:PS_Quiet state 492
6.17.15.1 State description 492
6.17.15.2 Transition XL12:PS_Quiet to XL0:Idle 492

6.18 SSP link layer 493
6.18.1 Opening an SSP connection 493
6.18.2 Full duplex 493
6.18.3 SSP frame transmission and reception 494
6.18.4 SSP flow control 494
6.18.5 Extending an SSP connection with persistent connections 495
6.18.6 Interlocked frames 495
6.18.7 Breaking an SSP connection 497
6.18.8 Closing an SSP connection 498
6.18.9 SSP (link layer for SSP phys) state machines 499
6.18.9.1 SSP state machines overview 499
6.18.9.2 SSP transmitter and receiver 503
6.18.9.3 SSP_TIM (transmit interlocked frame monitor) state machine 505
6.18.9.4 SSP_TCM (transmit frame credit monitor) state machine 505
6.18.9.5 SSP_D (DONE control) state machine 506
6.18.9.6 SSP_TF (transmit frame control) state machine 507
6.18.9.6.1 SSP_TF state machine overview 507
6.18.9.6.2 SSP_TF1:Connected_Idle state 508
6.18.9.6.2.1 State description 508
6.18.9.6.2.2 Transition SSP_TF1:Connected_Idle to SSP_TF2:Tx_Wait 508
6.18.9.6.2.3 Transition SSP_TF1:Connected_Idle to SSP_TF4:Transmit_DONE 508
6.18.9.6.3 SSP_TF2:Tx_Wait state 508
6.18.9.6.3.1 State description 508
6.18.9.6.3.2 Transition SSP_TF2:Tx_Wait to SSP_TF3:Transmit_Frame 509
6.18.9.6.3.3 Transition SSP_TF2:Tx_Wait to SSP_TF4:Transmit_DONE 509
6.18.9.6.4 SSP_TF3:Transmit_Frame state 509
6.18.9.6.4.1 State description 509
6.18.9.6.4.2 Transition SSP_TF3:Transmit_Frame to SSP_TF1:Connected_Idle 509
6.18.9.6.5 SSP_TF4:Transmit_DONE state 510
6.18.9.7 SSP_RF (receive frame control) state machine 510
6.18.9.8 SSP_RCM (receive frame credit monitor) state machine 511
6.18.9.9 SSP_RIM (receive interlocked frame monitor) state machine 512
6.18.9.10 SSP_TC (transmit credit control) state machine 512
6.18.9.11 SSP_TAN (transmit ACK/NAK control) state machine 512
6.18.9.12 SSP_EM (establish and manage persistent connection) state machine 513
6.18.9.12.1 SSP_EM state machine overview 513
6.18.9.12.2 SSP_EM1:Establish state 513
6.18.9.12.3 Transition SSP_EM1:Establish to SSP_EM2:Manage 514
6.18.9.12.4 SSP_EM2:Manage 514
6.18.9.12.5 Transition SSP_EM2:Manage to SSP_EM1:Establish 514
6.19 STP link layer 515
6.19.1 STP frame transmission and reception 515
6.19.2 STP flow control 515
6.19.2.1 STP flow control overview 515
6.19.2.2 SATA frame buffering 515
6.19.2.3 STP flow control buffer size 516
6.19.2.4 STP flow control example 517
6.19.2.5 STP insufficient buffer support 519
6.19.3 Continued primitive sequence 519
6.19.4 Affiliations 520
6.19.5 Opening an STP connection 522
6.19.6 Closing an STP connection 525
6.19.7 STP connection management examples 525
6.19.8 STP (link layer for STP phys) state machines 528
6.19.9 SMP target port support 528
6.20 SMP link layer 528
6.20.1 SMP frame transmission and reception 528

6.20.2 SMP flow control 528
6.20.3 Opening an SMP connection 528
6.20.4 Closing an SMP connection 529
6.20.5 SMP (link layer for SMP phys) state machines 529
6.20.5.1 SMP state machines overview 529
6.20.5.2 SMP transmitter and receiver 529
6.20.5.3 SMP_IP (link layer for SMP initiator phys) state machine 530
6.20.5.3.1 SMP_IP state machine overview 530
6.20.5.3.2 SMP_IP1:Idle state 531
6.20.5.3.2.1 State description 531
6.20.5.3.2.2 Transition SMP_IP1:Idle to SMP_IP2:Transmit_Frame 531
6.20.5.3.3 SMP_IP2:Transmit_Frame state 531
6.20.5.3.3.1 State description 531
6.20.5.3.3.2 Transition SMP_IP2:Transmit_Frame to SMP_IP3:Receive_Frame 531
6.20.5.3.4 SMP_IP3:Receive_Frame state 531
6.20.5.4 SMP_TP (link layer for SMP target phys) state machine 532
6.20.5.4.1 SMP_TP state machine overview 532
6.20.5.4.2 SMP_TP1:Receive_Frame state 533
6.20.5.4.2.1 State description 533
6.20.5.4.2.2 Transition SMP_TP1:Receive_Frame to SMP_TP2:Transmit_Frame 534
6.20.5.4.3 SMP_TP2:Transmit_Frame state 534

7 Port layer 535
7.1 Port layer overview 535
7.2 PL (port layer) state machines 535
7.2.1 PL state machines overview 535
7.2.2 PL_OC (port layer overall control) state machine 537
7.2.2.1 PL_OC state machine overview 537
7.2.2.2 PL_OC1:Idle state 539
7.2.2.2.1 PL_OC1:Idle state description 539
7.2.2.2.2 Transition PL_OC1:Idle to PL_OC2:Overall_Control 540
7.2.2.3 PL_OC2:Overall_Control state 540
7.2.2.3.1 PL_OC2:Overall_Control state overview 540
7.2.2.3.2 PL_OC2: Non-connection specific confirmations and requests 540
7.2.2.3.2.1 PL_OC2: Transmit Frame request 540
7.2.2.3.2.2 PL_OC2: HARD_RESET Received confirmation 541
7.2.2.3.2.3 PL_OC2: Notify Received (Power Loss Expected) confirmation 541
7.2.2.3.2.4 PL_OC2: Phy Disabled confirmation 541
7.2.2.3.2.5 PL_OC2: Start I_T Nexus Loss Timer request 542
7.2.2.3.3 PL_OC2:Overall_Control state establishing connections 542
7.2.2.3.4 PL_OC2:Overall_Control state connection established 546
7.2.2.3.5 PL_OC2:Overall_Control state unable to establish a connection — Unable To Connect message 546
7.2.2.3.6 PL_OC2:Overall_Control state unable to establish a connection — Unable To Connect message - Retry Open message processed as an Unable To Connect message 546
7.2.2.3.7 PL_OC2:Overall_Control state unable to establish a connection — I_T Nexus Loss timer expires 547
7.2.2.3.8 PL_OC2:Overall_Control state - I_T nexus loss event 547
7.2.2.3.9 PL_OC2:Overall_Control state connection management 547
7.2.2.3.10 PL_OC2:Overall_Control state frame transmission 549
7.2.2.3.11 PL_OC2:Overall_Control state frame transmission cancellations 550
7.2.2.3.12 Transition PL_OC2:Overall_Control to PL_OC1:Idle 550
7.2.3 PL_PM (port layer phy manager) state machine 551
7.2.3.1 PL_PM state machine overview 551
7.2.3.2 PL_PM1:Idle state 554
7.2.3.2.1 PL_PM1:Idle state description 554
7.2.3.2.2 Transition PL_PM1:Idle to PL_PM2:Req_Wait 554

7.2.3.2.3 Transition PL_PM1:Idle to PL_PM3:Connected 554
7.2.3.3 PL_PM2:Req_Wait state 554
7.2.3.3.1 PL_PM2:Req_Wait state overview 554
7.2.3.3.2 PL_PM2:Req_Wait establishing a connection 554
7.2.3.3.3 PL_PM2:Req_Wait connection established 555
7.2.3.3.4 PL_PM2:Req_Wait unable to establish a connection 555
7.2.3.3.5 PL_PM2:Req_Wait connection management 557
7.2.3.3.6 Transition PL_PM2:Req_Wait to PL_PM1:Idle 557
7.2.3.3.7 Transition PL_PM2:Req_Wait to PL_PM3:Connected 557
7.2.3.3.8 Transition PL_PM2:Req_Wait to PL_PM4:Wait_For_Close 557
7.2.3.4 PL_PM3:Connected state 557
7.2.3.4.1 PL_PM3:Connected state description 557
7.2.3.4.2 Transition PL_PM3:Connected to PL_PM1:Idle 561
7.2.3.5 PL_PM4:Wait_For_Close state 561
7.2.3.5.1 PL_PM4:Wait_For_Close state description 561
7.2.3.5.2 Transition PL_PM4:Wait_For_Close to PL_PM1:Idle 561

8 Transport layer 562
8.1 Transport layer overview 562
8.2 SSP transport layer 563
8.2.1 SSP frame format 563
8.2.2 Information units 567
8.2.2.1 COMMAND frame - Command information unit 567
8.2.2.2 TASK frame - Task Management Function information unit 568
8.2.2.3 XFER_RDY frame - Transfer Ready information unit 571
8.2.2.4 DATA frame - Data information unit 572
8.2.2.5 RESPONSE frame - Response information unit 574
8.2.2.5.1 RESPONSE frame - Response information unit overview 574
8.2.2.5.2 Response information unit - NO_DATA format 575
8.2.2.5.3 Response information unit - RESPONSE_DATA format 575
8.2.2.5.4 Response information unit - SENSE_DATA format 576
8.2.3 Sequences of SSP frames 577
8.2.3.1 Sequences of SSP frames overview 577
8.2.3.2 Task management function sequence of SSP frames 578
8.2.3.3 Non-data command sequence of SSP frames 578
8.2.3.4 Write command sequence of SSP frames 579
8.2.3.5 Read command sequence of SSP frames 579
8.2.3.6 Bidirectional command sequence of SSP frames 580
8.2.4 SSP transport layer handling of link layer errors 580
8.2.4.1 SSP transport layer handling of link layer errors overview 580
8.2.4.2 COMMAND frame - handling of link layer errors 581
8.2.4.3 TASK frame - handling of link layer errors 582
8.2.4.4 XFER_RDY frame - handling of link layer errors 582
8.2.4.4.1 XFER_RDY frame overview 582
8.2.4.4.2 XFER_RDY frame with transport layer retries enabled 582
8.2.4.4.3 XFER_RDY frame with transport layer retries disabled 583
8.2.4.5 Read DATA frame - handling of link layer errors 583
8.2.4.5.1 Read DATA frame overview 583
8.2.4.5.2 Read DATA frame with transport layer retries enabled 583
8.2.4.5.3 Read DATA frame with transport layer retries disabled 584
8.2.4.6 Write DATA frame - handling of link layer errors 584
8.2.4.6.1 Write DATA frame overview 584
8.2.4.6.2 Write DATA frame with transport layer retries enabled 584
8.2.4.6.3 Write DATA frame with transport layer retries disabled 585
8.2.4.7 RESPONSE frame - handling of link layer errors 585
8.2.5 SSP transport layer error handling summary 585
8.2.5.1 SSP transport layer error handling summary introduction 585

8.2.5.2 SSP initiator port transport layer error handling summary 585
8.2.5.3 SSP target port transport layer error handling summary 586
8.2.6 ST (transport layer for SSP ports) state machines 587
8.2.6.1 ST state machines overview 587
8.2.6.2 ST_I (transport layer for SSP initiator ports) state machines 588
8.2.6.2.1 ST_I state machines overview 588
8.2.6.2.2 ST_IFR (initiator frame router) state machine 590
8.2.6.2.2.1 ST_IFR state machine overview 590
8.2.6.2.2.2 Processing transport protocol service requests 590
8.2.6.2.2.3 Processing Frame Received confirmations 591
8.2.6.2.2.4 Processing Transmission Complete and Reception Complete messages 592
8.2.6.2.2.5 Processing miscellaneous requests 593
8.2.6.2.3 ST_ITS (initiator transport server) state machine 594
8.2.6.2.3.1 ST_ITS state machine overview 594
8.2.6.2.3.2 ST_ITS1:Initiator_Start state 595
8.2.6.2.3.2.1 State description 595
8.2.6.2.3.2.2 Transition ST_ITS1:Initiator_Start to ST_ITS3:Prepare_Command 595
8.2.6.2.3.2.3 Transition ST_ITS1:Initiator_Start to ST_ITS4:Prepare_Task 595
8.2.6.2.3.3 ST_ITS2:Initiator_Send_Frame state 595
8.2.6.2.3.3.1 Transition ST_ITS2:Initiator_Send_Frame to ST_ITS1:Initiator_Start 599
8.2.6.2.3.3.2 Transition ST_ITS2:Initiator_Send_Frame to ST_ITS5:Prepare_Data_Out 599
8.2.6.2.3.3.3 Transition ST_ITS2:Initiator_Send_Frame to ST_ITS6:Receive_Data_In 600
8.2.6.2.3.4 ST_ITS3:Prepare_Command state 600
8.2.6.2.3.4.1 State description 600
8.2.6.2.3.4.2 Transition ST_ITS3:Prepare_Command to ST_ITS2:Initiator_Send_Frame 600
8.2.6.2.3.5 ST_ITS4:Prepare_Task state 601
8.2.6.2.3.5.1 State description 601
8.2.6.2.3.5.2 Transition ST_ITS4:Prepare_Task to ST_ITS2:Initiator_Send_Frame 601
8.2.6.2.3.6 ST_ITS5:Prepare_Data_Out state 601
8.2.6.2.3.6.1 State description 601
8.2.6.2.3.6.2 Transition ST_ITS5:Prepare_Data_Out to ST_ITS2:Intiator_Send_Frame 602
8.2.6.2.3.7 ST_ITS6:Receive_Data_In state 602
8.2.6.2.3.7.1 State description 602
8.2.6.2.3.7.2 Transition ST_ITS6:Receive_Data_In to ST_ITS1:Initiator_Start 604
8.2.6.2.3.7.3 Transition ST_ITS6:Receive_Data_In to ST_ITS2:Initiator_Send_Frame 604
8.2.6.3 ST_T (transport layer for SSP target ports) state machines 604
8.2.6.3.1 ST_T state machines overview 604
8.2.6.3.2 ST_TFR (target frame router) state machine 606
8.2.6.3.2.1 ST_TFR state machine overview 606
8.2.6.3.2.2 Processing Frame Received confirmations 606
8.2.6.3.2.3 Processing transport protocol service requests and responses 608
8.2.6.3.2.4 Processing miscellaneous requests and confirmations 612
8.2.6.3.3 ST_TTS (target transport server) state machine 612
8.2.6.3.3.1 ST_TTS state machine overview 612
8.2.6.3.3.2 ST_TTS1:Target_Start state 613
8.2.6.3.3.2.1 State description 613
8.2.6.3.3.2.2 Transition ST_TTS1:Target_Start to ST_TTS3:Prepare_Data_In 614
8.2.6.3.3.2.3 Transition ST_TTS1:Target_Start to ST_TTS4:Prepare_Xfer_Rdy 614
8.2.6.3.3.2.4 Transition ST_TTS1:Target_Start to ST_TTS5:Receive_Data_Out 614
8.2.6.3.3.2.5 Transition ST_TTS1:Target_Start to ST_TTS7:Prepare_Response 614
8.2.6.3.3.3 ST_TTS2:Target_Send_Frame state 614
8.2.6.3.3.3.1 State description 614
8.2.6.3.3.3.2 Transition ST_TTS2:Target_Send_Frame to ST_TTS1:Target_Start 618
8.2.6.3.3.3.3 Transition ST_TTS2:Target_Send_Frame to ST_TTS3:Prepare_Data_In 618
8.2.6.3.3.3.4 Transition ST_TTS2:Target_Send_Frame to ST_TTS5:Receive_Data_Out 618
8.2.6.3.3.4 ST_TTS3:Prepare_Data_In state 619
8.2.6.3.3.4.1 State description 619

8.2.6.3.3.4.2 Transition ST_TTS3:Prepare_Data_In to ST_TTS2:Target_Send_Frame 620
8.2.6.3.3.5 ST_TTS4:Prepare_Xfer_Rdy state 620
8.2.6.3.3.5.1 State description 620
8.2.6.3.3.5.2 Transition ST_TTS4:Prepare_Xfer_Rdy to ST_TTS2:Target_Send_Frame 621
8.2.6.3.3.6 ST_TTS5:Receive_Data_Out state 621
8.2.6.3.3.6.1 State description 621
8.2.6.3.3.6.2 Transition ST_TTS5:Receive_Data_Out to ST_TTS1:Target_Start 622
8.2.6.3.3.6.3 Transition ST_TTS5:Receive_Data_Out to ST_TTS4:Prepare_Xfer_Rdy 622
8.2.6.3.3.7 ST_TTS6:Prepare_Response state 623
8.2.6.3.3.7.1 State description 623
8.2.6.3.3.7.2 Transition ST_TTS6:Prepare_Response to ST_TTS2:Target_Send_Frame 624
8.3 STP transport layer 624
8.3.1 Initial FIS 624
8.3.2 BIST Activate FIS 625
8.3.3 TT (transport layer for STP ports) state machines 625
8.4 SMP transport layer 625
8.4.1 SMP transport layer overview 625
8.4.2 SMP_REQUEST frame 626
8.4.3 SMP_RESPONSE frame 626
8.4.4 Sequence of SMP frames 627
8.4.5 MT (transport layer for SMP ports) state machines 627
8.4.5.1 SMP transport layer state machines overview 627
8.4.5.2 MT_IP (transport layer for SMP initiator ports) state machine 627
8.4.5.2.1 MT_IP state machine overview 627
8.4.5.2.2 MT_IP1:Idle state 628
8.4.5.2.2.1 State description 628
8.4.5.2.2.2 Transition MT_IP1:Idle to MT_IP2:Send 628
8.4.5.2.3 MT_IP2:Send state 629
8.4.5.2.3.1 State description 629
8.4.5.2.3.2 Transition MT_IP2:Send to MT_IP1:Idle 629
8.4.5.2.3.3 Transition MT_IP2:Send to MT_IP3:Receive 629
8.4.5.2.4 MT_IP3:Receive state 629
8.4.5.2.4.1 State description 629
8.4.5.2.4.2 Transition MT_IP3:Receive to MT_IP1:Idle 629
8.4.5.3 MT_TP (transport layer for SMP target ports) state machine 630
8.4.5.3.1 MT_TP state machine overview 630
8.4.5.3.2 MT_TP1:Idle state 630
8.4.5.3.2.1 State description 630
8.4.5.3.2.2 Transition MT_TP1:Idle to MT_TP2:Respond 631
8.4.5.3.3 MT_TP2:Respond state 631
8.4.5.3.3.1 State description 631
8.4.5.3.3.2 Transition MT_TP2:Respond to MT_TP1:Idle 631

9 Application layer 632
9.1 Application layer overview 632
9.2 SCSI application layer 632
9.2.1 SCSI transport protocol services 632
9.2.1.1 SCSI transport protocol services overview 632
9.2.1.2 Send SCSI Command transport protocol service 634
9.2.1.3 SCSI Command Received transport protocol service 635
9.2.1.4 Send Command Complete transport protocol service 636
9.2.1.5 Command Complete Received transport protocol service 637
9.2.1.6 Send Data-In transport protocol service 638
9.2.1.7 Data-In Delivered transport protocol service 639
9.2.1.8 Receive Data-Out transport protocol service 639
9.2.1.9 Data-Out Received transport protocol service 640
9.2.1.10 Terminate Data Transfer transport protocol service 641

9.2.1.11 Data Transfer Terminated transport protocol service 641
9.2.1.12 Send Task Management Request transport protocol service 641
9.2.1.13 Task Management Request Received transport protocol service 642
9.2.1.14 Task Management Function Executed transport protocol service 643
9.2.1.15 Received Task Management Function Executed transport protocol service 644
9.2.2 SCSI application client error handling 645
9.2.3 SCSI device server error handling 646
9.2.3.1 SCSI Command Received () error handling 646
9.2.3.2 Data-Out Received () error handling 646
9.2.4 Task router and task manager error handling 647
9.2.5 SCSI transport protocol services for event notifications 647
9.2.6 SCSI commands 648
9.2.6.1 INQUIRY command 648
9.2.6.2 LOG SELECT and LOG SENSE commands 648
9.2.6.3 MODE SELECT and MODE SENSE commands 648
9.2.6.4 SEND DIAGNOSTIC and RECEIVE DIAGNOSTIC RESULTS commands 648
9.2.6.5 START STOP UNIT command 648
9.2.7 SCSI mode parameters 649
9.2.7.1 SCSI mode parameters overview 649
9.2.7.2 Disconnect-Reconnect mode page 649
9.2.7.2.1 Disconnect-Reconnect mode page overview 649
9.2.7.2.2 BUS INACTIVITY LIMIT field 651
9.2.7.2.3 CONNECT TIME LIMIT field 651
9.2.7.2.4 MAXIMUM BURST SIZE field 651
9.2.7.2.5 FIRST BURST SIZE field 652
9.2.7.3 Protocol Specific Logical Unit mode page 652
9.2.7.4 Protocol Specific Port mode page 653
9.2.7.5 Phy Control And Discover mode page 655
9.2.7.6 Shared Port Control mode page 659
9.2.7.7 Enhanced Phy Control mode page 660
9.2.8 SCSI log parameters 663
9.2.8.1 Protocol Specific Port log page 663
9.2.8.2 Protocol Specific Port log parameter for SAS target ports 665
9.2.9 SCSI diagnostic parameters 668
9.2.9.1 SCSI diagnostic parameters overview 668
9.2.9.2 Protocol Specific diagnostic page 669
9.2.9.3 Enclosure Control diagnostic page 675
9.2.9.4 Enclosure Status diagnostic page 675
9.2.9.5 Additional Element Status diagnostic page 676
9.2.10 SCSI power conditions 676
9.2.10.1 SCSI power conditions overview 676
9.2.10.2 SA_PC (SCSI application layer power condition) state machine 676
9.2.10.2.1 SA_PC state machine overview 676
9.2.10.2.2 SA_PC_0:Powered_On state 680
9.2.10.2.2.1 State description 680
9.2.10.2.2.2 Transition SA_PC_0:Powered_On to SA_PC_4:Active_Wait 680
9.2.10.2.2.3 Transition SA_PC_0:Powered_On to SA_PC_8:Stopped 680
9.2.10.2.3 SA_PC_1:Active state 680
9.2.10.2.3.1 State description 680
9.2.10.2.3.2 Transition SA_PC_1:Active to SA_PC_5:Wait_Idle 680
9.2.10.2.3.3 Transition SA_PC_1:Active to SA_PC_6:Wait_Standby 680
9.2.10.2.3.4 Transition SA_PC_1:Active to SA_PC_10:Wait_Stopped 680
9.2.10.2.4 SA_PC_2:Idle state 680
9.2.10.2.4.1 State description 680
9.2.10.2.4.2 Transition SA_PC_2:Idle to SA_PC_4:Active_Wait 680
9.2.10.2.4.3 Transition SA_PC_2:Idle to SA_PC_5:Wait_Idle 681
9.2.10.2.4.4 Transition SA_PC_2:Idle to SA_PC_6:Wait_Standby 681

9.2.10.2.4.5 Transition SA_PC_2:Idle to SA_PC_7:Idle_Wait 681
9.2.10.2.4.6 Transition SA_PC_2:Idle to SA_PC_10:Wait_Stopped 681
9.2.10.2.5 SA_PC_3:Standby state 681
9.2.10.2.5.1 State description 681
9.2.10.2.5.2 Transition SA_PC_3:Standby to SA_PC_4:Active_Wait 681
9.2.10.2.5.3 Transition SA_PC_3:Standby to SA_PC_6:Wait_Standby 681
9.2.10.2.5.4 Transition SA_PC_3:Standby to SA_PC_7:Idle_Wait 681
9.2.10.2.5.5 Transition SA_PC_3:Standby to SA_PC_9: Standby_Wait 681
9.2.10.2.5.6 Transition SA_PC_3:Standby to SA_PC_10:Wait_Stopped 682
9.2.10.2.6 SA_PC_4:Active_Wait state 682
9.2.10.2.6.1 State description 682
9.2.10.2.6.2 Transition SA_PC_4:Active_Wait to SA_PC_1:Active 684
9.2.10.2.7 SA_PC_5:Wait_Idle state 684
9.2.10.2.7.1 SA_PC_5:Wait_Idle state description 684
9.2.10.2.7.2 Transition SA_PC_5:Wait_Idle to SA_PC_2:Idle 684
9.2.10.2.8 SA_PC_6:Wait_Standby state 684
9.2.10.2.8.1 SA_PC_6:Wait_Standby state description 684
9.2.10.2.8.2 Transition SA_PC_6:Wait_Standby to SA_PC_3:Standby 684
9.2.10.2.9 SA_PC_7:Idle_Wait state 684
9.2.10.2.9.1 State description 684
9.2.10.2.9.2 Transition SA_PC_7:Idle_Wait to SA_PC_2:Idle 686
9.2.10.2.10 SA_PC_8:Stopped state 686
9.2.10.2.10.1 State description 686
9.2.10.2.10.2 Transition SA_PC_8:Stopped to SA_PC_4:Active_Wait 686
9.2.10.2.10.3 Transition SA_PC_8:Stopped to SA_PC_7:Idle_Wait 686
9.2.10.2.10.4 Transition SA_PC_8:Stopped to SA_PC_9:Standby_Wait 686
9.2.10.2.11 SA_PC_9:Standby_Wait state 686
9.2.10.2.11.1 SA_PC_9:Standby_Wait state description 686
9.2.10.2.11.2 Transition SA_PC_9:Standby_Wait to SA_PC_3:Standby 686
9.2.10.2.12 SA_PC_10:Wait_Stopped state 686
9.2.10.2.12.1 SA_PC_10:Wait_Stopped state description 686
9.2.10.2.12.2 Transition SA_PC_10:Wait_Stopped to SA_PC_8:Stopped 686
9.2.11 SCSI vital product data (VPD) 687
9.2.11.1 SCSI vital product data (VPD) overview 687
9.2.11.2 Device Identification VPD page 687
9.2.11.3 Protocol Specific Logical Unit Information VPD page 688
9.2.11.4 Protocol Specific Port Information VPD page 690
9.3 ATA application layer 693
9.4 Management application layer 693
9.4.1 READY LED signal behavior 693
9.4.2 Management protocol services 695
9.4.3 SMP functions 695
9.4.3.1 SMP functions overview 695
9.4.3.2 SMP function request frame format 698
9.4.3.2.1 SMP function request frame format overview 698
9.4.3.2.2 SMP FRAME TYPE field 698
9.4.3.2.3 FUNCTION field 698
9.4.3.2.4 ALLOCATED RESPONSE LENGTH field 698
9.4.3.2.5 REQUEST LENGTH field 699
9.4.3.2.6 Additional request bytes 699
9.4.3.2.7 CRC field 700
9.4.3.3 SMP function response frame format 700
9.4.3.3.1 SMP function response frame format overview 700
9.4.3.3.2 SMP FRAME TYPE field 701
9.4.3.3.3 FUNCTION field 701
9.4.3.3.4 FUNCTION RESULT field 701
9.4.3.3.5 RESPONSE LENGTH field 709

9.4.3.3.6 Additional response bytes 709
9.4.3.3.7 CRC field 710
9.4.3.4 REPORT GENERAL function 710
9.4.3.5 REPORT MANUFACTURER INFORMATION function 717
9.4.3.6 REPORT SELF-CONFIGURATION STATUS function 721
9.4.3.6.1 REPORT SELF-CONFIGURATION STATUS function overview 721
9.4.3.6.2 REPORT SELF-CONFIGURATION STATUS request 721
9.4.3.6.3 REPORT SELF-CONFIGURATION STATUS response 723
9.4.3.6.4 Self-configuration status descriptor 725
9.4.3.7 REPORT ZONE PERMISSION TABLE function 727
9.4.3.7.1 REPORT ZONE PERMISSION TABLE function overview 727
9.4.3.7.2 REPORT ZONE PERMISSION TABLE request 728
9.4.3.7.3 REPORT ZONE PERMISSION TABLE response 730
9.4.3.7.4 Zone permission descriptor 731
9.4.3.8 REPORT ZONE MANAGER PASSWORD function 732
9.4.3.9 REPORT BROADCAST function 735
9.4.3.9.1 REPORT BROADCAST function overview 735
9.4.3.9.2 REPORT BROADCAST request 735
9.4.3.9.3 REPORT BROADCAST response 737
9.4.3.9.4 Broadcast descriptor 738
9.4.3.10 DISCOVER function 740
9.4.3.11 REPORT PHY ERROR LOG function 758
9.4.3.12 REPORT PHY SATA function 761
9.4.3.13 REPORT ROUTE INFORMATION function 765
9.4.3.14 REPORT PHY EVENT function 768
9.4.3.14.1 REPORT PHY EVENT function overview 768
9.4.3.14.2 REPORT PHY EVENT request 769
9.4.3.14.3 REPORT PHY EVENT response 770
9.4.3.14.4 Phy event descriptor 771
9.4.3.15 DISCOVER LIST function 772
9.4.3.15.1 DISCOVER LIST function overview 772
9.4.3.15.2 DISCOVER LIST request 773
9.4.3.15.3 DISCOVER LIST response 775
9.4.3.15.4 DISCOVER LIST response SHORT FORMAT descriptor 777
9.4.3.16 REPORT PHY EVENT LIST function 778
9.4.3.16.1 REPORT PHY EVENT LIST function overview 778
9.4.3.16.2 REPORT PHY EVENT LIST request 778
9.4.3.16.3 REPORT PHY EVENT LIST response 779
9.4.3.16.4 Phy event list descriptor 781
9.4.3.17 REPORT EXPANDER ROUTE TABLE LIST function 781
9.4.3.17.1 REPORT EXPANDER ROUTE TABLE LIST function overview 781
9.4.3.17.2 REPORT EXPANDER ROUTE TABLE LIST request 782
9.4.3.17.3 REPORT EXPANDER ROUTE TABLE LIST response 784
9.4.3.17.4 Expander route table descriptor 786
9.4.3.18 CONFIGURE GENERAL function 786
9.4.3.19 ENABLE DISABLE ZONING function 790
9.4.3.20 ZONED BROADCAST function 793
9.4.3.21 ZONE LOCK function 796
9.4.3.22 ZONE ACTIVATE function 799
9.4.3.23 ZONE UNLOCK function 800
9.4.3.24 CONFIGURE ZONE MANAGER PASSWORD function 802
9.4.3.25 CONFIGURE ZONE PHY INFORMATION function 805
9.4.3.25.1 CONFIGURE ZONE PHY INFORMATION function overview 805
9.4.3.25.2 CONFIGURE ZONE PHY INFORMATION request 806
9.4.3.25.3 Zone phy configuration descriptor 808
9.4.3.25.4 CONFIGURE ZONE PHY INFORMATION response 808
9.4.3.26 CONFIGURE ZONE PERMISSION TABLE function 809

9.4.3.26.1 CONFIGURE ZONE PERMISSION TABLE function overview 809
9.4.3.26.2 CONFIGURE ZONE PERMISSION TABLE request 810
9.4.3.26.3 Zone permission configuration descriptor 812
9.4.3.26.4 CONFIGURE ZONE PERMISSION TABLE response 813
9.4.3.27 CONFIGURE ROUTE INFORMATION function 814
9.4.3.28 PHY CONTROL function 817
9.4.3.29 PHY TEST FUNCTION function 826
9.4.3.30 CONFIGURE PHY EVENT function 830
9.4.3.30.1 CONFIGURE PHY EVENT function overview 830
9.4.3.30.2 CONFIGURE PHY EVENT request 831
9.4.3.30.3 Phy event configuration descriptor 832
9.4.3.30.4 CONFIGURE PHY EVENT response 833

Annex A (normative) Jitter tolerance patterns 834
A.1 Jitter tolerance pattern (JTPAT) 834
A.2 Compliant jitter tolerance pattern (CJTPAT) 834
A.3 Considerations for a phy transmitting JTPAT and CJTPAT 842
A.4 Considerations for a phy receiving JTPAT and CJTPAT 842

Annex B (informative) SAS to SAS phy reset sequence examples 844

Annex C (informative) CRC 849
C.1 CRC generator and checker implementation examples 849
C.2 CRC implementation in C 849
C.3 CRC implementation with XORs 851
C.4 CRC examples 852

Annex D (informative) SAS address hashing 853
D.1 SAS address hashing overview 853
D.2 Hash collision probability 853
D.3 Hash generation 854
D.4 Hash implementation in C 854
D.5 Hash implementation with XORs 855
D.6 Hash examples 856

Annex E (informative) Scrambling 860
E.1 Scrambler implementation example 860
E.2 Scrambler implementation in C 860
E.3 Scrambler implementation with XORs 861
E.4 Scrambler examples 862

Annex F (informative) ATA architectural notes 865
F.1 STP differences from Serial ATA (SATA) 865
F.2 STP differences from Serial ATA II 865
F.3 Affiliation policies 865
F.3.1 Affiliation policies overview 865
F.3.2 Affiliation policy for static STP initiator port to STP target port mapping 866
F.3.3 Affiliation policy with SATA queued commands and multiple STP initiator ports 866
F.3.4 Applicability of affiliation for STP target ports 866
F.4 SATA port selector considerations 866
F.5 SATA device not transmitting initial Register Device-to-Host FIS 867

Annex G (informative) Minimum deletable primitive insertion rate summary 868

Annex H (informative) Zone permission configuration descriptor examples 869

Annex I (informative) SAS addressing 872

I.1 SAS addressing in SAS domains 872
I.2 Expander device SAS addresses 872

Annex J (informative) Expander device handling of connections 873
J.1 Expander device handling of connections overview 873
J.2 Connection request - OPEN_ACCEPT 875
J.3 Connection request - OPEN_REJECT by end device 876
J.4 Connection request - OPEN_REJECT by expander device 877
J.5 Connection request - arbitration lost 878
J.6 Connection request - backoff and retry 879
J.7 Connection request - backoff and reverse path 880
J.8 Connection close - single step 881
J.9 Connection close - simultaneous 882
J.10 BREAK handling during path arbitration when the BREAK_REPLY method is disabled 883
J.11 BREAK handling during connection when the BREAK_REPLY method is disabled 884
J.12 BREAK handling during path arbitration when the BREAK_REPLY method is enabled 885
J.13 BREAK handling during connection when BREAK_REPLY method is enabled 886
J.14 STP connection - originated by STP initiator port 887
J.15 STP connection - originated by STP target port in an STP SATA bridge 888
J.16 STP connection close - originated by STP initiator port 889
J.17 STP connection close - originated by STP target port in an STP SATA bridge 890
J.18 Connection request - XL1:Request_Path to XL5:Forward_Open transition 891
J.19 Pathway blocked and pathway recovery example 892

Annex K (informative) Primitive encoding 894

Annex L (informative) Standards bodies contact information 897

Annex M (informative) Successful low phy power condition handshake sequence 898

Bibliography 901

Table 1 — Numbering conventions 81
Table 2 — Comparison of decimal prefixes and binary prefixes 82
Table 3 — Constraint and note notation 83
Table 4 — Class diagram notation for classes 83
Table 5 — Multiplicity notation 84
Table 6 — Class diagram notation for associations 85
Table 7 — Class diagram notation for aggregations 86
Table 8 — Class diagram notation for generalizations 86
Table 9 — Class diagram notation for dependency 87
Table 10 — Object diagram notation for objects 88
Table 11 — Object diagram notation for link 88
Table 12 — Data dword containing a value 92
Table 13 — Data dword containing four one-byte fields 92
Table 14 — Logical links 100
Table 15 — Broadcast types 116
Table 16 — Names and identifiers 119
Table 17 — SCSI architecture model object attribute mapping 119
Table 18 — NAA IEEE Registered format 120
Table 19 — NAA Locally Assigned format 121
Table 20 — Hashed SAS address code parameters 122
Table 21 — Device name created from the IDENTIFY (PACKET) DEVICE world wide name 123
Table 22 — Expander logical phy to ECM requests 147
Table 23 — Expander logical phy to ECM responses 147
Table 24 — ECM to expander logical phy confirmations 148
Table 25 — Expander logical phy to ECR to expander logical phy requests and indications 149
Table 26 — Expander logical phy to ECR to expander logical phy responses and confirmations 149
Table 27 — Expander logical phy to BPP requests 151
Table 28 — BPP to expander logical phy indications 152
Table 29 — Routing attributes and routing methods 152
Table 30 — Expander route table types 154
Table 31 — Expander route table levels for externally configurable expander device R phy A 166
Table 32 — Expander route table levels for externally configurable expander device N 167
Table 33 — Expander route entries for externally configurable expander device E0 phy 1 168
Table 34 — Expander route entries for externally configurable expander device F phy 0 169
Table 35 — Zone manager password 174
Table 36 — Zone phy information 177
Table 37 — Zone phy information usage 178
Table 38 — Zone groups 179
Table 39 — Zone permission table 181
Table 40 — Zone permission table granting minimal permissions 182
Table 41 — Source zone group determination 184
Table 42 — Destination zone group determination 184
Table 43 — REQUESTED INSIDE ZPSDS bit and INSIDE ZPSDS PERSISTENT bit changes after a link reset sequence 185
Table 44 — ZONE GROUP field values if the ZONE GROUP PERSISTENT bit is set to one 186
Table 45 — Conditions that cause the ZONE GROUP field to be updated if the ZONE GROUP PERSISTENT bit is set to zero 187
Table 46 — PHY EVENT SOURCE field 196
Table 47 — Bit designations 202
Table 48 — Conversion from byte notation to character name example 203
Table 49 — Data characters 205
Table 50 — Control characters 210
Table 51 — Control character usage 211
Table 52 — Delayed code violation example 212
Table 53 — SNW-3 phy capabilities 218
Table 54 — Requested logical link rate 219
Table 55 — Multiplexing negotiation 220

Table 56 — Supported settings bit priorities 221
Table 57 — Example SNW-3 phy capabilities values 222
Table 58 — Train_Tx-SNW TTIU bit 225
Table 59 — Train_Tx-SNW TTIU 226
Table 60 — PATTERN TYPE field 226
Table 61 — Control/Status TTIU 227
Table 62 — COEFFICIENT SETTINGS field 227
Table 63 — COEFFICIENT 1 REQUEST field, COEFFICIENT 2 REQUEST field, and COEFFICIENT 3 REQUEST field 228
Table 64 — Valid coefficient requests 229
Table 65 — COEFFICIENT 1 STATUS field, COEFFICIENT 2 STATUS field, and COEFFICIENT 3 STATUS field 230
Table 66 — Error Response TTIU 230
Table 67 — ERROR CODE field 232
Table 68 — Phy reset sequence timing specifications 233
Table 69 — SATA speed negotiation sequence timing specifications 235
Table 70 — SAS speed negotiation sequence timing specifications 240
Table 71 — SNW rates used in SNW-1, SNW-2, and Final-SNW 243
Table 72 — SNW-3 phy capabilities bit 244
Table 73 — Transmitter training pattern 246
Table 74 — Receiver training patterns 249
Table 75 — SP state machine timers 280
Table 76 — Messages to SP transmitter and SP receiver at start of RCDT 292
Table 77 — SP_DWS state machine timers 313
Table 78 — Mapping messages to the Training Control word 329
Table 79 — Mapping messages from PTT_SC1 state machine, PTT_SC2 state machine, and PTT_SC3 state machine to the Training Status word 329
Table 80 — Mapping Transmit Error Response message arguments to Error Response TTIU fields 330
Table 81 — Transmit Error Response message arguments sent to PTT_T state machine 336
Table 82 — Mapping the Training Status word to SP receiver messages 337
Table 83 — Mapping the Training Status word to PTT_GC1 state machine messages, PTT_GC2 state machine messages, and PTT_GC3 state machine messages 338
Table 84 — Mapping the Training Control word to PTT_SC1 state machine messages, PTT_SC2 state machine messages, and PTT_SC3 state machine messages 339
Table 85 — Mapping Coefficient Request byte to PTT_SC3 state machine message, PTT_SC2 state machine message, and PTT_SC1 state machine messages 340
Table 86 — Mapping messages to the PTT_T state machine 344
Table 87 — PTT_SC1 messages to substitute for PTT_SC2 messages 345
Table 88 — PTT_SC1 messages to substitute for PTT_SC3 messages 346
Table 89 — Mapping messages to the PTT_T state machine 348
Table 90 — PTT_GC1 messages to substitute for PTT_GC2 messages 349
Table 91 — PTT_GC1 messages to substitute for PTT_GC2 messages 349
Table 92 — Primitive format 356
Table 93 — Deletable primitives 357
Table 94 — Primitives not specific to type of connection 358
Table 95 — Primitives used inside SSP and SMP connections 362
Table 96 — Primitives used inside STP connections and on SATA physical links 364
Table 97 — Primitive encoding for deletable primitives 366
Table 98 — Primitive encoding for primitives not specific to type of connection 367
Table 99 — Primitive encoding for primitives used only inside SSP and SMP connections 369
Table 100 — Primitive encoding for primitives used only inside STP connections and only on SATA physical links 370
Table 101 — Primitive sequences 371
Table 102 — ALIGN primitives 376
Table 103 — MUX primitives 377
Table 104 — NOTIFY primitives 377
Table 105 — AIP primitives 379
Table 106 — BROADCAST primitives 380
Table 107 — CLOSE primitives 381

Table 108 — Abandon-class OPEN_REJECT primitives 382
Table 109 — Retry-class OPEN_REJECT primitives 383
Table 110 — PS_REQ primitives 384
Table 111 — DONE primitives 386
Table 112 — NAK primitives 387
Table 113 — RRDY primitives 387
Table 114 — Physical link rate tolerance management deletable primitive insertion requirement 390
Table 115 — CRC notation and definitions 392
Table 116 — Scrambling for different data dword types 396
Table 117 — Address frame format 402
Table 118 — ADDRESS FRAME TYPE field 402
Table 119 — IDENTIFY address frame format 403
Table 120 — DEVICE TYPE field 404
Table 121 — REASON field 404
Table 122 — POWER CAPABLE field 406
Table 123 — OPEN address frame format 407
Table 124 — SAS PROTOCOL field 408
Table 125 — FEATURES field 408
Table 126 — CONNECTION RATE field 408
Table 127 — ARBITRATION WAIT TIME field 410
Table 128 — SL_IR_IRC state machine timers 414
Table 129 — PS_ACK pattern 421
Table 130 — SL_P_S state machine timers 423
Table 131 — SL_P_C state machine timers 427
Table 132 — Connection results of a connection request 435
Table 133 — Arbitration priority for OPEN address frames passing on a logical link 436
Table 134 — Arbitration priority for a Request Path request in the ECM 439
Table 135 — Pathway recovery priority 441
Table 136 — Results of aborting a connection request 442
Table 137 — Results of closing a connection 445
Table 138 — Results of breaking a connection 446
Table 139 — Rate matching deletable primitive insertion requirements 447
Table 140 — SL_CC state machine timers 456
Table 141 — SL_CC state machine variables 456
Table 142 — OPEN_REJECT Received message to Open Failed confirmation mapping 460
Table 143 — XL state machine timers 471
Table 144 — XL state machine variable 471
Table 145 — SSP frame interlock requirements 495
Table 146 — SSP state machines timers 500
Table 147 — SSP state machines timers for persistent connections 500
Table 148 — STP link layer differences from SATA link layer during an STP connection 515
Table 149 — Affiliation policies 521
Table 150 — Affiliation context relative identifier example 522
Table 151 — PL_OC state machine timers 538
Table 152 — Confirmations from Unable To Connect messages 546
Table 153 — PL_PM state machine timers 551
Table 154 — Messages from Open Failed confirmations 555
Table 155 — SSP frame format 563
Table 156 — FRAME TYPE field 564
Table 157 — TLR CONTROL field for COMMAND frames 565
Table 158 — COMMAND frame - Command information unit 567
Table 159 — TASK ATTRIBUTE field 568
Table 160 — TASK frame - Task Management Function information unit 569
Table 161 — TASK MANAGEMENT FUNCTION field 570
Table 162 — XFER_RDY frame - Transfer Ready information unit 572
Table 163 — DATA frame - Data information unit 573
Table 164 — RESPONSE frame - Response information unit 574

Table 165 — DATAPRES field 575
Table 166 — RESPONSE DATA field 576
Table 167 — RESPONSE CODE field 576
Table 168 — Sequences of SSP frames 577
Table 169 — Confirmations sent to the SCSI application layer if a frame transmission error or reception error occurs 593
Table 170 — ST_ITS state machine variables 594
Table 171 — ST_ITS state machine arguments 595
Table 172 — Messages sent to the ST_IFR state machine 597
Table 173 — Transmission Complete messages for XFER_RDY frame verification failures 598
Table 174 — Reception Complete messages for read DATA frame verification failures 603
Table 175 — ST_T state machine timers 604
Table 176 — Task Management Function Executed Service Response argument mapping to Request (Send Transport Response) Service Response argument 609
Table 177 — Confirmations sent to the SCSI application layer 611
Table 178 — ST_TTS state machine variables 613
Table 179 — ST_TTS state machine arguments 613
Table 180 — Messages sent to the ST_TFR state machine 617
Table 181 — Additional messages sent to the ST_TFR state machine 618
Table 182 — Reception Complete message for write DATA frame verification failures 621
Table 183 — Request (Send Transport Response) message Service Response argument to RESPONSE frame RESPONSE DATA field mapping 624
Table 184 — SMP frame format 625
Table 185 — SMP FRAME TYPE field 625
Table 186 — SMP_REQUEST frame format 626
Table 187 — SMP_RESPONSE frame format 626
Table 188 — MT_TP time limits 630
Table 189 — Execute Command procedure call transport protocol services 633
Table 190 — Task management function procedure call transport protocol services 634
Table 191 — Send SCSI Command transport protocol service arguments 635
Table 192 — SCSI Command Received transport protocol service arguments 636
Table 193 — Send Command Complete transport protocol service arguments 637
Table 194 — Command Complete Received transport protocol service arguments 638
Table 195 — Send Data-In transport protocol service arguments 639
Table 196 — Data-In Delivered transport protocol service arguments 639
Table 197 — Receive Data-Out transport protocol service arguments 640
Table 198 — Data-Out Received transport protocol service arguments 640
Table 199 — Terminate Data Transfer transport protocol service arguments 641
Table 200 — Data Transfer Terminated transport protocol service arguments 641
Table 201 — Send Task Management Request transport protocol service arguments 642
Table 202 — Task Management Request Received transport protocol service arguments 643
Table 203 — Task Management Function Executed transport protocol service arguments 644
Table 204 — Received Task Management Function Executed transport protocol service arguments 645
Table 205 — Delivery Result to additional sense code mapping 647
Table 206 — SCSI transport protocol events 648
Table 207 — SSP target port mode pages 649
Table 208 — Disconnect-Reconnect mode page for SAS SSP 650
Table 209 — Protocol Specific Logical Unit mode page for SAS SSP 653
Table 210 — Protocol Specific Port mode page for SAS SSP 654
Table 211 — I_T NEXUS LOSS TIME field 655
Table 212 — Phy Control And Discover mode page 656
Table 213 — SAS phy mode descriptor 658
Table 214 — Shared Port Control mode page 659
Table 215 — Enhanced Phy Control mode page 661
Table 216 — Enhanced phy control mode descriptor 662
Table 217 — Protocol Specific Port log parameters 663
Table 218 — Protocol Specific Port log page for SAS SSP 664

Table 219 — Protocol Specific Port log parameter for SAS target ports 665
Table 220 — SAS phy log descriptor 666
Table 221 — SSP target port diagnostic pages 668
Table 222 — Diagnostic pages affected by zoning 669
Table 223 — Protocol Specific diagnostic page for SAS SSP 670
Table 224 — PHY TEST FUNCTION field 671
Table 225 — PHY TEST PATTERN field 672
Table 226 — PHY TEST FUNCTION SSC field 673
Table 227 — PHY TEST FUNCTION PHYSICAL LINK RATE field 673
Table 228 — PHY TEST PATTERN DWORDS CONTROL field 674
Table 229 — TWO_DWORDS phy test pattern examples 675
Table 230 — Summary of states in the SA_PC state machine 677
Table 231 — VPD pages with special requirements for SAS SSP 687
Table 232 — Device Identification VPD page designation descriptors for the SAS target port 687
Table 233 — Device Identification VPD page designation descriptors for the SAS target device 688
Table 234 — Protocol Specific Logical Unit Information VPD page for SAS SSP 689
Table 235 — Logical unit information descriptor for SAS SSP 690
Table 236 — Protocol Specific Port Information VPD page for SAS SSP 691
Table 237 — Port information descriptor for SAS SSP 692
Table 238 — SAS phy information descriptor for SAS SSP 693
Table 239 — READY LED signal behavior 694
Table 240 — SMP functions (FUNCTION field) 695
Table 241 — SMP request frame format 698
Table 242 — SMP response frame format 700
Table 243 — FUNCTION RESULT field 701
Table 244 — Function result priority 705
Table 245 — REPORT GENERAL request 710
Table 246 — REPORT GENERAL response 711
Table 247 — NUMBER OF ZONE GROUPS field 715
Table 248 — REPORT MANUFACTURER INFORMATION request 717
Table 249 — REPORT MANUFACTURER INFORMATION response 719
Table 250 — REPORT SELF-CONFIGURATION STATUS request 721
Table 251 — REPORT SELF-CONFIGURATION STATUS response 723
Table 252 — Self-configuration status descriptor 725
Table 253 — STATUS TYPE field 725
Table 254 — REPORT ZONE PERMISSION TABLE request 728
Table 255 — REPORT TYPE field 729
Table 256 — REPORT ZONE PERMISSION TABLE response 730
Table 257 — Zone permission descriptors 731
Table 258 — Zone permission descriptor for a source zone group (i.e., s) with 128 zone groups 731
Table 259 — Zone permission descriptor for a source zone group (i.e., s) with 256 zone groups 732
Table 260 — Zone permission descriptor bit requirements 732
Table 261 — REPORT ZONE MANAGER PASSWORD request 733
Table 262 — REPORT TYPE field 734
Table 263 — REPORT ZONE MANAGER PASSWORD response 734
Table 264 — REPORT BROADCAST request 735
Table 265 — REPORT BROADCAST response 737
Table 266 — Broadcast descriptor 738
Table 267 — BROADCAST REASON field for originated Broadcasts 739
Table 268 — DISCOVER request 740
Table 269 — DISCOVER response 741
Table 270 — ATTACHED DEVICE TYPE field 744
Table 271 — NEGOTIATED LOGICAL LINK RATE field and NEGOTIATED PHYSICAL LINK RATE field 746
Table 272 — NEGOTIATED PHYSICAL LINK RATE field and NEGOTIATED LOGICAL LINK RATE field combinations based on multiplexing 747
Table 273 — ATTACHED SATA PORT SELECTOR and ATTACHED SATA DEVICE bits 748
Table 274 — PROGRAMMED MINIMUM PHYSICAL LINK RATE field and PROGRAMMED MAXIMUM PHYSICAL

LINK RATE field 751
Table 275 — The HARDWARE MINIMUM PHYSICAL LINK RATE field and the HARDWARE MAXIMUM PHYSICAL LINK RATE field 751
Table 276 — ROUTING ATTRIBUTE field 752
Table 277 — PHY POWER CONDITION field 753
Table 278 — SAS POWER CAPABLE field 753
Table 279 — PWR_DIS SIGNAL field 754
Table 280 — PWR_DIS CONTROL CAPABLE field 754
Table 281 — ATTACHED DEVICE NAME field 755
Table 282 — SELF-CONFIGURATION STATUS field 756
Table 283 — SELF-CONFIGURATION LEVELS COMPLETED field 756
Table 284 — REPORT PHY ERROR LOG request 759
Table 285 — REPORT PHY ERROR LOG response 760
Table 286 — REPORT PHY SATA request 762
Table 287 — REPORT PHY SATA response 763
Table 288 — REPORT ROUTE INFORMATION request 765
Table 289 — REPORT ROUTE INFORMATION response 767
Table 290 — REPORT PHY EVENT request 769
Table 291 — REPORT PHY EVENT response 770
Table 292 — Phy event descriptor 771
Table 293 — DISCOVER LIST request 773
Table 294 — PHY FILTER field 774
Table 295 — DESCRIPTOR TYPE field 774
Table 296 — DISCOVER LIST response 775
Table 297 — SHORT FORMAT descriptor 777
Table 298 — REPORT PHY EVENT LIST request 778
Table 299 — REPORT PHY EVENT LIST response 779
Table 300 — Phy event list descriptor 781
Table 301 — REPORT EXPANDER ROUTE TABLE LIST request 782
Table 302 — REPORT EXPANDER ROUTE TABLE LIST response 784
Table 303 — Expander route table descriptor 786
Table 304 — CONFIGURE GENERAL request 787
Table 305 — STP SMP I_T NEXUS LOSS TIME field 789
Table 306 — CONFIGURE GENERAL response 790
Table 307 — ENABLE DISABLE ZONING request 791
Table 308 — SAVE field 792
Table 309 — ENABLE DISABLE ZONING field 792
Table 310 — ENABLE DISABLE ZONING response 793
Table 311 — ZONED BROADCAST request 794
Table 312 — BROADCAST TYPE field 795
Table 313 — ZONED BROADCAST response 796
Table 314 — ZONE LOCK request 797
Table 315 — ZONE LOCK response 798
Table 316 — ZONE ACTIVATE request 799
Table 317 — ZONE ACTIVATE response 800
Table 318 — ZONE UNLOCK request 801
Table 319 — ZONE UNLOCK response 802
Table 320 — CONFIGURE ZONE MANAGER PASSWORD request 803
Table 321 — SAVE field 804
Table 322 — CONFIGURE ZONE MANAGER PASSWORD response 804
Table 323 — CONFIGURE ZONE PHY INFORMATION request 806
Table 324 — SAVE field 807
Table 325 — Zone phy configuration descriptor 808
Table 326 — CONFIGURE ZONE PHY INFORMATION response 808
Table 327 — CONFIGURE ZONE PERMISSION TABLE request 810
Table 328 — NUMBER OF ZONE GROUPS field 811
Table 329 — SAVE field 811

Table 330 — Zone permission configuration descriptors 812
Table 331 — Zone permission configuration descriptor for source zone group for 128 zone groups 812
Table 332 — Zone permission configuration descriptor for source zone group for 256 zone groups 812
Table 333 — Zone permission configuration descriptor bit requirements 813
Table 334 — CONFIGURE ZONE PERMISSION TABLE response 813
Table 335 — CONFIGURE ROUTE INFORMATION request 815
Table 336 — CONFIGURE ROUTE INFORMATION response 816
Table 337 — PHY CONTROL request 818
Table 338 — PHY OPERATION field 820
Table 339 — PROGRAMMED MINIMUM PHYSICAL LINK RATE field and PROGRAMMED MAXIMUM PHYSICAL LINK RATE field 822
Table 340 — ENABLE SAS SLUMBER field 823
Table 341 — ENABLE SAS PARTIAL field 823
Table 342 — ENABLE SATA SLUMBER field 824
Table 343 — ENABLE SATA PARTIAL field 824
Table 344 — PWR_DIS CONTROL field 825
Table 345 — PHY CONTROL response 825
Table 346 — PHY TEST FUNCTION request 827
Table 347 — PHY TEST FUNCTION field 829
Table 348 — PHY TEST FUNCTION PHYSICAL LINK RATE field 829
Table 349 — PHY TEST FUNCTION response 830
Table 350 — CONFIGURE PHY EVENT request 831
Table 351 — Phy event configuration descriptor 832
Table 352 — CONFIGURE PHY EVENT response 833
Table A.1 — JTPAT for RD+ and RD- 834
Table A.2 — CJTPAT 836
Table A.3 — CJTPAT with fixed content 841
Table C.1 — CRC examples 852
Table D.1 — Monte-Carlo simulation results 854
Table D.2 — Hash results for simple SAS addresses 856
Table D.3 — Hash results for realistic SAS addresses 856
Table D.4 — Hash results for a walking ones pattern 857
Table D.5 — Hash results for a walking zeros pattern 858
Table E.1 — Scrambler examples 862
Table E.2 — Initial scrambler output 863
Table G.1 — Minimum deletable primitive insertion rate examples 868
Table H.1 — Zone permission table example initial value 869
Table H.2 — CONFIGURE ZONE PERMISSION TABLE request example 869
Table H.3 — Zone permission table after processing first zone permission configuration descriptor 870
Table H.4 — Zone permission table after processing second zone permission configuration descriptor 871
Table J.1 — Column descriptions for connection examples 873
Table K.1 — Primitives with Hamming distance of at least 7 894
Table K.2 — Primitives without Hamming distance of 7 896
Table L.1 — Standards bodies 897

Figure 1 — Organization of this document 41
Figure 2 — SCSI document relationships 42
Figure 3 — ATA document relationships 42
Figure 4 — Examples of association relationships in class diagrams 85
Figure 5 — Examples of aggregation relationships in class diagrams 86
Figure 6 — Example of generalization relationships in class diagrams 87
Figure 7 — Example of a dependency relationship in class diagrams 87
Figure 8 — Examples of link relationships for object diagrams 89
Figure 9 — State machine conventions 90
Figure 10 — SAS Domain class diagram 95
Figure 11 — Phy class diagram 97
Figure 12 — SAS phy object diagram 98
Figure 13 — Expander phy object diagram 99
Figure 14 — Ports (narrow ports and wide ports) 101
Figure 15 — Port class diagram 102
Figure 16 — Port object diagram 103
Figure 17 — SAS devices 105
Figure 18 — Expander device 106
Figure 19 — Domains 107
Figure 20 — SAS domain bridging to ATA domains 108
Figure 21 — SAS domains bridging to ATA domains with SATA port selectors 109
Figure 22 — Devices spanning SAS domains 110
Figure 23 — Single expander device topology example 111
Figure 24 — Multiple expander device topologies and routing methods 112
Figure 25 — Potential pathways 113
Figure 26 — Multiple connections on wide ports 115
Figure 27 — State machines for SAS devices 125
Figure 28 — State machines for expander devices 126
Figure 29 — Transmit data path in a SAS phy 127
Figure 30 — SSP link, port, SSP transport, and SCSI application layer state machines 128
Figure 31 — SMP link, port, SMP transport, and management application layer state machines 129
Figure 32 — STP link, port, STP transport, and ATA application layer state machines 130
Figure 33 — Transmit data path and state machines in an expander phy 131
Figure 34 — Receive data path in a SAS phy 133
Figure 35 — Receive data path in an expander phy 134
Figure 36 — State machines and SAS Device classes 135
Figure 37 — State machines and Expander Device classes 136
Figure 38 — Reset terminology 138
Figure 39 — Expander device model 142
Figure 40 — Expander device interfaces 145
Figure 41 — Expander device interface detail 146
Figure 42 — Phy-based expander route table 154
Figure 43 — Expander-based expander route table 155
Figure 44 — Level-order traversal example 158
Figure 45 — Examples of invalid topologies 162
Figure 46 — Externally configurable expander device and table-to-table attachment 165
Figure 47 — Expander route index levels example 166
Figure 48 — Expander route index order example 168
Figure 49 — Zoning example 170
Figure 50 — One ZPSDS example 171
Figure 51 — Zone manager location examples 172
Figure 52 — Three ZPSDSes example 173
Figure 53 — Extending a ZPSDS example 175
Figure 54 — Overtaking a ZPSDS example 176
Figure 55 — Zoning expander route table 183
Figure 56 — SAS bit transmission logic 213
Figure 57 — SAS bit reception logic 214

Figure 58 — OOB signal transmission 215
Figure 59 — OOB signal detection 217
Figure 60 — TTIU transmitter BMC encoding 223
Figure 61 — TTIU bit cell transmitter encoding 224
Figure 62 — TTIU bit cell receiver decoding 225
Figure 63 — SATA OOB sequence 234
Figure 64 — SATA speed negotiation sequence 234
Figure 65 — SAS to SATA OOB sequence 236
Figure 66 — SAS to SAS OOB sequence 238
Figure 67 — SNW-1, SNW-2, and Final-SNW 242
Figure 68 — SNW-3 244
Figure 69 — Train_Tx-SNW 245
Figure 70 — Pattern marker transmission 247
Figure 71 — Valid pattern marker detection 248
Figure 72 — Train_Rx-SNW 249
Figure 73 — SAS speed negotiation sequence SNW flowchart 251
Figure 74 — SAS speed negotiation sequence (both phys SNW-1 through Train_Rx-SNW with no Train_Tx-SNW) 253
Figure 75 — SAS speed negotiation sequence (both phys SNW-1 through Train_Rx-SNW with Train_Tx-SNW) 254
Figure 76 — SAS speed negotiation sequence (phy A: SNW-1 through SNW-3, phy B: SNW-2 only) 255
Figure 77 — SAS speed negotiation sequence (phy A: SNW-3 only, phy B: SNW-1 only) 256
Figure 78 — SAS speed negotiation sequence - phy reset problem in Final-SNW 257
Figure 79 — SAS speed negotiation sequence - phy reset problem in SNW-3 258
Figure 80 — SAS speed negotiation sequence - phy reset problem in Train_Rx-SNW 259
Figure 81 — SAS speed negotiation sequence - multiple Train_Rx-SNWs 260
Figure 82 — Local phy achieves pattern lock before the attached phy achieves pattern lock 262
Figure 83 — Local phy achieves pattern lock after the attached phy achieves pattern lock 263
Figure 84 — Attached receiver handshake sequence (requesting two increments to coefficient 1) 265
Figure 85 — Attached receiver handshake sequence (requesting a decrement and an increment to coefficient 1) 266
Figure 86 — Handshake sequence to set local phy's receiver coefficients to no_equalization values (attached phy) 268
Figure 87 — Handshake sequence to set local phy's receiver coefficients to no_equalization values (local phy) 269
Figure 88 — Local phy's receiver indicates completion of training before the attached phy's receiver completes training 270
Figure 89 — Attached phy's receiver indicates completion of training before the local phy's receiver completes training 271
Figure 90 — Processing an invalid TTIU 273
Figure 91 — Hot-plug and the phy reset sequence 275
Figure 92 — Transition to active phy power condition 276
Figure 93 — Hot plug and low phy power condition 277
Figure 94 — SP (phy layer) state machine - OOB sequence states 283
Figure 95 — SP (phy layer) state machine - SAS speed negotiation states 290
Figure 96 — SP (phy layer) state machine - SAS speed negotiation states for SNW-3 and Train_Rx-SNW and Train_Tx-SNW 291
Figure 97 — SP (phy layer) state machine - SAS phy power condition states 303
Figure 98 — SP (phy layer) state machine - SATA host emulation states 306
Figure 99 — SP (phy layer) state machine – SATA port selector state 311
Figure 100 — SP (phy layer) state machine - SATA spinup hold state 312
Figure 101 — SP_DWS (phy layer dword synchronization) state machine 314
Figure 102 — PTT_T (phy layer transmitter training transmit pattern) state machine 326
Figure 103 — PTT_R (phy layer transmitter training receive pattern) state machine 334
Figure 104 — PTT_SC1, PTT_SC2, and PTT_SC3 (phy layer transmitter training set transmitter coefficient) state machines 342
Figure 105 — PTT_GC1, PTT_GC2, and PTT_GC3 (phy layer transmitter training get transmitter

coefficient) state machines 347
Figure 106 — PTT_PL (phy layer transmitter training pattern lock) state machine 351
Figure 107 — Multiplexing disabled 354
Figure 108 — Multiplexing enabled 355
Figure 109 — Transmitting a repeated primitive sequence 372
Figure 110 — Receiving a repeated primitive sequence 372
Figure 111 — Extended primitive sequences 373
Figure 112 — Triple primitive sequences 374
Figure 113 — Redundant primitive sequences 375
Figure 114 — Elasticity buffer 389
Figure 115 — Address frame, SSP frame, and SMP frame CRC bit ordering 394
Figure 116 — STP frame CRC bit ordering 395
Figure 117 — Transmit path bit ordering 398
Figure 118 — Receive path bit ordering 399
Figure 119 — STP transmit path bit ordering 400
Figure 120 — STP receive path bit ordering 401
Figure 121 — Address frame transmission 402
Figure 122 — Identification sequence 412
Figure 123 — Hard reset sequence 413
Figure 124 — SL_IR (link layer identification and hard reset) state machines 415
Figure 125 — Transitioning from the active phy power condition to a low phy power condition 421
Figure 126 — SL_P_S (link layer power source device) state machine 424
Figure 127 — SL_P_C (link layer power consumer device) state machine 428
Figure 128 — Example simultaneous connection recommendations for wide ports 434
Figure 129 — Aborting a connection request with a BREAK primitive sequence 443
Figure 130 — Connection request timeout example 444
Figure 131 — Closing a connection example 445
Figure 132 — Rate matching example 448
Figure 133 — SL (link layer for SAS logical phys) state machines (part 1) 450
Figure 134 — SL (link layer for SAS logical phys) state machines (part 2) 451
Figure 135 — SL (link layer for SAS logical phys) state machines (part 3) 452
Figure 136 — XL (link layer for expander logical phys) state machine (part 1) 472
Figure 137 — XL (link layer for expander logical phys) state machine (part 2) 473
Figure 138 — XL (link layer for expander logical phys) state machine (part 3) 474
Figure 139 — XL (link layer for expander logical phys) state machine (part 4) 475
Figure 140 — SSP frame transmission 494
Figure 141 — Interlocked frames 496
Figure 142 — Non-interlocked frames with the same initiator port transfer tags 497
Figure 143 — Non-interlocked frames with different initiator port transfer tags 497
Figure 144 — Closing an SSP connection example 499
Figure 145 — SSP (link layer for SSP phys) state machines (part 1 - frame transmission) 501
Figure 146 — SSP (link layer for SSP phys) state machines (part 2 - frame reception) 502
Figure 147 — SSP (link layer for SSP phys) state machines (part 3 - persistent connection) 503
Figure 148 — STP frame transmission 515
Figure 149 — STP flow control 518
Figure 150 — Transmitting a continued primitive sequence 520
Figure 151 — Receiving a continued primitive sequence 520
Figure 152 — Example simultaneous connection recommendations for an expander device 524
Figure 153 — STP initiator port opening an STP connection 526
Figure 154 — STP target port opening an STP connection 527
Figure 155 — SMP frame transmission 528
Figure 156 — SMP_IP (link layer for SMP initiator phys) state machine 530
Figure 157 — SMP_TP (link layer for SMP target phys) state machine 533
Figure 158 — Port layer examples 536
Figure 159 — PL_OC (port layer overall control) state machine 539
Figure 160 — PL_PM (port layer phy manager) state machine (part 1) 552
Figure 161 — PL_PM (port layer phy manager) state machine (part 2) 553

Figure 162 — Task management function sequence of SSP frames 578
Figure 163 — Non-data command sequence of SSP frames 578
Figure 164 — Write command sequence of SSP frames 579
Figure 165 — Read command sequence of SSP frames 579
Figure 166 — Bidirectional command sequence of SSP frames 580
Figure 167 — ST_I (transport layer for SSP initiator ports) state machines 589
Figure 168 — ST_T (transport layer for SSP target ports) state machines 605
Figure 169 — Sequence of SMP frames 627
Figure 170 — MT_IP (transport layer for SMP initiator ports) state machine 628
Figure 171 — MT_TP (transport layer for SMP target ports) state machine 630
Figure 172 — SA_PC (SCSI application layer power condition) state machine for SAS 679
Figure A.1 — CJTPAT pre-scrambling 835
Figure B.1 — SAS speed negotiation sequence (phy A: SNW-1 only, phy B: SNW-1 only) 844
Figure B.2 — SAS speed negotiation sequence (phy A: SNW-1, SNW-2, phy B: SNW-1, SNW-2) 845
Figure B.3 — SAS speed negotiation sequence (phy A: SNW-1, SNW-2, and SNW-3, phy B: SNW-1 and SNW-2) 846
Figure B.4 — SAS speed negotiation sequence (phy A: SNW-2, SNW-3, phy B: SNW-1, SNW-2) 847
Figure B.5 — SAS speed negotiation sequence (phy A: SNW-1 only, phy B: SNW-2 only) 848
Figure C.1 — CRC generator example 849
Figure C.2 — CRC checker example 849
Figure D.1 — BCH(69, 39, 9) code generator 854
Figure E.1 — Scrambler 860
Figure J.1 — Example topology 873
Figure J.2 — Connection request - OPEN_ACCEPT 875
Figure J.3 — Connection request - OPEN_REJECT by end device 876
Figure J.4 — Connection request - OPEN_REJECT by expander device 877
Figure J.5 — Connection request - arbitration lost 878
Figure J.6 — Connection request - backoff and retry 879
Figure J.7 — Connection request - backoff and reverse path 880
Figure J.8 — Connection close - single step 881
Figure J.9 — Connection close - simultaneous 882
Figure J.10 — BREAK handling during path arbitration when the BREAK_REPLY method is disabled 883
Figure J.11 — BREAK handling during a connection when the BREAK_REPLY method is disabled 884
Figure J.12 — BREAK handling during path arbitration when the BREAK_REPLY method is enabled 885
Figure J.13 — BREAK handling during a connection when the BREAK_REPLY method is enabled 886
Figure J.14 — STP connection - originated by STP initiator port 887
Figure J.15 — STP connection - originated by STP target port in an STP SATA bridge 888
Figure J.16 — STP connection close - originated by STP initiator port 889
Figure J.17 — STP connection close - originated by STP target port in an STP SATA bridge 890
Figure J.18 — XL1:Request_Path to XL5:Forward_Open transition 891
Figure J.19 — Partial pathway recovery 892
Figure M.1 — Example of a requesting SAS device’s sequencing of a successful request for entering a partial phy power condition 899
Figure M.2 — Example of a SAS device’s sequencing for a successful request to enter a partial phy power condition 900