

ISO 14117:2019-09 (E)

Active implantable medical devices - Electromagnetic compatibility - EMC test protocols for implantable cardiac pacemakers, implant able cardioverter defibrillators and cardiac resynchronization devices

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms, definitions, symbols and abbreviated terms | 1 |
| 3.1 | Terms and definitions | 1 |
| 3.2 | Acronyms and abbreviations | 3 |
| 4 | Test requirements for the frequency band 0 Hz – 3 000 MHz | 4 |
| 4.1 | General requirements for all devices | 4 |
| 4.2 | Induced lead current | 5 |
| 4.2.1 | General requirements | 5 |
| 4.2.2 | Pacemakers and CRT-P devices | 5 |
| 4.2.3 | ICDs and CRT-D devices | 9 |
| 4.3 | Protection from persisting malfunction attributable to ambient electromagnetic fields | 12 |
| 4.3.1 | General requirements | 12 |
| 4.3.2 | Pacemaker and CRT-P devices | 12 |
| 4.3.3 | ICDs and CRT-D devices | 17 |
| 4.4 | Protection from malfunction caused by temporary exposure to CW sources | 23 |
| 4.4.1 | Pacemaker and CRT-P device' response to temporary continuous wave sources in the frequency range 16,6 Hz to 167 kHz | 23 |
| 4.4.2 | ICDs and CRT-D devices | 25 |
| 4.5 | Protection from sensing EMI as cardiac signals | 26 |
| 4.5.1 | General requirements | 26 |
| 4.5.2 | Protection from sensing EMI as cardiac signals in the frequency range of 16,6 Hz to 150 kHz | 27 |
| 4.5.3 | Protection from sensing EMI as cardiac signals in the frequency range of 150 kHz to 10 MHz | 30 |
| 4.5.4 | Protection from sensing EMI as cardiac signals in the frequency range of 10 MHz to 385 MHz | 33 |
| 4.6 | Protection from static magnetic fields of flux density up to 1 mT | 35 |
| 4.6.1 | General requirements | 35 |
| 4.6.2 | Pacemakers and CRT-P devices | 35 |
| 4.6.3 | ICDs and CRT-D devices | 36 |
| 4.7 | Protection from static magnetic fields of flux density up to 50 mT | 37 |
| 4.7.1 | General requirements | 37 |
| 4.7.2 | Pacemakers and CRT-P devices | 37 |
| 4.7.3 | ICDs and CRT-D devices | 37 |
| 4.8 | Protection from AC magnetic field exposure in the range of 1 kHz to 140 kHz | 37 |
| 4.8.1 | General requirements | 37 |
| 4.8.2 | Pacemakers and CRT-P devices | 37 |
| 4.8.3 | ICDs and CRT-D devices | 38 |
| 4.9 | Test requirements for the frequency range of 385 MHz – 3 000 MHz | 38 |
| 4.9.1 | General requirements | 38 |
| 4.9.2 | Test setup | 39 |

| | | |
|-------|--|-----|
| 4.9.3 | Test procedure | 40 |
| 4.9.4 | Performance criteria | 42 |
| 4.10 | Transient exposure to stationary low-frequency electromagnetic field sources in the frequency range 16,6 Hz to 167 kHz | 43 |
| 5 | Testing above frequency of 3 000 MHz | 43 |
| 6 | Protection of devices from EM fields encountered in a therapeutic environment | 43 |
| 6.1 | Protection of the device from damage caused by high-frequency surgical exposure | 43 |
| 6.1.1 | General requirements | 43 |
| 6.1.2 | Pacemakers and CRT-P devices | 44 |
| 6.1.3 | ICDs and CRT-D devices | 44 |
| 6.2 | Protection of the device from damage caused by external defibrillators | 45 |
| 6.2.1 | General requirements | 45 |
| 6.2.2 | Pacemakers and CRT-P devices | 45 |
| 6.2.3 | ICDs and CRT-D devices | 48 |
| 7 | Additional accompanying documentation | 49 |
| 7.1 | Disclosure of permanently programmable sensitivity settings | 49 |
| 7.2 | Descriptions of reversion modes | 49 |
| 7.3 | Known potential hazardous behaviour | 49 |
| 7.4 | Minimum separation distance from hand-held transmitters | 49 |
| | Annex A (informative) Rationale | 50 |
| | Annex B (informative) Rationale for test frequency ranges | 63 |
| | Annex C (informative) Code for describing modes of implantable generators | 64 |
| | Annex D (normative) Interface circuits | 66 |
| | Annex E (informative) Selection of capacitor Cx | 71 |
| | Annex F (normative) Calibration of the injection network (Figure D.5) | 74 |
| | Annex G (normative) Torso simulator | 76 |
| | Annex H (normative) Dipole antennas | 80 |
| | Annex I (normative) Pacemaker/ICD programming settings | 82 |
| | Annex J (normative) Simulated cardiac signal | 84 |
| | Annex K (normative) Calculation of net power into dipole antenna | 85 |
| | Annex L (informative) Loop area calculations | 90 |
| | Annex M (informative) Correlation between levels of test voltages used in this document and strengths of radiated fields | 96 |
| | Annex N (informative) Connections to DUTs having ports with more than two electrode connections | 104 |
| | Annex O (informative) Example method for evaluation of transient and permanent malfunction of a CIED due to temporary exposure to low frequency (<167 kHz) electromagnetic fields | 127 |
| | Bibliography | 132 |