ISO/IEC 14165-246:2019-12 (E)

Information technology - Fibre channel - Part 246 : Backbone - 6 (FC-BB-6)

Contents

Page

Foreword . . . xiv

Introduction . . . xviii

1 Scope . . . 1

2 Normative References . . . 5
2.1 Overview . . . 5
2.2 Approved references . . . 5
2.3 References under development . . . 6
2.4 ITU-T references . . . 6
2.5 IETF references . . . 6
2.6 IEEE references . . . 7

3 Definitions and conventions . . . 8
3.1 Common definitions . . . 8
3.2 FC-BB_IP definitions . . . 10
3.3 FC-BB_GFPT definitions . . . 12
3.4 FC-BB_PW definitions . . . 13
3.5 FC-BB_E definitions . . . 13
3.6 Editorial conventions . . . 16
3.7 List of commonly used acronyms and abbreviations . . . 17
3.7.1 General . . . 17
3.7.2 FC-BB_IP . . . 18
3.7.3 FC-BB_GFPT . . . 18
3.7.4 FC-BB_PW . . . 18
3.7.5 FC-BB_E . . . 18
3.8 Symbols . . . 19
3.9 Keywords . . . 19

4 FC-BB-6 Structure and Concepts . . . 20
4.1 FC-BB-6 backbone mappings . . . 20
4.2 FC-BB-6 reference models . . . 20
4.2.1 FC-BB-6 reference models overview . . . 20
4.2.2 FC-BB_IP reference model . . . 21
4.2.3 FC-BB_GFPT reference model . . . 23
4.2.4 FC-BB_PW reference model . . . 24
4.2.5 FC-BB_E reference models . . . 25
4.2.5.1 FC-BB_E VN_Port to VF_Port reference model . . . 25
4.2.5.2 FC-BB_E VE_Port to VE_Port reference model . . . 25
4.2.5.3 FC-BB_E VN_Port to VN_Port reference model . . . 26
4.2.5.4 FC-BB_E VA_Port to VA_Port reference model . . . 27
4.3 FC-BB-6 models overview . . . 27
4.3.1 FC-BB_IP . . . 27
4.3.2 FC-BB_GFPT . . . 28
4.3.3 FC-BB_PW . . . 28
4.3.4 FC-BB_E . . . 29
4.4 FC-BB-6 requirements . . . 29
4.4.1 Fibre Channel Class support . . . 29
4.4.2 Payload transparency . . . 29
4.4.2.1 FC-BB_IP . . . 29
4.4.2.2 Transparent FC-BB (FC-BB_GFPT and FC-BB_PW) . . . 30

4.4.2.3 FC-BB_E . . . 30
4.4.3 Latency delay and timeout value . . . 30
4.4.4 QoS and bandwidth . . . 31
4.4.5 In-order delivery . . . 31
4.4.6 Flow control . . . 31
4.5 FC-BB-6 SW_ILS codes . . . 32

5 FC-BB_IP Structure and Concepts . . . 33
5.1 Applicability . . . 33
5.2 FC-BB_IP overview . . . 33
5.3 VE_Port functional model . . . 34
5.3.1 FC-BB_IP interface protocol layers . . . 34
5.3.2 E_Port/F_Port FC interface . . . 36
5.3.3 FC Switching Element (SE) with FC routing . . . 36
5.3.4 FC-BB_IP protocol interface . . . 36
5.3.4.1 Major components . . . 36
5.3.4.2 FC and FCIP Entities . . . 36
5.3.4.3 VE_Port Virtual ISL exchanges . . . 39
5.3.4.4 Control and Service Module (CSM) . . . 39
5.3.4.5 Platform Management Module (PMM) . . . 39
5.3.5 IP network interface . . . 42
5.4 B_Access functional model . . . 42
5.4.1 FC-BB_IP interface protocol layers . . . 42
5.4.2 B_Port FC interface . . . 42
5.4.3 FC-BB_IP protocol interface . . . 42
5.4.3.1 Major components . . . 42
5.4.3.2 FC and FCIP Entities . . . 43
5.4.3.3 B_Access Virtual ISL exchanges . . . 45
5.4.3.4 B_Port Control and Service Module (CSM) . . . 49
5.4.3.5 B_Port Platform Management Module (PMM) . . . 49
5.4.4 IP Network Interface . . . 49
5.5 FC-BB_IP network topologies . . . 49
5.6 Mapping and message encapsulation using TCP/IP . . . 51
5.6.1 Encapsulated frame structures . . . 51
5.6.1.1 FC frame encapsulation structure . . . 51
5.6.1.2 Encapsulated FCIP Special Frame (FSF) structure . . . 52
5.6.2 TCP/IP encapsulation . . . 53
5.7 FC-BB_IP protocol procedures . . . 54
5.7.1 Overview . . . 54
5.7.2 Procedures for platform management . . . 54
5.7.2.1 Function . . . 54
5.7.2.2 Procedures for discovery . . . 54
5.7.2.3 Procedures for extending FC-SP-2 security . . . 54
5.7.3 Procedures for connection management . . . 56
5.7.3.1 Function . . . 56
5.7.3.2 Procedures for link setup . . . 57
5.7.3.3 Procedures for data transfer . . . 57
5.7.3.4 Procedures for FCIP Link disconnection . . . 58
5.7.3.5 Procedures for multiple connection management . . . 58
5.7.4 Procedures for error detection recovery . . . 58
5.7.4.1 Procedures for handling invalid FC frames . . . 58
5.7.4.2 Procedures for error recovery . . . 59
5.7.5 FC-BB_IP system parameters . . . 59
5.7.5.1 FC timers . . . 59

5.7.5.2 TCP timers . . . 59
5.7.5.3 Maximum number of attempts to complete an encapsulated FC frame transmission . . . 59
5.7.5.4 Maximum number of outstanding encapsulated FC frames . . . 60
5.8 FC-BB_IP service considerations . . . 60
5.8.1 Latency delay . . . 60
5.8.2 Throughput . . . 60
5.8.2.1 How timeouts affect throughput . . . 60
5.8.2.2 How loss affects throughput . . . 60
5.8.2.3 Other factors that affect throughput . . . 60
5.8.3 Reliability . . . 61
5.8.3.1 Loss of connectivity . . . 61
5.8.3.2 Loss of synchronization . . . 61
5.8.3.3 Loss or corruption of TCP segments . . . 61
5.8.3.4 Loss or corruption of FC frames . . . 61
5.8.3.5 FCIP error reporting . . . 61
5.8.4 Quality of Service (QoS) . . . 62
5.8.5 Delivery order . . . 62
5.8.6 IP multicast and broadcast . . . 62
5.8.7 Security and authentication . . . 62

6 Transparent FC-BB (FC-BB_GFPT and FC-BB_PW) Structure and Concepts . . . 64
6.1 Applicability . . . 64
6.2 FC-BB_GFPT overview . . . 64
6.3 FC-BB_PW overview . . . 65
6.4 Transparent FC-BB functional model . . . 66
6.4.1 Transparent FC-BB initialization . . . 66
6.4.2 Transparent FC-BB initialization state machine . . . 66
6.4.2.1 Initialization state machine keywords . . . 66
6.4.2.2 Initialization state machine . . . 66
6.4.3 Login Exchange Monitors . . . 71
6.4.4 Port initialization parameter observation and modification . . . 75
6.4.5 Handling of BB_SCs, BB_SCr, and R_RDY Primitive Signals and BB_Credit initialization . . . 76
6.4.6 Transparent FC-BB Primitive Signals . . . 77
6.4.7 Transparent FC-BB flow control . . . 78
6.4.7.1 Overview . . . 78
6.4.7.2 FC-BB_GFPT Alternate Simple Flow Control (ASFC) . . . 78
6.4.7.3 FC-BB_PW Alternate Simple Flow Control (ASFC) . . . 78
6.4.7.4 PING and PING_ACK signals . . . 79
6.4.8 Adaptation of FC information for Transparent FC-BB . . . 81
6.4.8.1 Adaptation of FC information for GFPT transport in FC-BB_GFPT . . . 81
6.4.8.2 Adaptation of FC information for PW transport in FC-BB_PW . . . 83
6.4.9 WAN Holdoff Timeout Value (WAN_HOLDOFF_TOV) . . . 85
6.4.10 Transparent FC-BB frame compression encoding . . . 85
6.4.10.1 FC-BB_GFPT FC frame compression . . . 85
6.4.10.2 FC-BB_PW FC frame compression . . . 86
6.4.10.3 LZS compression algorithm . . . 86

7 FC-BB_E Structure and Concepts . . . 87
7.1 Applicability . . . 87
7.2 FC-BB_E overview . . . 87
7.3 ENode functional model . . . 93
7.4 VN2VN ENode functional model . . . 94

7.5 FCF functional model 96
7.6 Controlling FCF functional model 99
7.7 FDF functional model 101
7.8 FCoE Virtual Links 103
7.9 VN_Port MAC addresses 108
7.10 FCoE frame format 108
7.11 FC-BB_E device initialization 109
7.11.1 FCoE Initialization Protocol (FIP) overview 109
7.11.2 FIP VLAN discovery protocol 110
7.11.2.1 Overview 110
7.11.2.2 ENode/FCF VLAN discovery 110
7.11.2.3 FCF/FCF VLAN discovery 112
7.11.2.4 VN2VN ENode VLAN discovery 112
7.11.2.5 ENode/FDF VLAN discovery 115
7.11.2.6 FDF/Controlling FCF VLAN discovery 115
7.11.3 FIP discovery protocol 115
7.11.3.1 Overview 115
7.11.3.2 ENode/FCF discovery 115
7.11.3.3 FCF/FCF discovery 118
7.11.3.4 FDF/Controlling FCF discovery 120
7.11.4 FCoE Virtual Link instantiation protocol 121
7.11.4.1 VN_Port to VF_Port Virtual Links 121
7.11.4.2 VE_Port to VE_Port Virtual Links 121
7.11.4.3 VN_Port to VN_Port Virtual Links 122
7.11.4.4 VA_Port to VA_Port Virtual Links 122
7.11.5 FCoE Virtual Link maintenance protocol 123
7.11.5.1 Virtual Link maintenance protocol overview 123
7.11.5.2 VN_Port to VF_Port Virtual Link maintenance protocol 123
7.11.5.3 VE_Port to VE_Port Virtual Link maintenance protocol 126
7.11.5.4 VN_Port to VN_Port Virtual Link and VN2VN Neighbor Set maintenance protocol 126
7.11.5.5 VA_Port to VA_Port Virtual Link maintenance protocol 127
7.11.6 Locally Unique N_Port_IDs 127
7.11.6.1 Overview 127
7.11.6.2 Multi-node operation 128
7.11.6.3 Point-to-point operation 130
7.11.6.4 Persistence of Locally Unique N_Port_IDs 131
7.11.7 FIP frames 132
7.11.7.1 FIP frame format 132
7.11.7.2 Encapsulated FIP operation 132
7.11.7.3 FIP descriptors 136
7.11.8 FIP operations 146
7.11.8.1 FIP operations overview 146
7.11.8.2 FIP Discovery Solicitation 150
7.11.8.3 FIP Discovery Advertisements 152
7.11.8.4 FIP Virtual Link Instantiation requests and replies 152
7.11.8.5 FIP Keep Alive 156
7.11.8.6 FIP Clear Virtual Links 156
7.11.8.7 FIP VLAN Request 157
7.11.8.8 FIP VLAN Notification 158
7.11.8.9 FIP VN2VN VLAN Notification 158
7.11.8.10 FIP Vendor Specific frames 158
7.11.8.11 N_Port_ID Probe Request 158
7.11.8.12 N_Port_ID Probe Reply 159

7.11.8.13 N_Port_ID Claim Notification . . . 159
7.11.8.14 N_Port_ID Claim Response . . . 159
7.11.8.15 N_Port_ID Beacon . . . 160
7.12 Timers and constants . . . 160
7.13 FC-BB_E Link Error Status Block (LESB) definition . . . 162
7.14 Link incidents definition . . . 163
7.15 Distributed FCF operations . . . 164

Annex A: FC-BB_GFPT Interoperability Guidelines (Informative) . . . 165
A.1 GFPT-specific interoperability guidelines . . . 165

Annex B: FCoE and FIP Frame Examples (Informative) . . . 166
B.1 Overview . . . 166

Annex C: Increasing FC-BB_E Robustness Using Access Control Lists (Informative) . . . 167
C.1 Overview . . . 167
C.2 Access Control Lists . . . 168
C.2.1 ACL overview . . . 168
C.2.2 ACL nomenclature . . . 169
C.3 Perimeter ACL construction . . . 169
C.3.1 Perimeter ACL construction overview . . . 169
C.3.2 FIP frame transmission . . . 170
C.3.3 Prevention of the transmission of frames using an FCF-MAC address for the source address . . . 170
C.3.4 Prevention of frames using FCoE Type or FCoE source addresses prior to successful completion of FIP FLOGI . . . 170
C.3.5 Enabling traffic after successful completion of FIP FLOGI or FIP NPIV FDISC 170
C.3.6 Prevention of duplicate VN_Port MAC addresses . . . 170
C.3.7 ACL summary . . . 171
C.4 Security in depth . . . 171
C.4.1 Overview . . . 171
C.4.2 Bridge-to-bridge link receiving ENode frames destined to FCF(s) . . . 172
C.4.3 Bridge-to-bridge link receiving FCF frames destined to ENode(s) . . . 172
C.4.4 Bridge-to-bridge link receiving both FCF and ENode frames . . . 173
C.4.5 Additional FCF protection . . . 173
C.5 Prevention of FCoE related traffic . . . 173
C.6 Automatic configuration of ACLs . . . 174
C.7 Ethernet bridge learning considerations . . . 174
C.8 VLAN considerations . . . 175
C.9 Access Control Lists in a Locally Unique N_Port_ID configuration . . . 175
C.9.1 Overview . . . 175
C.9.2 Prevention of FCoE traffic . . . 175
C.9.3 FCoE perimeter ACL . . . 175
C.9.4 Graceful handling of network joins . . . 176

Annex D: FCoE Security Recommendations (Informative) . . . 178
D.1 Overview . . . 178
D.2 Considerations . . . 178
D.3 General deployment recommendations . . . 178
D.4 Bridge recommendations . . . 178
D.5 ENode and FCF recommendations . . . 180
D.6 Additional threat isolation using FPMAs . . . 182

Annex E: FCoE MIB Definition (Normative) . . . 184
E.1 FCoE MIB definition . . . 184

Annex F: Locally Unique N_Port_ID (Informative) . . . 205

Annex G: Options for Handling FCoE and FIP Traffic (Informative) . . . 211

Tables **Page**

Table 1 – FC-BB-6 organization . . . 1
Table 2 – Reference models and resident FC_Port types . . . 21
Table 3 – FC-BB-6 SW_ILS codes . . . 32
Table 4 – FC-BB-6 ELS codes . . . 32
Table 5 – EBP request payload . . . 46
Table 6 – EBP accept payload . . . 46
Table 7 – EBP reject reason code explanation . . . 47
Table 8 – TCP/IP Segment structure carrying encapsulated FC frame . . . 51
Table 9 – Encapsulated FC frame structure . . . 51
Table 10 – TCP/IP Segment structure carrying encapsulated FSF . . . 52
Table 11 – Encapsulated FSF structure . . . 52
Table 12 – ASF request payload . . . 56
Table 13 – ASF accept response payload . . . 56
Table 14 – Transparent FC-BB initialization state machine keywords . . . 66
Table 15 – Login Exchange Monitor (LEM) state machine . . . 74
Table 16 – Values of FC-BB_GFPT ASFC_PAUSE and ASFC_RESUME Primitive Signals . . . 78
Table 17 – FC-BB_PW ASFC_PAUSE and ASFC_RESUME control frame payload values . . . 79
Table 18 – FC-BB_GFPT PING and PING_ACK Primitive Signal values . . . 80
Table 19 – FC-BB_GFPT PING and PING_ACK CCC bit field values . . . 80
Table 20 – FC-BB_PW PING and PING_ACK control frame payload values . . . 81
Table 21 – FC-BB_PW error indication control frame payload values . . . 85
Table 22 – FCoE PDU format . . . 108
Table 23 – FCoE SOF field . . . 109
Table 24 – FCoE EOF field . . . 109
Table 25 – FIP PDU format . . . 132
Table 26 – Encapsulated FIP operation format . . . 132
Table 27 – FIP Protocol Code and FIP Subcode field values . . . 133
Table 28 – Fabric Provided bit and Server Provided bit setting . . . 134
Table 29 – FIP descriptor type value ranges . . . 136
Table 30 – FIP descriptor types . . . 137
Table 31 – FIP Priority descriptor format . . . 138
Table 32 – FIP MAC address descriptor format . . . 138
Table 33 – FIP FC-MAP descriptor format . . . 138
Table 34 – FIP Name_Identifier descriptor format . . . 139
Table 35 – FIP Fabric descriptor format . . . 139
Table 36 – FIP Max FCoE Size descriptor format . . . 139
Table 37 – FIP FLOGI descriptor format . . . 140
Table 38 – FIP NPIV FDISC descriptor format . . . 140
Table 39 – FIP LOGO descriptor format . . . 141
Table 40 – FIP ELP descriptor format . . . 141
Table 41 – FIP Vx_Port Identification descriptor format . . . 141
Table 42 – FIP FKA_ADV_Period descriptor format . . . 142
Table 43 – FIP Vendor_ID descriptor format . . . 143
Table 44 – FIP VLAN descriptor format . . . 143
Table 45 – FIP Vendor Specific descriptor format . . . 143
Table 46 – FIP VN2VN Attributes descriptor format . . . 144
Table 47 – FIP Clear Virtual Links Reason Code descriptor format . . . 144
Table 48 – FIP Clear Virtual Links Reason Codes . . . 145
Table 49 – FIP Clear Virtual Links Reason Code Explanations . . . 145
Table 50 – FIP Clear Virtual Links Reason Code descriptor examples . . . 146
Table 51 – FIP operation descriptors and order . . . 147
Table 52 – FIP Fabric login rejections . . . 154
Table 53 – FC-BB_E timers and constants . . . 160
Table 54 – FC-BB_E Link Error Status Block format . . . 162
Table 55 – FC-BB_E Link Incidents . . . 164
Table B.1 – FCoE frame format example . . . 166
Table B.2 – FIP frame format example . . . 166
Table F.1 – FNV-1a Parameters . . . 208
Table G.1 – Options for handling FCoE and FIP traffic . . . 211

Figures **Page**

Figure 1 – Scope and components of FC-BB_IP model . . . 2
Figure 2 – Scope and components of FC-BB_GFPT model . . . 3
Figure 3 – Scope and components of FC-BB_PW model . . . 4
Figure 4 – Scope and components of FC-BB_E model . . . 4
Figure 5 – FC-BB_IP reference model . . . 22
Figure 6 – FC-BB_GFPT reference model . . . 23
Figure 7 – FC-BB_PW reference model . . . 24
Figure 8 – FC-BB_E VN_Port to VF_Port reference model . . . 25
Figure 9 – FC-BB_E VE_Port to VE_Port reference model . . . 25
Figure 10 – FC-BB_E VN_Port to VN_Port reference model . . . 26
Figure 11 – FC-BB_E VA_Port to VA_Port reference model . . . 27
Figure 12 – FC-BB_IP network configuration . . . 33
Figure 13 – FC-BB_IP VE_Port functional model . . . 35
Figure 14 – FC-BB_IP Protocol Layers . . . 37
Figure 15 – Scope of VE_Port Virtual ISL . . . 39
Figure 16 – Security layers . . . 41
Figure 17 – FC-BB_IP B_Access functional model . . . 44
Figure 18 – Scope of B_Access Virtual ISL . . . 45
Figure 19 – B_Access initialization state machine . . . 48
Figure 20 – FC-BB_IP network topologies . . . 50
Figure 21 – TCP/IP encapsulation of an encapsulated FC frame . . . 53
Figure 22 – FC-BB_GFPT protocol levels and layers . . . 64
Figure 23 – FC-BB_PW protocol levels and layers . . . 65
Figure 24 – Transparent FC-BB initialization state machine . . . 67
Figure 25 – Example port initialization process . . . 77
Figure 26 – FC-BB_PW error indication control frame format . . . 79
Figure 27 – FC-BB_PW PING and PING_ACK control frame format . . . 81
Figure 28 – FC-BB_PW error indication control frame format . . . 85
Figure 29 – FC-BB_E mapping . . . 87
Figure 30 – FC-BB_E protocol levels and layers . . . 88
Figure 31 – FCoE VN_Port to VF_Port network configuration example . . . 89
Figure 32 – FCoE VE_Port to VE_Port network configuration example . . . 89
Figure 33 – FCoE multi-node VN_Port to VN_Port network configuration example . . . 90
Figure 34 – FCoE mixed network configuration example . . . 91
Figure 35 – FCoE point-to-point VN_Port to VN_Port network configuration example . . . 91
Figure 36 – FCoE VA_Port to VA_Port network configuration example . . . 92
Figure 37 – ENode functional model . . . 93
Figure 38 – VN2VN ENode functional model . . . 95
Figure 39 – FCF functional model . . . 97
Figure 40 – Controlling FCF functional model . . . 100
Figure 41 – FDF functional model . . . 102
Figure 42 – VE_Port to VE_Port Virtual Links example . . . 104
Figure 43 – VN_Port to VF_Port Virtual Links example . . . 104
Figure 44 – VN_Port to VN_Port Virtual Links multi-node example . . . 105
Figure 45 – VN_Port to VN_Port and VN_Port to VF_Port Virtual Links example . . . 106
Figure 46 – VN_Port to VN_Port Virtual Link point-to-point example . . . 107
Figure 47 – VA_Port to VA_Port Virtual Link example . . . 107
Figure 48 – VLAN discovery processing example in an ENode MAC (informative) . . . 111
Figure 49 – VLAN discovery processing in a VN2VN ENode MAC . . . 114
Figure C.1 – Bridge port to ACE cross reference . . . 168