

# ISO/IEC 14165-246:2019-12 (E)

## Information technology - Fibre channel - Part 246 : Backbone - 6 (FC-BB-6)

---

### Contents

	Page
Foreword .....	xiv
Introduction .....	xviii
1 Scope .....	1
2 Normative References .....	5
2.1 Overview .....	5
2.2 Approved references .....	5
2.3 References under development .....	6
2.4 ITU-T references .....	6
2.5 IETF references .....	6
2.6 IEEE references .....	7
3 Definitions and conventions .....	8
3.1 Common definitions .....	8
3.2 FC-BB_IP definitions .....	10
3.3 FC-BB_GFPT definitions .....	12
3.4 FC-BB_PW definitions .....	13
3.5 FC-BB_E definitions .....	13
3.6 Editorial conventions .....	16
3.7 List of commonly used acronyms and abbreviations .....	17
3.7.1 General .....	17
3.7.2 FC-BB_IP .....	18
3.7.3 FC-BB_GFPT .....	18
3.7.4 FC-BB_PW .....	18
3.7.5 FC-BB_E .....	18
3.8 Symbols .....	19
3.9 Keywords .....	19
4 FC-BB-6 Structure and Concepts .....	20
4.1 FC-BB-6 backbone mappings .....	20
4.2 FC-BB-6 reference models .....	20
4.2.1 FC-BB-6 reference models overview .....	20
4.2.2 FC-BB_IP reference model .....	21
4.2.3 FC-BB_GFPT reference model .....	23
4.2.4 FC-BB_PW reference model .....	24
4.2.5 FC-BB_E reference models .....	25
4.2.5.1 FC-BB_E VN_Port to VF_Port reference model .....	25
4.2.5.2 FC-BB_E VE_Port to VE_Port reference model .....	25
4.2.5.3 FC-BB_E VN_Port to VN_Port reference model .....	26
4.2.5.4 FC-BB_E VA_Port to VA_Port reference model .....	27
4.3 FC-BB-6 models overview .....	27
4.3.1 FC-BB_IP .....	27
4.3.2 FC-BB_GFPT .....	28
4.3.3 FC-BB_PW .....	28
4.3.4 FC-BB_E .....	29
4.4 FC-BB-6 requirements .....	29
4.4.1 Fibre Channel Class support .....	29
4.4.2 Payload transparency .....	29
4.4.2.1 FC-BB_IP .....	29
4.4.2.2 Transparent FC-BB (FC-BB_GFPT and FC-BB_PW) .....	30

4.4.2.3 FC-BB_E	30
4.4.3 Latency delay and timeout value	30
4.4.4 QoS and bandwidth	31
4.4.5 In-order delivery	31
4.4.6 Flow control	31
4.5 FC-BB-6 SW_ILS codes	32
5 FC-BB_IP Structure and Concepts	33
5.1 Applicability	33
5.2 FC-BB_IP overview	33
5.3 VE_Port functional model	34
5.3.1 FC-BB_IP interface protocol layers	34
5.3.2 E_Port/F_Port FC interface	36
5.3.3 FC Switching Element (SE) with FC routing	36
5.3.4 FC-BB_IP protocol interface	36
5.3.4.1 Major components	36
5.3.4.2 FC and FCIP Entities	36
5.3.4.3 VE_Port Virtual ISL exchanges	39
5.3.4.4 Control and Service Module (CSM)	39
5.3.4.5 Platform Management Module (PMM)	39
5.3.5 IP network interface	42
5.4 B_Access functional model	42
5.4.1 FC-BB_IP interface protocol layers	42
5.4.2 B_Port FC interface	42
5.4.3 FC-BB_IP protocol interface	42
5.4.3.1 Major components	42
5.4.3.2 FC and FCIP Entities	43
5.4.3.3 B_Access Virtual ISL exchanges	45
5.4.3.4 B_Port Control and Service Module (CSM)	49
5.4.3.5 B_Port Platform Management Module (PMM)	49
5.4.4 IP Network Interface	49
5.5 FC-BB_IP network topologies	49
5.6 Mapping and message encapsulation using TCP/IP	51
5.6.1 Encapsulated frame structures	51
5.6.1.1 FC frame encapsulation structure	51
5.6.1.2 Encapsulated FCIP Special Frame (FSF) structure	52
5.6.2 TCP/IP encapsulation	53
5.7 FC-BB_IP protocol procedures	54
5.7.1 Overview	54
5.7.2 Procedures for platform management	54
5.7.2.1 Function	54
5.7.2.2 Procedures for discovery	54
5.7.2.3 Procedures for extending FC-SP-2 security	54
5.7.3 Procedures for connection management	56
5.7.3.1 Function	56
5.7.3.2 Procedures for link setup	57
5.7.3.3 Procedures for data transfer	57
5.7.3.4 Procedures for FCIP Link disconnection	58
5.7.3.5 Procedures for multiple connection management	58
5.7.4 Procedures for error detection recovery	58
5.7.4.1 Procedures for handling invalid FC frames	58
5.7.4.2 Procedures for error recovery	59
5.7.5 FC-BB_IP system parameters	59
5.7.5.1 FC timers	59

5.7.5.2	TCP timers	59
5.7.5.3	Maximum number of attempts to complete an encapsulated FC frame transmission	59
5.7.5.4	Maximum number of outstanding encapsulated FC frames	60
5.8	FC-BB_IP service considerations	60
5.8.1	Latency delay	60
5.8.2	Throughput	60
5.8.2.1	How timeouts affect throughput	60
5.8.2.2	How loss affects throughput	60
5.8.2.3	Other factors that affect throughput	60
5.8.3	Reliability	61
5.8.3.1	Loss of connectivity	61
5.8.3.2	Loss of synchronization	61
5.8.3.3	Loss or corruption of TCP segments	61
5.8.3.4	Loss or corruption of FC frames	61
5.8.3.5	FCIP error reporting	61
5.8.4	Quality of Service (QoS)	62
5.8.5	Delivery order	62
5.8.6	IP multicast and broadcast	62
5.8.7	Security and authentication	62
6	Transparent FC-BB (FC-BB_GFPT and FC-BB_PW) Structure and Concepts	64
6.1	Applicability	64
6.2	FC-BB_GFPT overview	64
6.3	FC-BB_PW overview	65
6.4	Transparent FC-BB functional model	66
6.4.1	Transparent FC-BB initialization	66
6.4.2	Transparent FC-BB initialization state machine	66
6.4.2.1	Initialization state machine keywords	66
6.4.2.2	Initialization state machine	66
6.4.3	Login Exchange Monitors	71
6.4.4	Port initialization parameter observation and modification	75
6.4.5	Handling of BB_SCs, BB_SCr, and R_RDY Primitive Signals and BB_Credit initialization	76
6.4.6	Transparent FC-BB Primitive Signals	77
6.4.7	Transparent FC-BB flow control	78
6.4.7.1	Overview	78
6.4.7.2	FC-BB_GFPT Alternate Simple Flow Control (ASFC)	78
6.4.7.3	FC-BB_PW Alternate Simple Flow Control (ASFC)	78
6.4.7.4	PING and PING_ACK signals	79
6.4.8	Adaptation of FC information for Transparent FC-BB	81
6.4.8.1	Adaptation of FC information for GFPT transport in FC-BB_GFPT	81
6.4.8.2	Adaptation of FC information for PW transport in FC-BB_PW	83
6.4.9	WAN Holdoff Timeout Value (WAN_HOLDOFF_TOV)	85
6.4.10	Transparent FC-BB frame compression encoding	85
6.4.10.1	FC-BB_GFPT FC frame compression	85
6.4.10.2	FC-BB_PW FC frame compression	86
6.4.10.3	LZS compression algorithm	86
7	FC-BB_E Structure and Concepts	87
7.1	Applicability	87
7.2	FC-BB_E overview	87
7.3	ENode functional model	93
7.4	VN2VN ENode functional model	94

7.5	FCF functional model	96
7.6	Controlling FCF functional model	99
7.7	FDL functional model	101
7.8	FCoE Virtual Links	103
7.9	VN_Port MAC addresses	108
7.10	FCoE frame format	108
7.11	FC-BB_E device initialization	109
7.11.1	FCoE Initialization Protocol (FIP) overview	109
7.11.2	FIP VLAN discovery protocol	110
7.11.2.1	Overview	110
7.11.2.2	ENode/FCF VLAN discovery	110
7.11.2.3	FCF/FCF VLAN discovery	112
7.11.2.4	VN2VN ENode VLAN discovery	112
7.11.2.5	ENode/FDL VLAN discovery	115
7.11.2.6	FDL/Controlling FCF VLAN discovery	115
7.11.3	FIP discovery protocol	115
7.11.3.1	Overview	115
7.11.3.2	ENode/FCF discovery	115
7.11.3.3	FCF/FCF discovery	118
7.11.3.4	FDL/Controlling FCF discovery	120
7.11.4	FCoE Virtual Link instantiation protocol	121
7.11.4.1	VN_Port to VF_Port Virtual Links	121
7.11.4.2	VE_Port to VE_Port Virtual Links	121
7.11.4.3	VN_Port to VN_Port Virtual Links	122
7.11.4.4	VA_Port to VA_Port Virtual Links	122
7.11.5	FCoE Virtual Link maintenance protocol	123
7.11.5.1	Virtual Link maintenance protocol overview	123
7.11.5.2	VN_Port to VF_Port Virtual Link maintenance protocol	123
7.11.5.3	VE_Port to VE_Port Virtual Link maintenance protocol	126
7.11.5.4	VN_Port to VN_Port Virtual Link and VN2VN Neighbor Set maintenance protocol	126
7.11.5.5	VA_Port to VA_Port Virtual Link maintenance protocol	127
7.11.6	Locally Unique N_Port_IDs	127
7.11.6.1	Overview	127
7.11.6.2	Multi-node operation	128
7.11.6.3	Point-to-point operation	130
7.11.6.4	Persistence of Locally Unique N_Port_IDs	131
7.11.7	FIP frames	132
7.11.7.1	FIP frame format	132
7.11.7.2	Encapsulated FIP operation	132
7.11.7.3	FIP descriptors	136
7.11.8	FIP operations	146
7.11.8.1	FIP operations overview	146
7.11.8.2	FIP Discovery Solicitation	150
7.11.8.3	FIP Discovery Advertisements	152
7.11.8.4	FIP Virtual Link Instantiation requests and replies	152
7.11.8.5	FIP Keep Alive	156
7.11.8.6	FIP Clear Virtual Links	156
7.11.8.7	FIP VLAN Request	157
7.11.8.8	FIP VLAN Notification	158
7.11.8.9	FIP VN2VN VLAN Notification	158
7.11.8.10	FIP Vendor Specific frames	158
7.11.8.11	N_Port_ID Probe Request	158
7.11.8.12	N_Port_ID Probe Reply	159

7.11.8.13 N_Port_ID Claim Notification	159
7.11.8.14 N_Port_ID Claim Response	159
7.11.8.15 N_Port_ID Beacon	160
7.12 Timers and constants	160
7.13 FC-BB_E Link Error Status Block (LESB) definition	162
7.14 Link incidents definition	163
7.15 Distributed FCF operations	164
Annex A: FC-BB_GFPT Interoperability Guidelines (Informative)	165
A.1 GFPT-specific interoperability guidelines	165
Annex B: FCoE and FIP Frame Examples (Informative)	166
B.1 Overview	166
Annex C: Increasing FC-BB_E Robustness Using Access Control Lists (Informative)	167
C.1 Overview	167
C.2 Access Control Lists	168
C.2.1 ACL overview	168
C.2.2 ACL nomenclature	169
C.3 Perimeter ACL construction	169
C.3.1 Perimeter ACL construction overview	169
C.3.2 FIP frame transmission	170
C.3.3 Prevention of the transmission of frames using an FCF-MAC address for the source address	170
C.3.4 Prevention of frames using FCoE Type or FCoE source addresses prior to successful completion of FIP FLOGI	170
C.3.5 Enabling traffic after successful completion of FIP FLOGI or FIP NPIV FDISC	170
C.3.6 Prevention of duplicate VN_Port MAC addresses	170
C.3.7 ACL summary	171
C.4 Security in depth	171
C.4.1 Overview	171
C.4.2 Bridge-to-bridge link receiving ENode frames destined to FCF(s)	172
C.4.3 Bridge-to-bridge link receiving FCF frames destined to ENode(s)	172
C.4.4 Bridge-to-bridge link receiving both FCF and ENode frames	173
C.4.5 Additional FCF protection	173
C.5 Prevention of FCoE related traffic	173
C.6 Automatic configuration of ACLs	174
C.7 Ethernet bridge learning considerations	174
C.8 VLAN considerations	175
C.9 Access Control Lists in a Locally Unique N_Port_ID configuration	175
C.9.1 Overview	175
C.9.2 Prevention of FCoE traffic	175
C.9.3 FCoE perimeter ACL	175
C.9.4 Graceful handling of network joins	176
Annex D: FCoE Security Recommendations (Informative)	178
D.1 Overview	178
D.2 Considerations	178
D.3 General deployment recommendations	178
D.4 Bridge recommendations	178
D.5 ENode and FCF recommendations	180
D.6 Additional threat isolation using FPMAs	182
Annex E: FCoE MIB Definition (Normative)	184
E.1 FCoE MIB definition	184
Annex F: Locally Unique N_Port_ID (Informative)	205
Annex G: Options for Handling FCoE and FIP Traffic (Informative)	211

<b>Tables</b>	<b>Page</b>
Table 1 – FC-BB-6 organization . . . . .	1
Table 2 – Reference models and resident FC_Port types . . . . .	21
Table 3 – FC-BB-6 SW_ILS codes . . . . .	32
Table 4 – FC-BB-6 ELS codes . . . . .	32
Table 5 – EBP request payload . . . . .	46
Table 6 – EBP accept payload . . . . .	46
Table 7 – EBP reject reason code explanation . . . . .	47
Table 8 – TCP/IP Segment structure carrying encapsulated FC frame . . . . .	51
Table 9 – Encapsulated FC frame structure . . . . .	51
Table 10 – TCP/IP Segment structure carrying encapsulated FSF . . . . .	52
Table 11 – Encapsulated FSF structure . . . . .	52
Table 12 – ASF request payload . . . . .	56
Table 13 – ASF accept response payload . . . . .	56
Table 14 – Transparent FC-BB initialization state machine keywords . . . . .	66
Table 15 – Login Exchange Monitor (LEM) state machine . . . . .	74
Table 16 – Values of FC-BB_GFPT ASFC_PAUSE and ASFC_RESUME Primitive Signals. . . . .	78
Table 17 – FC-BB_PW ASFC_PAUSE and ASFC_RESUME control frame payload values. . . . .	79
Table 18 – FC-BB_GFPT PING and PING_ACK Primitive Signal values. . . . .	80
Table 19 – FC-BB_GFPT PING and PING_ACK CCC bit field values . . . . .	80
Table 20 – FC-BB_PW PING and PING_ACK control frame payload values. . . . .	81
Table 21 – FC-BB_PW error indication control frame payload values . . . . .	85
Table 22 – FCoE PDU format . . . . .	108
Table 23 – FCoE SOF field . . . . .	109
Table 24 – FCoE EOF field . . . . .	109
Table 25 – FIP PDU format . . . . .	132
Table 26 – Encapsulated FIP operation format. . . . .	132
Table 27 – FIP Protocol Code and FIP Subcode field values . . . . .	133
Table 28 – Fabric Provided bit and Server Provided bit setting . . . . .	134
Table 29 – FIP descriptor type value ranges. . . . .	136
Table 30 – FIP descriptor types . . . . .	137
Table 31 – FIP Priority descriptor format. . . . .	138
Table 32 – FIP MAC address descriptor format . . . . .	138
Table 33 – FIP FC-MAP descriptor format . . . . .	138
Table 34 – FIP Name_Identifier descriptor format . . . . .	139
Table 35 – FIP Fabric descriptor format . . . . .	139
Table 36 – FIP Max FCoE Size descriptor format. . . . .	139
Table 37 – FIP FLOGI descriptor format. . . . .	140
Table 38 – FIP NPIV FDISC descriptor format . . . . .	140
Table 39 – FIP LOGO descriptor format . . . . .	141
Table 40 – FIP ELP descriptor format. . . . .	141
Table 41 – FIP Vx_Port Identification descriptor format . . . . .	141
Table 42 – FIP FKA_ADV_Period descriptor format. . . . .	142
Table 43 – FIP Vendor_ID descriptor format. . . . .	143
Table 44 – FIP VLAN descriptor format . . . . .	143
Table 45 – FIP Vendor Specific descriptor format. . . . .	143
Table 46 – FIP VN2VN Attributes descriptor format . . . . .	144
Table 47 – FIP Clear Virtual Links Reason Code descriptor format . . . . .	144
Table 48 – FIP Clear Virtual Links Reason Codes . . . . .	145
Table 49 – FIP Clear Virtual Links Reason Code Explanations . . . . .	145
Table 50 – FIP Clear Virtual Links Reason Code descriptor examples . . . . .	146
Table 51 – FIP operation descriptors and order . . . . .	147
Table 52 – FIP Fabric login rejections. . . . .	154
Table 53 – FC-BB_E timers and constants . . . . .	160
Table 54 – FC-BB_E Link Error Status Block format. . . . .	162
Table 55 – FC-BB_E Link Incidents. . . . .	164
Table B.1 – FCoE frame format example . . . . .	166
Table B.2 – FIP frame format example . . . . .	166
Table F.1 – FNV-1a Parameters . . . . .	208
Table G.1 – Options for handling FCoE and FIP traffic . . . . .	211

<b>Figures</b>	<b>Page</b>
Figure 1 – Scope and components of FC-BB_IP model . . . . .	2
Figure 2 – Scope and components of FC-BB_GFPT model . . . . .	3
Figure 3 – Scope and components of FC-BB_PW model . . . . .	4
Figure 4 – Scope and components of FC-BB_E model . . . . .	4
Figure 5 – FC-BB_IP reference model . . . . .	22
Figure 6 – FC-BB_GFPT reference model . . . . .	23
Figure 7 – FC-BB_PW reference model . . . . .	24
Figure 8 – FC-BB_E VN_Port to VF_Port reference model . . . . .	25
Figure 9 – FC-BB_E VE_Port to VE_Port reference model . . . . .	25
Figure 10 – FC-BB_E VN_Port to VN_Port reference model . . . . .	26
Figure 11 – FC-BB_E VA_Port to VA_Port reference model . . . . .	27
Figure 12 – FC-BB_IP network configuration . . . . .	33
Figure 13 – FC-BB_IP VE_Port functional model . . . . .	35
Figure 14 – FC-BB_IP Protocol Layers . . . . .	37
Figure 15 – Scope of VE_Port Virtual ISL . . . . .	39
Figure 16 – Security layers . . . . .	41
Figure 17 – FC-BB_IP B_Access functional model . . . . .	44
Figure 18 – Scope of B_Access Virtual ISL . . . . .	45
Figure 19 – B_Access initialization state machine . . . . .	48
Figure 20 – FC-BB_IP network topologies . . . . .	50
Figure 21 – TCP/IP encapsulation of an encapsulated FC frame . . . . .	53
Figure 22 – FC-BB_GFPT protocol levels and layers . . . . .	64
Figure 23 – FC-BB_PW protocol levels and layers . . . . .	65
Figure 24 – Transparent FC-BB initialization state machine . . . . .	67
Figure 25 – Example port initialization process . . . . .	77
Figure 26 – FC-BB_PW error indication control frame format . . . . .	79
Figure 27 – FC-BB_PW PING and PING_ACK control frame format . . . . .	81
Figure 28 – FC-BB_PW error indication control frame format . . . . .	85
Figure 29 – FC-BB_E mapping . . . . .	87
Figure 30 – FC-BB_E protocol levels and layers . . . . .	88
Figure 31 – FCoE VN_Port to VF_Port network configuration example . . . . .	89
Figure 32 – FCoE VE_Port to VE_Port network configuration example . . . . .	89
Figure 33 – FCoE multi-node VN_Port to VN_Port network configuration example . . . . .	90
Figure 34 – FCoE mixed network configuration example . . . . .	91
Figure 35 – FCoE point-to-point VN_Port to VN_Port network configuration example . . . . .	91
Figure 36 – FCoE VA_Port to VA_Port network configuration example . . . . .	92
Figure 37 – ENode functional model . . . . .	93
Figure 38 – VN2VN ENode functional model . . . . .	95
Figure 39 – FCF functional model . . . . .	97
Figure 40 – Controlling FCF functional model . . . . .	100
Figure 41 – FDF functional model . . . . .	102
Figure 42 – VE_Port to VE_Port Virtual Links example . . . . .	104
Figure 43 – VN_Port to VF_Port Virtual Links example . . . . .	104
Figure 44 – VN_Port to VN_Port Virtual Links multi-node example . . . . .	105
Figure 45 – VN_Port to VN_Port and VN_Port to VF_Port Virtual Links example . . . . .	106
Figure 46 – VN_Port to VN_Port Virtual Link point-to-point example . . . . .	107
Figure 47 – VA_Port to VA_Port Virtual Link example . . . . .	107
Figure 48 – VLAN discovery processing example in an ENode MAC (informative) . . . . .	111
Figure 49 – VLAN discovery processing in a VN2VN ENode MAC . . . . .	114
Figure C.1 – Bridge port to ACE cross reference . . . . .	168