

# ISO/IEC TR 11801-9909:2020-06 (E)

## Information technology - Generic cabling systems for customer premises - Part 9909: Evaluation of balanced cabling in support of 25 Gbit/s for reach greater than 30 metres

---

<b>Contents</b>	<b>Page</b>
FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references .....	7
3 Terms and definitions .....	7
3.1 Terms and definitions.....	7
3.2 Abbreviated terms.....	7
4 Extended reach channel specifications .....	8
4.1 General.....	8
4.2 Channel performance enhancement methods for increased SNR .....	8
4.2.1 General .....	8
4.2.2 Reduced delay and delay skew.....	9
4.2.3 Enhanced cable.....	9
4.2.4 Enhanced connector .....	9
4.3 Example channel specifications with length scaling.....	9
4.3.1 General .....	9
4.3.2 Return loss (RL) .....	10
4.3.3 Insertion loss (IL).....	10
4.3.4 Near-end crosstalk loss (NEXT).....	11
4.3.5 Attenuation to crosstalk loss ratio near-end (ACR-N).....	11
4.3.6 Attenuation to crosstalk ratio far-end (ACR-F) .....	12
4.3.7 Alien (exogenous) crosstalk.....	12
4.3.8 DC loop resistance .....	13
4.3.9 Propagation delay.....	13
4.3.10 Delay skew.....	13
4.3.11 Unbalance attenuation near end (TCL) and far end (ELTCTL), and coupling attenuation .....	14
Annex A (informative) Reduced delay and delay skew .....	15
A.1 Reduced delay relation to extended reach .....	15
A.1.1 General .....	15
A.1.2 Example reduced delay evaluation.....	15
A.2 Delay relation to insertion loss (IL).....	15
A.2.1 General .....	15
A.2.2 Relation of variable relative permittivity to attenuation .....	16
A.2.3 Relation of dissipation factor to attenuation: .....	16
Annex B (informative) Enhanced capacity .....	18
B.1 Enhanced cabling components.....	18
B.1.1 General .....	18
B.1.2 Enhanced cable.....	18
B.1.3 Enhanced connector .....	18

B.2	Channel SNR margin-to-capacity .....	18
B.2.1	General .....	18
B.2.2	Margin-to-capacity calculation and comparison.....	18
B.2.3	Margin-to-capacity versus frequency.....	19
B.2.4	Margin-to-capacity versus reach .....	20
Bibliography.....		21
Figure B.1 – Margin-to-capacity versus frequency for 25 Gbit/s rate for 50 m reach .....		19
Figure B.2 – Margin-to-capacity versus reach for 25 Gbit/s at 1 000 MHz frequency .....		20
Table 1 – Enhancement methods for 25 Gbit/s extended reach.....		9
Table 2 – Formulae for return loss specifications for example 50 m channel .....		10
Table 3 – Formulae for insertion loss specifications for example 50 m channel .....		10
Table 4 – Formulae for pair-to-pair NEXT specifications for example 50 m channel .....		11
Table 5 – Formula for PS NEXT specifications for example 50 m channel.....		11
Table 6 – Formulae for ACR-F specifications for example 50 m channel .....		12
Table 7 – Formulae for PS ACR-F specifications for example 50 m channel.....		12
Table 8 – Formulae for PS ANEXT specifications for example 50 m channel.....		13
Table 9 – Formulae for PS AACR-F specifications for example 50 m channel .....		13
Table 10 – Formulae for propagation delay specifications for a 50 m channel .....		13
Table 11 – Delay skew specifications for a 50 m channel.....		13
Table 12 – TCL for example 50 m channel .....		14
Table 13 – ELTCTL for example 50 m channel.....		14
Table 14 – Coupling attenuation for example 50 m channel for $E_1$ and $E_2$ .....		14