ISO/IEC 14165-147:2021-02 (E)

Information technology - Fibre channel - Part 147: Physical interfaces - 7 (FC-PI-7)

Contents

Page

1 Scope 1

2 Normative references 1
2.1 General 1
2.2 Normative references 1
2.2.1 Approved references 1
2.2.2 References under development 2

3 Definitions and conventions 3
3.1 Definitions 3
3.2 Editorial conventions 7
3.2.1 Conventions 7
3.2.2 Keywords 8
3.2.3 Abbreviations, acronyms, and symbols 8
3.2.3.1 Acronyms and other abbreviations 9
3.2.3.2 Signaling rate abbreviations 10

4 FC-PI-7 functional characteristics 11
4.1 General characteristics 11
4.2 Compliance test points 11
4.3 FC-0 functions 13
4.3.1 Transmitter functions 13
4.3.2 Receiver functions 13
4.4 Limitations on invalid code 14
4.5 Receiver stabilization time 14
4.6 Loss of signal (Rx_LOS) function 14
4.7 Speed agile ports that support speed negotiation and training 14
4.8 Transmission codes 14
4.9 Frame scrambling and emission lowering protocol 14
4.10 Forward error correction (FEC) 15
4.11 Bit error ratio per link locations and segments 15
4.12 FC-PI-7 variants 16

5 Optical interface specification 17
5.1 TxRx connections 17
5.2 Laser safety issues 17
5.3 Optical signal modulation format 17
5.4 SM data links 18
5.4.1 SM general information 18
5.4.2 SM optical output interface 18
5.4.3 SM optical input interface 18
5.4.4 Transmitter transition time 18
5.4.5 TDECQ Test 18
5.4.6 SECQ Measurement 18
5.4.7 SRS Test 18
5.5 MM data links 20
5.5.1 MM general information 20
5.5.2 MM optical output interface 20
5.5.3 MM optical input interface 20
5.5.4 Transmitter transition time 20
5.5.5 TDECQ Test 21

5.5.6 SECQ Measurement . . . 21
5.5.7 SRS Test . . . 21
5.6 SM Cable Plant . . . 23
5.6.1 Cable plant overview . . . 23
5.6.2 Optical Return Loss . . . 23
5.6.3 Connector and Splices . . . 24
5.7 MM Cable Plant . . . 24
5.7.1 Cable plant overview . . . 24
5.7.2 Optical Return Loss . . . 24
5.7.3 Connector and Splices . . . 24

6 Electrical interface specification - single lane segments . . . 25
6.1 General electrical characteristics . . . 25
6.2 Compliance test point definitions . . . 25
6.2.1 Test method . . . 25
6.2.2 Host test points . . . 26
6.2.3 Module test points . . . 26
6.2.4 Host input calibration point . . . 27
6.2.5 Module input calibration point . . . 28
6.3 Transmitted signal characteristics . . . 29
6.4 Receive signal characteristics . . . 30
6.5 Differential return loss and mode conversion requirements . . . 31
6.5.1 Differential return loss . . . 31
6.5.2 Common to differential-mode and differential to common-mode conversion . . . 31

7 Backplane variant, 64GFC-EA . . . 33
7.1 TxRx Connections . . . 33
7.2 Test Fixtures . . . 33
7.3 Transmitter specification . . . 35
7.4 Receiver specification . . . 37
7.4.1 Receiver input return loss . . . 37
7.4.2 Receiver interference tolerance . . . 38
7.4.3 Receiver jitter tolerance . . . 39
7.5 Channel Specification . . . 39
7.5.1 Channel Operating Margin . . . 39
7.5.2 Channel Return Loss . . . 41
7.5.3 Channel AC coupling . . . 41

Annex A (informative)
Optical cable plant usage . . . 42

Annex B (informative)
Structured cabling environment . . . 44
B.1 Specification of operating distances . . . 44
B.2 Alternate connection loss operating distances . . . 44

Annex C (informative)
Electrical channel . . . 45

List of Tables

Table 1 - ISO convention 7
Table 2 - Acronyms and other abbreviations. 9
Table 3 - Signaling rate abbreviations. 10
Table 4 - BER per link Location / Segment 15
Table 5 - Fibre Channel Variants in FC-PI-7 16
Table 6 - Single-mode link parameters (OS2). 19
Table 7 - Multimode link parameters. 22
Table 8 - Maximum value of each discrete reflectance 23
Table 9 - General electrical characteristics 25
Table 10 - Transmitter compliance requirements at nominal signal rate of 28 900 MBd 29
Table 11 - Receiver compliance requirements 30
Table 12 - Transmitter electrical specifications at A 35
Table 13 - Summary of receiver characteristics at test point D. 37
Table 14 - Receiver interference tolerance parameters 39
Table 15 - Receiver jitter tolerance parameters 39
Table 16 - Channel Operating Margin (COM) parameters 40
Table A.1 - Worst case (nominal bandwidth) multimode cable link power budget 42
Table A.2 - Worst-case single mode cable link power budget 43
Table B.1 - 64GFC-SW (MM) and 64GFC-LW (SM) max operating distance & loss budget for different connection losses 44
Table C.1 - Informative host to module channel characteristics, high loss channel 45

List of Figures

Figure 1 - Fibre Channel hierarchy 12
Figure 2 - Compliance points for 64GFC PMDs 13
Figure 3 - BER per Section 15
Figure 4 - Optical Eye Diagram of a PAM4 Signal 17
Figure 5 - Host Compliance Board 26
Figure 6 - Module Compliance Board 27
Figure 7 - Host input calibration point C". 27
Figure 8 - Module input calibration point B" 28
Figure 9 - SDD11 and SDD22 for all compliance points 31
Figure 10 - SDC22 for transmitter output and SCD11 for receiver input. 32
Figure 11 - Test fixture and test points 33
Figure 12 - Test fixture reference insertion loss 34
Figure 13 - Test fixture differential return loss. 34
Figure 14 - Transmitter and receiver differential return loss limit 36
Figure 15 - Transmitter common-mode return loss. 37
Figure 16 - Receiver differential to common-mode return loss limit 38
Figure 17 - Channel return loss limit 41
Figure C.1 - Typical FC-PI-7 electrical channel construction 45
Figure C.2 - FC-PI-7 full channel electrical reference model, high loss channel. 45