

# ISO/IEC 14165-147:2021-02 (E)

## Information technology - Fibre channel - Part 147: Physical interfaces - 7 (FC-PI-7)

---

### Contents

Page

- 1 Scope** ..... 1
- 2 Normative references** ..... 1
  - 2.1 General ..... 1
  - 2.2 Normative references ..... 1
    - 2.2.1 Approved references ..... 1
    - 2.2.2 References under development ..... 2
- 3 Definitions and conventions** ..... 3
  - 3.1 Definitions ..... 3
  - 3.2 Editorial conventions ..... 7
    - 3.2.1 Conventions ..... 7
    - 3.2.2 Keywords ..... 8
    - 3.2.3 Abbreviations, acronyms, and symbols ..... 8
      - 3.2.3.1 Acronyms and other abbreviations ..... 9
      - 3.2.3.2 Signaling rate abbreviations ..... 10
- 4 FC-PI-7 functional characteristics** ..... 11
  - 4.1 General characteristics ..... 11
  - 4.2 Compliance test points ..... 11
  - 4.3 FC-0 functions ..... 13
    - 4.3.1 Transmitter functions ..... 13
    - 4.3.2 Receiver functions ..... 13
  - 4.4 Limitations on invalid code ..... 14
  - 4.5 Receiver stabilization time ..... 14
  - 4.6 Loss of signal (Rx\_LOS) function ..... 14
  - 4.7 Speed agile ports that support speed negotiation and training ..... 14
  - 4.8 Transmission codes ..... 14
  - 4.9 Frame scrambling and emission lowering protocol ..... 14
  - 4.10 Forward error correction (FEC) ..... 15
  - 4.11 Bit error ratio per link locations and segments ..... 15
  - 4.12 FC-PI-7 variants ..... 16
- 5 Optical interface specification** ..... 17
  - 5.1 TxRx connections ..... 17
  - 5.2 Laser safety issues ..... 17
  - 5.3 Optical signal modulation format ..... 17
  - 5.4 SM data links ..... 18
    - 5.4.1 SM general information ..... 18
    - 5.4.2 SM optical output interface ..... 18
    - 5.4.3 SM optical input interface ..... 18
    - 5.4.4 Transmitter transition time ..... 18
    - 5.4.5 TDECQ Test ..... 18
    - 5.4.6 SECQ Measurement ..... 18
    - 5.4.7 SRS Test ..... 18
  - 5.5 MM data links ..... 20
    - 5.5.1 MM general information ..... 20
    - 5.5.2 MM optical output interface ..... 20
    - 5.5.3 MM optical input interface ..... 20
    - 5.5.4 Transmitter transition time ..... 20
    - 5.5.5 TDECQ Test ..... 21

|                              |  |           |
|------------------------------|--|-----------|
| 5.5.6                        | SECQ Measurement   | 21        |
| 5.5.7                        | SRS Test   | 21        |
| 5.6                          | SM Cable Plant   | 23        |
| 5.6.1                        | Cable plant overview   | 23        |
| 5.6.2                        | Optical Return Loss  | 23        |
| 5.6.3                        | Connector and Splices  | 24        |
| 5.7                          | MM Cable Plant   | 24        |
| 5.7.1                        | Cable plant overview   | 24        |
| 5.7.2                        | Optical Return Loss  | 24        |
| 5.7.3                        | Connector and Splices  | 24        |
| <b>6</b>                     | <b>Electrical interface specification - single lane segments</b>       | <b>25</b> |
| 6.1                          | General electrical characteristics                                     | 25        |
| 6.2                          | Compliance test point definitions                                      | 25        |
| 6.2.1                        | Test method  | 25        |
| 6.2.2                        | Host test points   | 26        |
| 6.2.3                        | Module test points   | 26        |
| 6.2.4                        | Host input calibration point   | 27        |
| 6.2.5                        | Module input calibration point   | 28        |
| 6.3                          | Transmitted signal characteristics                                     | 29        |
| 6.4                          | Receive signal characteristics   | 30        |
| 6.5                          | Differential return loss and mode conversion requirements              | 31        |
| 6.5.1                        | Differential return loss   | 31        |
| 6.5.2                        | Common to differential-mode and differential to common-mode conversion | 31        |
| <b>7</b>                     | <b>Backplane variant, 64GFC-EA</b>                                     | <b>33</b> |
| 7.1                          | TxRx Connections   | 33        |
| 7.2                          | Test Fixtures  | 33        |
| 7.3                          | Transmitter specification  | 35        |
| 7.4                          | Receiver specification   | 37        |
| 7.4.1                        | Receiver input return loss   | 37        |
| 7.4.2                        | Receiver interference tolerance  | 38        |
| 7.4.3                        | Receiver jitter tolerance  | 39        |
| 7.5                          | Channel Specification  | 39        |
| 7.5.1                        | Channel Operating Margin   | 39        |
| 7.5.2                        | Channel Return Loss  | 41        |
| 7.5.3                        | Channel AC coupling  | 41        |
| <b>Annex A (informative)</b> |  |           |
|                              | <b>Optical cable plant usage</b>                                       | <b>42</b> |
| <b>Annex B (informative)</b> |  |           |
|                              | <b>Structured cabling environment</b>                                  | <b>44</b> |
| B.1                          | Specification of operating distances                                   | 44        |
| B.2                          | Alternate connection loss operating distances                          | 44        |
| <b>Annex C (informative)</b> |  |           |
|                              | <b>Electrical channel</b>  | <b>45</b> |

## List of Tables

|  |    |
|--|----|
| Table 1 - ISO convention   | 7  |
| Table 2 - Acronyms and other abbreviations   | 9  |
| Table 3 - Signaling rate abbreviations   | 10 |
| Table 4 - BER per link Location / Segment  | 15 |
| Table 5 - Fibre Channel Variants in FC-PI-7  | 16 |
| Table 6 - Single-mode link parameters (OS2)  | 19 |
| Table 7 - Multimode link parameters  | 22 |
| Table 8 - Maximum value of each discrete reflectance   | 23 |
| Table 9 - General electrical characteristics   | 25 |
| Table 10 - Transmitter compliance requirements at nominal signal rate of 28 900 MBd                              | 29 |
| Table 11 - Receiver compliance requirements  | 30 |
| Table 12 - Transmitter electrical specifications at A  | 35 |
| Table 13 - Summary of receiver characteristics at test point D   | 37 |
| Table 14 - Receiver interference tolerance parameters  | 39 |
| Table 15 - Receiver jitter tolerance parameters  | 39 |
| Table 16 - Channel Operating Margin (COM) parameters   | 40 |
| Table A.1 - Worst case (nominal bandwidth) multimode cable link power budget                                     | 42 |
| Table A.2 - Worst-case single mode cable link power budget   | 43 |
| Table B.1 - 64GFC-SW (MM) and 64GFC-LW (SM) max operating distance & loss budget for different connection losses | 44 |
| Table C.1 - Informative host to module channel characteristics, high loss channel                                | 45 |

## List of Figures

|   |    |
|---|----|
| Figure 1 - Fibre Channel hierarchy  | 12 |
| Figure 2 - Compliance points for 64GFC PMDs                                     | 13 |
| Figure 3 - BER per Section  | 15 |
| Figure 4 - Optical Eye Diagram of a PAM4 Signal                                 | 17 |
| Figure 5 - Host Compliance Board  | 26 |
| Figure 6 - Module Compliance Board  | 27 |
| Figure 7 - Host input calibration point C"                                      | 27 |
| Figure 8 - Module input calibration point B"                                    | 28 |
| Figure 9 - SDD11 and SDD22 for all compliance points                            | 31 |
| Figure 10 - SDC22 for transmitter output and SCD11 for receiver input           | 32 |
| Figure 11 - Test fixture and test points  | 33 |
| Figure 12 - Test fixture reference insertion loss                               | 34 |
| Figure 13 - Test fixture differential return loss                               | 34 |
| Figure 14 - Transmitter and receiver differential return loss limit             | 36 |
| Figure 15 - Transmitter common-mode return loss                                 | 37 |
| Figure 16 - Receiver differential to common-mode return loss limit              | 38 |
| Figure 17 - Channel return loss limit   | 41 |
| Figure C.1 - Typical FC-PI-7 electrical channel construction                    | 45 |
| Figure C.2 - FC-PI-7 full channel electrical reference model, high loss channel | 45 |