ISO/IEC TS 11801-9903:2021-03 (E)

Information technology - Generic cabli ng systems for customer premises - Part 9903: Matrix modelling of channels and links

Contents

Page

FOREWORD 5
INTRODUCTION 7
1 Scope 9
2 Normative references 9
3 Terms, definitions and abbreviated terms 9
3.1 Terms and definitions 9
3.2 Symbols and abbreviated terms 10
4 Matrix model 11
5 Matrix definition 11
5.1 General 11
5.2 Quadriports 11
5.3 Matrix port definition for a two-pair system representative for modelling purposes 11
5.4 Operational scattering matrix 12
5.5 General naming convention 12
5.6 S-matrix 13
5.7 Passivity 13
5.8 Operational reflection loss matrix 14
5.9 Transmission matrix (T-matrix) 14
5.10 S-matrix of cabling 14
6 Calculation with matrices using limit lines 15
7 Extracting limit lines 15
8 General case using mixed-mode matrices 16
8.1 General 16
8.2 M-parameters 16
9 Submatrix DD 17
9.1 General 17
9.2 Equations to extract the cabling limit lines 17
9.2.1 General 17
9.2.2 Operational attenuation 17
9.2.3 Near-end crosstalk 17
9.2.4 Attenuation to far-end crosstalk ratio 17
9.2.5 Reflection (RL) 18
10 Component values to be used as input to the model 18
10.1 General 18
10.2 Cable 19
10.2.1 General 19
10.2.2 Wave attenuation 19
10.2.3 Near-end crosstalk 19
10.2.4 Far-end crosstalk 19
10.2.5 Reflection 20

10.3 Connections 21
10.3.1 General 21
10.3.2 As a point source of disturbance 21
10.3.3 As a transmission line 21
11 Submatrices CC, CD and DC 22
11.1 General 22
11.2 Submatrix CD 22
11.3 Submatrix DC 22
11.4 Submatrix CC 22
Annex A (informative) Matrix conversion formulas 23
A.1 Overview 23
A.2 Formulas 23
A.2.1 Mixed-mode to T-matrix 23
A.2.2 T-matrix to M-matrix 23
A.2.3 Conversion matrices 23
Annex B (normative) Channel and permanent link models for balanced cabling 25
B.1 General 25
B.2 Insertion loss 25
B.2.1 Insertion loss of the channel configuration 25
B.2.2 Insertion loss of the permanent link configurations 26
B.2.3 Assumptions for insertion loss 26
B.3 NEXT 27
B.3.1 NEXT of the channel configuration 27
B.3.2 NEXT of the permanent link configurations 27
B.3.3 Assumptions for NEXT 28
B.4 ACR-F 31
B.4.1 ACR-F of the channel configuration 31
B.4.2 ACR-F for the permanent link configurations 31
B.4.3 Assumptions for ACR-F 32
B.5 No Return loss 32
B.5.1 Return loss of the channel and permanent link configurations 32
B.5.2 Assumptions for the return loss circuit analysis method 33
B.6 PS ANEXT link modelling 36
B.6.1 General 36
B.6.2 PS ANEXT between connectors 36
B.6.3 PS ANEXT between cable segments 36
B.6.4 Principles of link modelling 36
B.7 PS AACR-F link modelling 37
B.7.1 General 37
B.7.2 PS AFEXT between connectors 37
B.7.3 PS AACR-F between cable segments 37
B.7.4 Principles of link modelling 37
B.7.5 Impact of PS AACR-F in channels and links with substantially different lengths 38
B.8 Component assumptions for modelling purposes 41
Annex C (informative) Terms and definitions 43
C.1 Comparison of namings 43
C.2 General 44

C.3 Background of terms and definitions 44
C.3.1 Operational attenuation 44
C.3.2 Operational transfer function (T_B) 46
C.3.3 Image or wave transfer function (T) 46
C.3.4 Insertion transfer function of a two-port (T_{BI}) 46
C.3.5 Insertion transfer function (T_{BI}) measured with a vector network analyser 46
C.3.6 Operational reflection loss transfer function (T_{ref} = S_{ref}) of a junction 46
Bibliography 48

Figure 1 – Link configurations of ISO/IEC 11801-1 7
Figure 2 – Matrix definition of a 4-port two twisted pair system 12
Figure 3 – Operational scattering parameters example from port 2 12
Figure 4 – Transmission matrix concatenation showing an example of a 2-connector permanent link 14
Figure 5 – Graphical example of a NEXT calculation showing statistical results (red) and final calculation (blue) 16
Figure 6 – One pair M-matrix showing the submatrices 16
Figure 7 – 100 m cable return loss without reflection at both ends 20
Figure 8 – 100 m cable return loss with a reflection of 0,03 at both ends (6 Ω mismatch, ~23 dB return loss at 1 MHz) 21
Figure A.1 – X matrices 24
Figure B.1 – Example of computation of NEXT with higher precision 28
Figure B.2 – Example of increased impact of PS AFEXT 38
Figure C.1 – Defining the operational attenuation and the operational transfer functions of a two-port 45
Figure C.2 – Defining the reflection transfer functions and the return loss of a junction 47

Table 1 – All four ports operational scattering parameter definition 12
Table 2 – Equal S-parameters for real components 13
Table B.1 – Insertion loss deviation 26
Table B.2 – Modelling assumptions for cable transmission parameters 41
Table B.3 – Model input assumptions used in the statistical calculation (Class E_A) 41
Table B.4 – Model input assumptions used in the statistical calculation (Class F_A) 42
Table C.1 – Comparison of naming in ISO/IEC 11801-1 and ISO/IEC TS 11801-9903 43