

ISO/IEC 14763-4:2021-03 (E)

Information technology - Implementation and operation of customer premises cabling - Part 4: Measurement of end-to-end (E2E)- Links

Contents	Page
FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references	7
3 Terms, definitions and abbreviated terms	8
3.1 Terms and definitions.....	8
3.2 Abbreviated terms.....	8
4 Conformance.....	8
5 Transmission performance of E2E links, MPTLs and direct attach cabling	8
6 Transmission limits of E2E link, MPTLs and direct attach cabling	8
7 Reference planes of E2E link, MPTL and direct attach cabling.....	9
7.1 Reference planes of E2E link.....	9
7.2 Reference planes of MPTL.....	9
7.3 Reference planes of direct attach cabling.....	10
8 Testing	11
8.1 General.....	11
8.2 Laboratory testing of E2E link, MPTL and direct attach cabling	11
8.3 Field testing of E2E link, MPTL and direct attach cabling	11
8.3.1 Basic criteria	11
8.3.2 Requirements of field test equipment.....	12
8.3.3 Field test measurement parameters.....	12
9 Test head requirements	12
9.1 General.....	12
9.2 Additional test head requirements in accordance with the IEC 60603-7 series	12
9.3 Test head requirements of IEC 61076-2-101	13
9.4 Test head requirements of IEC 61076-2-109.....	13
Annex A (informative) Example performance of E2E link test heads.....	14
A.1 Example Category 5 test head performance.....	14
A.2 Example Category 6 test head performance.....	14
Annex B (normative) Test regime for reference performance and installation performance of E2E link, MPTL and direct attach cabling.....	16
Bibliography.....	18
Figure 1 – Reference planes of E2E links	9
Figure 2 – Reference planes of 2-connection MPTL	10
Figure 3 – Reference planes of 3-connection MPTL	10
Figure 4 – Reference planes of direct attach cabling.....	11

Table 1 – Transmission performance limits8

Table 2 – Overview level for field test equipment of performance of E2E link, direct attach cabling and MPTLs..... 12

Table A.1 – Category 5 test head of E2E link de-embedded NEXT performance in the frequency range $50 \text{ MHz} \leq f < 100 \text{ MHz}$ 14

Table A.2 – Category 6 test head of E2E link de-embedded NEXT performance in the frequency range $50 \text{ MHz} \leq f < 250 \text{ MHz}$ 15

Table B.1 – Reference Classes of E2E link, direct attach cabling and MPTL 16

Table B.2 – Test regime for reference performance and installation performance of E2E link, direct attach cabling and MPTL 16