ISO/IEC 14763-4:2021-03 (E)

Information technology - Implementation and operation of customer premises cabling - Part 4: Measurement of end-to-end (E2E)- Links

Contents

Page

FOREWORD 4
INTRODUCTION 6
1 Scope 7
2 Normative references 7
3 Terms, definitions and abbreviated terms 8
3.1 Terms and definitions 8
3.2 Abbreviated terms 8
4 Conformance 8
5 Transmission performance of E2E links, MPTLs and direct attach cabling 8
6 Transmission limits of E2E link, MPTLs and direct attach cabling 8
7 Reference planes of E2E link, MPTL and direct attach cabling 9
7.1 Reference planes of E2E link 9
7.2 Reference planes of MPTL 9
7.3 Reference planes of direct attach cabling 10
8 Testing 11
8.1 General 11
8.2 Laboratory testing of E2E link, MPTL and direct attach cabling 11
8.3 Field testing of E2E link, MPTL and direct attach cabling 11
8.3.1 Basic criteria 11
8.3.2 Requirements of field test equipment 12
8.3.3 Field test measurement parameters 12
9 Test head requirements 12
9.1 General 12
9.2 Additional test head requirements in accordance with the IEC 60603-7 series 12
9.3 Test head requirements of IEC 61076-2-101 13
9.4 Test head requirements of IEC 61076-2-109 13
Annex A (informative) Example performance of E2E link test heads 14
A.1 Example Category 5 test head performance 14
A.2 Example Category 6 test head performance 14
Annex B (normative) Test regime for reference performance and installation performance of E2E link, MPTL and direct attach cabling 16
Bibliography 18

Figure 1 – Reference planes of E2E links 9
Figure 2 – Reference planes of 2-connection MPTL 10
Figure 3 – Reference planes of 3-connection MPTL 10
Figure 4 – Reference planes of direct attach cabling 11

Table 1 – Transmission performance limits 8
Table 2 – Overview level for field test equipment of performance of E2E link, direct attach cabling and MPTLs 12
Table A.1 – Category 5 test head of E2E link de-embedded NEXT performance in the frequency range 50 MHz ≤ f < 100 MHz 14
Table A.2 – Category 6 test head of E2E link de-embedded NEXT performance in the frequency range 50 MHz ≤ f < 250 MHz 15
Table B.1 – Reference Classes of E2E link, direct attach cabling and MPTL 16
Table B.2 – Test regime for reference performance and installation performance of E2E link, direct attach cabling and MPTL 16