ISO/IEC 14543-4-302:2023-04 (E)

Information technology - Home Electronic System (HES) architecture - Part 4-302: Application protocols for electrical storage systems and controllers

Contents

Page

FOREWORD 5
INTRODUCTION 7
1 Scope 8
2 Normative references 8
3 Terms, definitions and abbreviated terms 8
3.1 Terms and definitions 8
3.2 Abbreviations 9
4 Conformance 10
5 Configuration 10
5.1 General 10
5.2 Configuration and components 10
5.3 Connection configuration 11
6 Application layer 12
6.1 General 12
6.2 NECD objects 12
6.3 NECD services 12
6.4 Object-specific NECD properties 12
6.5 Application operation 14
6.5.1 General 14
6.5.2 Continuous requests 14
6.5.3 Response wait time value for controllers 15
6.5.4 Resending a frame 15
6.5.5 Processing object property counter 15
6.5.6 Property values of write requests 15
7 Normal operation 16
7.1 General 16
7.2 Start-up operation 18
7.2.1 General 18
7.2.2 Start-up processing of NECD nodes 18
7.2.3 Search processing 18
7.2.4 Obtaining NECD attribute information 18
7.2.5 Obtaining electrical storage system attribute information 19
7.3 Occasional operation 22
7.3.1 General 22
7.3.2 Obtaining electrical storage system status 22
7.3.3 Setting and updating "AC charge amount target value" property (or "AC discharge amount target value" property) 25
7.3.4 Setting and updating "Charging electric power setting" property (or "Discharging electric power setting" property) (optional) 28
7.3.5 Setting "Charging method" property (or "Discharging method" property) (optional) 31
7.3.6 Setting "Operation mode setting" property 34

7.3.7 Terminating charging (or discharging) operation of the storage battery based on "AC charging amount target value" property (or "AC discharging amount target value" property) 37
7.4 Fault status notification 41
8 Remote control 42
8.1 General 42
8.2 Setting and updating "AC charge amount target value" property (or "AC discharge amount target value" property) on remote control 42
8.3 Setting "Operation mode setting" property when remotely controlling 44
9 Considerations on controllers 46
9.1 General 46
9.2 Restrictions by electrical storage system implementations 47
Annex A (informative) Terms and NECD protocol frame format on ISO/IEC 14543-4-3 and IEC 62394 48
A.1 Terms correspondence between ISO/IEC 14543-4-3 and IEC 62394 48
A.2 NECD protocol frame format 48
Annex B (informative) Relationship between ISO/IEC 14543-4 series and the HES gateway, based on ISO/IEC 15045 series and ISO/IEC 18012 series 50
Bibliography 51

Figure 1 – Relationship between IEC 62394, ISO/IEC 14543-4-3 and ISO/IEC 14543-4-302 7
Figure 2 – Example of electrical storage system configuration and components 10
Figure 3 – Connection configurations 11
Figure 4 – Assumed network stack 11
Figure 5 – Summary of normal operation sequences 17
Figure 6 – Sequence for obtaining NECD attribute information 19
Figure 7 – Sequence of obtaining electrical storage system attribute information 21
Figure 8 – Sequence to obtain status of electrical storage systems 25
Figure 9 – Sequence for setting "AC charge amount target value" property (or "AC discharge amount target value" property) 28
Figure 10 – Sequence for setting "Charging electric power setting" property (or "Discharging electric power setting" property) 31
Figure 11 – Sequence for setting "Charging method" property (or "Discharging method" property) 33
Figure 12 – Sequence for setting "Charging method" property (or "Discharging method" property) when no response is received from the storage battery 34
Figure 13 – Sequence for setting "Operation mode setting" property 36
Figure 14 – Sequence for setting "Operation mode setting" property when no response is received from the storage battery 37
Figure 15 – Sequence of terminating charging (discharging) operation based on "AC charge amount target value" property ("AC discharge amount target value" property) 40
Figure 16 – Sequence of terminating charge (discharge) operation based on "AC charge amount target value" property ("AC discharge amount target value" property) when "Operation mode setting" property is changed 41
Figure 17 – Remote control 42
Figure 18 – Example of setting sequence for "AC charge amount target value" property ("AC discharge amount target value" property) when "Remote control setting" property is used 44

Figure 19 – Example of setting sequence for "Operation mode setting" property when "Remote control setting" property is used 45
Figure 20 – Example of setting sequence for "Operation mode setting" property when "Remote control setting" property is used, in case that no response is made by electrical storage system 46

Figure A.1 – NECD protocol frame format 49

Table 1 – NECD objects 12
Table 2 – NECD services 12
Table 3 – NECD properties of device object (super class) 13
Table 4 – NECD properties of device object 13
Table 5 – Response wait time values for controllers 15
Table 6 – Re-set wait time for the AC charge (or discharge) amount target value 27
Table 7 – Wait time for re-setting charging and discharging electric power setting 30
Table 8 – Wait time for charging and discharging method for re-setting 32
Table 9 – Wait time for re-setting operation mode 35
Table A.1 – Terms correspondence table between ISO/IEC 14543-4-3 and IEC 62394 48
Table B.1 – Partial list of the translation between ISO/IEC 14543-4-302 and HES gateway lexicon (ISO/IEC 18012-3) 50