ISO/IEC 14543-5-104:2024-01 (E)

Information technology - Home electronic systems (HES) architecture - Part 5-104: Intelligent grouping and resource sharing for HES Class 2 and Class 3 - RA server-based smart lock application

Contents

Page

FOREWORD 4
INTRODUCTION 6
1 Scope 9
2 Normative references 9
3 Terms, definitions and abbreviated terms 9
3.1 Terms and definitions 9
3.2 Abbreviated terms 10
4 Conformance 11
5 Overview 11
6 Smart lock server management framework 11
6.1 Overview 11
6.2 Bluetooth smart lock server management framework: remote access server (RAS) 13
6.3 Bluetooth smart lock server management framework: remote access client (RAC) 14
6.4 Bluetooth smart lock server management framework: Bluetooth gateway (BGW) 15
6.5 Bluetooth smart lock server management framework: Bluetooth smart lock device (BSLD) 17
6.6 Bluetooth smart lock server management framework: third party service platform (TPSP) 20
7 Standard interfaces between remote access client and server management framework 20
7.1 User registration management 20
7.2 User authentication management 20
7.3 Bluetooth smart lock device (BSLD) discovery 21
7.4 Bluetooth smart lock device (BSLD) registration management 21
7.5 Bluetooth smart lock device (BSLD) removal management 22
7.6 Response status code 22
7.7 Generic message format used between remote access client (RAC) and remote access server (RAS) 23
8 Standard data format used among remote access client (RAC), Bluetooth gateway (BGW) and Bluetooth smart lock device (BSLD) 23
Annex A (informative) Specific example of interfaces between remote access client (RAC) and remote access server (RAS) 27
Bibliography 28

Figure 1 – Interaction models of Bluetooth smart lock device in the server management framework 12
Figure 2 – BSLSMF RAS components 13
Figure 3 – BSLSMF RAC components 14
Figure 4 – BSLSMF BGW components 16
Figure 5 – BGW message flow process 17

Figure 6 – BSLD registration process to RAS 18
Figure 7 – BSLD control flow process 19
Figure 8 – User registration request message 20
Figure 9 – User authentication request message 21
Figure 10 BSLD authentication request message 21
Figure 11 – BSLD registration request message 21
Figure 12 – BSLD removal request message 22
Figure A.1 – User registration request message 27
Figure A.2 – User registration response message 27

Table 1 – Response status codes and their message contents 22
Table 2 – Message push data format between RAS and RAC 23
Table 3 – Write user account ID request 24
Table 4 – Write user account ID response 24
Table 5 – Authenticate user account ID request 25
Table 6 – Authenticate user account ID response 25
Table 7 – BSLD lock and unlock operation request 26
Table 8 – BSLD lock and unlock operation response 26