

# ISO/IEC 17760-105:2024-03 (E)

## Information technology - AT Attachment - Part 105: ATA Command Set - 5 (ACS-5)

<b>Contents</b>	<b>Page</b>
Contents.....	i
Tables .....	xii
Figures .....	xx
Foreword .....	xxi
Introduction .....	xxiv
1 Scope .....	1
2 Normative references .....	2
3 Definitions, abbreviations, and conventions .....	3
3.1 Definitions .....	3
3.2 Symbols and abbreviations .....	9
3.2.1 Abbreviations .....	9
3.2.2 Units .....	11
3.2.3 Symbols .....	11
3.2.4 Mathematical operators .....	11
3.3 Keywords .....	11
3.4 Conventions .....	12
3.4.1 Overview .....	12
3.4.2 Precedence .....	13
3.4.3 Lists .....	13
3.4.4 Numbering .....	14
3.4.5 Bit conventions .....	14
3.4.6 Number range convention .....	14
3.4.7 State diagram conventions .....	15
3.4.8 Byte, word, DWord, QWord, and DQWord Relationships .....	17
3.4.9 ATA string convention .....	18
3.4.10 Offset Convention .....	19
4 Feature set definitions .....	20
4.1 Overview .....	20
4.1.1 Feature set summary .....	20
4.1.2 Capacity reporting .....	21
4.2 General feature set .....	22
4.2.1 Overview .....	22
4.2.2 Unexpected power removal .....	22
4.2.3 Interactions with volatile caches .....	23
4.3 48-bit Address feature set .....	24
4.4 Accessible Max Address Configuration feature set .....	25
4.4.1 Overview .....	25
4.4.2 SET ACCESSIBLE MAX ADDRESS EXT description .....	25
4.4.3 Interactions with device statistics data .....	25
4.5 Advanced Background Operation feature set (ABO) .....	26
4.5.1 Overview .....	26
4.5.2 Host-initiated advanced background operations .....	26
4.5.3 Device-initiated advanced background operations .....	27
4.6 Advanced Power Management (APM) feature set .....	28
4.7 Command Duration Limits feature set .....	29
4.7.1 Overview .....	29

4.7.2	COMMAND DURATION LIMITS INDEX field .....	30
4.7.3	Command duration limits operation .....	30
4.7.4	High Priority Enhancement feature .....	31
4.8	Device Statistics Notification (DSN) feature set .....	33
4.8.1	Overview .....	33
4.8.2	DSN notifications .....	33
4.8.3	DSN notifications setup .....	34
4.9	Extended Power Conditions (EPC) feature set .....	35
4.9.1	Overview .....	35
4.9.2	Power conditions .....	35
4.9.3	Power condition timers .....	35
4.9.4	Interaction with resets, commands, and other features if the EPC feature set is enabled .....	36
4.10	Free-fall Control feature set .....	38
4.11	General Purpose Logging (GPL) feature set .....	39
4.12	Hybrid Information feature set .....	40
4.12.1	Hybrid Information feature overview .....	40
4.12.2	Syncing .....	42
4.12.3	Interactions with ATA power management .....	42
4.12.4	Other Hybrid conditions .....	43
4.13	Long Logical Sector (LLS) feature set .....	45
4.14	Long Physical Sector (LPS) feature set .....	47
4.15	Native Command Queuing (NCQ) feature set .....	49
4.15.1	Overview .....	49
4.15.2	Priority .....	49
4.15.3	Unload with NCQ commands outstanding .....	50
4.15.4	Command Phases .....	50
4.15.5	NCQ command processing order requirements .....	51
4.15.6	ATA device commands encapsulated in NCQ feature set commands .....	51
4.15.7	Returning sense data for successful NCQ feature set commands .....	51
4.16	Out Of Band Management Interface .....	53
4.17	Power Management feature set .....	55
4.17.1	Overview .....	55
4.17.2	Power management commands .....	55
4.17.3	Standby timer .....	55
4.17.4	Power Management states and transitions .....	56
4.18	Power-Up In Standby (PUIS) feature set .....	60
4.18.1	Overview .....	60
4.18.2	Interactions with the IDENTIFY DEVICE command .....	60
4.18.3	PUIS feature set device spin-up subcommand .....	60
4.19	Rebuild Assist feature set .....	61
4.19.1	Overview .....	61
4.19.2	Enabling the Rebuild Assist feature set .....	61
4.19.3	Using the Rebuild Assist feature set .....	61
4.19.4	Disabling the Rebuild Assist feature set .....	63
4.19.5	Testing the Rebuild Assist feature set .....	63
4.20	Sanitize Device feature set .....	64
4.20.1	Overview .....	64
4.20.2	Sanitize operation scope .....	64
4.20.3	Sanitize commands .....	64
4.20.4	Sanitize operations .....	64
4.20.5	Interactions of the Sanitize Device feature set and Security feature set .....	65
4.20.6	Command processing during sanitize operations .....	65
4.20.7	Sanitize Operation Completed Without Error value .....	66
4.20.8	Failure Mode Policy value .....	66
4.20.9	Sanitize Antifreeze value .....	67
4.20.10	Sanitize Device state machine .....	67
4.21	SATA Hardware Feature Control feature set .....	70

4.22 Security feature set .....	71
4.22.1 Overview .....	71
4.22.2 Disabling and enabling the Security feature set .....	71
4.22.3 Passwords .....	71
4.22.4 Master password capability .....	71
4.22.5 Frozen mode .....	72
4.22.6 Commands .....	72
4.22.7 Security initial setting .....	72
4.22.8 Password Rules .....	72
4.22.9 Password attempt counter and SECURITY COUNT EXPIRED bit .....	72
4.22.10 Master Password Identifier feature .....	73
4.22.11 Security states .....	73
4.23 Self-Monitoring, Analysis, and Reporting Technology (SMART) feature set .....	85
4.23.1 Overview .....	85
4.23.2 Background data collection .....	85
4.23.3 Off-line/Captive mode data collection .....	85
4.23.4 Threshold exceeded condition .....	85
4.23.5 SMART feature set commands .....	85
4.23.6 SMART operation with power management modes .....	85
4.23.7 SMART device error log reporting .....	85
4.24 Sense Data Reporting feature set .....	87
4.24.1 General .....	87
4.24.2 Current information sense data and deferred error sense data .....	88
4.25 Software Settings Preservation (SSP) feature set .....	89
4.26 Storage Element Depopulation feature set .....	90
4.26.1 Overview .....	90
4.26.2 Status change notification .....	90
4.26.3 Repurposing Depopulation .....	91
4.26.4 Repurposing Depopulation Restoration .....	92
4.26.5 Effects of storage depopulation commands on other commands .....	93
4.26.6 Interactions with logs .....	94
4.26.7 Interactions with caches .....	94
4.27 Streaming feature set .....	95
4.27.1 Streaming feature set overview .....	95
4.27.2 Streaming commands .....	95
4.28 Trusted Computing feature set .....	97
4.29 User Data Initialization feature set .....	98
4.29.1 Overview .....	98
4.29.2 User data initialization operation .....	98
4.29.3 MUTATE EXT command .....	100
4.30 Write-Read-Verify feature set .....	101
5 ATA protocols .....	102
6 Normal and Error Output field descriptions .....	103
6.1 Overview .....	103
6.2 STATUS field .....	103
6.2.1 Overview .....	103
6.2.2 ALIGNMENT ERROR bit .....	103
6.2.3 BUSY bit .....	103
6.2.4 DATA REQUEST bit .....	104
6.2.5 DEFERRED WRITE ERROR bit .....	104
6.2.6 DEVICE FAULT bit .....	104
6.2.7 DEVICE READY bit .....	104
6.2.8 ERROR bit .....	104
6.2.9 SENSE DATA AVAILABLE bit .....	104

6.2.11 Transport Dependent bits and fields .....	105
6.3 ERROR field .....	105
6.3.1 Overview .....	105
6.3.2 ABORT bit .....	105
6.3.3 COMMAND COMPLETION TIME OUT bit .....	106
6.3.4 ID NOT FOUND bit .....	106
6.3.5 INTERFACE CRC bit .....	106
6.3.6 UNCORRECTABLE ERROR bit .....	106
6.4 COUNT field .....	106
6.4.1 Overview .....	106
6.4.2 Contiguous stream logical sectors that contain potentially bad data .....	106
6.4.3 NCQ Tag .....	106
6.5 SACTIVE field .....	106
6.6 SATA STATUS field .....	107
6.7 LBA field .....	107
6.7.1 Overview .....	107
6.7.2 LBA of First Unrecoverable Error .....	107
6.8 Sense code definitions .....	107
6.8.1 Overview .....	107
6.8.2 ACCESS DENIED - NO ACCESS RIGHTS .....	108
6.8.3 COMMAND SEQUENCE ERROR .....	109
6.8.4 COMMAND TIMEOUT BEFORE PROCESSING .....	109
6.8.5 COMMAND TIMEOUT DURING PROCESSING .....	109
6.8.6 DATA CURRENTLY UNAVAILABLE .....	109
6.8.7 DEPOPULATION FAILED .....	109
6.8.8 DEPOPULATION IN PROGRESS .....	109
6.8.9 DEPOPULATION RESTORATION FAILED .....	109
6.8.10 DEPOPULATION RESTORATION IN PROGRESS .....	109
6.8.11 FAILURE PREDICTION THRESHOLD EXCEEDED .....	109
6.8.12 INFORMATION UNIT iuCRC ERROR DETECTED .....	109
6.8.13 INITIATOR RESPONSE TIMEOUT .....	109
6.8.14 INSUFFICIENT RESOURCES .....	109
6.8.15 INTERNAL TARGET FAILURE .....	110
6.8.16 INVALID COMMAND OPERATION CODE .....	110
6.8.17 INVALID FIELD IN CDB .....	110
6.8.18 INVALID FIELD IN PARAMETER LIST .....	110
6.8.19 LOGICAL BLOCK ADDRESS OUT OF RANGE .....	110
6.8.20 LOGICAL UNIT FAILED SELF-TEST .....	110
6.8.21 LOGICAL UNIT NOT READY, FORMAT IN PROGRESS .....	110
6.8.22 LOGICAL UNIT NOT READY, INITIALIZING COMMAND REQUIRED .....	110
6.8.23 LOGICAL UNIT NOT READY, MICROCODE ACTIVATION REQUIRED .....	110
6.8.24 LOGICAL UNIT NOT READY, POWER CYCLE REQUIRED .....	110
6.8.25 LOGICAL UNIT NOT READY, SANITIZE IN PROGRESS .....	110
6.8.26 MEDIUM FORMAT CORRUPTED .....	110
6.8.27 MULTIPLE READ ERRORS .....	111
6.8.28 MULTIPLE WRITE ERRORS .....	111
6.8.29 NO ADDITIONAL SENSE INFORMATION .....	111
6.8.30 NO DEFECT SPARE LOCATION AVAILABLE .....	111
6.8.31 OVERLAPPED COMMANDS ATTEMPTED .....	111
6.8.32 READ ERROR - LBA MARKED BAD BY APPLICATION CLIENT .....	111
6.8.33 UNRECOVERED READ ERROR .....	111
6.8.34 WARNING – DEVICE STATISTICS NOTIFICATION ACTIVE .....	111
6.8.35 WRITE ERROR .....	111
7 Command descriptions .....	112
7.1 Command description introduction .....	112
7.2 Accessible Max Address Configuration .....	119

7.2.1 Accessible Max Address Configuration overview .....	119
7.2.2 GET NATIVE MAX ADDRESS EXT – 78h/0000h, Non-Data .....	120
7.2.3 SET ACCESSIBLE MAX ADDRESS EXT – 78h/0001h, Non-Data .....	121
7.2.4 FREEZE ACCESSIBLE MAX ADDRESS EXT – 78h/0002h, Non-Data .....	123
7.3 CHECK POWER MODE – E5h, Non-Data .....	124
7.4 CONFIGURE STREAM – 51h, Non-Data .....	125
7.5 DATA SET MANAGEMENT – 06h, DMA .....	127
7.6 DATA SET MANAGEMENT XL – 07h, DMA .....	131
7.7 DOWNLOAD MICROCODE – 92h, PIO Data-Out/Non-Data .....	133
7.8 DOWNLOAD MICROCODE DMA – 93h, DMA/Non-Data .....	147
7.9 EXECUTE DEVICE DIAGNOSTIC – 90h, Execute Device Diagnostic .....	148
7.10 FLUSH CACHE – E7h, Non-Data .....	150
7.11 FLUSH CACHE EXT – EAh, Non-Data .....	151
7.12 GET PHYSICAL ELEMENT STATUS – 12h, DMA .....	152
7.13 IDENTIFY DEVICE – ECh, PIO Data-In .....	157
7.14 IDLE – E3h, Non-Data .....	191
7.15 IDLE IMMEDIATE – E1h, Non-Data .....	193
7.16 MUTATE EXT - 96h, Non-Data .....	195
7.17 NCQ NON-DATA – 63h, Non-Data .....	197
7.18 NOP – 00h, Non-Data .....	221
7.19 READ BUFFER – E4h, PIO Data-In .....	222
7.20 READ BUFFER DMA – E9h, DMA .....	223
7.21 READ DMA – C8h, DMA .....	224
7.22 READ DMA EXT – 25h, DMA .....	225
7.23 READ FPDMA QUEUED – 60h, DMA Queued .....	227
7.24 READ LOG EXT – 2Fh, PIO Data-In .....	229
7.25 READ LOG DMA EXT – 47h, DMA .....	231
7.26 READ SECTOR(S) – 20h, PIO Data-In .....	233
7.27 READ SECTOR(S) EXT – 24h, PIO Data-In .....	234
7.28 READ STREAM DMA EXT – 2Ah, DMA .....	235
7.29 READ STREAM EXT – 2Bh, PIO Data-In .....	238
7.30 READ VERIFY SECTOR(S) – 40h, Non-Data .....	239
7.31 READ VERIFY SECTOR(S) EXT – 42h, Non-Data .....	240
7.32 RECEIVE FPDMA QUEUED – 65h, DMA Queued .....	241
7.33 REMOVE ELEMENT AND TRUNCATE – 7Ch, Non-Data .....	243
7.34 REQUEST SENSE DATA EXT – 0Bh, Non-Data .....	245
7.35 RESTORE ELEMENTS AND REBUILD – 7Dh, Non-Data .....	246
7.36 Sanitize Device .....	248
7.36.1 Sanitize Device Overview .....	248
7.36.2 BLOCK ERASE EXT – B4h/0012h, Non-Data .....	249
7.36.3 CRYPTO SCRAMBLE EXT – B4h/0011h, Non-Data .....	252
7.36.4 OVERWRITE EXT – B4h/0014h, Non-Data .....	255
7.36.5 SANITIZE ANTIFREEZE LOCK EXT – B4h/0040h, Non-Data .....	258
7.36.6 SANITIZE FREEZE LOCK EXT – B4h/0020h, Non-Data .....	261
7.36.7 SANITIZE STATUS EXT – B4h/0000h, Non-Data .....	263
7.37 SECURITY DISABLE PASSWORD – F6h, PIO Data-Out .....	265
7.38 SECURITY ERASE PREPARE – F3h, Non-Data .....	267
7.39 SECURITY ERASE UNIT – F4h, PIO Data-Out .....	268
7.40 SECURITY FREEZE LOCK – F5h, Non-Data .....	271
7.41 SECURITY SET PASSWORD – F1h, PIO Data-Out .....	272
7.42 SECURITY UNLOCK – F2h, PIO Data-Out .....	275
7.43 SEND FPDMA QUEUED – 64h, DMA Queued .....	278
7.43.8 HYBRID EVICT – 64h/1h, DMA Queued .....	280
7.44 SET DATE & TIME EXT – 77h, Non-Data .....	284
7.45 SET FEATURES – EFh, Non-Data .....	285
7.45.1 Introduction .....	285
7.45.2 SET FEATURES subcommands .....	286

7.45.3	Enable/disable volatile write cache .....	288
7.45.4	Set transfer mode .....	289
7.45.5	Enable/disable the APM feature set .....	290
7.45.6	Enable/disable the PUIS feature set .....	290
7.45.7	PUIS feature set device spin-up .....	290
7.45.8	Enable/Disable Write-Read-Verify feature set .....	291
7.45.9	Enable/disable device life control .....	292
7.45.10	Enable/Disable Command Duration Limits feature set .....	292
7.45.11	Set Maximum Host Interface Sector Times .....	294
7.45.12	Set rate basis .....	294
7.45.13	Enable/disable read look-ahead .....	294
7.45.14	Enable/disable reverting to defaults .....	295
7.45.15	Enable/Disable the Free-fall Control feature set .....	295
7.45.16	Enable/Disable SATA feature .....	295
7.45.17	Enable/Disable the Sense Data Reporting feature set .....	299
7.45.18	Enable/Disable sense data return for successful NCQ commands .....	299
7.45.19	Long Physical Sector Alignment Error Reporting Control .....	300
7.45.20	Extended Power Conditions subcommand .....	301
7.45.21	Enable/Disable the DSN feature set .....	312
7.45.22	Advanced Background Operation Control .....	312
7.46	SET SECTOR CONFIGURATON EXT – B2h, Non-Data .....	315
7.47	SLEEP – E6h, Non-Data .....	318
7.48	SMART .....	319
7.48.1	Overview .....	319
7.48.2	SMART READ LOG – B0h/D5h, PIO Data-In .....	320
7.48.3	SMART RETURN STATUS – B0h/DAh, Non-Data .....	321
7.48.4	SMART WRITE LOG – B0h/D6h, PIO Data-Out .....	322
7.49	STANDBY – E2h, Non-Data .....	324
7.50	STANDBY IMMEDIATE – E0h, Non-Data .....	325
7.51	TRUSTED NON-DATA – 5Bh, Non-Data .....	326
7.52	TRUSTED RECEIVE – 5Ch, PIO Data-In .....	328
7.53	TRUSTED RECEIVE DMA – 5Dh, DMA .....	335
7.54	TRUSTED SEND – 5Eh, PIO Data-Out .....	336
7.55	TRUSTED SEND DMA – 5Fh, DMA .....	338
7.56	WRITE BUFFER – E8h, PIO Data-Out .....	339
7.57	WRITE BUFFER DMA – EBh, DMA .....	340
7.58	WRITE DMA – CAh, DMA .....	341
7.59	WRITE DMA EXT – 35h, DMA .....	342
7.60	WRITE DMA FUA EXT – 3Dh, DMA .....	343
7.61	WRITE FPDMA QUEUED – 61h, DMA Queued .....	345
7.62	WRITE LOG EXT – 3Fh, PIO Data-Out .....	347
7.63	WRITE LOG DMA EXT – 57h, DMA .....	349
7.64	WRITE SECTOR(S) – 30h, PIO Data-Out .....	351
7.65	WRITE SECTOR(S) EXT – 34h, PIO Data-Out .....	352
7.66	WRITE STREAM DMA EXT – 3Ah, DMA .....	353
7.67	WRITE STREAM EXT – 3Bh, PIO Data-Out .....	356
7.68	WRITE UNCORRECTABLE EXT – 45h, Non-Data .....	357
7.69	ZERO EXT – 44h, Non-Data .....	360
8	SCT Command Transport .....	362
8.1	Introduction .....	362
8.1.1	Overview .....	362
8.1.2	SCT command interactions with ATA commands .....	363
8.1.3	NCQ accesses to the SCT logs .....	363
8.1.4	Resets .....	363
8.2	Processing SCT commands .....	364
8.2.1	Processing SCT commands overview .....	364

8.2.2	SCT capability identification .....	364
8.2.3	SCT Command transfer .....	364
8.2.4	SCT data transfer .....	369
8.2.5	SCT status .....	375
8.3	SCT Command Set .....	382
8.3.1	Overview .....	382
8.3.2	SCT Write Same command .....	383
8.3.3	SCT Error Recovery Control command .....	388
8.3.4	SCT Feature Control command .....	393
8.3.5	SCT Data Table command.....	397
9	Log Definitions .....	401
9.1	Overview .....	401
9.2	General Purpose Log Directory (GPL Log Address 00h) .....	404
9.3	SMART Log Directory (SMART Logging Log Address 00h) .....	405
9.4	Comprehensive SMART Error log (Log Address 02h) .....	406
9.4.1	Overview .....	406
9.4.2	SMART error log version .....	406
9.4.3	Error log index .....	406
9.4.4	Error log data structure .....	406
9.4.5	Device error count .....	407
9.4.6	Data structure checksum .....	407
9.5	Device Statistics log (Log Address 04h) .....	408
9.5.1	Overview .....	408
9.5.2	FEATURE field for GPL commands .....	410
9.5.3	List of Supported Device Statistics log pages (log page 00h) .....	411
9.5.4	Command Duration Limits Statistics (log page 09h) .....	411
9.5.5	Free Fall Statistics (log page 02h) .....	419
9.5.6	General Statistics (log page 01h) .....	421
9.5.7	General Errors Statistics (log page 04h) .....	428
9.5.8	Rotating Media Statistics (log page 03h) .....	431
9.5.9	Solid State Device Statistics (log page 07h) .....	436
9.5.10	Temperature Statistics (log page 05h) .....	436
9.5.11	Transport Statistics (log page 06h) .....	444
9.5.12	Vendor Specific Statistics (log page FFh) .....	445
9.6	Device Vendor Specific logs (Log Addresses A0h-DFh) .....	447
9.7	Extended Comprehensive SMART Error log (Log Address 03h) .....	448
9.7.1	Overview .....	448
9.7.2	SMART error log version .....	448
9.7.3	Error log index .....	448
9.7.4	Extended Error log data structure .....	448
9.7.5	Device error count .....	452
9.7.6	Data structure checksum .....	452
9.8	Power Conditions log (Log Address 08h) .....	453
9.8.1	Overview .....	453
9.8.2	Idle power conditions (log page 00h) .....	453
9.8.3	Standby power conditions (log page 01h) .....	453
9.8.4	Power Conditions log descriptor .....	454
9.9	Host Specific logs (Log Addresses 80h-9Fh) .....	458
9.10	IDENTIFY DEVICE data log (Log Address 30h) .....	459
9.10.1	Overview .....	459
9.10.2	List of Supported IDENTIFY DEVICE data log pages (Page 00h) .....	460
9.10.3	Copy of IDENTIFY DEVICE data (page 01h) .....	460
9.10.4	Capacity (page 02) .....	461
9.10.5	Supported Capabilities (page 03h) .....	464
9.10.6	Current Settings (page 04h) .....	490
9.10.7	Strings (page 05h) .....	498

9.10.8 Security (page 06h) .....	499
9.10.9 Parallel ATA (page 07h) .....	504
9.10.10 Serial ATA (page 08h) .....	515
9.11 Command Duration Limits log (Log Address 18h) .....	525
9.11.1 Command Duration Limits log overview .....	525
9.11.2 Command Duration Limits Descriptor .....	527
9.12 LBA Status log (Log Address 19h) .....	532
9.12.1 Overview .....	532
9.12.2 Number of LBA Valid Ranges log page (Page 0000h) .....	532
9.12.3 LBA Status log pages .....	532
9.12.4 LBA Status Descriptor .....	533
9.13 LPS Mis-alignment log (Log Address 0Dh) .....	535
9.14 NCQ Command Error log (Log Address 10h) .....	537
9.14.1 Overview .....	537
9.14.2 NCQ TAG field .....	538
9.14.3 NQ bit .....	538
9.14.4 UNL bit .....	538
9.14.5 Return Fields .....	539
9.14.6 NCQ Autosense .....	539
9.14.7 FINAL LBA IN ERROR field .....	539
9.14.8 Checksum .....	539
9.14.9 WRITE POINTER VALID field .....	539
9.14.10 WRITE POINTER[0..31] fields .....	540
9.14.11 WRITE POINTER CHECKSUM field .....	540
9.15 Read Stream Error log (Log Address 22h) .....	541
9.16 SATA Phy Event Counters log (Log Address 11h) .....	543
9.16.1 Overview .....	543
9.16.2 Counter x Identifier .....	543
9.16.3 Counter x Value .....	543
9.16.4 Counter x Length .....	543
9.16.5 Checksum .....	543
9.17 SATA NCQ Non-Data log (Log Address 12h) .....	544
9.17.1 Overview .....	544
9.17.2 SUPPORTS ABORT NCQ QUEUE bit .....	546
9.17.3 SUPPORTS ABORT ALL AT bit .....	546
9.17.4 SUPPORTS ABORT STREAMING AT bit .....	546
9.17.5 SUPPORTS ABORT NON-STREAMING AT bit .....	546
9.17.6 SUPPORTS ABORT SELECTED TTAG AT bit .....	546
9.17.7 SUPPORTS DEADLINE HANDLING bit .....	546
9.17.8 SUPPORTS WDNC bit .....	546
9.17.9 SUPPORTS RDNC bit .....	546
9.17.10 SUPPORTS HYBRID DEMOTE BY SIZE bit .....	547
9.17.11 SUPPORTS HYBRID CHANGE BY LBA RANGE bit .....	547
9.17.12 SUPPORTS HYBRID CONTROL bit .....	547
9.17.13 QUEUED SET FEATURES SUPPORTED bit .....	547
9.17.14 QUEUED ZERO EXT SUPPORTED bit .....	547
9.17.15 SUPPORTS ZAC MANAGEMENT OUT bit .....	547
9.17.16 SUPPORTS DURABLE/ORDERED WRITE NOTIFICATION bit .....	547
9.17.17 SUPPORTS D/OW bit .....	547
9.18 SATA NCQ Send and Receive log (Log Address 13h) .....	548
9.18.1 Overview .....	548
9.18.2 QUEUED DATA SET MANAGEMENT XL SUPPORTED bit .....	548
9.18.3 SUPPORTS HYBRID EVICT bit .....	549
9.18.4 QUEUED DATA SET MANAGEMENT SUPPORTED bit .....	549
9.18.5 QUEUED DATA SET MANAGEMENT SUPPORTS TRIM bit .....	549
9.18.6 QUEUED READ LOG DMA EXT FEATURE FIELD SUPPORTED bit .....	549
9.18.7 SEQUENTIAL QUEUED READ LOG DMA EXT SUPPORTED bit .....	549

9.18.8 QUEUED READ LOG DMA EXT SUPPORTED bit .....	549
9.18.9 SEQUENTIAL QUEUED WRITE LOG DMA EXT SUPPORTED bit .....	549
9.18.10 QUEUED WRITE LOG DMA EXT SUPPORTED bit .....	549
9.18.11 SUPPORTS ZAC MANAGEMENT IN bit .....	550
9.18.12 SUPPORTS ZAC MANAGEMENT OUT bit .....	550
9.19 Hybrid Information log (Log Address 14h) .....	551
9.19.1 Hybrid Information log overview .....	551
9.19.2 Hybrid Information Header .....	552
9.19.3 Hybrid Information Descriptor .....	555
9.20 Rebuild Assist log (Log Address 15h) .....	557
9.20.1 Overview .....	557
9.20.2 MANAGE REBUILD ASSIST ENABLED bit .....	558
9.20.3 PHYSICAL ELEMENT LENGTH field .....	558
9.20.4 DISABLED PHYSICAL ELEMENT MASK field .....	558
9.20.5 DISABLED PHYSICAL ELEMENTS field .....	558
9.21 Selective Self-Test log (Log Address 09h) .....	559
9.21.1 Overview .....	559
9.21.2 REVISION NUMBER field .....	559
9.21.3 Test span starting LBA and ending LBA .....	559
9.21.4 CURRENT LBA UNDER TEST field .....	559
9.21.5 CURRENT SPAN UNDER TEST field .....	560
9.21.6 FEATURE FLAGS field .....	560
9.21.7 SELECTIVE SELF-TEST PENDING TIME field .....	560
9.21.8 CHECKSUM field .....	560
9.22 Summary SMART Error log (Log Address 01h) .....	561
9.22.1 Overview .....	561
9.22.2 SMART error log version .....	561
9.22.3 Error log index .....	561
9.22.4 Error log data structure .....	561
9.22.5 Device error count .....	564
9.22.6 Data structure checksum .....	564
9.23 Write Stream Error log (Log Address 21h) .....	565
9.24 Current Device Internal Status Data log (Log Address 24h) .....	566
9.24.1 Overview .....	566
9.24.2 Current Device Internal Status Data header page .....	567
9.24.3 Current Device Internal Status data pages .....	568
9.24.4 Examples of data area usage .....	569
9.25 Saved Device Internal Status Data log (Log Address 25h) .....	571
9.25.1 Overview .....	571
9.25.2 Saved Device Internal Status Data header page .....	571
9.25.3 Current Device Internal Status data pages .....	572
9.26 Device Statistics Notifications log (Log Address 0Ah) .....	573
9.27 Pending Defects log (Log Address 0Ch) .....	577
9.27.1 Overview .....	577
9.27.2 Detection of an uncorrectable media error .....	577
9.27.3 Adding descriptors to the Pending Defects log .....	577
9.27.4 Removing descriptors from the Pending Defects log .....	577
9.27.5 Contents of the Pending Defects log .....	577
9.27.6 NUMBER OF LOG DESCRIPTORS field .....	578
9.27.7 Pending Defects descriptor format .....	578
9.28 Sense Data for Successful NCQ Commands log (Log address 0Fh) .....	579
9.28.1 Overview .....	579
9.28.2 SENSE DATA VALID field .....	580
9.28.3 Successful Sense Data descriptor .....	581
9.29 Sector Configuration log (Log Address 2Fh) .....	582
9.29.1 Overview .....	582
9.29.2 Sector Configuration descriptors (log page 00h) .....	582

9.30 Mutate Configurations log (Log Address 42h) .....	584
9.30.1 Overview .....	584
9.30.2 Zero padding .....	584
9.30.3 Mutate Configurations header .....	584
9.30.4 Mutate Configuration descriptor .....	585
9.31 Concurrent Positioning Ranges log (Log Address 47h) .....	591
9.31.1 Concurrent Positioning Ranges log overview .....	591
9.31.2 Concurrent Positioning Ranges header .....	591
9.31.3 LBA range descriptor .....	591
9.31.4 Padding .....	592
9.31.5 Example Concurrent Positioning Ranges log .....	592
9.32 Sense Data log (Log Address 53h) .....	594
9.32.1 Overview .....	594
9.32.2 DEFERRED ERROR bit .....	595
9.32.3 Return Fields .....	595
9.32.4 SENSE KEY field, ADDITIONAL SENSE CODE field, and ADDITIONAL SENSE CODE QUALIFIER field .....	595
9.32.5 FINAL LBA IN ERROR field .....	595
9.32.6 Checksum .....	595
9.33 Out Of Band Management Control log (Log Address 16h) .....	596
9.33.1 Out Of Band Management Control log overview .....	596
9.33.2 NUMBER OF VALID DESCRIPTORS field .....	596
9.33.3 REPORTING ENABLED bit .....	596
9.33.4 VOLATILE bit .....	597
9.33.5 PROTOCOL REVISION CODE field .....	597
9.33.6 Attribute Control Descriptor .....	597
9.33.7 Temperature attribute control descriptor format .....	599
10 Normal and Error Outputs .....	602
10.1 Overview .....	602
10.2 Normal Outputs .....	602
10.3 Error Outputs .....	617
Annex A (informative) Command Set Summary .....	645
Annex B (informative) How to Use SCT Commands .....	672
B.1 How to Use SCT Commands Overview .....	672
B.2 Examples of Log Page Command Sequences .....	674
B.3 Issuing an SCT Command to a Device .....	679
B.3.1 Step 1 – Build a Key Page .....	679
B.3.2 Step 2 – Issue the SCT command .....	680
B.3.3 Step 3 – Transfer Data if Required .....	681
B.3.4 Step 4 – Final Status/SCT Command Completion .....	682
Annex C (informative) Implementation Guidelines for 1 024- and 4 096-Byte Sector Sizes.....	683
C.1 Scope .....	683
C.2 Overview .....	683
C.3 Implementation .....	685
C.3.1 4 096-Byte Physical Sector Size Implementation .....	685
C.3.2 Reporting Alignment (512-Byte LBA Only) .....	685
C.3.3 RMW operations (512-Byte LBA Only) .....	686
C.4 Implementation Issues (512-Byte LBA Only) .....	686
C.4.1 Overview .....	686
C.4.2 Drive Partitioning .....	687
C.4.3 File System Formatting .....	688
C.4.4 Virtual Memory accessing .....	688
C.4.5 Booting .....	688

Annex D (informative) The DATA SET MANAGEMENT command with Trim .....	689
D.1 Overview .....	689
D.2 Trim interaction with volatile caches .....	690
Annex E (informative) Using repurposing depopulation.....	692
Bibliography .....	693

## Tables

	Page
Table 1 - Numbering conventions .....	14
Table 2 - ATA string byte swapping .....	18
Table 3 - FIRMWARE REVISION field example .....	19
Table 4 - Feature set summary .....	20
Table 5 - IDENTIFY DEVICE capacity reporting .....	21
Table 6 - Command Duration Limits descriptor selection .....	30
Table 7 - Caching Priority .....	40
Table 8 - Power Source interactions .....	43
Table 9 - Words transferred per COUNT field unit by command .....	45
Table 10 - PRIO field .....	50
Table 11 - Summary of Security States and Security Characteristics .....	73
Table 12 - Security Command Actions .....	74
Table 13 - Security page settings for the SEC1: Security Disabled/Not Locked/Not Frozen state .....	79
Table 14 - Security page settings for the SEC2: Security Disabled/Not Locked/Frozen state .....	80
Table 15 - Security page settings for the SEC4: Security Enabled/Locked/Not Frozen state .....	81
Table 16 - Security page settings for the SEC5: Security Enabled/Not Locked/Not Frozen state .....	82
Table 17 - Security page settings for the SEC6: Security Enabled/Not Locked/Frozen state .....	83
Table 18 - Preserved Feature Sets and Settings .....	89
Table 19 - STATUS field .....	103
Table 20 - ERROR field .....	105
Table 21 - COUNT field use for NCQ Tag .....	106
Table 22 - Sense Codes .....	108
Table 23 - Example Command Structure .....	113
Table 24 - Example Normal Output .....	114
Table 25 - Example Error Output .....	115
Table 26 - Summary of commands .....	116
Table 27 - Accessible Max Address Configuration FEATURE field values .....	119
Table 28 - GET NATIVE MAX ADDRESS EXT command inputs .....	120
Table 29 - SET ACCESSIBLE MAX ADDRESS EXT command inputs .....	121
Table 30 - FREEZE ACCESSIBLE MAX ADDRESS EXT command inputs .....	123
Table 31 - CHECK POWER MODE command inputs .....	124
Table 32 - CONFIGURE STREAM command inputs .....	125
Table 33 - DATA SET MANAGEMENT command inputs .....	127
Table 34 - DSM FUNCTION field .....	128
Table 35 - Data returned for trimmed logical sectors .....	128
Table 36 - LBA Range Entry page format .....	129
Table 37 - SEND FPDMA QUEUED command encapsulation for the subcommand specific inputs from a DATA SET MANAGEMENT command .....	130
Table 38 - DATA SET MANAGEMENT XL command inputs .....	131
Table 39 - XL LBA Range Entry page format .....	132
Table 40 - SEND FPDMA QUEUED command encapsulation for the subcommand specific inputs from a DATA SET MANAGEMENT XL command .....	132
Table 41 - SUBCOMMAND field .....	134
Table 42 - DOWNLOAD MICROCODE command inputs .....	145
Table 43 - COUNT field output for DOWNLOAD MICROCODE requesting the offset transfer method .....	146
Table 44 - DOWNLOAD MICROCODE DMA command inputs .....	147
Table 45 - EXECUTE DEVICE DIAGNOSTIC command inputs .....	148
Table 46 - Diagnostic codes .....	149
Table 47 - FLUSH CACHE command inputs .....	150
Table 48 - FLUSH CACHE EXT command inputs .....	151
Table 49 - GET PHYSICAL ELEMENT STATUS command inputs .....	152
Table 50 - FILTER field .....	153
Table 51 - REPORT TYPE field .....	153

Table 52 - GET PHYSICAL ELEMENT STATUS input from device to host .....	154
Table 53 - Physical element status descriptor .....	155
Table 54 - PHYSICAL ELEMENT TYPE field .....	155
Table 55 - PHYSICAL ELEMENT HEALTH field .....	156
Table 56 - IDENTIFY DEVICE command inputs .....	157
Table 57 - IDENTIFY DEVICE data .....	158
Table 58 - Specific configuration .....	175
Table 59 - Minor version number .....	181
Table 60 - Transport minor version number .....	190
Table 61 - IDLE command inputs .....	191
Table 62 - STANDBY TIMER PERIOD field .....	191
Table 63 - IDLE IMMEDIATE command inputs .....	193
Table 64 - IDLE IMMEDIATE with the Unload feature command inputs .....	194
Table 65 - MUTATE EXT command inputs .....	195
Table 66 - NCQ NON-DATA command inputs .....	197
Table 67 - NCQ NON-DATA Subcommands .....	198
Table 68 - HYBRID DEMOTE BY SIZE - Number of logical sectors affected .....	199
Table 69 - HYBRID DEMOTE BY SIZE command inputs .....	200
Table 70 - HYBRID INFORMATION field .....	201
Table 71 - Interactions with the requested caching priority level .....	202
Table 72 - Cache Behavior .....	206
Table 73 - HYBRID CHANGE BY LBA RANGE command inputs .....	208
Table 74 - HYBRID CONTROL command inputs .....	211
Table 75 - ABORT NCQ QUEUE command inputs .....	214
Table 76 - ABORT NCQ QUEUE Abort Types .....	215
Table 77 - DEADLINE HANDLING command inputs .....	216
Table 78 - DURABLE/ORDERED WRITE NOTIFICATION command inputs .....	219
Table 79 - NOP command inputs .....	221
Table 80 - READ BUFFER command inputs .....	222
Table 81 - READ BUFFER DMA command inputs .....	223
Table 82 - READ DMA command inputs .....	224
Table 83 - READ DMA EXT command inputs .....	225
Table 84 - READ FPDMA QUEUED command inputs .....	227
Table 85 - READ LOG EXT command inputs .....	229
Table 86 - READ LOG DMA EXT command inputs .....	231
Table 87 - RECEIVE FPDMA QUEUED command encapsulation for the subcommand specific inputs from a READ LOG DMA EXT command .....	232
Table 88 - READ SECTOR(S) command inputs .....	233
Table 89 - READ SECTOR(S) EXT command inputs .....	234
Table 90 - READ STREAM DMA EXT command inputs .....	235
Table 91 - READ STREAM EXT command inputs .....	238
Table 92 - READ VERIFY SECTOR(S) command inputs .....	239
Table 93 - READ VERIFY SECTOR(S) EXT command inputs .....	240
Table 94 - RECEIVE FPDMA QUEUED command inputs .....	241
Table 95 - RECEIVE FPDMA QUEUED Subcommands .....	242
Table 96 - REMOVE ELEMENT AND TRUNCATE command inputs .....	243
Table 97 - REQUEST SENSE DATA EXT command inputs .....	245
Table 98 - RESTORE ELEMENTS AND REBUILD command inputs .....	246
Table 99 - Sanitize Device FEATURE field values .....	248
Table 100 - BLOCK ERASE EXT command inputs .....	250
Table 101 - CRYPTO SCRAMBLE EXT command inputs .....	253
Table 102 - OVERWRITE EXT command inputs .....	256
Table 103 - SANITIZE ANTIFREEZE LOCK EXT command inputs .....	258
Table 104 - SANITIZE FREEZE LOCK EXT command inputs .....	261
Table 105 - SANITIZE STATUS EXT command inputs .....	263
Table 106 - SECURITY DISABLE PASSWORD command inputs .....	265
Table 107 - SECURITY DISABLE PASSWORD data content .....	266

Table 108 - SECURITY ERASE PREPARE command inputs .....	267
Table 109 - Erase Mode characteristics .....	268
Table 110 - SECURITY ERASE UNIT command inputs .....	269
Table 111 - SECURITY ERASE UNIT data content .....	270
Table 112 - SECURITY FREEZE LOCK command inputs .....	271
Table 113 - SECURITY SET PASSWORD command inputs .....	273
Table 114 - SECURITY SET PASSWORD data content .....	274
Table 115 - SECURITY UNLOCK command inputs .....	276
Table 116 - SECURITY UNLOCK data content .....	277
Table 117 - SEND FPDMA QUEUED command inputs .....	278
Table 118 - SEND FPDMA QUEUED Subcommands .....	279
Table 119 - HYBRID EVICT command inputs .....	281
Table 120 - Output from the host for the HYBRID EVICT command .....	282
Table 121 - SET DATE & TIME EXT command inputs .....	284
Table 122 - SET FEATURES command inputs .....	285
Table 123 - NCQ NON-DATA command encapsulation for the subcommand specific inputs from a SET FEATURES command .....	286
Table 124 - SET FEATURES command subcommand codes .....	286
Table 125 - Transfer modes .....	289
Table 126 - APM levels .....	290
Table 127 - Write-Read-Verify modes .....	291
Table 128 - Enable/Disable Command Duration Limits parameters .....	292
Table 129 - CDL ACTION field .....	293
Table 130 - Maximum Host Interface Sector Times .....	294
Table 131 - SATA features .....	295
Table 132 - Extended Uses of Hardware Feature Control .....	297
Table 133 - EPC subcommands .....	301
Table 134 - POWER CONDITION ID field .....	301
Table 135 - Restore Power Condition Settings inputs .....	302
Table 136 - Go To Power Condition inputs .....	304
Table 137 - Set Power Condition Timer inputs .....	306
Table 138 - Set Power Condition State inputs .....	308
Table 139 - Enable the EPC feature set inputs .....	309
Table 140 - Disable the EPC feature set inputs .....	310
Table 141 - Set EPC Power Source inputs .....	311
Table 142 - DSN feature set subcommands .....	312
Table 143 - SET FEATURES fields for Advanced Background Operation Control .....	312
Table 144 - ABO CONTROL field .....	313
Table 145 - SET SECTOR CONFIGURATION EXT command inputs .....	316
Table 146 - SLEEP command inputs .....	318
Table 147 - FEATURE field values .....	319
Table 148 - SMART READ LOG command inputs .....	320
Table 149 - SMART RETURN STATUS command inputs .....	321
Table 150 - SMART WRITE LOG command inputs .....	322
Table 151 - STANDBY command inputs .....	324
Table 152 - STANDBY IMMEDIATE command inputs .....	325
Table 153 - TRUSTED NON-DATA command inputs .....	326
Table 154 - TRUSTED RECEIVE command inputs .....	329
Table 155 - TRUSTED RECEIVE SECURITY PROTOCOL field .....	330
Table 156 - Security Protocol 00h SP SPECIFIC field .....	331
Table 157 - TRUSTED RECEIVE parameter data for SP Specific=0000h .....	331
Table 158 - TRUSTED RECEIVE parameter data for SP Specific=0001h .....	332
Table 159 - TRUSTED RECEIVE parameter data for SP Specific=0002h .....	333
Table 160 - Compliance Descriptor Type .....	333
Table 161 - Compliance Descriptor Header .....	333
Table 162 - Security Requirements for Cryptographic Modules descriptor .....	334
Table 163 - TRUSTED RECEIVE DMA command inputs .....	335

Table 164 - TRUSTED SEND command inputs.....	336
Table 165 - TRUSTED SEND – SECURITY PROTOCOL field.....	337
Table 166 - TRUSTED SEND DMA command inputs.....	338
Table 167 - WRITE BUFFER command inputs.....	339
Table 168 - WRITE BUFFER DMA command inputs.....	340
Table 169 - WRITE DMA command inputs.....	341
Table 170 - WRITE DMA EXT command inputs.....	342
Table 171 - WRITE DMA FUA EXT command inputs.....	343
Table 172 - WRITE FPDMA QUEUED command inputs.....	345
Table 173 - WRITE LOG EXT command inputs.....	347
Table 174 - WRITE LOG DMA EXT command inputs.....	349
Table 175 - SEND FPDMA QUEUED command encapsulation for the subcommand specific inputs from a WRITE LOG DMA EXT command.....	350
Table 176 - WRITE SECTOR(S) command inputs.....	351
Table 177 - WRITE SECTOR(S) EXT command inputs.....	352
Table 178 - WRITE STREAM DMA EXT command inputs.....	353
Table 179 - WRITE STREAM EXT command inputs.....	356
Table 180 - WRITE UNCORRECTABLE EXT command inputs.....	358
Table 181 - ZERO EXT command inputs.....	360
Table 182 - NCQ-NON-DATA command encapsulation for the subcommand specific inputs from a ZERO EXT command.....	361
Table 183 - Summary of SCT Command Transport logs.....	362
Table 184 - Summary of ATA commands used by the SCT Command Transport.....	362
Table 185 - Fields to send an SCT Command using SMART WRITE LOG.....	364
Table 186 - Fields to send an SCT Command using GPL write logs.....	365
Table 187 - Successful SCT Command response.....	366
Table 188 - SCT Command error response.....	367
Table 189 - EXTENDED STATUS CODE field.....	368
Table 190 - SCT data transfer using the SMART feature set.....	369
Table 191 - SCT data transfer using the GPL feature set.....	370
Table 192 - Successful SMART SCT data transfer response.....	371
Table 193 - Successful GPL SCT data transfer response.....	372
Table 194 - SMART SCT data transfer error response.....	373
Table 195 - GPL SCT data transfer error response.....	374
Table 196 - SCT status request using the SMART feature set.....	375
Table 197 - SCT status request using the GPL feature set.....	376
Table 198 - Successful SMART SCT status response.....	377
Table 199 - Successful GPL SCT status response.....	378
Table 200 - Format of SCT status response.....	379
Table 201 - SMART STATUS field.....	380
Table 202 - SMART and GPL SCT status error response.....	381
Table 203 - SCT command basic key page structure.....	382
Table 204 - ACTION CODE field.....	382
Table 205 - SCT Write Same command key page.....	386
Table 206 - SCT Write Same command status response.....	387
Table 207 - SCT Error Recovery Control command key page.....	389
Table 208 - SCT Error Recovery Control command status response.....	391
Table 209 - SCT ERROR RECOVERY CONTROL RETURNED VALUE field.....	392
Table 210 - SCT Feature Control command key page.....	393
Table 211 - Feature Code list.....	394
Table 212 - Options Flags for each Feature Code.....	395
Table 213 - SCT Feature Control command status response.....	396
Table 214 - SCT Data Table command.....	397
Table 215 - TABLE ID field.....	397
Table 216 - HDA Temperature History table.....	398
Table 217 - SCT Data Table command status response.....	400
Table 218 - Log address definition.....	401

Table 219 - General Purpose Log Directory .....	404
Table 220 - SMART Log Directory .....	405
Table 221 - Comprehensive SMART Error log .....	406
Table 222 - Defined Device Statistics log pages .....	408
Table 223 - Device Statistic format .....	408
Table 224 - DEVICE STATISTIC FLAGS field .....	409
Table 225 - FEATURE field for READ LOG EXT and READ LOG DMA EXT .....	410
Table 226 - List of supported Device Statistics log pages .....	411
Table 227 - Command Duration Limits Statistics .....	412
Table 228 - Free Fall Statistics .....	419
Table 229 - General Statistics .....	421
Table 230 - Workload Utilization device statistic .....	426
Table 231 - RATE VALIDITY field .....	426
Table 232 - RATE BASIS field .....	427
Table 233 - Utilization Usage Rate values .....	427
Table 234 - Random write resources values .....	428
Table 235 - General Error Statistics .....	429
Table 236 - Rotating Media Statistics .....	431
Table 237 - Solid State Device Statistics .....	436
Table 238 - Temperature Statistics .....	437
Table 239 - Transport Statistics .....	444
Table 240 - Vendor Specific Statistics .....	445
Table 241 - Extended Comprehensive SMART Error log .....	448
Table 242 - Extended Error log data structure .....	449
Table 243 - Command data structure .....	450
Table 244 - Error data structure .....	451
Table 245 - State field values .....	451
Table 246 - Idle Power Conditions log page .....	453
Table 247 - Standby Power Conditions log page .....	453
Table 248 - Power Conditions log descriptor .....	454
Table 249 - Defined IDENTIFY DEVICE data log pages .....	459
Table 250 - List of supported IDENTIFY DEVICE data log pages .....	460
Table 251 - Capacity .....	461
Table 252 - Supported Capabilities .....	464
Table 253 - Nominal Media Rotation Rate .....	479
Table 254 - NOMINAL FORM FACTOR field .....	479
Table 255 - World wide name format (word-based view) .....	480
Table 256 - IDENTIFY DEVICE data WWN format (word-based view) .....	481
Table 257 - IDENTIFY DEVICE data WWN format (byte-based view) .....	481
Table 258 - LOGICAL BLOCK MARKUPS SUPPORTED field .....	482
Table 259 - SCSI Block Commands logical block markup descriptor format .....	482
Table 260 - Operating system file logical block markup descriptor values .....	483
Table 261 - UTILIZATION TYPE field .....	484
Table 262 - UTILIZATION UNITS field .....	484
Table 263 - UTILIZATION INTERVAL field .....	485
Table 264 - Current Settings .....	490
Table 265 - POWER SOURCE field .....	494
Table 266 - ABO STATUS field .....	497
Table 267 - Strings .....	498
Table 268 - Security .....	499
Table 269 - Short format ENHANCED SECURITY ERASE TIME field .....	502
Table 270 - Extended format ENHANCED SECURITY ERASE TIME field .....	502
Table 271 - Short format NORMAL SECURITY ERASE TIME field .....	502
Table 272 - Extended format NORMAL SECURITY ERASE TIME field .....	503
Table 273 - Parallel ATA .....	504
Table 274 - PATA device number detected coded values .....	512
Table 275 - Serial ATA .....	515

Table 276 - CURRENT NEGOTIATED SERIAL ATA SIGNAL SPEED field .....	522
Table 277 - Command Duration Limits Log (page 0) .....	525
Table 278 - PERFORMANCE VERSUS COMMAND DURATION GUIDELINES field .....	526
Table 279 - Command Duration Limits Descriptor .....	527
Table 280 - INACTIVE TIME LIMIT POLICY field .....	527
Table 281 - ACTIVE TIME LIMIT POLICY field .....	528
Table 282 - COMMAND DURATION GUIDELINE POLICY field .....	528
Table 283 - COMMAND DURATION LIMITS STATISTIC SELECTOR field .....	530
Table 284 - Defined LBA Status log pages .....	532
Table 285 - Number of Valid LBA Ranges log page .....	532
Table 286 - LBA Status log page .....	533
Table 287 - LBA Status Descriptor .....	533
Table 288 - LPS Mis-alignment log (log page 0) .....	535
Table 289 - LPS Mis-alignment log (log pages 1..x) .....	536
Table 290 - NCQ Command Error log .....	537
Table 291 - Read Stream Error log .....	541
Table 292 - Stream Error Log Entry .....	542
Table 293 - SATA Phy Event Counters log Format .....	543
Table 294 - SATA NCQ Non-Data log (log page 00h) .....	544
Table 295 - SATA NCQ Send and Receive log (log page 00h) .....	548
Table 296 - Hybrid Information Log data .....	551
Table 297 - Hybrid Information Header .....	552
Table 298 - ENABLED field .....	553
Table 299 - HYBRID HEALTH field .....	553
Table 300 - SUPPORTED OPTIONS field .....	554
Table 301 - Hybrid Information Descriptor .....	555
Table 302 - Rebuild Assist log (log page 00h) .....	557
Table 303 - MANAGE REBUILD ASSIST bit .....	558
Table 304 - Selective Self-Test log .....	559
Table 305 - FEATURE FLAGS field .....	560
Table 306 - Summary SMART Error log .....	561
Table 307 - Error log data structure .....	561
Table 308 - Command data structure .....	562
Table 309 - Error data structure .....	563
Table 310 - State values .....	563
Table 311 - Write Stream Error log .....	565
Table 312 - Current Device Internal Status Data header (page 0) .....	567
Table 313 - Current Device Internal Status Data (pages 1..n) .....	568
Table 314 - Saved Device Internal Status Data header (page 0) .....	571
Table 315 - Saved Device Internal Status Data (pages 1..n) .....	572
Table 316 - Device Statistics Notifications pages .....	573
Table 317 - Summary page of the Device Statistics Notifications log .....	574
Table 318 - DSN Match Entry .....	574
Table 319 - Definition pages of the Device Statistics Notifications log .....	575
Table 320 - DSN CONDITION FLAGS field .....	576
Table 321 - Pending Defects log (page 0) .....	577
Table 323 - Pending Defects descriptor format .....	578
Table 322 - Pending Defects log (page 1..n) .....	578
Table 324 - Sense Data for Successful NCQ Commands log pages 0 and 1 .....	579
Table 325 - Successful Sense Data descriptor format .....	581
Table 326 - Sector Configuration descriptors (log page 00h) .....	582
Table 327 - Sector Configuration descriptor .....	582
Table 328 - Mutate Configurations log .....	584
Table 329 - Mutate Configurations header .....	584
Table 330 - Mutate Configuration descriptor .....	585
Table 331 - CONFIGURATION IDENTIFIER field .....	586
Table 332 - SCHEMA TYPE field .....	587

Table 333 - Host aware zones schema type specific information.....	588
Table 334 - Host managed zones schema type specific information.....	588
Table 335 - Zone domains and zone realms schema type specific information .....	590
Table 336 - Concurrent Positioning Ranges log .....	591
Table 337 - Concurrent Positioning Ranges header.....	591
Table 338 - LBA range descriptor .....	592
Table 339 - Sense Data log .....	594
Table 340 - Out Of Band Management Control Log .....	596
Table 341 - Attribute control descriptor format.....	597
Table 342 - DESCRIPTOR IDENTIFIER field .....	598
Table 343 - Temperature attribute control descriptor format.....	599
Table 344 - TEST MODE field .....	601
Table 345 - Generic Normal Output (No LBA Return Value) for Normal Output.....	602
Table 346 - Download Microcode Normal Output.....	603
Table 347 - Check Power Mode Normal Output .....	604
Table 348 - Stream Normal Output.....	606
Table 349 - Device Signatures for Normal Output .....	607
Table 350 - IDLE Unload Normal Output.....	608
Table 351 - SMART Return Status Normal Output.....	609
Table 352 - Generic Extended Normal Output.....	610
Table 353 - NCQ Command Acceptance Normal Output .....	611
Table 354 - NCQ Normal Output .....	612
Table 355 - REQUEST SENSE DATA EXT Normal Output .....	613
Table 356 - GET NATIVE MAX ADDRESS EXT Normal Output.....	614
Table 357 - Sanitize Device Normal Output.....	615
Table 358 - Restore Physical Elements Normal Output.....	616
Table 359 - Unsupported Command Error.....	618
Table 360 - Check Power Mode Abort Error.....	619
Table 361 - Generic Abort wo/ICRC Error .....	620
Table 362 - Generic Abort Error.....	621
Table 363 - Trusted Abort Error .....	622
Table 364 - Configure Stream Error.....	623
Table 365 - Flush Cache Error.....	624
Table 366 - Flush Cache Ext Error .....	625
Table 367 - Read DMA Ext Error .....	626
Table 368 - Read Log Ext Error .....	627
Table 369 - Read PIO Error .....	628
Table 370 - Read Stream Error.....	629
Table 371 - Write Log Error .....	630
Table 372 - Write Log Ext Error or Data Set Management Error .....	631
Table 373 - Write Extended Error .....	632
Table 374 - Write Stream Error.....	633
Table 375 - Non-Data Write Extended Error .....	634
Table 376 - NOP Error .....	635
Table 377 - SMART Read Log.....	636
Table 378 - Read PIO Extended Error.....	637
Table 379 - SET ACCESSIBLE MAX ADDRESS EXT Error .....	638
Table 380 - Write Error .....	639
Table 381 - Write DMA Error .....	640
Table 382 - NCQ Command Acceptance Error.....	641
Table 383 - Generic NCQ Command Aborted Error .....	642
Table 384 - NCQ Read Command Aborted Error .....	643
Table 385 - Sanitize Device Error .....	644
Table A.1 - Command Code Usage Matrix .....	645
Table A.2 - Command codes (sorted by command code).....	646
Table A.3 - Command codes (sorted by command name) .....	651
Table A.4 - Historical Command Assignments.....	654

Table A.5 - Historical SET FEATURE Code Assignments.....	663
Table B.1 - SCT command using SMART WRITE LOG command .....	680
Table B.2 - SCT command using WRITE LOG EXT command .....	681

## Figures

	Page
Figure 1 - ATA document relationships.....	1
Figure 2 - State diagram convention .....	15
Figure 3 - Byte, word, DWord, QWord, and DQWord relationships .....	17
Figure 4 - LLS and LPS Example .....	47
Figure 5 - Alignment 0.....	47
Figure 6 - Alignment 1.....	48
Figure 7 - Alignment 3.....	48
Figure 8 - Power management state diagram.....	56
Figure 9 - Sanitize Device state machine .....	67
Figure 10 - Security state diagram.....	78
Figure 11 - DOWNLOAD MICROCODE State Machine .....	136
Figure 12 - Example of a Device Internal Status log with data in all three data areas.....	569
Figure 13 - Example of a Device Internal Status log with no data .....	570
Figure 14 - Example of a Device Internal Status log with mixed data areas.....	570
Figure 15 - Example for Concurrent Positioning Ranges log with 4 LBA ranges.....	593
Figure B.1 - Example flowchart for SCT commands .....	673
Figure B.2 - Example sequence for foreground write same with a repeating write pattern.....	674
Figure B.3 - Example sequence for foreground write same with a repeating pattern .....	674
Figure B.4 - Example sequence for writing data using an SCT command with no background activity .....	675
Figure B.5 - Example sequence for reading data using an SCT command with no background activity.....	675
Figure B.6 - Example sequence for a Non-Data SCT command with no background activity .....	676
Figure B.7 - Example sequence for writing data using an SCT command with background activity .....	677
Figure B.8 - Example sequence for writing data using multiple write data transfers.....	678
Figure B.9 - Example sequence for a Non-Data SCT command with background activity .....	679
Figure C.1 - System Dependency Chain .....	683
Figure C.2 - Mapping Proposals .....	684
Figure C.3 - Logical Sector to Physical Mapping .....	684
Figure C.4 - Uncorrectable Error Handling.....	686
Figure C.5 - Typical HDD Layout Using A Master Boot Record.....	687