ISO/IEC TR 11801-9906:2025-01 (E)

Information technology - Generic cabling for customer premises - Part 9906: Balanced 1-pair cabling channels up to 600 MHz for single pair Ethernet (SPE)

Contents

Page

FOREWORD 4
INTRODUCTION 6
1 Scope 7
2 Normative references 7
3 Terms, definitions and symbols 8
3.1 Terms and definitions 8
3.2 Symbols 8
4 Single-pair Ethernet (SPE) link segment specifications 8
4.1 General 8
4.2 Link segment specifications 8
4.3 Environmental classifications 9
4.4 SPE link segment signal transmission specifications 9
4.4.1 SPE link segment return loss (RL) 9
4.4.2 SPE link segment insertion loss (IL) 10
4.4.3 SPE link segment unbalance attenuation and coupling attenuation 11
4.4.4 SPE link segment alien (exogenous) crosstalk 14
4.4.5 SPE link segment DC loop resistance 16
4.4.6 SPE link segment propagation delay 16
5 Balanced single-pair cabling channels 16
5.1 General 16
5.2 Component specifications 17
5.3 Environmental classifications 17
5.4 Channel reference implementations 17
Annex A (informative) Balanced single-pair cable specifications 18
A.1 General 18
A.2 Cables using alternative conductor sizes 18
A.3 Balanced single-pair cable specifications 19
A.3.1 Return loss (RL) 19
A.3.2 Insertion loss (IL) 19
A.3.3 Unbalance attenuation and coupling attenuation 20
A.3.4 Alien (exogenous) crosstalk 22
A.3.5 DC resistance 24
A.3.6 Propagation delay 24
Annex B (informative) Balanced single-pair connector specifications 25
Annex C (informative) Conductor size effects for reduced insertion loss 26
C.1 Channel parameters affected by conductor size and AWG 26
C.2 IL parameter variation due to conductor size variation 27
C.3 AWG 27
Bibliography 28

Table 1 – SPE link segment characteristics 9
Table 2 – SPE link segment return loss (RL) 10
Table 3 – SPE link segment IL 11
Table 4 – SPE link segment TCL 12
Table 5 – SPE link segment ELTCTL 13
Table 6 – SPE link segment coupling attenuation 14
Table 7 – SPE link segment PS ANEXT 15
Table 8 – SPE link segment PS AACR-F 15
Table 9 – SPE link segment DC loop resistance 16
Table 10 – SPE link segment propagation delay 16
Table 11 – Balanced single-pair cabling channels 17
Table A.1 – Balanced single-pair cable standards 18
Table A.2 – Balanced single-pair cable RL 19
Table A.3 – Balanced single-pair cable IL 19
Table A.4 – Balanced single-pair cable TCL 20
Table A.5 – Balanced single-pair cable ELTCTL 21
Table A.6 – Balanced single-pair cable coupling attenuation and low-frequency coupling attenuation 22
Table A.7 – Balanced single-pair cable PS ANEXT 23
Table A.8 – Balanced single-pair cable PS AACR-F 23
Table A.9 – Balanced single-pair cable DC resistance 24
Table A.10 – Balanced single-pair cable propagation delay 24
Table B.1 – Balanced single-pair connector standards 25
Table C.1 – Conductor diameter IL factors to be used with example 24 AWG cable with 1,8 conductor IL coefficient 26