

# ISO/IEC TS 11801-9903:2025-10 (E)

## Information technology - Generic cabling systems for customer premises - Part 9903: Matrix modelling of channels and links

---

Contents	Page
FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references .....	7
3 Terms, definitions, symbols and abbreviated terms.....	7
3.1 Terms and definitions.....	7
3.2 Symbols and abbreviated terms .....	8
4 Matrix model.....	9
4.1 General.....	9
4.2 Matrix definition .....	10
4.2.1 General .....	10
4.2.2 Quadriports .....	10
4.2.3 Matrix port definition for a two-pair system representative for modelling purposes .....	10
4.2.4 Operational scattering matrix .....	10
4.2.5 General naming convention .....	11
4.2.6 S-matrix.....	12
4.2.7 Passivity.....	12
4.2.8 Operational reflection loss matrix.....	13
4.2.9 Transmission matrix (T-matrix) .....	13
4.2.10 S-matrix of cabling.....	13
4.3 General case using mixed-mode matrices.....	14
4.3.1 General .....	14
4.3.2 Mixed-mode S-parameters matrix and submatrices.....	14
Annex A (informative) S to T and T to S-matrix conversion formulas .....	17
A.1 Overview.....	17
A.2 Formulas.....	17
A.2.1 S to T-matrix.....	17
A.2.2 T to S matrix.....	17
A.2.3 Conversion matrices .....	17
Annex B (informative) Transmission model terms and definitions .....	19
B.1 Comparison of namings .....	19
B.2 General.....	20
B.3 Background of terms and definitions .....	20
B.3.1 Operational attenuation .....	20
B.3.2 Operational transfer function ( $T_B$ ).....	22
B.3.3 Image or wave transfer function ( $T$ ) .....	22
B.3.4 Insertion transfer function of a two-port ( $T_{BI}$ ).....	22
B.3.5 Insertion transfer function ( $T_{BI}$ ) .....	22
B.3.6 Operational reflection loss transfer function ( $T_{ref} = S_{ref}$ ) of a junction.....	22

Annex C (informative) Channel and permanent link models for balanced cabling .....	24
C.1 General.....	24
C.2 Insertion loss .....	24
C.2.1 Insertion loss of the channel configuration .....	24
C.2.2 Insertion loss of the permanent link configurations.....	25
C.2.3 Assumptions for insertion loss .....	25
C.3 NEXT.....	26
C.3.1 NEXT of the channel configuration.....	26
C.3.2 NEXT of the permanent link configurations .....	26
C.3.3 Assumptions for NEXT.....	27
C.4 ACR-F .....	30
C.4.1 ACR-F of the channel configuration .....	30
C.4.2 ACR-F for the permanent link configurations.....	31
C.4.3 Assumptions for ACR-F .....	31
C.5 No Return loss .....	31
C.5.1 Return loss of the channel and permanent link configurations.....	31
C.5.2 Assumptions for the return loss circuit analysis method .....	32
C.6 PS ANEXT link modelling.....	35
C.6.1 General .....	35
C.6.2 PS ANEXT between connectors.....	35
C.6.3 PS ANEXT between cable segments .....	35
C.6.4 Principles of link modelling .....	36
C.7 PS AACR-F link modelling .....	36
C.7.1 General .....	36
C.7.2 PS AFEXT between connectors .....	36
C.7.3 PS AACR-F between cable segments .....	36
C.7.4 Principles of link modelling .....	37
C.7.5 Impact of PS AACR-F in channels and links with substantially different lengths .....	37
C.8 Component assumptions for modelling purposes.....	40
Annex D (informative) Alternative calculation of matrix terms for limit lines .....	42
D.1 General.....	42
D.2 Extracting limit lines.....	42
D.3 Formulas to extract the cabling limit lines.....	43
D.3.1 Operational attenuation .....	43
D.3.2 Crosstalk .....	43
D.3.3 Reflection and return loss (RL) .....	44
D.4 Component values used as input to the model .....	44
D.4.1 General .....	44
D.4.2 Cable.....	45
D.4.3 Connections .....	47
Annex E (informative) Signal-to-noise ratio modelling .....	49
E.1 General.....	49
E.2 Transmission system model.....	49
E.2.1 General .....	49
E.2.2 Transmitter pulse.....	49
E.2.3 Receiving criteria.....	49
E.2.4 The electrical channel.....	49
E.2.5 Power spectral density (PSD): .....	50
E.2.6 Noise definition.....	50
E.2.7 Modulation.....	51
E.2.8 Bit error ratio (BER).....	52
E.2.9 Signal-to-noise ratio (SNR).....	52
E.3 Calculation examples.....	53

E.3.1	General .....	53
E.3.2	Comparison with other calculations:.....	53
	Bibliography.....	56
Figure 1	– Matrix definition of a 4-port two twisted pair system .....	10
Figure 2	– Operational scattering parameters example from port 2 .....	11
Figure 3	– Transmission matrix concatenation showing an example of a 2-connector permanent link .....	13
Figure B.1	– Defining the operational attenuation and the operational transfer functions of a two-port .....	21
Figure B.2	– Defining the reflection transfer functions and the return loss of a junction .....	23
Figure C.1	– Example of computation of NEXT with higher precision .....	27
Figure C.2	– Example of increased impact of PS AFEXT.....	37
Figure D.1	– Graphical example of a NEXT calculation showing statistical results (red dots) and final calculation (blue line).....	43
Figure D.2	– 100 m cable return loss without reflection at both ends .....	47
Figure D.3	– 100 m cable return loss with a reflection of 0,03 at both ends (6 $\Omega$ mismatch, ~23 dB return loss at 1 MHz).....	47
Figure E.1	– Different noise spectra.....	51
Figure E.2	– Results using this calculation, which show good agreement with similar calculations in [12].....	54
Figure E.3	– Presentation on best modulation scheme (PAM4) and signal-to-noise ratio (SNR) .....	55
Table 1	– All four ports operational scattering parameter definition .....	11
Table 2	– TCL/TCTL and LCL/LCTL port designations .....	11
Table 3	– Equal S-parameters for real components.....	12
Table 4	– Interrelation of mixed-mode mode-conversion and related parameters .....	14
Table 5	– Mixed-mode S-parameter notation.....	15
Table B.1	– Comparison of naming in ISO/IEC 11801-1 and ISO/IEC TS 11801-9903 .....	19
Table C.1	– Insertion loss deviation .....	25
Table C.2	– Modelling assumptions for cable transmission parameters .....	40
Table C.3	– Model input assumptions used in the statistical calculation (Class E <sub>A</sub> ).....	41
Table C.4	– Model input assumptions used in the statistical calculation (Class F <sub>A</sub> ).....	41
Table E.1	– Typical noise limits for 1-pair channels.....	51
Table E.2	– Comparison of different modulation PAM levels .....	52
Table E.3	– Summary .....	54