ISO/IEC 14543-4-303:2026-06 (E)

Information technology - Home electronic system (HES) architecture - Part 4-303: Application protocol for electric vehicle supply equipment (EVSE) chargers and controllers

Contents

Page

INTRODUCTION 5
1 Scope 6
2 Normative references 6
3 Terms, definitions, and abbreviated terms 6
3.1 Terms and definitions 6
3.2 Abbreviated terms 8
4 Conformance 8
5 Configuration 8
6 Application layer 10
6.1 General 10
6.2 NECD objects 10
6.3 NECD services 11
6.4 Object-specific NECD properties 11
6.5 Application operation 13
6.5.1 General 13
6.5.2 Continuous requests 13
6.5.3 Response wait time value for controllers 13
6.5.4 Resending a frame 13
6.5.5 Processing object property counter 13
6.5.6 Property values of write requests 13
6.5.7 Property values of read requests 14
7 Normal operation 14
7.1 General 14
7.2 Start-up operation 15
7.2.1 General 15
7.2.2 Start-up processing of NECD nodes 15
7.2.3 Search processing 16
7.2.4 Obtaining NECD attribute information 16
7.2.5 Obtaining EVSE charger attribute information 17
7.3 Occasional operation 18
7.3.1 General 18
7.3.2 Obtaining vehicle connection and chargeable status 18
7.3.3 Controlling EVSE charger 20
7.4 Fault status notification 22
8 Remote control 22
9 Considerations on controllers 23

Annex A (informative) Terms and NECD protocol frame format on ISO/IEC 14543-4-3 and IEC 62394 24

A.1 Terms correspondence between ISO/IEC 14543-4-3 and IEC 62394 24
A.2 NECD protocol frame format 24
Annex B (informative) Communication link between EVSE charger and CEM in IEC 63380-1 26
Annex C (informative) Relationship between ISO/IEC 14543-4 series and the HES gateway, based on ISO/IEC 15045 series and ISO/IEC 18012 series 27
Bibliography 34

Figure 1 – Relationship between IEC 62394, ISO/IEC 14543-4-3, and ISO/IEC 14543-4-303 5
Figure 2 – Physical configuration, and the path and direction of electricity and communication 9
Figure 3 – NECD configurations 9
Figure 4 – Assumed network stack 10
Figure 5 – Summary of normal operation sequences 15
Figure 6 – Sequence for obtaining NECD attribute information 17
Figure 7 – Sequence of obtaining EVSE charger attribute information 18
Figure 8 – Sequence to obtain vehicle connection and chargeable status of EVSE charger 19
Figure 9 – Sequence to control EVSE charger 21
Figure 10 – Remote control 22
Figure A.1 – NECD protocol frame format 25
Figure B.1 – Communication link between EVSE charger and CEM in IEC 63380-1 26
Figure C.1 – Measurement points for AC EVSEs translated into ISO/IEC 18012-3 32
Figure C.2 – Measurement points for DC EVSEs translated into ISO/IEC 18012-3 33

Table 1 – NECD objects for EVSE chargers 10
Table 2 – NECD objects for controllers 11
Table 3 – NECD services 11
Table 4 – NECD properties of device object (super class) 11
Table 5 – NECD properties of device object 12
Table 6 – Response wait time values for controllers 13
Table A.1 – Terms correspondence table between ISO/IEC 14543-4-3 and IEC 62394 24
Table C.1 – List of the translation between ISO/IEC 14543-4-303, IEC 62394, and HES gateway lexicon (ISO/IEC 18012-3) supported 27
Table C.2 – List of the translation between ISO/IEC 14543-4-303, IEC 62394, and HES gateway lexicon (ISO/IEC 18012-3) not supported at this time 31