

# ISO/IEC 14165-141:2001-06 (E)

## Information technology\_ - Fibre Channel\_ - Part\_141: Fabric Generic Requirements (FC-FG)

---

### Contents

	Page
FOREWORD . . . . .	v
INTRODUCTION . . . . .	vi
<b>1</b> Scope . . . . .	<b>1</b>
<b>2</b> Normative references . . . . .	<b>1</b>
<b>3</b> Definitions and conventions . . . . .	<b>2</b>
3.1 Definitions . . . . .	2
3.2 Editorial conventions . . . . .	5
3.3 Abbreviations and acronyms . . . . .	5
<b>4</b> Fabric concepts . . . . .	<b>6</b>
4.1 Fabric and Fabric Elements . . . . .	6
4.1.1 Sub-Fabric . . . . .	6
4.1.2 Region . . . . .	8
4.1.3 Translator . . . . .	8
4.1.4 Extended Region . . . . .	8
4.1.5 Zone . . . . .	8
4.2 Typical Fabric topologies . . . . .	8
4.2.1 Switch topology . . . . .	9
4.2.1.1 Dedicated Connections . . . . .	9
4.2.1.2 Connectionless service . . . . .	9
4.2.1.3 Connection-oriented service . . . . .	10
4.2.2 Distributed Fabric Element topology (DFE) . . . . .	10
4.2.3 Other topologies . . . . .	10
4.3 Fabric frame . . . . .	10
4.4 Fabric_Ports . . . . .	11
4.5 Fabric Service Parameters . . . . .	11
4.6 Fabric addressing . . . . .	11
4.6.1 Address identifiers . . . . .	11
4.6.2 Address space partitioning . . . . .	12
4.7 Fabric addressable service elements . . . . .	12
4.7.1 Broadcast Alias_ID . . . . .	12
4.7.2 Fabric F_Port/Login server . . . . .	12
4.7.3 Fabric Controller . . . . .	13
4.7.4 Directory server . . . . .	13
4.7.5 Time server . . . . .	13
4.7.6 Management server . . . . .	13

	Page
4.7.7 Quality of Service Facilitator - Class 4 (QoSf) . . . . .	13
4.7.8 Alias Server . . . . .	13
<b>5 Fabric entity requirements and characteristics . . . . .</b>	<b>13</b>
5.1 General requirements . . . . .	13
5.2 Link_Control response . . . . .	14
5.3 Frame validity checking . . . . .	14
5.4 Connection independence . . . . .	14
5.5 Class 1 bandwidth & frame jitter . . . . .	14
5.6 Fabric Controller . . . . .	14
5.7 Login Server . . . . .	14
5.8 Service Parameter extent . . . . .	14
5.9 E_D_TOV, R_A_TOV enforcement . . . . .	14
5.10 Non-duplication of frames . . . . .	15
5.11 Phase discontinuities . . . . .	15
<b>6 Fabric_Port requirements and characteristics . . . . .</b>	<b>15</b>
6.1 General requirements . . . . .	15
6.2 Class 1 service - Dedicated Connection . . . . .	15
6.3 Buffered Class 1 service . . . . .	16
6.4 Dedicated Simplex service . . . . .	16
6.5 Class 2 service - Multiplex . . . . .	16
6.6 Class 3 service - Datagram . . . . .	17
6.7 Class 4 service - Fractional . . . . .	17
6.8 Intermix service . . . . .	17
6.9 Class F service - Fabric signaling . . . . .	17
6.9.1 Class F Frame formats . . . . .	17
6.9.2 Class F function . . . . .	17
6.9.3 Class F rules . . . . .	18
6.9.4 Class F delimiters . . . . .	19
6.9.4.1 Class F frame size . . . . .	19
6.9.4.2 Class F flow control . . . . .	19
6.9.5 Link Control . . . . .	19
6.10 Fabric Login . . . . .	19
<b>7 Initialization and configuration control . . . . .</b>	<b>20</b>
7.1 Initialization . . . . .	20

7.1.1	Power On	20
7.1.2	Link Initialization Protocol	20
7.1.3	Link Attachment Protocol	20
7.1.4	Addressing and Configuration Determination	21
7.1.5	F_Port Activation	21
7.1.6	N_Port Login with Fabric	21
7.2	Configuration Changes	21
8	Fabric inter-operation	22

## Annex

A	Address Space Partitioning	23
A.1	Address partitioning	23
A.1.1	Port Identifier partition	23
A.1.2	Fabric-Assisted functions	23
A.1.3	Vendor Unique partitions	23

## Table

1	Well-known Address Identifiers	12
2	Address Partitioning	24

## Figures

1	Document relationship	vii
2	Fabric model	6
3	Fabric with Sub-Fabric illustrations	7
4	Class 2 Sub-Fabrics and an extended region	8
5	Example of Switch topology	9
6	Example of Distributed Fabric Element topology	10
7	The Class F frame format	18