

# ISO/IEC 14776-321:2002-08 (E)

## Information technology\_ - Small Computer System Interface-3 (SCSI-3)\_ - Part\_321: SCSI-3 Block Commands\_(SBC)

---

### CONTENTS

- FOREWORD ..... 8
- INTRODUCTION ..... 9
- 1 Scope .....10
- 2 Normative references .....12
  - 2.1 Normative reference overview .....12
  - 2.2 Approved references .....12
  - 2.3 References under development .....12
- 3 Definitions, symbols and abbreviations .....13
  - 3.1 Definitions .....13
    - 3.1.1 Definitions specific to direct access devices .....13
    - 3.1.2 Definitions specific to optical memory block devices and to write-once block devices .....15
  - 3.2 Symbols and abbreviations .....15
  - 3.3 Keywords .....16
  - 3.4 Conventions .....17
- 4 General .....17
- 5 SCSI block device models .....18
  - 5.1 Direct-access device type model .....18
    - 5.1.0 General .....18
    - 5.1.1 Removable medium .....18
    - 5.1.2 Logical blocks .....19
    - 5.1.3 Ready state .....19
    - 5.1.4 Power conditions .....19
    - 5.1.5 Initialization .....21
    - 5.1.6 Medium defects .....22
    - 5.1.7 Cache memory .....22
    - 5.1.8 Reservations .....23
    - 5.1.9 Seek(10) .....25
    - 5.1.10 Notched devices .....25
    - 5.1.11 Rotational position locking .....25
    - 5.1.12 Relative addressing .....25
    - 5.1.13 Error reporting .....25
    - 5.1.14 Examples .....26
    - 5.1.15 Model for XOR commands .....27
  - 5.2 Model for optical memory block devices .....36
    - 5.2.0 General .....36
    - 5.2.1 Defect management .....37
    - 5.2.2 Error reporting .....37
  - 5.3 Model for write-once block devices .....38
    - 5.3.0 General .....38
    - 5.3.1 Logical blocks .....38
    - 5.3.2 Initialization .....39
    - 5.3.3 Physical medium defects .....39
    - 5.3.4 Error reporting .....39
- 6 Commands for block devices .....40

6.1	Commands for direct-access block devices overview.....	40
6.1.1	Commands for direct-access block devices .....	40
6.1.2	FORMAT UNIT command.....	42
6.1.3	LOCK UNLOCK CACHE command.....	50
6.1.4	PRE-FETCH command.....	51
6.1.5	READ(6) command .....	52
6.1.6	READ(10) command .....	53
6.1.7	READ CAPACITY command.....	54
6.1.8	READ DEFECT DATA(10) command.....	55
6.1.9	READ LONG command.....	57
6.1.10	REASSIGN BLOCKS command.....	58
6.1.11	REBUILD command .....	60
6.1.12	REGENERATE command.....	62
6.1.13	SEEK(10) command.....	63
6.1.14	SET LIMITS(10) command.....	64
6.1.15	START STOP UNIT command.....	65
6.1.16	SYNCHRONIZE CACHE command.....	67
6.1.17	VERIFY command.....	68
6.1.18	WRITE(6) command.....	69
6.1.19	WRITE(10) command.....	70
6.1.20	WRITE AND VERIFY command.....	70
6.1.21	WRITE LONG command .....	71
6.1.22	WRITE SAME command .....	72
6.1.23	XDREAD command.....	73
6.1.24	XDWRITE command.....	74
6.1.25	XDWRITE EXTENDED command.....	75
6.1.26	XPWRITE command .....	76
6.2	Commands for optical memory block devices .....	77
6.2.0	General.....	77
6.2.1	ERASE(10) command .....	79
6.2.2	ERASE(12) command .....	80
6.2.3	MEDIUM SCAN command.....	81
6.2.4	READ(12) command .....	83
6.2.5	READ DEFECT DATA(12) command.....	84
6.2.6	READ GENERATION command .....	85
6.2.7	READ UPDATED BLOCK(10) command.....	86
6.2.8	SET LIMITS(12) command .....	87
6.2.9	UPDATE BLOCK command.....	88
6.2.10	VERIFY(10) command.....	89
6.2.11	VERIFY(12) command.....	90
6.2.12	WRITE(10) command.....	91
6.2.13	WRITE(12) command.....	91
6.2.14	WRITE AND VERIFY(10) command .....	92
6.2.15	WRITE AND VERIFY(12) command .....	93
6.3	Commands for write-once block devices.....	94
7	Parameters for block devices .....	96
7.1	Parameters for direct-access block devices.....	96
7.1.1	Diagnostic parameters .....	96
7.1.2	Log parameters.....	101

7.1.3	Mode parameters .....	103
7.1.4	Parameters for optical memory block devices .....	129
7.1.5	Parameters for write-once block devices .....	132
Annex A (informative)	XOR command examples .....	133
A.1	XOR annex overview .....	133
A.2	Storage array controller supervised XOR operations .....	133
A.2.1	Update write operation .....	133
A.2.2	Regenerate operation .....	134
A.2.3	Rebuild operation .....	135
A.3	Third-party XOR operations .....	136
A.3.1	Update write operation .....	136
A.3.2	Regenerate operation .....	137
A.3.3	Rebuild operation .....	138
A.4	Hybrid subsystem XOR operations .....	139
A.4.1	Regenerate operation .....	139
A.4.2	Rebuild operation .....	140
Bibliography	.....	142
Figure 1	– SCSI standards – General structure .....	11
Figure 2	– SCSI power conditions flow control (automatic switching) .....	20
Figure 3	– SCSI power conditions flow control (controlled switching) .....	21
Figure 4	– Power conditions flowchart .....	119
Figure A.1	– Rebuild operation .....	134
Figure A.2	– Regenerate operation .....	135
Figure A.3	– Rebuild operation .....	136
Figure A.4	– Update write operation .....	137
Figure A.5	– Regenerate operation .....	138
Figure A.6	– Rebuild operation .....	139
Figure A.7	– Regenerate operation .....	140
Figure A.8	– Rebuild operation .....	141

Table 1 – Sample error conditions .....	26
Table 2 – Sample error conditions .....	38
Table 3 – Sample error conditions .....	39
Table 4 – Commands for direct-access block devices .....	40
Table 5 – FORMAT UNIT command.....	42
Table 6 – FORMAT UNIT parameter list.....	43
Table 7 – DEFECT LIST HEADER.....	44
Table 8 – FORMAT UNIT defect descriptor format and requirements .....	45
Table 9 – DEFECT DESCRIPTOR – Block format.....	47
Table 10 – DEFECT DESCRIPTOR – Bytes from index format.....	47
Table 11 – DEFECT DESCRIPTOR – Physical sector format .....	48
Table 12 – Initialization pattern descriptor .....	48
Table 13 – Initialization pattern modifier.....	49
Table 14 – Initialization pattern type.....	49
Table 15 – LOCK UNLOCK CACHE command .....	50
Table 16 – PRE-FETCH command.....	51
Table 17 – READ(6) command .....	52
Table 18 – READ(10) command .....	53
Table 19 – READ CAPACITY command.....	54
Table 20 – READ CAPACITY data .....	55
Table 21 – READ DEFECT DATA(10) command .....	55
Table 22 – READ DEFECT DATA(10) defect list .....	56
Table 23 – READ LONG command .....	57
Table 24 – REASSIGN BLOCKS command.....	58
Table 25 – REASSIGN BLOCKS defect list .....	59
Table 26 – REBUILD command .....	60
Table 27 – PORT CONTROL field.....	61
Table 28 – REBUILD and REGENERATE parameter data .....	61
Table 29 – SOURCE DESCRIPTOR format .....	62
Table 30 – REGENERATE command.....	63
Table 31 – SEEK(10) command.....	64
Table 32 – SET LIMITS(10) command .....	64
Table 33 – START STOP UNIT command.....	65
Table 34 – POWER CONDITIONS .....	66
Table 35 – SYNCHRONIZE CACHE command.....	67
Table 36 – VERIFY command.....	68
Table 37 – WRITE(6) command.....	69
Table 38 – WRITE(10) command.....	70
Table 39 – WRITE AND VERIFY command.....	71
Table 40 – WRITE LONG command .....	72
Table 41 – WRITE SAME command .....	73
Table 42 – XDREAD command.....	74
Table 43 – XDWRITE command .....	74

Table 44 – XDWRITE EXTENDED command.....	75
Table 45 – XPWRITE command .....	77
Table 46 – Commands for optical memory block devices .....	78
Table 47 – ERASE(10) command .....	80
Table 48 – ERASE(12) command .....	81
Table 49 – MEDIUM SCAN command .....	81
Table 50 – MEDIUM SCAN parameter list.....	82
Table 51 – READ(12) command .....	84
Table 52 – READ DEFECT DATA(12) command .....	84
Table 53 – READ DEFECT DATA(12) list header .....	85
Table 54 – READ GENERATION command .....	85
Table 55 – Maximum generation data block .....	86
Table 56 – READ UPDATED BLOCK(10) command .....	86
Table 57 – SET LIMITS(12) command .....	87
Table 58 – UPDATE BLOCK command.....	88
Table 59 – VERIFY command.....	89
Table 60 – VERIFY(12) command.....	90
Table 61 – WRITE(10) command.....	91
Table 62 – WRITE(12) command.....	92
Table 63 – WRITE AND VERIFY(10) command .....	92
Table 64 – WRITE AND VERIFY(12) command .....	94
Table 65 – Commands for write-once block devices.....	95
Table 66 – Diagnostic page codes .....	97
Table 67 – Translate address page – SEND DIAGNOSTIC .....	97
Table 68 – Translate address page – RECEIVE DIAGNOSTIC .....	98
Table 69 – Device status page – SEND DIAGNOSTIC .....	99
Table 70 – Device status page – RECEIVE DIAGNOSTIC.....	100
Table 71 – SYNCHRONIZATION field .....	100
Table 72 – Log page codes.....	101
Table 73 – Format status log page.....	102
Table 74 – Direct-access medium-type codes .....	103
Table 75 – Device specific parameter .....	103
Table 76 – Mode page codes.....	104
Table 77 – Caching page.....	105
Table 78 – Demand read retention priority and write retention priority.....	106
Table 79 – Flexible disk page .....	109
Table 80 – Examples of transfer rates .....	110
Table 81 – PIN 34 field .....	111
Table 82 – PIN 4 field .....	112
Table 83 – PIN 1 field .....	112
Table 84 – Format device page.....	113
Table 85 – Reporting of default sector formatting support .....	115
Table 86 – Reporting of changeable sector formatting support .....	115

Table 87 – Medium types supported page .....	115
Table 88 – Notch page .....	116
Table 89 – Power condition page .....	118
Table 90 – Read-write error recovery page .....	119
Table 91 – Error recovery bit definitions .....	121
Table 92 – Combined error recovery parameter descriptions .....	122
Table 93 – Rigid disk device geometry page .....	125
Table 94 – Rotational position locking .....	126
Table 95 – Verify error recovery page .....	127
Table 96 – XOR control mode page .....	128
Table 97 – Diagnostic page codes .....	129
Table 98 – Log page codes .....	129
Table 99 – Optical memory medium-type codes .....	130
Table 100 – Optical memory block device specific parameter .....	130
Table 101 – Optical memory density codes .....	131
Table 102 – Mode page codes .....	131
Table 103 – Optical memory page .....	132