ISO/IEC 14776-331:2002-09 (E)

Information technology_- Small computer system interface (SCSI)_- Part_331: Stream commands (SSC)

CONTENTS

FOREWORD 6
INTRODUCTION 7
1 Scope 8
2 Normative references 9
3 Definitions, symbols and abbreviations 9
3.1 Definitions 9
3.2 Symbols and abbreviations 11
3.3 Keywords 11
3.4 Conventions 12
4 General 13
4.1 Overview 13
4.2 Physical models 13
5 Sequential-access devices 13
5.1 Definitions specific to sequential access devices 13
5.2 Sequential-access device model 16
5.2.1 Physical elements 16
5.2.2 Early warning 19
5.2.3 Partitions within a volume 19
5.2.4 Logical elements within a partition 21
5.2.5 Data buffering 22
5.2.6 Tagged command queuing 22
5.2.7 Recorded object descriptors (block identifiers) 23
5.2.8 Direction and position definitions 23
5.2.9 Write protection 25
5.2.10 Progress indication 27
5.2.11 TapeAlert application client interface 28
5.2.12 Device reservations and command behavior 31
5.3 Command descriptions for sequential-access devices 32
5.3.1 ERASE command 34
5.3.2 FORMAT MEDIUM command 34
5.3.3 LOAD UNLOAD command 36
5.3.4 LOCATE command 38
5.3.5 READ command 39
5.3.6 READ BLOCK LIMITS command 41
5.3.7 READ POSITION command 42
5.3.8 READ REVERSE command 45
5.3.9 RECOVER BUFFERED DATA command 46
5.3.10 REPORT DENSITY SUPPORT command 47
5.3.11 REWIND command 50
5.3.12 SPACE command 51
5.3.13 VERIFY command 54
5.3.14 WRITE command 55
5.3.15 WRITE FILEMARKS command 57

5.4 Parameters for sequential-access devices 58
5.4.1 Diagnostic parameters 58
5.4.2 Log parameters 58
5.4.3 Mode parameters 60
6 Printer devices 79
6.1 Model for printer devices 79
6.2 Commands for printer devices 80
6.2.1 FORMAT command 81
6.2.2 PRINT command 82
6.2.3 RECOVER BUFFERED DATA command 83
6.2.4 SLEW AND PRINT command 83
6.2.5 STOP PRINT command 84
6.2.6 SYNCHRONIZE BUFFER command 84
6.3 Parameters for printer devices 85
6.3.1 Diagnostic parameters 85
6.3.2 Log parameters 85
6.3.3 Mode parameters 86
Annex A (informative) Historical density codes 94
Annex B (normative) TapeAlert log page parameter codes (flags) 96
Bibliography 101

Figure 1 – SCSI standards - general structure 8
Figure 2 – Typical volume layout 17
Figure 3 – Typical medium track layout 17
Figure 4 – Serpentine recording example 18
Figure 5 – Parallel recording example 18
Figure 6 – Helical scan recording example 18
Figure 7 – Early-warning example 19
Figure 8 – Partitioning example – one partition per track group 20
Figure 9 – Partitioning example – one partition per two track groups 20
Figure 10 – Partitioning example – two partitions per track group 20
Figure 11 – SCSI printer model 80

Table 1 – Error conditions and sense keys 24
Table 2 – Write protect ASC/ASCQ combinations 26
Table 3 – Commands providing progress indication without changing ready state 27
Table 4 – Commands changing ready state and providing progress indication 28
Table 5 – TapeAlert default informational exceptions control page 29
Table 6 – TapeAlert flag types 30
Table 7 – TapeAlert flags minimum subset 30
Table 8 – TapeAlert flag definitions 31
Table 9 – Streaming commands that are allowed in the presence of various reservations 32
Table 10 – Commands for sequential-access devices 33
Table 11 – ERASE command 34
Table 12 – FORMAT MEDIUM command 35
Table 13 – Format field definition 36

Table 14 – LOAD UNLOAD command 37
Table 15 – LOCATE command 38
Table 16 – READ command 39
Table 17 – READ BLOCK LIMITS command 41
Table 18 – READ BLOCK LIMITS data 41
Table 19 – READ POSITION command 42
Table 20 – READ POSITION data format, short form 43
Table 21 – READ POSITION data format, long form 44
Table 22 – READ REVERSE command 45
Table 23 – RECOVER BUFFERED DATA command 46
Table 24 – REPORT DENSITY SUPPORT command 47
Table 25 – Density support header 48
Table 26 – Density support data block descriptor 48
Table 27 – REWIND command 51
Table 28 – SPACE command 51
Table 29 – Code definition 52
Table 30 – VERIFY command 54
Table 31 – WRITE command 55
Table 32 – WRITE FILEMARKS command 57
Table 33 – Diagnostic page codes 58
Table 34 – Log page codes 59
Table 35 – Parameter codes for sequential-access device page 60
Table 36 – TapeAlert log page 60
Table 37 – Device-specific parameter 61
Table 38 – Buffered modes 61
Table 39 – Speed field definition 61
Table 40 – Sequential-access density codes 62
Table 41 – Mode page codes 63
Table 42 – Data compression page 64
Table 43 – Possible boundaries and resulting sense keys due to data compression 65
Table 44 – Compression algorithm identifiers 67
Table 45 – Device configuration page 67
Table 46 – EOD defined values 69
Table 47 – Medium partition page(1) 71
Table 48 – PSUM values 72
Table 49 – Medium format recognition values 74
Table 50 – Medium partition page(2-4) 75
Table 51 – Read-write error recovery page 76
Table 52 – Informational exceptions control page 78
Table 53 – TapeAlert test descriptions 78
Table 54 – Commands for printer devices 81
Table 55 – FORMAT command 82
Table 56 – Format type values 82

Table 57 – PRINT command 82
Table 58 – RECOVER BUFFERED DATA command 83
Table 59 – SLEW AND PRINT command 83
Table 60 – STOP PRINT command 84
Table 61 – SYNCHRONIZE BUFFER command 85
Table 62 – Diagnostic page codes 85
Table 63 – Log page codes 86
Table 64 – Printer device-specific parameter 86
Table 65 – Mode page codes 87
Table 66 – Parallel printer interface 87
Table 67 – Parity select codes 88
Table 68 – VFU control byte 88
Table 69 – Printer options 89
Table 70 – Font identification values 89
Table 71 – Slew mode codes 90
Table 72 – Line slew codes 90
Table 73 – Form slew codes 91
Table 74 – Data termination option codes 91
Table 75 – Serial printer interface 92
Table 76 – Parity selection codes 92
Table 77 – Pacing protocol codes 93
Table A.1 – Historical sequential-access density codes 94
Table B.1 – TapeAlert log page parameter codes 96