

ISO/IEC 14776-150:2004-11 (E)

Information technology – Small computer system interface (SCSI) – Part 150: Serial Attached SCSI (SAS)

CONTENTS

| | |
|--|----|
| Foreword | 25 |
| Introduction | 26 |
| 1 Scope..... | 29 |
| 2 References..... | 29 |
| 2.1 Normative references | 29 |
| 2.2 References under development | 29 |
| 2.3 Bibliography..... | 29 |
| 3 Definitions, symbols, abbreviations, keywords, and conventions | 30 |
| 3.1 Definitions..... | 30 |
| 3.2 Symbols and abbreviations | 39 |
| 3.3 Keywords..... | 41 |
| 3.4 Editorial conventions | 42 |
| 3.5 Object and class diagram conventions..... | 43 |
| 3.6 State machine conventions | 46 |
| 3.6.1 State machine conventions overview..... | 46 |
| 3.6.2 Transitions | 46 |
| 3.6.3 Messages, requests, indications, confirmations, responses, and event notifications | 47 |
| 3.7 Bit and byte ordering | 47 |
| 3.8 Notation for procedures and functions..... | 48 |
| 4 General | 49 |
| 4.1 Architecture | 49 |
| 4.1.1 Architecture overview..... | 49 |
| 4.1.2 Physical links and phys..... | 50 |
| 4.1.3 Ports (narrow ports and wide ports)..... | 52 |
| 4.1.4 SAS devices..... | 54 |
| 4.1.5 Expander devices (edge expander devices and fanout expander devices)..... | 55 |
| 4.1.6 Service delivery subsystem | 57 |
| 4.1.7 Domains..... | 57 |
| 4.1.8 Expander device topologies..... | 59 |
| 4.1.8.1 Expander device topology overview..... | 59 |
| 4.1.8.2 Edge expander device set..... | 59 |
| 4.1.8.3 Expander device topologies | 60 |
| 4.1.9 Pathways | 63 |
| 4.1.10 Connections | 64 |
| 4.2 Names and identifiers..... | 66 |
| 4.2.1 Names and identifiers overview | 66 |
| 4.2.2 SAS addresses | 67 |
| 4.2.3 Hashed SAS address..... | 68 |
| 4.2.4 Device names | 68 |
| 4.2.5 Port names..... | 68 |
| 4.2.6 Port identifiers | 68 |
| 4.2.7 Phy identifiers | 69 |
| 4.3 State machines..... | 69 |
| 4.3.1 State machine overview..... | 69 |
| 4.3.2 Transmit data path | 71 |
| 4.3.3 State machines and SAS device, SAS port, and SAS phy objects..... | 76 |
| 4.4 Resets | 77 |
| 4.4.1 Reset overview | 77 |
| 4.4.2 Hard reset | 79 |
| 4.5 I_T nexus loss | 79 |
| 4.6 Expander device model..... | 79 |
| 4.6.1 Expander device model overview | 79 |
| 4.6.2 Expander ports..... | 80 |

| | |
|---|-----|
| 4.6.3 Expander connection manager (ECM)..... | 81 |
| 4.6.4 Expander connection router (ECR)..... | 81 |
| 4.6.5 Broadcast primitive processor (BPP)..... | 81 |
| 4.6.6 Expander device interfaces..... | 81 |
| 4.6.6.1 Expander device interface overview..... | 81 |
| 4.6.6.2 Expander device interfaces detail | 83 |
| 4.6.6.3 ECM interface..... | 83 |
| 4.6.6.4 ECR interface | 85 |
| 4.6.6.5 BPP interface | 86 |
| 4.6.7 Expander device routing | 86 |
| 4.6.7.1 Routing attributes and routing methods | 86 |
| 4.6.7.2 Connection request routing | 87 |
| 4.6.7.3 Expander route table..... | 87 |
| 4.6.7.4 Discover process..... | 88 |
| 4.6.7.5 Expander route index order..... | 90 |
| 5 Physical layer..... | 97 |
| 5.1 Physical layer overview | 97 |
| 5.2 Passive interconnect | 97 |
| 5.2.1 SATA cables and connectors..... | 97 |
| 5.2.2 SAS cables and connectors..... | 97 |
| 5.2.3 Connectors..... | 100 |
| 5.2.3.1 Connectors overview..... | 100 |
| 5.2.3.2 SAS plug connector..... | 100 |
| 5.2.3.3 SAS internal cable receptacle connector | 100 |
| 5.2.3.4 SAS backplane receptacle connector | 101 |
| 5.2.3.5 SAS internal connector pin assignments..... | 102 |
| 5.2.3.6 SAS external cable plug connector | 103 |
| 5.2.3.7 SAS external receptacle connector | 103 |
| 5.2.3.8 SAS external connector pin assignments..... | 104 |
| 5.2.4 Cables..... | 104 |
| 5.2.4.1 SAS internal cables | 104 |
| 5.2.4.2 SAS external cables..... | 107 |
| 5.2.5 Backplanes | 107 |
| 5.3 Transmitter and receiver electrical characteristics | 107 |
| 5.3.1 Compliance points | 107 |
| 5.3.2 General interface specification..... | 107 |
| 5.3.3 Eye masks | 109 |
| 5.3.3.1 Eye masks overview..... | 109 |
| 5.3.3.2 Receive eye mask at IR, CR, and XR | 110 |
| 5.3.3.3 Jitter tolerance masks | 110 |
| 5.3.4 Signal characteristics at IT, CT, and XT | 111 |
| 5.3.5 Signal characteristics at IR, CR, and XR | 113 |
| 5.3.6 Jitter | 115 |
| 5.3.7 Receiver jitter tolerance | 116 |
| 5.3.8 Compliant jitter test pattern (CJTPAT) | 116 |
| 5.3.9 Impedance specifications..... | 116 |
| 5.3.10 Electrical TxRx connections..... | 117 |
| 5.3.11 Transmitter characteristics..... | 118 |
| 5.3.12 Receiver characteristics..... | 120 |
| 5.3.13 Spread spectrum clocking..... | 121 |
| 5.3.14 Non-tracking clock architecture..... | 121 |
| 5.4 READY LED signal electrical characteristics..... | 121 |
| 6 Phy layer..... | 122 |
| 6.1 Phy layer overview | 122 |
| 6.2 Encoding (8b10b)..... | 122 |
| 6.2.1 Encoding overview..... | 122 |

| | |
|---|-----|
| 6.2.2 8b10b coding introduction..... | 122 |
| 6.2.3 8b10b coding notation conventions | 122 |
| 6.3 Character encoding and decoding..... | 123 |
| 6.3.1 Introduction | 123 |
| 6.3.2 Transmission order | 124 |
| 6.3.3 Valid and invalid transmission characters..... | 124 |
| 6.3.3.1 Definitions..... | 124 |
| 6.3.3.2 Generating transmission characters..... | 128 |
| 6.3.3.3 Validity of received transmission characters | 128 |
| 6.4 Bit order | 128 |
| 6.5 Out of band (OOB) signals | 130 |
| 6.6 Phy reset sequences | 134 |
| 6.6.1 Phy reset sequences overview | 134 |
| 6.6.2 SATA phy reset sequence | 135 |
| 6.6.2.1 SATA OOB sequence | 135 |
| 6.6.2.2 SATA speed negotiation sequence | 136 |
| 6.6.3 SAS to SATA phy reset sequence..... | 136 |
| 6.6.4 SAS to SAS phy reset sequence | 137 |
| 6.6.4.1 SAS OOB sequence..... | 137 |
| 6.6.4.2 SAS speed negotiation sequence | 139 |
| 6.6.5 Phy reset sequence after devices are attached..... | 141 |
| 6.7 SP (phy layer) state machine | 142 |
| 6.7.1 SP state machine overview..... | 142 |
| 6.7.2 SP transmitter and receiver | 143 |
| 6.7.3 OOB sequence states..... | 145 |
| 6.7.3.1 OOB sequence states overview | 145 |
| 6.7.3.2 SP0:OOB_COMINIT state..... | 146 |
| 6.7.3.2.1 State description | 146 |
| 6.7.3.2.2 Transition SP0:OOB_COMINIT to SP1:OOB_AwaitCOMX..... | 146 |
| 6.7.3.2.3 Transition SP0:OOB_COMINIT to SP3:OOB_AwaitCOMINIT_Sent..... | 146 |
| 6.7.3.2.4 Transition SP0:OOB_COMINIT to SP4:OOB_COMSAS..... | 146 |
| 6.7.3.3 SP1:OOB_AwaitCOMX state | 146 |
| 6.7.3.3.1 State description | 146 |
| 6.7.3.3.2 Transition SP1:OOB_AwaitCOMX to SP0:OOB_COMINIT..... | 146 |
| 6.7.3.3.3 Transition SP1:OOB_AwaitCOMX to SP4:OOB_COMSAS | 146 |
| 6.7.3.4 SP2:OOB_NoCOMSASTimeout state..... | 146 |
| 6.7.3.4.1 State description | 146 |
| 6.7.3.4.2 Transition SP2:OOB_NoCOMSASTimeout to SP0:OOB_COMINIT | 146 |
| 6.7.3.4.3 Transition SP2:OOB_NoCOMSASTimeout to SP4:OOB_COMSAS..... | 146 |
| 6.7.3.5 SP3:OOB_AwaitCOMINIT_Sent state | 147 |
| 6.7.3.5.1 State description | 147 |
| 6.7.3.5.2 Transition SP3:OOB_AwaitCOMINIT_Sent to SP4:OOB_COMSAS | 147 |
| 6.7.3.6 SP4:OOB_COMSAS state | 147 |
| 6.7.3.6.1 State description | 147 |
| 6.7.3.6.2 Transition SP4:OOB_COMSAS to SP5:OOB_AwaitCOMSAS_Sent..... | 147 |
| 6.7.3.6.3 Transition SP4:OOB_COMSAS to SP6:OOB_AwaitNoCOMSAS..... | 147 |
| 6.7.3.6.4 Transition SP4:OOB_COMSAS to SP7:OOB_AwaitCOMSAS | 147 |
| 6.7.3.7 SP5:OOB_AwaitCOMSAS_Sent state..... | 147 |
| 6.7.3.7.1 State description | 147 |
| 6.7.3.7.2 Transition SP5:OOB_AwaitCOMSAS_Sent to SP6:OOB_AwaitNoCOMSAS..... | 147 |
| 6.7.3.8 SP6:OOB_AwaitNoCOMSAS state..... | 147 |
| 6.7.3.8.1 State description | 147 |
| 6.7.3.8.2 Transition SP6:OOB_AwaitNoCOMSAS to SP8:SAS_Start..... | 147 |
| 6.7.3.9 SP7:OOB_AwaitCOMSAS state | 147 |
| 6.7.3.9.1 State description | 147 |
| 6.7.3.9.2 Transition SP7:OOB_AwaitCOMSAS to SP0:OOB_COMINIT..... | 148 |
| 6.7.3.9.3 Transition SP7:OOB_AwaitCOMSAS to SP6:OOB_AwaitNoCOMSAS..... | 148 |
| 6.7.3.9.4 Transition SP7:OOB_AwaitCOMSAS to SP16:SATA_COMWAKE..... | 148 |

| | |
|--|-----|
| 6.7.3.9.5 Transition SP7:OOB_AwaitCOMSAS to SP2:OOB_NoCOMSASTimeout..... | 148 |
| 6.7.4 SAS speed negotiation states..... | 148 |
| 6.7.4.1 SAS speed negotiation states overview..... | 148 |
| 6.7.4.2 SP8:SAS_Start state..... | 150 |
| 6.7.4.2.1 State description..... | 150 |
| 6.7.4.2.2 Transition SP8:SAS_Start to SP10:SAS_AwaitALIGN..... | 150 |
| 6.7.4.2.3 Transition SP8:SAS_Start to SP9:SAS_RateNotSupported..... | 150 |
| 6.7.4.3 SP9:SAS_RateNotSupported state..... | 150 |
| 6.7.4.3.1 State description..... | 150 |
| 6.7.4.3.2 Transition SP9:SAS_RateNotSupported to SP14:SAS_Fail..... | 150 |
| 6.7.4.4 SP10:SAS_AwaitALIGN state..... | 150 |
| 6.7.4.4.1 State description..... | 150 |
| 6.7.4.4.2 Transition SP10:SAS_AwaitALIGN to SP0:OOB_COMINIT..... | 150 |
| 6.7.4.4.3 Transition SP10:SAS_AwaitALIGN to SP11:SAS_AwaitALIGN1..... | 150 |
| 6.7.4.4.4 Transition SP10:SAS_AwaitALIGN to SP12:SAS_AwaitSNW..... | 151 |
| 6.7.4.4.5 Transition SP10:SAS_AwaitALIGN to SP14:SAS_Fail..... | 151 |
| 6.7.4.5 SP11:SAS_AwaitALIGN1 state..... | 151 |
| 6.7.4.5.1 State description..... | 151 |
| 6.7.4.5.2 Transition SP11:SAS_AwaitALIGN1 to SP0:OOB_COMINIT..... | 151 |
| 6.7.4.5.3 Transition SP11:SAS_AwaitALIGN1 to SP14:SAS_Fail..... | 151 |
| 6.7.4.5.4 Transition SP11:SAS_AwaitALIGN1 to SP12:SAS_AwaitSNW..... | 151 |
| 6.7.4.6 SP12:SAS_AwaitSNW state..... | 151 |
| 6.7.4.6.1 State description..... | 151 |
| 6.7.4.6.2 Transition SP12:SAS_AwaitSNW to SP0:OOB_COMINIT..... | 151 |
| 6.7.4.6.3 Transition SP12:SAS_AwaitSNW to SP13:SAS_Pass..... | 151 |
| 6.7.4.7 SP13:SAS_Pass state..... | 151 |
| 6.7.4.7.1 State description..... | 151 |
| 6.7.4.7.2 Transition SP13:SAS_Pass to SP0:OOB_COMINIT..... | 152 |
| 6.7.4.7.3 Transition SP13:SAS_Pass to SP8:SAS_Start..... | 152 |
| 6.7.4.7.4 Transition SP13:SAS_Pass to SP15:SAS_PHY_Ready..... | 152 |
| 6.7.4.8 SP14:SAS_Fail state..... | 152 |
| 6.7.4.8.1 State description..... | 152 |
| 6.7.4.8.2 Transition SP14:SAS_Fail to SP1:OOB_AwaitCOMX..... | 152 |
| 6.7.4.8.3 Transition SP14:SAS_Fail to SP8:SAS_Start..... | 152 |
| 6.7.4.9 SP15:SAS_PHY_Ready state..... | 153 |
| 6.7.4.9.1 State description..... | 153 |
| 6.7.4.9.2 Transition SP15:SAS_PHY_Ready to SP0:OOB_COMINIT..... | 153 |
| 6.7.5 SATA host emulation states..... | 153 |
| 6.7.5.1 SATA host emulation states overview..... | 153 |
| 6.7.5.2 SP16:SATA_COMWAKE state..... | 154 |
| 6.7.5.2.1 State description..... | 154 |
| 6.7.5.2.2 Transition SP16:SATA_COMWAKE to SP17:SATA_AwaitCOMWAKE..... | 155 |
| 6.7.5.3 SP17:SATA_AwaitCOMWAKE state..... | 155 |
| 6.7.5.3.1 State description..... | 155 |
| 6.7.5.3.2 Transition SP17:SATA_AwaitCOMWAKE to SP18:SATA_AwaitNoCOMWAKE..... | 155 |
| 6.7.5.4 SP18:SATA_AwaitNoCOMWAKE state..... | 155 |
| 6.7.5.4.1 State description..... | 155 |
| 6.7.5.4.2 Transition SP18:SATA_AwaitNoCOMWAKE to SP19:SATA_AwaitALIGN..... | 155 |
| 6.7.5.5 SP19:SATA_AwaitALIGN state..... | 155 |
| 6.7.5.5.1 State description..... | 155 |
| 6.7.5.5.2 Transition SP19:SATA_AwaitALIGN to SP20:SATA_AdjustSpeed..... | 155 |
| 6.7.5.5.3 Transition SP19:SATA_AwaitALIGN to SP0:OOB_COMINIT..... | 155 |
| 6.7.5.6 SP20:SATA_AdjustSpeed state..... | 155 |
| 6.7.5.6.1 State description..... | 155 |
| 6.7.5.6.2 Transition SP20:SATA_AdjustSpeed to SP0:OOB_COMINIT..... | 155 |
| 6.7.5.6.3 Transition SP20:SATA_AdjustSpeed to SP21:SATA_TransmitALIGN..... | 156 |
| 6.7.5.7 SP21:SATA_TransmitALIGN state..... | 156 |
| 6.7.5.7.1 State description..... | 156 |

| | | |
|------------|---|-----|
| 6.7.5.7.2 | Transition SP21:SATA_TransmitALIGN to SP0:OOB_COMINIT | 156 |
| 6.7.5.7.3 | Transition SP21:SATA_TransmitALIGN to SP22:SATA_PHY_Ready | 156 |
| 6.7.5.8 | SP22:SATA_PHY_Ready state | 156 |
| 6.7.5.8.1 | State description | 156 |
| 6.7.5.8.2 | Transition SP22:SATA_PHY_Ready to SP1:OOB_COMINIT | 156 |
| 6.7.5.8.3 | Transition SP22:SATA_PHY_Ready to SP23:SATA_PM_Partial | 156 |
| 6.7.5.8.4 | Transition SP22:SATA_PHY_Ready to SP24:SATA_PM_Slumber | 156 |
| 6.7.5.9 | SP23:SATA_PM_Partial state | 156 |
| 6.7.5.9.1 | State description | 156 |
| 6.7.5.9.2 | Transition SP23:SATA_PM_Partial to SP16:SATA_COMWAKE | 156 |
| 6.7.5.9.3 | Transition SP23:SATA_PM_Partial to SP18:SATA_AwaitNoCOMWAKE | 156 |
| 6.7.5.10 | SP24:SATA_PM_Slumber state | 157 |
| 6.7.5.10.1 | State description | 157 |
| 6.7.5.10.2 | Transition SP24:SATA_PM_Slumber to SP16:SATA_COMWAKE | 157 |
| 6.7.5.10.3 | Transition SP24:SATA_PM_Slumber to SP18:SATA_AwaitNoCOMWAKE | 157 |
| 6.8 | SP_DWS (phy layer dword synchronization) state machine | 157 |
| 6.8.1 | SP_DWS state machine overview | 157 |
| 6.8.2 | SP_DWS receiver | 159 |
| 6.8.3 | SP_DWS0:AcquireSync state | 159 |
| 6.8.3.1 | State description | 159 |
| 6.8.3.2 | Transition SP_DWS0:AcquireSync to SP_DWS1:Valid1 | 159 |
| 6.8.4 | SP_DWS1:Valid1 state | 159 |
| 6.8.4.1 | State description | 159 |
| 6.8.4.2 | Transition SP_DWS1:Valid1 to SP_DWS0:AcquireSync | 159 |
| 6.8.4.3 | Transition SP_DWS1:Valid1 to SP_DWS2:Valid2 | 160 |
| 6.8.5 | SP_DWS2:Valid2 state | 160 |
| 6.8.5.1 | State description | 160 |
| 6.8.5.2 | Transition SP_DWS2:Valid2 to SP_DWS0:AcquireSync | 160 |
| 6.8.5.3 | Transition SP_DWS2:Valid2 to SP_DWS3:SyncAcquired | 160 |
| 6.8.6 | SP_DWS3:SyncAcquired state | 160 |
| 6.8.6.1 | State description | 160 |
| 6.8.6.2 | Transition SP_DWS3:SyncAcquired to SP_DWS4:Lost1 | 160 |
| 6.8.7 | SP_DWS4:Lost1 state | 160 |
| 6.8.7.1 | State description | 160 |
| 6.8.7.2 | Transition SP_DWS4:Lost1 to SP_DWS5:Lost1Recovered | 160 |
| 6.8.7.3 | Transition SP_DWS4:Lost1 to SP_DWS6:Lost2 | 160 |
| 6.8.8 | SP_DWS5:Lost1Recovered state | 160 |
| 6.8.8.1 | State description | 160 |
| 6.8.8.2 | Transition SP_DWS5:Lost1Recovered to SP_DWS3:SyncAcquired | 161 |
| 6.8.8.3 | Transition SP_DWS5:Lost1Recovered to SP_DWS6:Lost2 | 161 |
| 6.8.9 | SP_DWS6:Lost2 state | 161 |
| 6.8.9.1 | State description | 161 |
| 6.8.9.2 | Transition SP_DWS6:Lost2 to SP_DWS7:Lost2Recovered | 161 |
| 6.8.9.3 | Transition SP_DWS6:Lost2 to SP_DWS8:Lost3 | 161 |
| 6.8.10 | SP_DWS7:Lost2Recovered state | 161 |
| 6.8.10.1 | State description | 161 |
| 6.8.10.2 | Transition SP_DWS7:Lost2Recovered to SP_DWS4:Lost1 | 161 |
| 6.8.10.3 | Transition SP_DWS7:Lost2Recovered to SP_DWS8:Lost3 | 161 |
| 6.8.11 | SP_DWS8:Lost3 state | 161 |
| 6.8.11.1 | State description | 161 |
| 6.8.11.2 | Transition SP_DWS8:Lost3 to SP_DWS9:Lost3Recovered | 161 |
| 6.8.11.3 | Transition SP_DWS8:Lost3 to SP_DWS0:AcquireSync | 161 |
| 6.8.12 | SP_DWS9:Lost3Recovered state | 162 |
| 6.8.12.1 | State description | 162 |
| 6.8.12.2 | Transition SP_DWS9:Lost3Recovered to SP_DWS6:Lost2 | 162 |
| 6.8.12.3 | Transition SP_DWS9:Lost3Recovered to SP_DWS0:AcquireSync | 162 |
| 6.9 | Spin-up | 162 |

| | |
|--|-----|
| 7 Link layer..... | 163 |
| 7.1 Link layer overview | 163 |
| 7.2 Primitives | 163 |
| 7.2.1 Primitives overview | 163 |
| 7.2.2 Primitive summary | 164 |
| 7.2.3 Primitive encodings..... | 168 |
| 7.2.4 Primitive sequences..... | 172 |
| 7.2.4.1 Primitive sequences overview | 172 |
| 7.2.4.2 Single primitive sequence | 172 |
| 7.2.4.3 Repeated primitive sequence..... | 172 |
| 7.2.4.4 Triple primitive sequence | 172 |
| 7.2.4.5 Redundant primitive sequence..... | 173 |
| 7.2.5 Primitives not specific to type of connections | 174 |
| 7.2.5.1 AIP (Arbitration in progress)..... | 174 |
| 7.2.5.2 ALIGN..... | 175 |
| 7.2.5.3 BREAK | 176 |
| 7.2.5.4 BROADCAST | 176 |
| 7.2.5.5 CLOSE | 176 |
| 7.2.5.6 EOAF (End of address frame)..... | 177 |
| 7.2.5.7 ERROR | 177 |
| 7.2.5.8 HARD_RESET | 177 |
| 7.2.5.9 NOTIFY | 177 |
| 7.2.5.10 OPEN_ACCEPT..... | 178 |
| 7.2.5.11 OPEN_REJECT | 178 |
| 7.2.5.12 SOAF (Start of address frame)..... | 181 |
| 7.2.6 Primitives used only inside SSP and SMP connections | 181 |
| 7.2.6.1 ACK (Acknowledge) | 181 |
| 7.2.6.2 CREDIT_BLOCKED | 181 |
| 7.2.6.3 DONE | 181 |
| 7.2.6.4 EOF (End of frame) | 182 |
| 7.2.6.5 NAK (Negative acknowledgement) | 182 |
| 7.2.6.6 RRDY (Receiver ready)..... | 182 |
| 7.2.6.7 SOF (Start of frame)..... | 182 |
| 7.2.7 Primitives used only inside STP connections and on SATA physical links..... | 182 |
| 7.2.7.1 SATA_ERROR | 182 |
| 7.2.7.2 SATA_PMACK, SATA_PMNAK, SATA_PMREQ_P, and SATA_PMREQ_S (Power management acknowledgements and requests) | 182 |
| 7.2.7.3 SATA_HOLD and SATA_HOLDA (Hold and hold acknowledge)..... | 183 |
| 7.2.7.4 SATA_R_RDY and SATA_X_RDY (Receiver ready and transmitter ready)..... | 183 |
| 7.2.7.5 Other primitives used inside STP connections and on SATA physical links | 183 |
| 7.3 Clock skew management | 183 |
| 7.4 Idle physical links..... | 184 |
| 7.5 CRC..... | 185 |
| 7.5.1 CRC overview | 185 |
| 7.5.2 CRC generation | 185 |
| 7.5.3 CRC checking | 187 |
| 7.6 Scrambling..... | 187 |
| 7.7 Bit order of CRC and scrambler | 189 |
| 7.8 Address frames | 192 |
| 7.8.1 Address frames overview..... | 192 |
| 7.8.2 IDENTIFY address frame..... | 194 |
| 7.8.3 OPEN address frame..... | 196 |
| 7.9 Identification and hard reset sequence..... | 198 |
| 7.9.1 Identification and hard reset sequence overview | 198 |
| 7.9.2 SAS initiator device rules | 199 |
| 7.9.3 Fanout expander device rules..... | 199 |
| 7.9.4 Edge expander device rules | 199 |
| 7.9.5 SL_IR (link layer identification and hard reset) state machines | 199 |

| | |
|--|-----|
| 7.9.5.1 SL_IR state machines overview | 199 |
| 7.9.5.2 SL_IR transmitter and receiver..... | 202 |
| 7.9.5.3 SL_IR_TIR (transmit IDENTIFY or HARD_RESET) state machine | 202 |
| 7.9.5.3.1 SL_IR_TIR state machine overview | 202 |
| 7.9.5.3.2 SL_IR_TIR1:Idle state | 202 |
| 7.9.5.3.2.1 State description | 202 |
| 7.9.5.3.2.2 Transition SL_IR_TIR1:Idle to SL_IR_TIR2:Transmit_Identify | 202 |
| 7.9.5.3.2.3 Transition SL_IR_TIR1:Idle to SL_IR_TIR3:Transmit_Hard_Reset..... | 202 |
| 7.9.5.3.3 SL_IR_TIR2:Transmit_Identify state..... | 202 |
| 7.9.5.3.3.1 State description | 202 |
| 7.9.5.3.3.2 Transition SL_IR_TIR2:Transmit_Identify to SL_IR_TIR4:Completed | 203 |
| 7.9.5.3.4 SL_IR_TIR3:Transmit_Hard_Reset state | 203 |
| 7.9.5.3.4.1 State description | 203 |
| 7.9.5.3.4.2 Transition SL_IR_TIR3:Transmit_Hard_Reset to SL_IR_TIR4:Completed | 203 |
| 7.9.5.3.5 SL_IR_TIR4:Completed state..... | 203 |
| 7.9.5.4 SL_IR_RIF (receive IDENTIFY address frame) state machine..... | 203 |
| 7.9.5.4.1 SL_IR_RIF state machine overview | 203 |
| 7.9.5.4.2 SL_IR_RIF1:Idle state | 203 |
| 7.9.5.4.2.1 State description | 203 |
| 7.9.5.4.2.2 Transition SL_IR_RIF1:Idle to SL_IR_RIF2:Receive_Identify_Frame | 203 |
| 7.9.5.4.3 SL_IR_RIF2:Receive_Identify_Frame state | 203 |
| 7.9.5.4.3.1 State description | 203 |
| 7.9.5.4.3.2 Transition SL_IR_RIF2:Receive_Identify_Frame to SL_IR_RIF3:Completed | 204 |
| 7.9.5.4.4 SL_IR_RIF3:Completed state..... | 204 |
| 7.9.5.5 SL_IR_IRC (identification and hard reset control) state machine | 204 |
| 7.9.5.5.1 SL_IR_IRC state machine overview | 204 |
| 7.9.5.5.2 SL_IR_IRC1:Idle state | 204 |
| 7.9.5.5.2.1 State description | 204 |
| 7.9.5.5.2.2 Transition SL_IR_IRC1:Idle to SL_IR_IRC2:Wait | 204 |
| 7.9.5.5.3 SL_IR_IRC2:Wait state..... | 205 |
| 7.9.5.5.3.1 State description | 205 |
| 7.9.5.5.3.2 Transition SL_IR_IRC2:Wait to SL_IR_IRC3:Completed | 205 |
| 7.9.5.5.4 SL_IR_IRC3:Completed state | 205 |
| 7.10 Power management | 205 |
| 7.11 SAS domain changes | 206 |
| 7.12 Connections..... | 206 |
| 7.12.1 Connections overview..... | 206 |
| 7.12.2 Opening a connection..... | 206 |
| 7.12.2.1 Connection request | 206 |
| 7.12.2.2 Connection responses..... | 207 |
| 7.12.3 Arbitration fairness..... | 207 |
| 7.12.4 Arbitration and resource management in an expander device | 208 |
| 7.12.4.1 Arbitration overview..... | 208 |
| 7.12.4.2 Arbitration status | 209 |
| 7.12.4.3 Partial Pathway Timeout timer | 209 |
| 7.12.4.4 Pathway recovery..... | 210 |
| 7.12.5 Expander devices and connection requests | 210 |
| 7.12.5.1 All expander devices | 210 |
| 7.12.5.2 Edge expander devices..... | 210 |
| 7.12.5.3 Fanout expander devices..... | 210 |
| 7.12.6 Aborting a connection request | 211 |
| 7.12.7 Closing a connection..... | 213 |
| 7.12.8 Breaking a connection | 214 |
| 7.13 Rate matching | 214 |
| 7.14 SL (link layer for SAS phys) state machines | 216 |
| 7.14.1 SL state machines overview | 216 |
| 7.14.2 SL transmitter and receiver..... | 218 |
| 7.14.3 SL_RA (receive OPEN address frame) state machine..... | 219 |

| | |
|---|-----|
| 7.14.4 SL_CC (connection control) state machine | 220 |
| 7.14.4.1 SL_CC state machine overview | 220 |
| 7.14.4.2 SL_CC0:Idle state | 220 |
| 7.14.4.2.1 State description | 220 |
| 7.14.4.2.2 Transition SL_CC0:Idle to SL_CC1:ArbSel | 221 |
| 7.14.4.2.3 Transition SL_CC0:Idle to SL_CC2:Selected | 221 |
| 7.14.4.3 SL_CC1:ArbSel state | 221 |
| 7.14.4.3.1 State description | 221 |
| 7.14.4.3.2 Transition SL_CC1:ArbSel to SL_CC0:Idle | 222 |
| 7.14.4.3.3 Transition SL_CC1:ArbSel to SL_CC2:Selected | 222 |
| 7.14.4.3.4 Transition SL_CC1:ArbSel to SL_CC3:Connected | 222 |
| 7.14.4.3.5 Transition SL_CC1:ArbSel to SL_CC5:BreakWait | 222 |
| 7.14.4.3.6 Transition SL_CC1:ArbSel to SL_CC6:Break | 222 |
| 7.14.4.4 SL_CC2:Selected state | 223 |
| 7.14.4.4.1 State description | 223 |
| 7.14.4.4.2 Transition SL_CC2:Selected to SL_CC0:Idle | 223 |
| 7.14.4.4.3 Transition SL_CC2:Selected to SL_CC3:Connected | 223 |
| 7.14.4.4.4 Transition SL_CC2:Selected to SL_CC6:Break | 223 |
| 7.14.4.5 SL_CC3:Connected state | 223 |
| 7.14.4.5.1 State description | 223 |
| 7.14.4.5.2 Transition SL_CC3:Connected to SL_CC4:DisconnectWait | 224 |
| 7.14.4.5.3 Transition SL_CC3:Connected to SL_CC5:BreakWait | 224 |
| 7.14.4.5.4 Transition SL_CC3:Connected to SL_CC6:Break | 224 |
| 7.14.4.5.5 Transition SL_CC3:Connected to SL_CC7:CloseSTP | 224 |
| 7.14.4.6 SL_CC4:DisconnectWait state | 224 |
| 7.14.4.6.1 State description | 224 |
| 7.14.4.6.2 Transition SL_CC4:DisconnectWait to SL_CC0:Idle | 224 |
| 7.14.4.6.3 Transition SL_CC4:DisconnectWait to SL_CC5:BreakWait | 225 |
| 7.14.4.6.4 Transition SL_CC4:DisconnectWait to SL_CC6:Break | 225 |
| 7.14.4.7 SL_CC5:BreakWait state | 225 |
| 7.14.4.7.1 State description | 225 |
| 7.14.4.7.2 Transition SL_CC5:BreakWait to SL_CC0:Idle | 225 |
| 7.14.4.8 SL_CC6:Break state | 225 |
| 7.14.4.8.1 State description | 225 |
| 7.14.4.8.2 Transition SL_CC6:Break to SL_CC0:Idle | 225 |
| 7.14.4.9 SL_CC7:CloseSTP state | 225 |
| 7.14.4.9.1 State description | 225 |
| 7.14.4.9.2 Transition SL_CC7:CloseSTP to SL_CC0:Idle | 225 |
| 7.15 XL (link layer for expander phys) state machine | 226 |
| 7.15.1 XL state machine overview | 226 |
| 7.15.2 XL transmitter and receiver | 230 |
| 7.15.3 XL0:Idle state | 230 |
| 7.15.3.1 State description | 230 |
| 7.15.3.2 Transition XL0:Idle to XL1:Request_Path | 230 |
| 7.15.3.3 Transition XL0:Idle to XL5:Forward_Open | 231 |
| 7.15.4 XL1:Request_Path state | 231 |
| 7.15.4.1 State description | 231 |
| 7.15.4.2 Transition XL1:Request_Path to XL2:Request_Open | 231 |
| 7.15.4.3 Transition XL1:Request_Path to XL4:Open_Reject | 231 |
| 7.15.4.4 Transition XL1:Request_Path to XL0:Idle | 232 |
| 7.15.4.5 Transition XL1:Request_Path to XL9:Break | 232 |
| 7.15.5 XL2:Request_Open state | 232 |
| 7.15.5.1 State description | 232 |
| 7.15.5.2 Transition XL2:Request_Open to XL3:Open_Confirm_Wait | 232 |
| 7.15.6 XL3:Open_Confirm_Wait state | 232 |
| 7.15.6.1 State description | 232 |
| 7.15.6.2 Transition XL3:Open_Confirm_Wait to XL0:Idle | 233 |
| 7.15.6.3 Transition XL3:Open_Confirm_Wait to XL1:Request_Path | 233 |

| | | |
|--------------|--|-----|
| 7.15.6.4 | Transition XL3:Open_Confirm_Wait to XL5:Forward_Open | 233 |
| 7.15.6.5 | Transition XL3:Open_Confirm_Wait to XL7:Connected..... | 233 |
| 7.15.6.6 | Transition XL3:Open_Confirm_Wait to XL9:Break..... | 233 |
| 7.15.6.7 | Transition XL3:Open_Confirm_Wait to XL10:Break_Wait..... | 233 |
| 7.15.7 | XL4:Open_Reject state..... | 233 |
| 7.15.7.1 | State description..... | 233 |
| 7.15.7.2 | Transition XL4:Open_Reject to XL0:Idle | 233 |
| 7.15.8 | XL5:Forward_Open state..... | 233 |
| 7.15.8.1 | State description..... | 233 |
| 7.15.8.2 | Transition XL5:Forward_Open to XL6:Open_Response_Wait..... | 233 |
| 7.15.9 | XL6:Open_Response_Wait state..... | 234 |
| 7.15.9.1 | State description..... | 234 |
| 7.15.9.2 | Transition XL6:Open_Response_Wait to XL0:Idle..... | 235 |
| 7.15.9.3 | Transition XL6:Open_Response_Wait to XL1:Request_Path..... | 235 |
| 7.15.9.4 | Transition XL6:Open_Response_Wait to XL2:Request_Open | 235 |
| 7.15.9.5 | Transition XL6:Open_Response_Wait to XL7:Connected | 235 |
| 7.15.9.6 | Transition XL6:Open_Response_Wait to XL9:Break | 235 |
| 7.15.9.7 | Transition XL6:Open_Response_Wait to XL10:Break_Wait..... | 235 |
| 7.15.10 | XL7:Connected state | 235 |
| 7.15.10.1 | State description..... | 235 |
| 7.15.10.2 | Transition XL7:Connected to XL8:Close_Wait..... | 235 |
| 7.15.10.3 | Transition XL7:Connected to XL9:Break | 235 |
| 7.15.10.4 | Transition XL7:Connected to XL10:Break_Wait..... | 235 |
| 7.15.11 | XL8:Close_Wait state | 236 |
| 7.15.11.1 | State description..... | 236 |
| 7.15.11.2 | Transition XL8:Close_Wait to XL0:Idle..... | 236 |
| 7.15.11.3 | Transition XL8:Close_Wait to XL9:Break | 236 |
| 7.15.11.4 | Transition XL8:Close_Wait to XL10:Break_Wait..... | 236 |
| 7.15.12 | XL9:Break state | 236 |
| 7.15.12.1 | State description..... | 236 |
| 7.15.12.2 | Transition XL9:Break to XL0:Idle..... | 236 |
| 7.15.13 | XL10:Break_Wait state | 236 |
| 7.15.13.1 | State description..... | 236 |
| 7.15.13.2 | Transition XL10:Break_Wait to XL0:Idle | 236 |
| 7.16 | SSP link layer | 237 |
| 7.16.1 | Opening an SSP connection..... | 237 |
| 7.16.2 | Full duplex..... | 237 |
| 7.16.3 | SSP frame transmission and reception..... | 237 |
| 7.16.4 | SSP flow control..... | 237 |
| 7.16.5 | Interlocked frames | 238 |
| 7.16.6 | Closing an SSP connection | 239 |
| 7.16.7 | SSP (link layer for SSP phys) state machines | 240 |
| 7.16.7.1 | SSP state machines overview..... | 240 |
| 7.16.7.2 | SSP transmitter and receiver | 243 |
| 7.16.7.3 | SSP_TIM (transmit interlocked frame monitor) state machine..... | 244 |
| 7.16.7.4 | SSP_TCM (transmit frame credit monitor) state machine..... | 245 |
| 7.16.7.5 | SSP_D (DONE control) state machine..... | 245 |
| 7.16.7.6 | SSP_TF (transmit frame control) state machine | 246 |
| 7.16.7.6.1 | SSP_TF state machine overview..... | 246 |
| 7.16.7.6.2 | SSP_TF1:Connected_Idle state | 246 |
| 7.16.7.6.2.1 | State description | 246 |
| 7.16.7.6.2.2 | Transition SSP_TF1:Connected_Idle to SSP_TF2:Tx_Wait..... | 246 |
| 7.16.7.6.2.3 | Transition SSP_TF1:Connected_Idle to SSP_TF4:Indicate_DONE_Tx..... | 246 |
| 7.16.7.6.3 | SSP_TF2:Tx_Wait state | 247 |
| 7.16.7.6.3.1 | State description | 247 |
| 7.16.7.6.3.2 | Transition SSP_TF2:Tx_Wait to SSP_TF3:Indicate_Frame_Tx..... | 247 |
| 7.16.7.6.3.3 | Transition SSP_TF2:Tx_Wait to SSP_TF4:Indicate_DONE_Tx..... | 247 |
| 7.16.7.6.4 | SSP_TF3:Indicate_Frame_Tx state | 247 |

| | |
|---|-----|
| 7.16.7.6.4.1 State description | 247 |
| 7.16.7.6.4.2 Transition SSP_TF3:Indicate_Frame_Tx to SSP_TF1:Connected_Idle | 247 |
| 7.16.7.6.5 SSP_TF4:Indicate_DONE_Tx state | 248 |
| 7.16.7.7 SSP_RF (receive frame control) state machine | 248 |
| 7.16.7.8 SSP_RCM (receive frame credit monitor) state machine | 249 |
| 7.16.7.9 SSP_RIM (receive interlocked frame monitor) state machine | 249 |
| 7.16.7.10 SSP_TC (transmit credit control) state machine | 250 |
| 7.16.7.11 SSP_TAN (transmit ACK/NAK control) state machine | 250 |
| 7.17 STP link layer | 250 |
| 7.17.1 STP frame transmission and reception | 250 |
| 7.17.2 STP flow control | 250 |
| 7.17.3 Affiliations | 253 |
| 7.17.4 Opening an STP connection | 253 |
| 7.17.5 Closing an STP connection | 253 |
| 7.17.6 STP connection management examples | 254 |
| 7.17.7 STP (link layer for STP phys) state machines | 257 |
| 7.17.8 SMP target port support | 257 |
| 7.18 SMP link layer | 257 |
| 7.18.1 SMP frame transmission and reception | 257 |
| 7.18.2 SMP flow control | 257 |
| 7.18.3 Closing an SMP connection | 257 |
| 7.18.4 SMP (link layer for SMP phys) state machines | 257 |
| 7.18.4.1 SMP state machines overview | 257 |
| 7.18.4.2 SMP transmitter and receiver | 258 |
| 7.18.4.3 SMP_IP (link layer for SMP initiator phys) state machine | 258 |
| 7.18.4.3.1 SMP_IP state machine overview | 258 |
| 7.18.4.3.2 SMP_IP1:Idle state | 259 |
| 7.18.4.3.2.1 State description | 259 |
| 7.18.4.3.2.2 Transition SMP_IP1:Idle to SMP_IP2:Transmit_Frame | 259 |
| 7.18.4.3.3 SMP_IP2:Transmit_Frame state | 260 |
| 7.18.4.3.3.1 State description | 260 |
| 7.18.4.3.3.2 Transition SMP_IP2:Transmit_Frame to SMP_IP3:Receive_Frame | 260 |
| 7.18.4.3.4 SMP_IP3:Receive_Frame state | 260 |
| 7.18.4.4 SMP_TP (link layer for SMP target ports) state machine | 260 |
| 7.18.4.4.1 SMP_TP state machine overview | 260 |
| 7.18.4.4.2 SMP_TP1:Receive_Frame state | 261 |
| 7.18.4.4.2.1 State description | 261 |
| 7.18.4.4.2.2 Transition SMP_TP1:Receive_Frame to SMP_TP2:Transmit_Frame | 261 |
| 7.18.4.4.3 SMP_TP2:Transmit_Frame state | 262 |
| 8 Port layer | 263 |
| 8.1 Port layer overview | 263 |
| 8.2 PL (port layer) state machines | 263 |
| 8.2.1 PL state machines overview | 263 |
| 8.2.2 PL_OC (port layer overall control) state machine | 265 |
| 8.2.2.1 PL_OC state machine overview | 265 |
| 8.2.2.2 PL_OC1:Idle state | 266 |
| 8.2.2.2.1 PL_OC1:Idle state description | 266 |
| 8.2.2.2.2 Transition PL_OC1:Idle to PL_OC2:Overall_Control | 267 |
| 8.2.2.3 PL_OC2:Overall_Control state | 267 |
| 8.2.2.3.1 PL_OC2:Overall_Control state overview | 267 |
| 8.2.2.3.2 PL_OC2:Overall_Control state establishing connections | 267 |
| 8.2.2.3.3 PL_OC2:Overall_Control state connection established | 270 |
| 8.2.2.3.4 PL_OC2:Overall_Control state unable to establish a connection | 270 |
| 8.2.2.3.5 PL_OC2:Overall_Control state connection management | 271 |
| 8.2.2.3.6 PL_OC2:Overall_Control state frame transmission | 272 |
| 8.2.2.3.7 PL_OC2:Overall_Control state frame transmission cancellations | 273 |
| 8.2.2.3.8 Transition PL_OC2:Overall_Control to PL_OC1:Idle | 273 |

| | |
|---|-----|
| 8.2.3 PL_PM (port layer phy manager) state machine | 273 |
| 8.2.3.1 PL_PM state machine overview | 273 |
| 8.2.3.2 PL_PM1:Idle state | 276 |
| 8.2.3.2.1 PL_PM1:Idle state description | 276 |
| 8.2.3.2.2 Transition PL_PM1:Idle to PL_PM2:Req_Wait | 277 |
| 8.2.3.2.3 Transition PL_PM1:Idle to PL_PM3:Connected | 277 |
| 8.2.3.3 PL_PM2:Req_Wait state | 277 |
| 8.2.3.3.1 PL_PM2:Req_Wait state overview | 277 |
| 8.2.3.3.2 PL_PM2:Req_Wait establishing a connection | 277 |
| 8.2.3.3.3 PL_PM2:Req_Wait connection established | 277 |
| 8.2.3.3.4 PL_PM2:Req_Wait unable to establish a connection | 278 |
| 8.2.3.3.5 PL_PM2:Req_Wait connection management | 278 |
| 8.2.3.3.6 Transition PL_PM2:Req_Wait to PL_PM1:Idle | 278 |
| 8.2.3.3.7 Transition PL_PM2:Req_Wait to PL_PM3:Connected | 279 |
| 8.2.3.3.8 Transition PL_PM2:Req_Wait to PL_PM4:Wait_For_Close | 279 |
| 8.2.3.4 PL_PM3:Connected state | 279 |
| 8.2.3.4.1 PL_PM3:Connected state description | 279 |
| 8.2.3.4.2 Transition PL_PM3:Connected to PL_PM1:Idle | 280 |
| 8.2.3.5 PL_PM4:Wait_For_Close state | 281 |
| 8.2.3.5.1 PL_PM4:Wait_For_Close state description | 281 |
| 8.2.3.5.2 Transition PL_PM4:Wait_For_Close to PL_PM1:Idle | 281 |
| 9 Transport layer | 282 |
| 9.1 Transport layer overview | 282 |
| 9.2 SSP transport layer | 283 |
| 9.2.1 SSP frame format | 283 |
| 9.2.2 Information units | 285 |
| 9.2.2.1 COMMAND information unit | 285 |
| 9.2.2.2 TASK information unit | 286 |
| 9.2.2.3 XFER_RDY information unit | 288 |
| 9.2.2.4 DATA information unit | 288 |
| 9.2.2.5 RESPONSE information unit | 289 |
| 9.2.2.5.1 RESPONSE information unit overview | 289 |
| 9.2.2.5.2 RESPONSE information unit NO_DATA format | 291 |
| 9.2.2.5.3 RESPONSE information unit RESPONSE_DATA format | 291 |
| 9.2.2.5.4 RESPONSE information unit SENSE_DATA format | 292 |
| 9.2.3 Sequences of SSP frames | 292 |
| 9.2.4 SSP transport layer handling of link layer errors | 294 |
| 9.2.4.1 COMMAND frame | 294 |
| 9.2.4.2 TASK frame | 294 |
| 9.2.4.3 XFER_RDY frame | 294 |
| 9.2.4.4 DATA frame | 295 |
| 9.2.4.5 RESPONSE frame | 295 |
| 9.2.5 SSP transport layer error handling | 295 |
| 9.2.5.1 SSP target port error handling | 295 |
| 9.2.5.2 SSP initiator port error handling | 296 |
| 9.2.6 ST (transport layer for SSP ports) state machines | 297 |
| 9.2.6.1 ST state machines overview | 297 |
| 9.2.6.2 ST_I (transport layer for SSP initiator ports) state machines | 297 |
| 9.2.6.2.1 ST_I state machines overview | 297 |
| 9.2.6.2.2 ST_ISF (initiator send frame) state machine | 299 |
| 9.2.6.2.2.1 ST_ISF state machine overview | 299 |
| 9.2.6.2.2.2 ST_ISF1:Send_Frame state | 299 |
| 9.2.6.2.2.2.1 State description | 299 |
| 9.2.6.2.2.2.2 Transition ST_ISF1:Send_Frame to ST_ISF2:Prepare_Command_Task | 301 |
| 9.2.6.2.2.2.3 Transition ST_ISF1:Send_Frame to ST_ISF3:Prepare_Data_Out | 301 |
| 9.2.6.2.2.3 ST_ISF2:Prepare_Command_Task state | 301 |
| 9.2.6.2.2.3.1 State description | 301 |

| | |
|---|-----|
| 9.2.6.2.2.3.2 Transition ST_ISF2:Prepare_Command_Task to ST_ISF1:Send_Frame | 301 |
| 9.2.6.2.2.4 ST_ISF3:Prepare_Data_Out state | 301 |
| 9.2.6.2.2.4.1 State description | 301 |
| 9.2.6.2.2.4.2 Transition ST_ISF3:Prepare_Data_Out to ST_ISF1:Send_Frame | 302 |
| 9.2.6.2.3 ST_IPD (initiator process data) state machine | 302 |
| 9.2.6.2.4 ST_IPR (initiator process response) state machine | 302 |
| 9.2.6.2.5 ST_IFR (initiator frame router) state machine | 303 |
| 9.2.6.3 ST_T (transport layer for SSP target ports) state machines | 304 |
| 9.2.6.3.1 ST_T state machines overview | 304 |
| 9.2.6.3.2 ST_TFR (target frame router) state machine | 305 |
| 9.2.6.3.3 ST_TTS (target transport server) state machine | 307 |
| 9.2.6.3.3.1 ST_TTS state machine overview | 307 |
| 9.2.6.3.3.2 ST_TTS1:Start state | 307 |
| 9.2.6.3.3.2.1 State description | 307 |
| 9.2.6.3.3.2.2 Transition ST_TTS1:Start to ST_TTS2:Send_Frame | 308 |
| 9.2.6.3.3.2.3 Transition ST_TTS1:Start to ST_TTS7:Prepare_Response | 308 |
| 9.2.6.3.3.3 ST_TTS2:Send_Frame state | 308 |
| 9.2.6.3.3.3.1 State description | 308 |
| 9.2.6.3.3.3.2 Transition ST_TTS2:Send_Frame to ST_TTS3:Prepare_Data_In | 309 |
| 9.2.6.3.3.3.3 Transition ST_TTS2:Send_Frame to ST_TTS4:Receive_Data_Out | 310 |
| 9.2.6.3.3.3.4 Transition ST_TTS2:Send_Frame to ST_TTS7:Prepare_Response | 310 |
| 9.2.6.3.3.4 ST_TTS3:Prepare_Data_In state | 310 |
| 9.2.6.3.3.4.1 State description | 310 |
| 9.2.6.3.3.4.2 Transition ST_TTS3:Prepare_Data_In to ST_TTS2:Send_Frame | 310 |
| 9.2.6.3.3.5 ST_TTS4:Receive_Data_Out state | 310 |
| 9.2.6.3.3.5.1 State description | 310 |
| 9.2.6.3.3.5.2 Transition ST_TTS4:Receive_Data_Out to ST_TTS5:Prepare_Xfer_Rdy | 311 |
| 9.2.6.3.3.5.3 Transition ST_TTS4:Receive_Data_Out to ST_TTS6:Process_Data_Out | 311 |
| 9.2.6.3.3.6 ST_TTS5:Prepare_Xfer_Rdy state | 311 |
| 9.2.6.3.3.6.1 State description | 311 |
| 9.2.6.3.3.6.2 Transition ST_TTS5:Prepare_Xfer_Rdy to ST_TTS2:Send_Frame | 312 |
| 9.2.6.3.3.7 ST_TTS6:Process_Data_Out state | 312 |
| 9.2.6.3.3.7.1 State description | 312 |
| 9.2.6.3.3.7.2 Transition ST_TTS6:Process_Data_Out to ST_TTS4:Receive_Data_Out | 312 |
| 9.2.6.3.3.8 ST_TTS7:Prepare_Response state | 312 |
| 9.2.6.3.3.8.1 State description | 312 |
| 9.2.6.3.3.8.2 Transition ST_TTS7:Prepare_Response to ST_TTS2:Send_Frame | 313 |
| 9.3 STP transport layer | 313 |
| 9.3.1 Initial FIS | 313 |
| 9.3.2 BIST Activate FIS | 313 |
| 9.3.3 TT (transport layer for STP ports) state machines | 313 |
| 9.4 SMP transport layer | 314 |
| 9.4.1 SMP transport layer overview | 314 |
| 9.4.2 SMP_REQUEST frame | 315 |
| 9.4.3 SMP_RESPONSE frame | 315 |
| 9.4.4 Sequence of SMP frames | 316 |
| 9.4.5 MT (transport layer for SMP ports) state machines | 316 |
| 9.4.5.1 SMP transport layer state machines overview | 316 |
| 9.4.5.2 MT_IP (transport layer for SMP initiator ports) state machine | 316 |
| 9.4.5.2.1 MT_IP state machine overview | 316 |
| 9.4.5.2.2 MT_IP1:Idle state | 317 |
| 9.4.5.2.2.1 State description | 317 |
| 9.4.5.2.2.2 Transition MT_IP1:Idle to MT_IP2:Send | 317 |
| 9.4.5.2.3 MT_IP2:Send state | 317 |
| 9.4.5.2.3.1 State description | 317 |
| 9.4.5.2.3.2 Transition MT_IP2:Send to MT_IP1:Idle | 318 |
| 9.4.5.2.3.3 Transition MT_IP2:Send to MT_IP3:Receive | 318 |
| 9.4.5.2.4 MT_IP3:Receive state | 318 |

| | |
|---|-----|
| 9.4.5.2.4.1 State description | 318 |
| 9.4.5.2.4.2 Transition MT_IP3:Receive to MT_IP1:Idle | 318 |
| 9.4.5.3 MT_TP (transport layer for SMP target ports) state machine..... | 318 |
| 9.4.5.3.1 MT_TP state machine overview | 318 |
| 9.4.5.3.2 MT_TP1:Idle state | 319 |
| 9.4.5.3.2.1 State description | 319 |
| 9.4.5.3.2.2 Transition MT_TP1:Idle to MT_TP2:Respond..... | 319 |
| 9.4.5.3.3 MT_TP2:Respond state..... | 319 |
| 9.4.5.3.3.1 State description | 319 |
| 9.4.5.3.3.2 Transition MT_TP2:Respond to MT_TP1:Idle..... | 319 |
| 10 Application layer..... | 321 |
| 10.1 Application layer overview | 321 |
| 10.2 SCSI application layer | 321 |
| 10.2.1 SCSI transport protocol services | 321 |
| 10.2.1.1 SCSI transport protocol services overview..... | 321 |
| 10.2.1.2 Send SCSI Command transport protocol service..... | 322 |
| 10.2.1.3 SCSI Command Received transport protocol service | 323 |
| 10.2.1.4 Send Command Complete transport protocol service..... | 324 |
| 10.2.1.5 Command Complete Received transport protocol service | 324 |
| 10.2.1.6 Send Data-In transport protocol service..... | 325 |
| 10.2.1.7 Data-In Delivered transport protocol service | 326 |
| 10.2.1.8 Receive Data-Out transport protocol service | 326 |
| 10.2.1.9 Data-Out Received transport protocol service | 327 |
| 10.2.1.10 Send Task Management Request transport protocol service | 327 |
| 10.2.1.11 Task Management Request Received transport protocol service..... | 328 |
| 10.2.1.12 Task Management Function Executed transport protocol service | 328 |
| 10.2.1.13 Received Task Management Function-Executed transport protocol service | 329 |
| 10.2.2 Application client error handling..... | 330 |
| 10.2.3 Device server error handling..... | 331 |
| 10.2.4 SCSI transport protocol event notifications..... | 331 |
| 10.2.5 SCSI commands | 331 |
| 10.2.5.1 INQUIRY command..... | 331 |
| 10.2.5.2 LOG SELECT and LOG SENSE commands | 332 |
| 10.2.5.3 MODE SELECT and MODE SENSE commands | 332 |
| 10.2.5.4 START STOP UNIT command..... | 332 |
| 10.2.6 SCSI mode parameters | 332 |
| 10.2.6.1 Disconnect-Reconnect mode page | 332 |
| 10.2.6.1.1 Disconnect-Reconnect mode page overview | 332 |
| 10.2.6.1.2 BUS INACTIVITY TIME LIMIT field | 333 |
| 10.2.6.1.3 MAXIMUM CONNECT TIME LIMIT field..... | 334 |
| 10.2.6.1.4 MAXIMUM BURST SIZE field | 334 |
| 10.2.6.1.5 FIRST BURST SIZE field..... | 334 |
| 10.2.6.2 Protocol-Specific Port mode page..... | 335 |
| 10.2.6.2.1 Protocol-Specific Port mode page overview | 335 |
| 10.2.6.2.2 Protocol-Specific Port mode page - short format..... | 335 |
| 10.2.6.2.3 Protocol-Specific Port mode page - Phy Control And Discover subpage | 336 |
| 10.2.6.3 Protocol-Specific Logical Unit mode page..... | 339 |
| 10.2.7 SCSI log parameters..... | 339 |
| 10.2.7.1 Protocol-Specific log page..... | 339 |
| 10.2.8 SCSI power conditions..... | 342 |
| 10.2.8.1 SCSI power conditions overview..... | 342 |
| 10.2.8.2 SA_PC (SCSI application layer power condition) state machine | 342 |
| 10.2.8.2.1 SA_PC state machine overview | 342 |
| 10.2.8.2.2 SA_PC_0:Powered_On state | 343 |
| 10.2.8.2.2.1 State description | 343 |
| 10.2.8.2.2.2 Transition SA_PC_0:Powered_On to SA_PC_4:Stopped | 343 |
| 10.2.8.2.2.3 Transition SA_PC_0:Powered_On to SA_PC_5:Active_Wait..... | 344 |

| | |
|---|-----|
| 10.2.8.2.3 SA_PC_1:Active state | 344 |
| 10.2.8.2.3.1 State description | 344 |
| 10.2.8.2.3.2 Transition SA_PC_1:Active to SA_PC_2:Idle | 344 |
| 10.2.8.2.3.3 Transition SA_PC_1:Active to SA_PC_3:Standby..... | 344 |
| 10.2.8.2.3.4 Transition SA_PC_1:Active to SA_PC_4:Stopped..... | 344 |
| 10.2.8.2.4 SA_PC_2:Idle state | 344 |
| 10.2.8.2.4.1 State description | 344 |
| 10.2.8.2.4.2 Transition SA_PC_2:Idle to SA_PC_1:Active | 344 |
| 10.2.8.2.4.3 Transition SA_PC_2:Idle to SA_PC_3:Standby..... | 344 |
| 10.2.8.2.4.4 Transition SA_PC_2:Idle to SA_PC_4:Stopped..... | 344 |
| 10.2.8.2.5 SA_PC_3:Standby state | 345 |
| 10.2.8.2.5.1 State description | 345 |
| 10.2.8.2.5.2 Transition SA_PC_3:Standby to SA_PC_4:Stopped | 345 |
| 10.2.8.2.5.3 Transition SA_PC_3:Standby to SA_PC_5:Active_Wait..... | 345 |
| 10.2.8.2.5.4 Transition SA_PC_3:Standby to SA_PC_6:Idle_Wait..... | 345 |
| 10.2.8.2.6 SA_PC_4:Stopped state..... | 345 |
| 10.2.8.2.6.1 State description | 345 |
| 10.2.8.2.6.2 Transition SA_PC_4:Stopped to SA_PC_3:Standby | 345 |
| 10.2.8.2.6.3 Transition SA_PC_4:Stopped to SA_PC_5:Active_Wait | 345 |
| 10.2.8.2.6.4 Transition SA_PC_4:Stopped to SA_PC_6:Idle_Wait | 346 |
| 10.2.8.2.7 SA_PC_5:Active_Wait state | 346 |
| 10.2.8.2.7.1 State description | 346 |
| 10.2.8.2.7.2 Transition SA_PC_5:Active_Wait to SA_PC_1:Active | 346 |
| 10.2.8.2.7.3 Transition SA_PC_5:Active_Wait to SA_PC_3:Standby..... | 346 |
| 10.2.8.2.7.4 Transition SA_PC_5:Active_Wait to SA_PC_4:Stopped | 346 |
| 10.2.8.2.7.5 Transition SA_PC_5:Active_Wait to SA_PC_6:Idle_Wait..... | 346 |
| 10.2.8.2.8 SA_PC_6:Idle_Wait state | 346 |
| 10.2.8.2.8.1 State description | 346 |
| 10.2.8.2.8.2 Transition SA_PC_6:Idle_Wait to SA_PC_2:Idle | 347 |
| 10.2.8.2.8.3 Transition SA_PC_6:Idle_Wait to SA_PC_3:Standby..... | 347 |
| 10.2.8.2.8.4 Transition SA_PC_6:Idle_Wait to SA_PC_4:Stopped | 347 |
| 10.2.8.2.8.5 Transition SA_PC_6:Idle_Wait to SA_PC_5:Active_Wait..... | 347 |
| 10.2.9 SCSI vital product data (VPD) | 348 |
| 10.3 ATA application layer..... | 348 |
| 10.4 Management application layer..... | 349 |
| 10.4.1 READY LED signal behavior | 349 |
| 10.4.2 Management protocol services | 349 |
| 10.4.3 SMP functions..... | 350 |
| 10.4.3.1 SMP function request frame format..... | 350 |
| 10.4.3.2 SMP function response frame format..... | 352 |
| 10.4.3.3 REPORT GENERAL function..... | 354 |
| 10.4.3.4 REPORT MANUFACTURER INFORMATION function | 356 |
| 10.4.3.5 DISCOVER function..... | 358 |
| 10.4.3.6 REPORT PHY ERROR LOG function..... | 363 |
| 10.4.3.7 REPORT PHY SATA function..... | 365 |
| 10.4.3.8 REPORT ROUTE INFORMATION function..... | 367 |
| 10.4.3.9 CONFIGURE ROUTE INFORMATION function | 370 |
| 10.4.3.10 PHY CONTROL function..... | 372 |
| Annex A (normative) Compliant jitter test pattern (CJTPAT) | 376 |
| Annex B (informative) SAS to SAS phy reset sequence examples | 383 |
| Annex C (informative) CRC..... | 385 |
| C.1 CRC generator and checker implementation examples | 385 |
| C.2 CRC implementation in C | 385 |
| C.3 CRC implementation with XORs..... | 386 |
| C.4 CRC examples..... | 388 |

| | |
|---|-----|
| Annex D (informative) SAS address hashing..... | 389 |
| D.1 SAS address hashing overview | 389 |
| D.2 Hash collision probability | 389 |
| D.3 Hash generation..... | 390 |
| D.4 Hash implementation in C..... | 390 |
| D.5 Hash implementation with XORs | 391 |
| D.6 Hash examples | 392 |
| Annex E (informative) Scrambling..... | 395 |
| E.1 Scrambler implementation example..... | 395 |
| E.2 Scrambler implementation in C | 395 |
| E.3 Scrambler implementation with XORs | 396 |
| E.4 Scrambler examples | 397 |
| Annex F (informative) ATA architectural notes | 398 |
| F.1 STP differences from Serial ATA (SATA)..... | 398 |
| F.2 STP differences from Serial ATA II | 398 |
| F.3 Affiliation policies..... | 398 |
| F.3.1 Affiliation policies overview | 398 |
| F.3.2 Affiliation policy for static STP initiator port to STP target port mapping | 399 |
| F.3.3 Affiliation policy with SATA queued commands and multiple STP initiator ports..... | 399 |
| F.3.4 Applicability of affiliation for STP target ports | 399 |
| Annex G (informative) Expander device handling of connections..... | 400 |
| G.1 Expander device handling of connections overview | 400 |
| G.2 Connection request - OPEN_ACCEPT..... | 402 |
| G.3 Connection request - OPEN_REJECT by end device | 403 |
| G.4 Connection request - OPEN_REJECT by expander device | 404 |
| G.5 Connection request - arbitration lost..... | 405 |
| G.6 Connection request - backoff and retry..... | 406 |
| G.7 Connection request - backoff and reverse path..... | 407 |
| G.8 Connection close - single step..... | 408 |
| G.9 Connection close - simultaneous..... | 409 |
| G.10 BREAK handling during path arbitration | 410 |
| G.11 BREAK handling during connection..... | 411 |
| G.12 STP connection - originated by STP initiator port..... | 412 |
| G.13 STP connection - originated by STP target port in an STP/SATA bridge | 413 |
| G.14 STP connection close - originated by STP initiator port | 414 |
| G.15 STP connection close - originated by STP target port in an STP/SATA bridge..... | 415 |
| G.16 Pathway blocked and pathway recovery example..... | 416 |
| Annex H (informative) Primitive encoding..... | 417 |
| Annex I (informative) Messages between state machines..... | 420 |
| I.1 Messages between phy layer and other layers | 420 |
| I.2 Messages between link layer, port layer, and management application layer for all protocols | 420 |
| I.3 Messages between link layer, port layer, and transport layer for SSP | 422 |
| I.4 Messages between link layer, port layer, and transport layer for SMP | 424 |
| I.5 Messages from transport layer to application layer for SSP..... | 425 |
| I.6 Messages from transport layer to application layer for SMP | 426 |
| Annex J (informative) Discover process example implementation..... | 427 |
| J.1 Discover process example implementation overview | 427 |
| J.2 Header file | 427 |
| J.3 Source file..... | 440 |
| Annex K (informative) SAS icon..... | 451 |

List of figures

| | Page |
|--|------|
| Figure 1 — SCSI document relationships | 26 |
| Figure 2 — ATA document relationships | 26 |
| Organization of this standard | 28 |
| Figure 3 — Object and class diagram conventions | 44 |
| Figure 4 — Class diagram conventions for aggregation and generalization | 45 |
| Figure 5 — State machine conventions | 46 |
| Figure 6 — SAS object model | 50 |
| Figure 7 — Physical links and phys | 51 |
| Figure 8 — Phy object classes | 52 |
| Figure 9 — Ports (narrow ports and wide ports) | 53 |
| Figure 10 — Port object classes | 54 |
| Figure 11 — SAS devices | 55 |
| Figure 12 — Expander device | 56 |
| Figure 13 — Expander device object classes | 56 |
| Figure 14 — Domains | 57 |
| Figure 15 — SAS domain bridging to ATA domains | 58 |
| Figure 16 — Devices spanning SAS domains | 58 |
| Figure 17 — Edge expander device set | 60 |
| Figure 18 — Maximum expander device set topology | 61 |
| Figure 19 — Fanout expander device topology | 62 |
| Figure 20 — Edge expander device set to edge expander device set topology | 63 |
| Figure 21 — Potential pathways | 64 |
| Figure 22 — Multiple connections on wide ports | 66 |
| Figure 23 — State machines for SAS devices | 69 |
| Figure 24 — State machines for expander devices | 70 |
| Figure 25 — Transmit data path in a SAS phy | 71 |
| Figure 26 — SSP link, port, SSP transport, and SCSI application layer state machines | 72 |
| Figure 27 — SMP link, port, SMP transport, and management application layer state machines | 73 |
| Figure 28 — STP link, port, STP transport, and ATA application layer state machines | 74 |
| Figure 29 — Transmit data path and state machines in an expander phy | 75 |
| Figure 30 — State machine and SAS device, SAS port, and SAS phy objects | 76 |
| Figure 31 — State machine and expander device, expander port, and expander phy objects | 77 |
| Figure 32 — Reset terminology | 78 |
| Figure 33 — Expander device model | 80 |
| Figure 34 — Expander device interfaces | 82 |
| Figure 35 — Expander device interface detail | 83 |
| Figure 36 — Expander route table example | 88 |
| Figure 37 — Level-order traversal example | 89 |
| Figure 38 — Expander route index levels example | 91 |
| Figure 39 — Expander route index levels example with fanout expander device | 92 |
| Figure 40 — Expander route index order example | 95 |
| Figure 41 — SATA cables and connectors | 97 |
| Figure 42 — SAS cables and connectors - external environment | 98 |
| Figure 43 — SAS cables and connectors - internal environment | 99 |
| Figure 44 — SAS single-port internal cable assembly and destination pin assignments | 105 |
| Figure 45 — SAS dual-port internal cable assembly and destination pin assignments | 106 |
| Figure 46 — Transmitter transient test circuit | 108 |
| Figure 47 — Receiver transient test circuit | 108 |
| Figure 48 — Eye mask at IR, CR, and XR | 110 |
| Figure 49 — Deriving a tolerance mask at IR, CR, or XR | 110 |
| Figure 50 — Sinusoidal jitter mask | 111 |
| Figure 51 — Compliance interconnect test load | 119 |
| Figure 52 — Zero-length test load | 119 |
| Figure 53 — ISI loss example at 3,0 Gbps | 120 |
| Figure 54 — ISI loss example at 1,5 Gbps | 120 |

| | |
|--|-----|
| Figure 55 — SAS bit transmission logic | 129 |
| Figure 56 — SAS bit reception logic | 130 |
| Figure 57 — OOB signal transmission | 132 |
| Figure 58 — OOB signal detection | 134 |
| Figure 59 — SATA OOB sequence | 135 |
| Figure 60 — SATA speed negotiation sequence | 136 |
| Figure 61 — SAS to SATA OOB sequence | 137 |
| Figure 62 — SAS to SAS OOB sequence | 138 |
| Figure 63 — SAS speed negotiation window | 139 |
| Figure 64 — SAS speed negotiation sequence (phy A: G1, G2, G3, phy B: G2 only) | 140 |
| Figure 65 — SAS speed negotiation sequence (phy A: G1, G2, G3, phy B: G1, G2) that fails | 141 |
| Figure 66 — Hot-plug and the phy reset sequence | 142 |
| Figure 67 — SP (phy layer) state machine - OOB sequence states | 145 |
| Figure 68 — SP (phy layer) state machine - SAS speed negotiation states | 149 |
| Figure 69 — SP (phy layer) state machine - SATA host emulation states | 154 |
| Figure 70 — SP_DWS (phy layer dword synchronization) state machine | 158 |
| Figure 71 — Repeated primitive sequence | 172 |
| Figure 72 — Triple primitive sequence | 173 |
| Figure 73 — Redundant primitive sequence | 174 |
| Figure 74 — Elasticity buffers | 183 |
| Figure 75 — CRC generator bit order | 186 |
| Figure 76 — STP CRC bit ordering | 187 |
| Figure 77 — Transmit path bit ordering | 189 |
| Figure 78 — Receive path bit ordering | 190 |
| Figure 79 — STP transmit path bit ordering | 191 |
| Figure 80 — STP receive path bit ordering | 192 |
| Figure 81 — SL_IR (link layer identification and hard reset) state machines | 201 |
| Figure 82 — Aborting a connection request with BREAK | 212 |
| Figure 83 — Connection request timeout example | 213 |
| Figure 84 — Closing a connection example | 214 |
| Figure 85 — Rate matching example | 215 |
| Figure 86 — SL (link layer for SAS phys) state machines (part 1) | 217 |
| Figure 87 — SL (link layer for SAS phys) state machines (part 2) | 218 |
| Figure 88 — XL (link layer for expander phys) state machine (part 1) | 227 |
| Figure 89 — XL (link layer for expander phys) state machine (part 2) | 228 |
| Figure 90 — XL (link layer for expander phys) state machine (part 3) | 229 |
| Figure 91 — SSP frame transmission | 237 |
| Figure 92 — Interlocked frames | 238 |
| Figure 93 — Non-interlocked frames with the same tag | 239 |
| Figure 94 — Non-interlocked frames with different tags | 239 |
| Figure 95 — Closing an SSP connection example | 240 |
| Figure 96 — SSP (link layer for SSP phys) state machines (part 1 - frame transmission) | 242 |
| Figure 97 — SSP (link layer for SSP phys) state machines (part 2 - frame reception) | 243 |
| Figure 98 — STP frame transmission | 250 |
| Figure 99 — STP flow control | 252 |
| Figure 100 — STP initiator port opening an STP connection | 255 |
| Figure 101 — STP target port opening an STP connection | 256 |
| Figure 102 — SMP frame transmission | 257 |
| Figure 103 — SMP_IP (link layer for SMP initiator phys) state machine | 259 |
| Figure 104 — SMP_TP (link layer for SMP target phys) state machine | 261 |
| Figure 105 — Port layer examples | 264 |
| Figure 106 — PL_OC (port layer overall control) state machine | 266 |
| Figure 107 — PL_PM (port layer phy manager) state machine (part 1) | 275 |
| Figure 108 — PL_PM (port layer phy manager) state machine (part 2) | 276 |
| Figure 109 — Task management function sequence of SSP frames | 292 |
| Figure 110 — Write command sequence of SSP frames | 293 |
| Figure 111 — Read command sequence of SSP frames | 293 |
| Figure 112 — Bidirectional command sequence of SSP frames | 294 |

| | |
|--|-----|
| Figure 113 — ST_I (transport layer for SSP initiator ports) state machines | 298 |
| Figure 114 — ST_T (transport layer for SSP target ports) state machines | 305 |
| Figure 115 — Sequence of SMP frames | 316 |
| Figure 116 — MT_IP (transport layer for SMP initiator ports) state machine | 317 |
| Figure 117 — MT_TP (transport layer for SMP target ports) state machine | 319 |
| Figure 118 — SA_PC (SCSI application layer power condition) state machine for SAS | 343 |
| Figure B.1 — SAS speed negotiation sequence (phy A: G1 only, phy B: G1 only) | 383 |
| Figure B.2 — SAS speed negotiation sequence (phy A: G1, G2, G3, phy B: G1, G2) | 384 |
| Figure C.1 — CRC generator example | 385 |
| Figure C.2 — CRC checker example | 385 |
| Figure D.1 — BCH(69, 39, 9) code generator | 390 |
| Figure E.1 — Scrambler | 395 |
| Figure G.1 — Example topology | 400 |
| Figure G.2 — Connection request - OPEN_ACCEPT | 402 |
| Figure G.3 — Connection request - OPEN_REJECT by end device | 403 |
| Figure G.4 — Connection request - OPEN_REJECT by expander device | 404 |
| Figure G.5 — Connection request - arbitration lost | 405 |
| Figure G.6 — Connection request - backoff and retry | 406 |
| Figure G.7 — Connection request - backoff and reverse path | 407 |
| Figure G.8 — Connection close - single step | 408 |
| Figure G.9 — Connection close - simultaneous | 409 |
| Figure G.10 — BREAK handling during path arbitration | 410 |
| Figure G.11 — BREAK handling during a connection | 411 |
| Figure G.12 — STP connection - originated by STP initiator port | 412 |
| Figure G.13 — STP connection - originated by STP target port in an STP/SATA bridge | 413 |
| Figure G.14 — STP connection close - originated by STP initiator port | 414 |
| Figure G.15 — STP connection close - originated by STP target port in an STP/SATA bridge | 415 |
| Figure G.16 — Partial pathway recovery | 416 |
| Figure K.1 — SAS icon | 451 |

Tables

| | Page |
|--|------|
| Table 1 ISO and American numbering conventions | 43 |
| Table 2 Data dword containing a value | 47 |
| Table 3 Data dword containing four one-byte fields | 48 |
| Table 4 Names and identifiers | 67 |
| Table 5 SAM-3 object mapping | 67 |
| Table 6 SAS address format | 67 |
| Table 7 Hashed SAS address code parameter | 68 |
| Table 8 Expander phy to ECM requests | 83 |
| Table 9 Expander phy to ECM responses | 84 |
| Table 10 ECM to expander phy confirmations | 84 |
| Table 11 Expander phy to ECR to expander phy requests and indications | 85 |
| Table 12 Expander phy to ECR to expander phy responses and confirmations | 85 |
| Table 13 Expander phy to BPP requests | 86 |
| Table 14 BPP to expander phy indications | 86 |
| Table 15 Expander route table levels for edge expander device R or fanout expander device R | 93 |
| Table 16 Expander route table levels for edge expander device N | 94 |
| Table 17 Expander route entries for edge expander E0 phy 0 | 96 |
| Table 18 Expander route entries for fanout expander device F phy 0 | 96 |
| Table 19 Connectors | 100 |
| Table 20 SAS target device connector pin assignments | 102 |
| Table 21 Physical link usage in SAS external connector | 104 |
| Table 22 Compliance points | 107 |
| Table 23 General interface characteristics | 109 |
| Table 24 Signal characteristics at IT, CT, XT | 112 |
| Table 25 Signal characteristics at IR, CR, and XR | 113 |
| Table 26 Maximum allowable jitter at IR, CR, XR | 115 |
| Table 27 Receiver jitter tolerance | 116 |
| Table 28 Impedance requirements | 116 |
| Table 29 Output characteristics of the READY LED signal | 121 |
| Table 30 Special character usage | 122 |
| Table 31 Bit designations | 123 |
| Table 32 Conversion example | 123 |
| Table 33 Valid data characters | 125 |
| Table 34 Valid special characters | 127 |
| Table 35 Delayed code violation example | 128 |
| Table 36 OOB signal timing specifications | 131 |
| Table 37 OOB signal transmitter requirements | 131 |
| Table 38 OOB signal receiver burst time detection requirements | 133 |
| Table 39 OOB signal receiver idle time detection requirements | 133 |
| Table 40 OOB signal receiver negation time detection requirements | 133 |
| Table 41 Phy reset sequence timing specifications | 135 |
| Table 42 SATA speed negotiation sequence timing specifications | 136 |
| Table 43 SAS speed negotiation sequence timing specifications | 139 |
| Table 44 SP state machine timers | 143 |
| Table 45 SP_DWS timers | 158 |
| Table 46 Primitive format | 163 |
| Table 47 Primitives not specific to type of connection | 164 |
| Table 48 Primitives used only inside SSP and SMP connections | 166 |
| Table 49 Primitives used only inside STP connections and on SATA physical links | 167 |
| Table 50 Primitive encoding for primitives not specific to type of connection | 168 |
| Table 51 Primitive encoding for primitives used only inside SSP and SMP connections | 170 |
| Table 52 Primitive encoding for primitives used only inside STP connections and on SATA physical links | 171 |
| Table 53 Primitive sequences | 172 |
| Table 54 AIP primitives | 175 |
| Table 55 ALIGN primitives | 175 |

| | |
|---|-----|
| Table 56 BROADCAST primitives | 176 |
| Table 57 CLOSE primitives | 177 |
| Table 58 NOTIFY primitives | 178 |
| Table 59 OPEN_REJECT abandon primitives | 179 |
| Table 60 OPEN_REJECT retry primitives | 180 |
| Table 61 DONE primitives | 181 |
| Table 62 NAK primitives | 182 |
| Table 63 RRDY primitives | 182 |
| Table 64 Clock skew management ALIGN or NOTIFY insertion requirements | 184 |
| Table 65 CRC polynomials | 185 |
| Table 66 Scrambling for different data dword types | 188 |
| Table 67 Address frame format | 193 |
| Table 68 Address frame types | 193 |
| Table 69 IDENTIFY address frame format | 194 |
| Table 70 Device types | 194 |
| Table 71 OPEN address frame format | 196 |
| Table 72 Protocol | 197 |
| Table 73 Connection rate | 197 |
| Table 74 Arbitration wait time | 198 |
| Table 75 SL_IR timers | 200 |
| Table 76 Connection responses | 207 |
| Table 77 Arbitration priority for OPENS passing on a physical link | 208 |
| Table 78 Arbitration priority for contending path requests in the ECM | 209 |
| Table 79 Pathway recovery priority | 210 |
| Table 80 Abort connection responses | 211 |
| Table 81 Close connection responses | 213 |
| Table 82 Break connection responses | 214 |
| Table 83 SL_CC timers | 220 |
| Table 84 XL timers | 226 |
| Table 85 SSP frame interlock requirements | 238 |
| Table 86 SSP link layer timers | 241 |
| Table 87 PL_OC state machine timers | 265 |
| Table 88 Confirmations from Unable To Connect or Retry Open messages | 271 |
| Table 89 PL_PM state machine timers | 274 |
| Table 90 Messages from Open Failed confirmations | 278 |
| Table 91 SSP frame format | 283 |
| Table 92 FRAME TYPE field | 284 |
| Table 93 COMMAND information unit | 285 |
| Table 94 TASK ATTRIBUTE field | 286 |
| Table 95 TASK information unit | 286 |
| Table 96 Task management functions | 287 |
| Table 97 XFER_RDY information unit | 288 |
| Table 98 DATA information unit | 288 |
| Table 99 RESPONSE information unit | 290 |
| Table 100 DATAPRES field | 290 |
| Table 101 RESPONSE DATA field | 291 |
| Table 102 RESPONSE CODE field | 291 |
| Table 103 Delivery Failure to Command Complete Received mapping | 303 |
| Table 104 ST_T state machine timers | 304 |
| Table 105 Response Data argument to RESPONSE frame content mapping | 312 |
| Table 106 SMP frame format | 314 |
| Table 107 SMP FRAME TYPE field | 314 |
| Table 108 SMP_REQUEST frame format | 315 |
| Table 109 SMP_RESPONSE frame format | 315 |
| Table 110 MT_IP timers | 316 |
| Table 111 SCSI architecture mapping | 322 |
| Table 112 Send SCSI Command transport protocol service arguments | 323 |
| Table 113 SCSI Command Received transport protocol service arguments | 323 |

| | |
|---|-----|
| Table 114 Send Command Complete transport protocol service arguments | 324 |
| Table 115 Command Complete Received transport protocol service arguments | 325 |
| Table 116 Send Data-In transport protocol service arguments | 326 |
| Table 117 Data-In Delivered transport protocol service arguments | 326 |
| Table 118 Receive Data-Out transport protocol service arguments | 327 |
| Table 119 Data-Out Received transport protocol service arguments | 327 |
| Table 120 Send Task Management Request transport protocol service arguments | 328 |
| Table 121 Task Management Request Received transport protocol service arguments | 328 |
| Table 122 Task Management Function Executed transport protocol service arguments | 329 |
| Table 123 Received Task Management Function-Executed transport protocol service arguments | 330 |
| Table 124 Delivery Result to additional sense code mapping | 331 |
| Table 125 SCSI transport protocol events | 331 |
| Table 126 Disconnect-Reconnect mode page for SSP | 333 |
| Table 127 Protocol-Specific Port Control mode page subpages | 335 |
| Table 128 Protocol-Specific Port Control mode page for SAS SSP - short format | 335 |
| Table 129 I_T nexus loss time | 336 |
| Table 130 Protocol-Specific Port Control mode page for SAS SSP - Phy Control And Discover subpage | 336 |
| Table 131 SAS phy mode descriptor | 338 |
| Table 132 Protocol-Specific log page for SAS | 339 |
| Table 133 Protocol-Specific log parameter format for SAS | 340 |
| Table 134 Parameter control bits for SAS log parameters | 340 |
| Table 135 SAS phy log descriptor | 341 |
| Table 136 Device Identification VPD page required identification descriptors | 348 |
| Table 137 SMP request frame format | 350 |
| Table 138 SMP functions | 351 |
| Table 139 SMP response frame format | 352 |
| Table 140 Function results | 353 |
| Table 141 REPORT GENERAL request | 354 |
| Table 142 REPORT GENERAL response | 355 |
| Table 143 REPORT MANUFACTURER INFORMATION request | 356 |
| Table 144 REPORT MANUFACTURER INFORMATION response | 357 |
| Table 145 DISCOVER request | 358 |
| Table 146 DISCOVER response | 359 |
| Table 147 Attached device types | 360 |
| Table 148 Negotiated physical link rate | 360 |
| Table 149 Programmed minimum and maximum physical link rates | 362 |
| Table 150 Hardware minimum and maximum physical link rates | 362 |
| Table 151 Routing attributes | 363 |
| Table 152 REPORT PHY ERROR LOG request | 363 |
| Table 153 REPORT PHY ERROR LOG response | 364 |
| Table 154 REPORT PHY SATA request | 365 |
| Table 155 REPORT PHY SATA response | 366 |
| Table 156 REPORT ROUTE INFORMATION request | 368 |
| Table 157 REPORT ROUTE INFORMATION response | 369 |
| Table 158 CONFIGURE ROUTE INFORMATION request | 371 |
| Table 159 CONFIGURE ROUTE INFORMATION response | 372 |
| Table 160 PHY CONTROL request | 373 |
| Table 161 Phy operation | 374 |
| Table 162 Programmed minimum and maximum physical link rate | 375 |
| Table 163 PHY CONTROL response | 375 |
| Table A.1 CJTPAT for RD+ | 376 |
| Table A.2 CJTPAT for RD- | 377 |
| Table A.3 CJTPAT for RD+ and RD- | 378 |
| Table A.4 CJTPAT scrambled in an SSP DATA frame | 379 |
| Table C.1 CRC examples | 388 |
| Table D.1 Monte-Carlo simulation results | 389 |
| Table D.2 Hash results for simple SAS addresses | 392 |
| Table D.3 Hash results for realistic SAS addresses | 392 |

| | |
|---|-----|
| Table D.4 Hash results for a walking ones pattern | 393 |
| Table D.5 Hash results for a walking zeros pattern | 394 |
| Table E.1 Scrambler examples | 397 |
| Table G.1 Column descriptions for connection examples | 401 |
| Table H.1 Primitives with Hamming distance of 8 | 417 |
| Table I.1 Requests from management application layer or link layer to phy layer | 420 |
| Table I.2 Confirmations from phy layer to link layer | 420 |
| Table I.3 Requests between link layer and port layer | 420 |
| Table I.4 Confirmations between link layer and port layer | 421 |
| Table I.5 Requests from management application layer to link layer | 421 |
| Table I.6 Confirmations between link layer and port layer, link layer, or application layer | 421 |
| Table I.7 Requests between link layer, port layer, and transport layer for SSP | 422 |
| Table I.8 Confirmations from port layer to transport layer for SSP | 422 |
| Table I.9 Confirmations between SL link layer, port layer, and SSP transport layer | 423 |
| Table I.10 Confirmations between SSP link layer, port layer, and SSP transport layer | 424 |
| Table I.11 Requests between SL/SMP link layer, port layer, and SMP transport layer | 424 |
| Table I.12 Confirmations between link layer, port layer, and SMP transport layer | 425 |
| Table I.13 Requests and responses from SCSI application layer to SSP transport layer | 425 |
| Table I.14 Confirmations and indications from SSP transport layer to SCSI application layer | 426 |
| Table I.15 Requests from management application layer to SMP transport layer | 426 |
| Table I.16 Confirmations from SMP transport layer to management application layer | 426 |
| Table J.1 C program files | 427 |