

ISO/IEC 14165-241 :2005-06 (E)

Information technology_ - Fibre Channel_ - Part_241: Backbone 2 (FC-BB-2)

Contents

- FOREWORD 10
- INTRODUCTION 11
- 1 Scope 13**
- 2 Normative references 13**
 - 2.1 Approved references 13
 - 2.2 Other references 13
- 3 Definitions and Conventions 14**
 - 3.1 Common Defintions 14
 - 3.2 FC-BB-2_ATM Definitions 15
 - 3.3 FC-BB-2_SONET Definitions 17
 - 3.4 FCIP and TCP/IP Definitions 18
 - 3.5 Symbols and abbreviations 20
 - 3.5.1 General 20
 - 3.5.2 FC-BB-2_ATM 20
 - 3.5.3 FC-BB-2_SONET 21
 - 3.5.4 FC-BB-2_IP 21
 - 3.6 Keywords 21
 - 3.6.1 expected 21
 - 3.6.2 invalid 21
 - 3.6.3 mandatory 22
 - 3.6.4 may 22
 - 3.6.5 may not 22
 - 3.6.6 obsolete 22
 - 3.6.7 optional 22
 - 3.6.8 reserved 22
 - 3.6.9 shall 22
 - 3.6.10 should 22
 - 3.7 Conventions 22
 - 3.8 Notations for Procedure and Functions 23
- 4 FC-BB-2 Structure and Concepts 24**
 - 4.1 FC-BB-2 Backbone Mappings 24
 - 4.2 FC-BB-2 Reference Models 24
 - 4.3 FC-BB-2 Specifications Overview 25
 - 4.3.1 FC-BB-2_ATM 25
 - 4.3.2 FC-BB-2_SONET 26
 - 4.3.3 FC-BB-2_IP 26
 - 4.4 FC-BB-2 Requirements 26
 - 4.4.1 Fibre Channel Class support 26
 - 4.4.2 Payload transparency 27
 - 4.4.3 Latency delay and timeout value 27
 - 4.4.4 QoS and bandwidth 27
 - 4.4.5 In-order delivery 27
 - 4.4.6 Flow control 27
 - 4.5 FC-BB-2 Link Service Codes 28
- 5 FC-BB-2_ATM and FC-BB-2_SONET messages and formats 29**
 - 5.1 Applicability 29

5.2	Message Formats	29
5.2.1	LLC/SNAP Header format	29
5.2.2	BBW_Header format	30
5.2.3	BBW message payload format for SFC	31
5.2.4	BBW message payload format for SR	31
5.2.4.1	SR_Header Formats	31
5.2.4.2	SR_BBW messages	33
5.2.4.3	Format Field Parameters	34
5.2.4.4	SR Commands and Responses	34
5.2.4.5	Exception condition reporting and recovery	37
6	The SR and SFC Protocol Procedures	41
6.1	Applicability	41
6.2	SR Protocol Overview	41
6.3	Description of the SR procedure	42
6.3.1	SR mode of operation	42
6.3.2	SR procedure for addressing	42
6.3.3	SR procedure for the use of the P/F bit	42
6.3.4	SR procedure for data link set-up and disconnection	42
6.3.4.1	Data link set-up	42
6.3.4.2	Information transfer phase	43
6.3.4.3	Data link disconnection	43
6.3.4.4	Disconnected Phase	44
6.3.4.5	Collision of unnumbered commands	44
6.3.4.6	Collision of SR_DM response with SR_SM or SR_DISC command	45
6.3.4.7	Collision of SR_DM responses	45
6.3.5	Procedures for information transfer using multi-selective reject	45
6.3.5.1	Procedures for SR_I messages	45
6.3.5.2	Sending new SR_I messages	45
6.3.5.3	Receiving an in-sequence SR_I message	45
6.3.5.4	Reception of invalid messages	46
6.3.5.5	Reception of out-of-sequence SR_I messages	46
6.3.5.6	Receiving acknowledgement	47
6.3.5.7	Receiving a SR_SREJ response message	47
6.3.5.8	Receiving a SR_RNR message	48
6.3.5.9	BBW busy condition	48
6.3.5.10	Awaiting acknowledgement	49
6.3.5.11	Receiving a SR_RR response messages with the F bit set to 1	49
6.3.5.12	Responding to command messages with the P bit set to 1	50
6.3.6	SR conditions for data link resetting or data link re-initialization (data link set-up)	50
6.3.6.1	Condition 1	50
6.3.6.2	Condition 2	50
6.3.6.3	Condition 3	50
6.3.6.4	Condition 4	50
6.3.7	SR procedure for data link resetting	50
6.3.7.1	Procedure 1	50
6.3.7.2	Procedure 2	51
6.3.7.3	Procedure 3	51
6.3.8	List of SR system parameters	52
6.3.8.1	Timer T1	52
6.3.8.2	Parameter T2	52
6.3.8.3	Maximum number of attempts to complete a transmission N2	52
6.3.8.4	Maximum number of outstanding SR_I messages k	52

6.4	Simple Flow Control (SFC)	53
7	FC-BB-2_ATM Structure and Concepts	54
7.1	Applicability	54
7.2	FC-BB-2_ATM Overview	54
7.3	FC-BB-2_ATM Functional Model	55
7.3.1	B_Port Network Interface	55
7.3.2	ATM Network Interface	55
7.3.3	Mapping and Encapsulation	55
7.3.4	FC-BB-2_ATM Forwarding	56
7.3.5	Call Handling and ATM Service	56
7.3.6	Frame Handling	57
8	Mapping and Message Encapsulation using AAL5	58
8.1	Applicability	58
8.2	Overview	58
8.3	Mapping BBW messages to AAL5	58
9	FC-BB-2_ATM Service Considerations	61
9.1	Applicability	61
9.2	ATM Service Type	61
9.3	Latency Delay and Timeout Value	61
9.4	Bandwidth Sharing and Allocation	61
9.5	Quality of Service (QoS)	62
9.6	Delivery Order	62
9.7	Loss and Flow Control	63
10	FC-BB-2_SONET Structure and Concepts	64
10.1	Applicability and Related Clauses	64
10.2	FC-BB-2_SONET Overview	64
10.3	FC-BB-2_SONET Functional Model	65
10.3.1	Fibre Channel Network Interface	65
10.3.2	SONET Network Interface	66
10.3.3	Mapping and Encapsulation	67
10.3.4	FC-BB-2_SONET Forwarding	67
10.3.5	Call Handling	67
10.3.6	Frame Handling	67
11	Mapping and Message Encapsulation using HDLC-like Framing	68
11.1	Applicability	68
11.2	Overview	68
11.3	Mapping of BBW messages to HDLC format	68
11.4	Mapping HDLC frames to SONET/SDH	70
12	FC-BB-2_SONET Service Considerations	74
12.1	Applicability	74
12.2	Latency Delay and Timeout Value	74
12.3	Delivery Order	74
12.4	Loss and Flow Control	74
13	FC-BB-2_IP Structure and Concepts	75
13.1	Applicability and Related Clauses	75
13.2	FC-BB-2_IP Overview	75
13.3	VE_Port Functional Model	76

13.3.1	FC-BB-2_IP Interface Protocol Layers	76
13.3.2	E_Port/F_Port FC Interface	76
13.3.3	FC-BB-2_IP Protocol Interface	76
13.3.3.1	Major Components	76
13.3.3.2	FC Switching Element (SE) with FC Routing	77
13.3.3.3	FC and FCIP Entities	78
13.3.3.4	VE_Port Virtual ISL Exchanges	80
13.3.3.5	Control and Service Module (CSM)	81
13.3.3.6	Platform Management Module (PMM)	82
13.3.4	IP Network Interface	84
13.4	The B_Access Functional Model	84
13.4.1	FC-BB-2_IP Interface Protocol Layers	84
13.4.2	B_Port FC Interface	84
13.4.3	FC-BB-2_IP Protocol Interface	85
13.4.3.1	Major Components	85
13.4.3.2	FC and FCIP Entities	85
13.4.3.3	B_Access Virtual ISL Exchanges	87
13.4.3.4	B_Port Control and Service Module (CSM)	90
13.4.3.5	B_Port Platform Management Module (PMM)	90
13.4.4	IP Network Interface	90
13.5	FC-BB-2_IP Network Topologies	91
14	Mapping and Message Encapsulation using TCP/IP	93
14.1	Applicability	93
14.2	Encapsulated Frame Structures	93
14.2.1	FC frame Encapsulation Structure	93
14.2.2	Encapsulated FCIP Special Frame (FSF) structure	94
14.3	TCP/IP Encapsulation	95
15	The FC-BB-2_IP Protocol Procedures	96
15.1	Applicability	96
15.2	FC-BB-2_IP Protocol Procedures	96
15.3	Procedures for Platform Management	96
15.3.1	Function	96
15.3.2	Procedures for Discovery	96
15.3.3	Procedures for Extending FC-SP Security	96
15.3.3.1	Authentication Mechanisms	96
15.3.3.2	Authenticate Special Frame (ASF)	97
15.4	Procedures for Connection Management	98
15.4.1	Function	98
15.4.2	Procedures for Link Setup	98
15.4.3	Procedures for Data Transfer	99
15.4.4	Procedures for FCIP Link Disconnection	99
15.4.5	Procedures for Multiple Connection Management	99
15.5	Procedures for Error Detection Recovery	100
15.5.1	Procedures for Handling Invalid FC frames	100
15.5.2	Procedures for Error Recovery	100
15.6	List of FC-BB-2_IP System Parameters	101
15.6.1	FC Timers	101
15.6.2	TCP Timers	101
15.6.3	Maximum number of attempts to complete an Encapsulated FC Frame transmission	101
15.6.4	Maximum number of outstanding Encapsulated FC Frames	101

16 FC-BB-2_IP Service Considerations	102
16.1 Applicability	102
16.2 Latency Delay	102
16.3 Throughput	102
16.3.1 How Timeouts affect Throughput	102
16.3.2 How loss affects Throughput	102
16.3.3 Other factors that affect Throughput	102
16.4 Reliability	103
16.4.1 Loss of Connectivity	103
16.4.2 Loss of Synchronization	103
16.4.3 Loss or Corruption of TCP Segments	103
16.4.4 Loss or Corruption of FC frames	103
16.4.5 FCIP Error Reporting	103
16.5 Quality of Service (QoS)	104
16.6 Delivery Order	104
16.7 IP Multicast and Broadcast	104
16.8 Security and Authentication	104
Annex A (normative) Encoded SOF and EOF Ordered Sets	105
A.1 Ordered Sets	105
A.2 SOF and EOF OS-Codes	105
A.3 FC-BB-2 SOF OS codes	106
A.4 FC-BB-2 EOF OS codes	106
Annex B (informative) ATM Traffic Management and Signaling	108
B.1 ATM Traffic Management	108
B.2 ATM QoS Parameters	108
B.3 ATM Traffic Parameters	111
B.4 ATM Service Categories	112
B.5 ATM Adaptation Layer (AAL) Types	114
B.6 ATM Multiplexing	114
B.7 Summary of ATM Services and Guarantees	115
B.8 ATM Signaling UNI Standard	115
Annex C (informative) SR Protocol Parameter Guidelines and State Diagram	118
C.1 Assumptions	118
C.2 Calculated Ack Delay (T2) Timer variable	118
C.3 Calculated Window size	118
C.4 Calculated Ack (T1) Timer variable	118
C.5 SR Protocol State Diagram	119
Bibliography	121

Figure

Figure 1 – Scope and components of FC-BB-2 specification	11
Figure 2 – FC-BB-2_ATM Reference Model	24
Figure 3 – FC-BB-2_SONET Reference Model	25
Figure 4 – FC-BB-2_IP Reference Model.	25
Figure 5 – SR Flow Control Protocol Between two BBWs	41
Figure 6 – FC-BB-2_ATM Network Configuration	54
Figure 7 – FC-BB-2_ATM Functional Block Diagram.	56
Figure 8 – AAL5 Mapping of a BBW message with SFC	59
Figure 9 – AAL5 Mapping of a BBW message with SR.	60
Figure 10 – Recommended ATM Bandwidth Allocation for multiple VCs	61
Figure 11 – FC-BB-2_SONET Network Configuration	64
Figure 12 – FC-BB-2_SONET Functional Block Diagram.	66
Figure 13 – SONET SPE HDLC Mapping Example.	71
Figure 14 – Path Signal label: C2	71
Figure 15 – Encapsulation of BBW message into HDLC frame using SFC.	72
Figure 16 – Encapsulation of BBW message into HDLC frame using SR.	73
Figure 17 – FC-BB-2_IP Network Configuration.	75
Figure 18 – FC-BB-2_IP VE_Port Functional Model.	77
Figure 19 – FC-BB-2_IP Protocol Layers.	78
Figure 20 – Scope of VE_Port Virtual ISL	80
Figure 21 – Security Layers.	83
Figure 22 – FC-BB-2_IP B_Access Functional Model.	86
Figure 23 – Scope of B_Access Virtual ISL	87
Figure 24 – B_Access Initialization State Machine.	90
Figure 25 – FC-BB-2_IP Network Topologies	92
Figure 26 – TCP/IP Encapsulation of an Encapsulated FC Frame	95
Figure B.1 – Cell Transfer Delay Distribution	110
Figure B.2 – SVC Signaling at the UNI and Switched payload.	117
Figure C.1 – SR Protocol State Diagram.	119

Table

Table 1 – FC-BB-2 Organization.	12
Table 2 – ISO and International Conventions	23
Table 3 – Specification and FC Port Types Supported	24
Table 4 – FC-BB-2 SW_ILS Codes.	28
Table 5 – FC-BB-2 ELS Codes	28
Table 6 – BBW message structure.	29
Table 7 – LLC/SNAP Header	29
Table 8 – SNAP PID	30
Table 9 – BBW_Header.	30
Table 10 – Flow Control Protocol Type Encodings	30
Table 11 – BBW message payload structure for SFC	31
Table 12 – BBW message payload structure for SR	31
Table 13 – SR_Header format	32
Table 14 – SS bits encoding.	32
Table 15 – MMMMM bit encoding.	32
Table 16 – SR_BBW messages	33
Table 17 – SR_I message format.	35
Table 18 – SR_SREJ payload format	36
Table 19 – SR_FRMR payload format	38
Table 20 – Mapping of BBW messages to AAL5 CPCS	58
Table 21 – ATM VBR-NRT Service Specification.	62
Table 22 – SONET/SDH Data Rates.	66
Table 23 – Mapping of BBW messages to HDLC format.	69
Table 24 – FC-BB-2_SONET Protocol Stack.	71
Table 25 – LKA payload	81
Table 26 – LKA Accept payload.	81
Table 27 – EBP Request payload.	87
Table 28 – EBP Accept payload	88
Table 29 – EBP Reject Reason Code Explanation	88
Table 30 – TCP/IP Segment structure carrying Encapsulated FC Frame	93
Table 31 – Encapsulated FC Frame structure	93
Table 32 – TCP/IP Segment structure carrying Encapsulated FSF.	94
Table 33 – Encapsulated FSF structure	94
Table 34 – ASF Request Payload	97
Table 35 – ASF Accept Response Payload	98
Table A.1 – Byte-encoded frame delimiter format	105
Table A.2 – OS-Code Definition	105
Table A.3 – FC-BB-2 SOF Codes	106
Table A.4 – FC-BB-2 EOF Codes.	106
Table B.1 – I.356 defined QoS Parameters for different Traffic Classes.	111
Table B.2 – Service Categories and its Traffic and QoS Attributes	113
Table B.3 – ATM Service Categories and Guarantees	115