

# ISO/IEC 14165-222 :2005-06 (E)

## Information technology\_ - Fibre Channel\_ - Part\_222: Single-byte command sets-2 mapping protocol (FC-SB-2)

---

- Foreword ..... 9
- Introduction ..... 10
- 1 Scope** ..... 12
- 2 Normative references** ..... 13
  - 2.1 General information concerning references ..... 13
  - 2.2 Approved references ..... 13
  - 2.3 References under development ..... 13
- 3 Definitions and conventions** ..... 14
  - 3.1 Definitions ..... 14
  - 3.2 Keywords ..... 15
  - 3.3 Conventions ..... 16
    - 3.3.1 English usage conventions ..... 16
    - 3.3.2 FC-PH ..... 17
    - 3.3.3 Bit numbering ..... 17
    - 3.3.4 Binary notation ..... 17
    - 3.3.5 Hexadecimal notation ..... 17
    - 3.3.6 Abbreviations, acronyms and symbols ..... 17
- 4 Structure and concepts** ..... 19
  - 4.1 Introduction ..... 19
  - 4.2 FC-4 General description ..... 19
  - 4.3 SB-2 overview ..... 19
    - 4.3.1 SB-2 instance ..... 19
    - 4.3.2 SB-2 protocols ..... 19
  - 4.4 Channel-path elements ..... 20
    - 4.4.1 Overview of channel-path elements ..... 20
    - 4.4.2 Channel ..... 20
    - 4.4.3 Channel image ..... 20
    - 4.4.4 Control unit ..... 21
    - 4.4.5 Control-unit image ..... 21
    - 4.4.6 Link ..... 22
  - 4.5 Channel-path configurations ..... 22
    - 4.5.1 Channel-path configuration overview ..... 22
    - 4.5.2 Point-to-point configuration ..... 22
    - 4.5.3 Fabric configuration ..... 23
    - 4.5.4 Physical path ..... 24
    - 4.5.5 Logical path ..... 25
    - 4.5.6 Channel-to-channel communication ..... 25
  - 4.6 Information transfer ..... 26
  - 4.7 Protocols ..... 27
    - 4.7.1 Protocol overview ..... 27
    - 4.7.2 Link level ..... 27
    - 4.7.3 Device level ..... 28
    - 4.7.4 Addressing ..... 28
- 5 FC-PH Link Control** ..... 30
  - 5.1 FC-PH Link control overview ..... 30

5.2	Class of service .....	30
5.3	Buffer-to-buffer credit reclamation .....	30
5.4	SB-2 Sequences and exchanges .....	31
5.4.1	SB-2 sequences .....	31
5.4.2	SB-2 exchange pairs .....	31
5.5	FC-PH frame header fields .....	33
5.5.1	Frame header field overview .....	33
5.5.2	R_CTL field .....	33
5.5.3	D_ID and S_ID fields .....	33
5.5.4	CS_CTL .....	34
5.5.5	TYPE field .....	34
5.5.6	F_CTL field .....	34
5.5.7	SEQ_ID .....	34
5.5.8	DF_CTL .....	34
5.5.9	SEQ_CNT .....	34
5.5.10	OX_ID .....	34
5.5.11	RX_ID .....	34
5.5.12	Parameter field .....	35
5.6	Other FC-PH mechanisms .....	35
<b>6</b>	<b>Link-Level functions .....</b>	<b>36</b>
6.1	Link-level function overview .....	36
6.2	FC-PH Basic-link-services .....	36
6.2.1	Abort sequence .....	36
6.3	FC-PH Extended link services .....	36
6.3.1	F_Port login .....	36
6.3.2	N_Port login .....	36
6.3.3	N_Port logout .....	37
6.3.4	Reinstate recovery qualifier .....	37
6.3.5	Registered state change notification .....	37
6.3.6	State-change registration .....	38
6.3.7	Request Node-Identification Data .....	39
6.3.8	Registered Link-Incident Record .....	43
6.3.9	Registered Link-Incident Record requests and responses .....	43
6.3.10	Link-Incident-Record Registration .....	47
6.4	SB-2 Link-control functions .....	47
6.4.1	SB-2 Link-control function overview .....	47
6.4.2	Establish logical path .....	49
6.4.3	Remove logical path .....	52
6.4.4	Logical path established .....	52
6.4.5	Logical path removed .....	53
6.4.6	Link-level acknowledgment .....	54
6.4.7	Test initialization .....	55
6.4.8	Test initialization result .....	56
6.4.9	Link-level reject .....	57
6.4.10	Link-level busy .....	58
<b>7</b>	<b>N_Port link initialization .....</b>	<b>60</b>
7.1	N_Port link initialization overview .....	60
7.2	Link-initialization procedure .....	61
7.3	Initialization process for a channel .....	62

7.3.1	Channel initialization overview	62
7.3.2	Channel login	62
7.3.3	Channel Node-Identifier acquisition	63
7.3.4	Channel state-change registration	64
7.3.5	Channel Link-Incident-Record registration	64
7.3.6	Channel Logical-Path establishment	65
7.4	Initialization process for a control unit	66
7.4.1	Control unit initialization overview	66
7.4.2	Control-unit login	66
7.4.3	Control unit node-identifier acquisition	67
7.4.4	Control unit State-Change registration	69
7.4.5	Control unit logical-path establishment	69
<b>8</b>	<b>SB-2 Information units</b>	<b>71</b>
8.1	SB-2 Information unit overview	71
8.2	Rules for sending SB-2 IUs	71
8.2.1	Overview of rules for sending SB-2 information units	71
8.2.2	Rules for device-level functions	72
8.3	SB-2 IU structure	73
8.4	SB-2 header	75
8.4.1	SB-2 header format	75
8.4.2	Channel image ID	75
8.4.3	Control-unit image ID	75
8.4.4	Device address	75
8.5	IU header	76
8.5.1	IU header format	76
8.5.2	Information-unit identifier	76
8.5.3	Device-header flags	78
8.5.4	CCW number	80
8.5.5	Token	82
8.6	Device information block (DIB) structure	83
8.6.1	DIB structure overview	83
8.6.2	DIB header	83
8.6.3	Longitudinal-Redundancy-Check field	84
8.6.4	DIB data field	84
8.6.5	Cyclic-Redundancy-Check field	85
8.7	Command DIB structure	87
8.7.1	Command DIB overview	87
8.7.2	Command header	87
8.8	Command-Data DIB Structure	93
8.9	Data DIB structure	93
8.9.1	Data DIB overview	93
8.9.2	Data Header	94
8.10	Status DIB	94
8.10.1	Status DIB processing	94
8.10.2	Status DIB structure	96
8.10.3	Status header	97
8.10.4	Supplemental Status Field	108
8.11	Control DIB structure	110
8.11.1	Control DIB structure overview	110
8.11.2	Control header	110

8.12	Link-Control DIB structure .....	121
8.12.1	Link-Control DIB structure overview .....	121
8.12.2	Link header .....	122
8.12.3	Link payload .....	123
<b>9</b>	<b>Device-Level functions and protocols .....</b>	<b>124</b>
9.1	Device-Level operations .....	124
9.1.1	Overview of Device-Level operations .....	124
9.1.2	Channel program execution .....	124
9.1.3	Initiating an I/O operation .....	124
9.1.4	Data-Transfer protocol .....	127
9.1.5	Ending an I/O operation .....	133
9.1.6	Command chaining .....	136
9.2	Device-Level controls .....	137
9.2.1	Overview of Device-Level control functions .....	137
9.2.2	Stacking Status Function .....	138
9.2.3	Cancel function .....	139
9.2.4	System-Reset function .....	141
9.2.5	Selective-Reset function .....	142
9.2.6	Request-Status function .....	144
9.2.7	Device-Level-Exception function .....	145
9.2.8	Status-Acceptance function .....	145
9.2.9	Device-Level-Acknowledgment function .....	146
9.2.10	Control-Unit-Busy condition .....	146
9.3	Error handling at the device level .....	146
9.3.1	Purge path function .....	146
9.3.2	Command retry .....	147
9.3.3	Channel-Initiated recovery procedures .....	149
9.3.4	Address-Exception condition .....	153
9.4	Resetting event .....	153
9.5	Special functions .....	155
9.5.1	Path groups .....	155
9.5.2	Dynamic reconnection .....	155
<b>10</b>	<b>Link error detection .....</b>	<b>157</b>
10.1	Link error detection overview .....	157
10.2	SB-2 Timeouts .....	157
10.2.1	Overview of SB-2 timeouts .....	157
10.2.2	SB-2 Protocol time-out value .....	157
10.2.3	SB-2 time-out value .....	158
10.2.4	Logical path time-out value .....	158
10.2.5	Cancel function timeout .....	159
10.3	SB-2 link failure .....	159
10.4	Logical path timeout error .....	159
10.5	SB-2 exchange error .....	159
10.5.1	SB-2 exchange error overview .....	159
10.5.2	SB-2 protocol timeout .....	159
10.5.3	SB-2 IU integrity error .....	159
10.5.4	SB-2 protocol errors .....	160
10.5.5	Receive ABTS .....	161
10.5.6	Cancel function timeout error .....	161

10.5.7	Abnormal termination of exchange .....	161
10.6	Logical-Path-Not-Established error .....	161
10.7	Test initialization result error .....	161
<b>11</b>	<b>Error recovery actions</b> .....	<b>163</b>
11.1	Error recovery action overview .....	163
11.2	Link-Level recovery .....	164
11.2.1	Link-Level recovery overview .....	164
11.2.2	Recovery for an SB-2 link failure .....	165
11.2.3	Logical path timeout error .....	165
11.2.4	Recovery for an SB-2 offline condition .....	165
11.2.5	Recovery for an FC-PH link failure condition .....	166
11.2.6	Recovery for an SB-2 exchange error .....	166
11.2.7	Recovery for a Logical-Path-Not-Established error .....	167
11.2.8	Recovery for Link-Level Reject, P_RJT and F_RJT .....	167
11.2.9	Recovery for a Test-Initialization-Result error .....	168
11.3	Device-Level recovery .....	169
11.3.1	Device-Level recovery overview .....	169
11.3.2	Errors that cause the removal of a logical path .....	169
11.3.3	Errors that do not cause the removal of a logical path .....	170
<b>Annex A</b>	(informative) Fabric address assignment.....	<b>173</b>
A.1	Background .....	173
A.2	Description .....	173
<b>Annex B</b>	(informative) Correlation of exchanges of an exchange pair.....	<b>174</b>
B.1	Correlation of exchanges .....	174
<b>Annex C</b>	(normative) LRC calculation.....	<b>175</b>
C.1	LRC calculation procedure .....	175
C.2	LRC calculation example .....	175
<b>Annex D</b>	(normative) Status/chaining summary.....	<b>177</b>
D.1	Requirements for sending status and chaining .....	177
Bibliography	.....	178
Index	.....	179

## Tables

<b>Table 1</b> – Information categories of SB-2 IUs	33
<b>Table 2</b> – SB-2 specific Link-Incident Record	43
<b>Table 3</b> – Incident-Specific Information	46
<b>Table 4</b> – Summary of link-control request and response IUs	49
<b>Table 5</b> – Logical path field	56
<b>Table 6</b> – Characteristics of IUs sent by a channel	71
<b>Table 7</b> – Characteristics of IUs Sent by a Control Unit	72
<b>Table 8</b> – DIB-type settings	77
<b>Table 9</b> – EE-bit table	80
<b>Table 10</b> – Contents of the command field	88
<b>Table 11</b> – Required Commands	88
<b>Table 12</b> – LRI and RV bit usage	99
<b>Table 13</b> – Status byte	100
<b>Table 14</b> – QTF/QTU relationship	104
<b>Table 15</b> – DTF/DTU relationship	107
<b>Table 16</b> – Bits 0 - 5 of Sense-data byte 0	110
<b>Table 17</b> – Summary of Device-Level control functions	111
<b>Table 18</b> – Summary of control IUs	113
<b>Table 19</b> – Interpretation of the RO and RU bits	118
<b>Table 20</b> – Exception code assignments	119
<b>Table 21</b> – Permitted responses to a Selective-Reset IU	150
<b>Table C.1</b> – Headers of IU	175
<b>Table C.2</b> – LRC Calculation Example	176
<b>Table D.1</b> – Status/will	177

## Figures

<b>Figure 1</b> – Document relationship	10
<b>Figure 2</b> – FC-PH and SB-2 bit numbering conventions	17
<b>Figure 3</b> – Channel images	20
<b>Figure 4</b> – Control unit images	22
<b>Figure 5</b> – Point-to-point channel-path configuration (single logical image)	23
<b>Figure 6</b> – Point-to-point channel-path configuration (multiple logical images)	23
<b>Figure 7</b> – Fabric channel-path configuration (multiple channel images)	24
<b>Figure 8</b> – Fabric channel-path configuration (multiple channel images, CTC connection)	26
<b>Figure 9</b> – Relationships among link level, device level, physical path, and logical path	27
<b>Figure 10</b> – Contents of the node descriptor	40
<b>Figure 11</b> – Link-control information field of the LRJ IU	58
<b>Figure 12</b> – IU payload structures	74
<b>Figure 13</b> – SB-2 header	75
<b>Figure 14</b> – IU header	76
<b>Figure 15</b> – IU identifier	76
<b>Figure 16</b> – Device-header flags	78
<b>Figure 17</b> – Basic DIB structure	83
<b>Figure 18</b> – DIB header structure	83
<b>Figure 19</b> – DIB data field	84
<b>Figure 20</b> – Addends of the alternative initialized value of the CRC generator	86
<b>Figure 21</b> – Command header	87
<b>Figure 22</b> – CCW control flag field	89
<b>Figure 23</b> – Command-flag field	91
<b>Figure 24</b> – Data header	94
<b>Figure 25</b> – Status header	97
<b>Figure 26</b> – Status-flag field	97
<b>Figure 27</b> – Queue-time parameter (QTP) format	104
<b>Figure 28</b> – Queue-time parameter example	105
<b>Figure 29</b> – Defer time parameter format	106
<b>Figure 30</b> – Defer-time parameter example	108
<b>Figure 31</b> – Control header	110
<b>Figure 32</b> – Control-parameter field for the selective-reset IU	116
<b>Figure 33</b> – Control-parameter field for the device-level exception IU	119
<b>Figure 34</b> – Link header	122
<b>Figure 35</b> – Link-control field	122
<b>Figure 36</b> – Link error detection	157
<b>Figure 37</b> – Recovery actions for the channel and control units	164