

ISO/IEC 14776-452 :2005-08 (E)

Information technology_ - Small Computer System Interface (SCSI)_ - Part_452: SCSI Primary Commands-2 (SPC-2)

Contents

	Page
Foreword.....	13
Introduction	14
1 Scope.....	17
2 Normative references.....	17
2.1 General.....	17
2.2 Approved references	17
2.3 References under development	17
3 Definitions, symbols, abbreviations, and conventions	18
3.1 Definitions.....	18
3.2 Acronyms.....	23
3.3 Keywords.....	24
3.4 Conventions.....	25
3.5 Notation for procedures and functions.....	26
4 General concepts	27
4.1 Introduction.....	27
4.2 The request-response model.....	27
4.3 The Command Descriptor Block (CDB).....	27
4.3.1 CDB usage and structure	27
4.3.2 The fixed length CDB formats	28
4.3.3 The variable length CDB formats	30
4.3.4 Common CDB fields	31
4.3.4.1 Operation code	31
4.3.4.2 Service action	31
4.3.4.3 Logical block address	32
4.3.4.4 Transfer length	32
4.3.4.5 Parameter list length.....	32
4.3.4.6 Allocation length	32
4.3.4.7 Control	32

5 Model common to all device types	33
5.1 Introduction to the model common to all device types.....	33
5.2 Commands implemented by all SCSI device servers.....	33
5.2.1 Summary of commands implemented by all SCSI device servers	33
5.2.2 Using the INQUIRY command.....	33
5.2.3 Using the REQUEST SENSE command.....	33
5.2.4 Using the TEST UNIT READY command.....	33
5.3 Parameter rounding.....	33
5.4 Self-test Operations.....	34
5.4.1 Default self-test.....	34
5.4.2 The short and extended self-tests	34
5.4.3 Self-test modes.....	34
5.4.3.1 Foreground mode	34
5.4.3.2 Background mode	35
5.4.3.3 Elements common to foreground and background self-test modes	36
5.5 Reservations.....	36
5.5.1 Reservations overview	36
5.5.2 The Reserve/Release management method.....	39
5.5.3 The Persistent Reservations management method	40
5.5.3.1 Overview of the Persistent Reservations management method.....	40
5.5.3.2 Preserving persistent reservations	40
5.5.3.3 Finding persistent reservations and reservation keys	41
5.5.3.3.1 Summary of commands for finding persistent reservations and reservation keys	41
5.5.3.3.2 Reporting reservation keys.....	41
5.5.3.3.3 Reporting persistent reservations.....	42
5.5.3.3.4 Registering	42
5.5.3.3.5 Creating a persistent reservation when there is no persistent reservation.....	43
5.5.3.3.6 Removing registrations and persistent reservations.....	44
5.5.3.3.6.1 Overview of removing registrations and persistent reservations	44
5.5.3.3.6.2 Releasing a persistent reservation	44
5.5.3.3.6.3 Preempting an existing persistent reservation with the PREEMPT service action.....	45
5.5.3.3.6.3.1 Overview of preempting an existing persistent reservation with the PREEMPT service action	45
5.5.3.3.6.3.2 Failed persistent reservation preempt	46
5.5.3.3.6.3.3 Preempting reservations.....	46
5.5.3.3.6.3.4 Removing registrations.....	47
5.5.3.3.6.3.4 Preempting an existing persistent reservation with the PREEMPT AND ABORT service action.....	47
5.5.3.3.6.3.5 Clearing a persistent reservation.....	48
5.6 Multiple port and multiple initiator behavior	49
5.7 Removable medium devices with an attached medium changer	49
6 Model for processor devices	50

7 Commands for all device types	52
7.1 Summary of commands for all device types	52
7.2 EXTENDED COPY command	53
7.2.1 EXTENDED COPY command introduction	53
7.2.2 Errors detected before starting processing of the segment descriptors	55
7.2.3 Errors detected during processing of segment descriptors	56
7.2.4 Abort task management functions	57
7.2.5 Descriptor type codes	58
7.2.6 Target descriptors.....	59
7.2.6.1 Target descriptors introduction	59
7.2.6.2 Fibre Channel World Wide Name target descriptor format.....	61
7.2.6.3 Fibre Channel N_Port target descriptor format.....	62
7.2.6.4 Fibre Channel N_Port with World Wide Name checking target descriptor format.....	63
7.2.6.5 Parallel Interface T_L target descriptor format	64
7.2.6.6 Identification descriptor target descriptor format	65
7.2.6.7 Device type specific target descriptor parameters for block device types	66
7.2.6.8 Device type specific target descriptor parameters for sequential-access device types.....	66
7.2.6.9 Device type specific target descriptor parameters for processor device types.....	67
7.2.7 Segment Descriptors	68
7.2.7.1 Segment descriptors introduction	68
7.2.7.2 Segment descriptor processing	68
7.2.7.3 Block device to stream device operations	72
7.2.7.4 Stream device to block device operations	73
7.2.7.5 Block device to block device operations.....	74
7.2.7.6 Stream device to stream device operations	75
7.2.7.7 Inline data to stream device operation.....	77
7.2.7.8 Embedded data to stream device operation.....	78
7.2.7.9 Stream device to discard operation	79
7.2.7.10 Verify device operation	80
7.2.7.11 Block device with offset to stream device operation.....	81
7.2.7.12 Stream device to block device with offset operation.....	82
7.2.7.13 Block device with offset to block device with offset operation	83
7.2.7.14 Write filemarks operation	84
7.2.7.15 Space operation	85
7.2.7.16 Locate operation.....	86
7.2.7.17 Tape device image copy operation.....	87
7.2.7.18 Register key operation.....	88
7.3 INQUIRY command.....	89
7.3.1 INQUIRY command introduction	89
7.3.2 Standard INQUIRY data	91
7.3.3 SCSI Parallel Interface specific INQUIRY data	98

7.3.4 Vital product data.....	99
7.3.5 Command support data.....	100
7.4 LOG SELECT command.....	102
7.5 LOG SENSE command.....	104
7.6 MODE SELECT(6) command.....	106
7.7 MODE SELECT(10) command.....	108
7.8 MODE SENSE(6) command.....	108
7.8.1 MODE SENSE(6) command introduction.....	108
7.8.2 Current values.....	110
7.8.3 Changeable values.....	110
7.8.4 Default values.....	110
7.8.5 Saved values.....	110
7.8.6 Initial responses.....	110
7.9 MODE SENSE(10) command.....	111
7.10 PERSISTENT RESERVE IN command.....	112
7.10.1 PERSISTENT RESERVE IN command introduction.....	112
7.10.2 PERSISTENT RESERVE IN service actions.....	112
7.10.2.1 Summary of PERSISTENT RESERVE IN service actions.....	112
7.10.2.2 Read Keys.....	112
7.10.2.3 Read Reservations.....	113
7.10.3 PERSISTENT RESERVE IN parameter data for READ KEYS.....	113
7.10.4 PERSISTENT RESERVE IN parameter data for READ RESERVATION.....	114
7.10.4.1 Format of PERSISTENT RESERVE IN parameter data for READ RESERVATION.....	114
7.10.4.2 Persistent reservations Scope.....	115
7.10.4.2.1 Summary of persistent reservations Scope.....	115
7.10.4.2.2 Logical unit scope.....	115
7.10.4.2.3 Element scope.....	115
7.10.4.3 Persistent Reservations Type.....	116
7.11 PERSISTENT RESERVE OUT command.....	117
7.11.1 PERSISTENT RESERVE OUT command introduction.....	117
7.11.2 PERSISTENT RESERVE OUT Service Actions.....	118
7.11.3 PERSISTENT RESERVE OUT parameter list.....	119
7.12 PREVENT ALLOW MEDIUM REMOVAL command.....	121
7.13 READ BUFFER command.....	122
7.13.1 READ BUFFER command introduction.....	122
7.13.2 Combined header and data mode (0000b).....	123
7.13.3 Vendor specific mode (0001b).....	123
7.13.4 Data mode (0010b).....	123
7.13.5 Descriptor mode (0011b).....	124
7.13.6 Read Data from echo buffer (1010b).....	124
7.13.7 Echo buffer descriptor mode (1011b).....	125
7.14 RECEIVE COPY RESULTS command.....	126
7.14.1 RECEIVE COPY RESULTS command introduction.....	126
7.14.2 COPY STATUS service action.....	127
7.14.3 RECEIVE DATA service action.....	129
7.14.4 OPERATING PARAMETERS service action.....	130
7.14.5 FAILED SEGMENT DETAILS service action.....	132
7.15 RECEIVE DIAGNOSTIC RESULTS command.....	133
7.16 RELEASE(10) command.....	134
7.16.1 RELEASE(10) command introduction.....	134
7.16.2 Logical unit release.....	134
7.16.3 Third-party release.....	134
7.17 RELEASE(6) command.....	135
7.18 REPORT DEVICE IDENTIFIER command.....	136
7.19 REPORT LUNS command.....	138
7.20 REQUEST SENSE command.....	140
7.20.1 REQUEST SENSE command introduction.....	140
7.20.2 Sense data format.....	141
7.20.3 Sense-key specific.....	143
7.20.4 Current errors.....	144

7.20.5 Deferred errors	144
7.20.6 Sense key and sense code definitions	146
7.21 RESERVE(10) command	158
7.21.1 RESERVE(10) command introduction.....	158
7.21.2 Logical unit reservation.....	158
7.21.3 Third-party reservation	159
7.21.4 Superseding reservations.....	160
7.22 RESERVE(6) command	160
7.23 SEND DIAGNOSTIC command	161
7.24 SET DEVICE IDENTIFIER command	163
7.25 TEST UNIT READY command.....	165
7.26 WRITE BUFFER command.....	166
7.26.1 WRITE BUFFER command introduction	166
7.26.2 Combined header and data mode (0000b).....	167
7.26.3 Vendor specific mode (0001b).....	167
7.26.4 Data mode (0010b).....	167
7.26.5 Download microcode mode (0100b).....	167
7.26.6 Download microcode and save mode (0101b)	167
7.26.7 Download microcode with offsets (0110b).....	168
7.26.8 Download microcode with offsets and save mode (0111b)	168
7.26.9 Write data to echo buffer (1010b).....	169
8 Parameters for all device types.....	170
8.1 Diagnostic parameters.....	170
8.1.1 Diagnostic page format and page codes for all device types	170
8.1.2 Supported diagnostic pages	172
8.2 Log parameters	173
8.2.1 Log page structure and page codes for all device types	173
8.2.2 Application client page.....	176
8.2.3 Buffer over-run/under-run page	177
8.2.4 Error counter pages.....	179
8.2.5 Last n deferred errors or asynchronous events page	179
8.2.6 Last n error events page.....	179
8.2.7 Non-medium error page	180
8.2.8 Self-test results page.....	180
8.2.9 Start-stop cycle counter page.....	183
8.2.10 Supported log pages	185
8.2.11 Temperature page	185
8.3 Mode parameters	187
8.3.1 Mode parameters overview	187
8.3.2 Mode parameter list format.....	187
8.3.3 Mode parameter header formats	187
8.3.4 Mode parameter block descriptor formats	188
8.3.4.1 General block descriptor format	188
8.3.4.2 Direct-access device block descriptor format for LONGLBA=0	189
8.3.4.3 Long LBA block descriptor format	190
8.3.5 Mode page format and page codes.....	191
8.3.6 Control mode page	192
8.3.7 Disconnect-reconnect page.....	196
8.3.8 Informational exceptions control page.....	198
8.3.9 Power condition page	200
8.3.10 Protocol specific LUN page	202
8.3.11 Protocol specific port page	203
8.4 Vital product data parameters	204
8.4.1 Vital product data parameters overview and page codes.....	204
8.4.2 ASCII implemented operating definition page	204
8.4.3 ASCII information page	205
8.4.4 Device identification page.....	205
8.4.5 Supported vital product data pages.....	208
8.4.6 Unit serial number page	209

9 Commands for processor type devices.....	210
9.1 Summary of commands for processor type devices.....	210
9.2 RECEIVE command.....	211
9.3 SEND command.....	211
10 Parameters for processor type devices	212
10.1 Diagnostic parameters.....	212
10.2 Log parameters	213
10.3 Vital product data parameters	213
Annex A	
Procedures for logging operations in SCSI	214
A.1 Procedures for logging operations in SCSI introduction	214
A.2 Logging operations terminology	214
A.3 LOG SENSE command.....	215
A.4 LOG SELECT command.....	218
A.5 Exception conditions during logging.....	221
Annex B	
Commands allowed in the presence of various reservations.....	224
B.1 SBC commands	224
B.2 SMC commands.....	228
Annex C	
Numeric order codes.....	230
C.1 Numeric order codes introduction	230
C.2 Additional Sense Codes.....	230
C.3 Operation Codes	242
C.4 Log Page Codes	248
C.5 Mode Page Codes	249
C.6 Version Descriptor Values	251
C.7 Variable Length CDB Service Action Codes.....	258
Annex D	
Vendor identification	259
Annex E	
References and general structure of SCSI	266

Tables

	Page
1 Typical CDB for 6-byte commands	28
2 Typical CDB for 10-byte commands	28
3 Typical CDB for 12-byte commands	29
4 Typical CDB for 16-byte commands	29
5 Typical CDB for long LBA 16-byte commands	30
6 Typical variable length CDB	30
7 Typical variable length CDB for long LBA 32-byte commands	31
8 Exception commands for background self-tests	35
9 Self-test mode summary	36
10 SPC commands that are allowed in the presence of various reservations	38
11 PERSISTENT RESERVE OUT service actions that are allowed in the presence of various reservations	39
12 Processor commands that are allowed in the presence of various reservations	51
13 Commands for all device types	52
14 EXTENDED COPY command	53
15 EXTENDED COPY parameter list	54
16 EXTENDED COPY descriptor type codes	58
17 Target descriptor format	59
18 Device type specific parameters in target descriptors	60
19 Fibre Channel World Wide Name target descriptor format	61
20 Fibre Channel N_Port target descriptor format	62
21 Fibre Channel N_Port with World Wide Name checking target descriptor format	63
22 Parallel Interface T_L target descriptor format	64
23 Identification descriptor target descriptor format	65
24 Device type specific target descriptor parameters for block device types	66
25 Device type specific target descriptor parameters for sequential-access device types	66
26 Stream device transfer lengths	67
27 Device type specific target descriptor parameters for processor device types	67
28 Segment descriptor header	68
29 Descriptor Type Code Dependent Copy Manager Processing	69
30 PAD and CAT bit definitions	71
31 Block device to or from stream device segment descriptor	72
32 Block device to block device segment descriptor	74
33 Stream device to stream device segment descriptor	75
34 Inline data to stream device segment descriptor	77
35 Embedded data to stream device segment descriptor	78
36 Stream device to discard segment descriptor	79
37 Verify device operation segment descriptor	80
38 Block device with offset to or from stream device segment descriptor	81
39 Block device with offset to block device with offset segment descriptor	83
40 Write filemarks operation segment descriptor	84
41 Space operation segment descriptor	85
42 Locate operation segment descriptor	86
43 Tape device image copy segment descriptor	87
44 Register key segment descriptor	88
45 INQUIRY command	89
46 Standard INQUIRY data format	91
47 Peripheral qualifier	92
48 Peripheral device type	92
49 Version	93
50 Relationship of BQUE and CMDQUE bits	94
51 Version descriptor values	95
52 SPI-specific standard INQUIRY bits	98
53 Maximum logical device configuration table	98
54 CLOCKING field	99
55 Command support data format	100
56 SUPPORT values and meanings	100
57 LOG SELECT command	102
58 Page control field	102

59 LOG SENSE command	104
60 MODE SELECT(6) command	106
61 MODE SELECT(10) command	108
62 MODE SENSE(6) command	108
63 Page control field	109
64 Mode page code usage for all devices	109
65 MODE SENSE(10) command	111
66 PERSISTENT RESERVE IN command	112
67 PERSISTENT RESERVE IN service action codes	112
68 PERSISTENT RESERVE IN parameter data for READ KEYS	113
69 PERSISTENT RESERVE IN parameter data for READ RESERVATION	114
70 PERSISTENT RESERVE IN reservation descriptor	114
71 Persistent reservation scope codes	115
72 Persistent reservation type codes	116
73 PERSISTENT RESERVE OUT command	117
74 PERSISTENT RESERVE OUT service action codes	118
75 PERSISTENT RESERVE OUT parameter list	119
76 PERSISTENT RESERVE OUT service actions and valid parameters	120
77 PREVENT ALLOW MEDIUM REMOVAL command	121
78 PREVENT ALLOW MEDIUM REMOVAL PREVENT field	121
79 READ BUFFER command	122
80 READ BUFFER MODE field	122
81 READ BUFFER header	123
82 READ BUFFER descriptor	124
83 Buffer offset boundary	124
84 Echo buffer descriptor	125
85 RECEIVE COPY RESULTS command	126
86 RECEIVE COPY RESULTS service action codes	126
87 Parameter data for the COPY STATUS service action	127
88 COPY STATUS STATUS values	128
89 COPY STATUS TRANSFER COUNT UNITS values	128
90 Parameter data for the RECEIVE DATA service action	129
91 Parameter data for the OPERATING PARAMETERS service action	130
92 Parameter data for the FAILED SEGMENT DETAILS service action	132
93 RECEIVE DIAGNOSTIC RESULTS command	133
94 RELEASE(10) command	134
95 RELEASE(10) parameter list	135
96 RELEASE(6) command	135
97 REPORT DEVICE IDENTIFIER command	136
98 REPORT DEVICE IDENTIFIER parameter list	137
99 REPORT LUNS command	138
100 REPORT LUNS parameter list format	139
101 REQUEST SENSE command	140
102 Response codes 70h and 71h sense data format	141
103 Field pointer bytes	143
104 Actual retry count bytes	143
105 Progress indication bytes	144
106 Segment pointer bytes	144
107 Sense key descriptions	146
108 ASC and ASCQ assignments	147
109 RESERVE(10) command	158
110 RESERVE(10) ID only parameter list	159
111 RESERVE(6) command	160
112 SEND DIAGNOSTIC command	161
113 SELF-TEST CODE field values	161
114 SET DEVICE IDENTIFIER command	163
115 SET DEVICE IDENTIFIER parameter list	164
116 TEST UNIT READY command	165
117 Preferred TEST UNIT READY responses	165
118 WRITE BUFFER command	166

119 WRITE BUFFER MODE field.....	166
120 Diagnostic page format.....	170
121 Diagnostic page codes.....	171
122 Supported diagnostic pages	172
123 Log page format.....	173
124 Log parameter.....	173
125 Threshold met criteria	174
126 Log page codes	176
127 Application client page	176
128 General usage application client parameter data	177
129 Parameter control bits for general usage parameters (0000h through 0FFFh).....	177
130 Parameter code field for buffer over-run/under-run counters.....	178
131 Count basis definition.....	178
132 Cause field definition.....	178
133 Parameter codes for error counter pages	179
134 Non-medium error event parameter codes	180
135 Self-test results page	180
136 Self-test results log parameter format.....	181
137 Parameter control bits for self-test results log parameters.....	181
138 Self-test results values	182
139 Start-stop cycle counter page	183
140 Parameter control bits for date of manufacture parameter (0001h).....	184
141 Parameter control bits for accounting date parameter (0002h).....	184
142 Parameter control bits for start-stop cycle counter parameters (0003h and 0004h).....	184
143 Supported log pages.....	185
144 Temperature page	185
145 Parameter control bits for temperature parameters (0000h and 0001h).....	186
146 Mode parameter list	187
147 Mode parameter header(6)	187
148 Mode parameter header(10)	187
149 General mode parameter block descriptor.....	188
150 Direct-access device mode parameter block descriptor	189
151 Long LBA mode parameter block descriptor.....	190
152 Mode page format.....	191
153 Mode page codes	192
154 Control mode page	192
155 Task set type.....	193
156 Queue algorithm modifier.....	193
157 Queue error management (QERR) field	194
158 AUTOLOAD MODE field	195
159 Disconnect-reconnect page	196
160 Data transfer disconnect control	197
161 Informational exceptions control page	198
162 Method of reporting informational exceptions (MRIE) field.....	199
163 Power condition page	201
164 Protocol specific LUN page.....	202
165 PROTOCOL IDENTIFIER values.....	203
166 Protocol specific port page.....	203
167 Vital product data page codes	204
168 ASCII implemented operating definition.....	204
169 ASCII information page.....	205
170 Device identification page	206
171 Identification descriptor	206
172 Code set.....	206
173 Association.....	207
174 Identifier type	207
175 Relative port identifier values	207
176 Device identification page example	208
177 Supported vital product data pages	208
178 Unit serial number page.....	209

179 Commands for processor devices	210
180 RECEIVE command	211
181 SEND command	211
182 SEND command – AER data format.....	212
183 Processor diagnostic page codes	212
184 Processor log page codes	213
185 Processor vital product data page codes	213
A.1 LOG SENSE Command CDB fields	215
A.2 LOG SENSE returned parameter values.....	216
A.3 LOG SENSE save options.....	217
A.4 LOG SELECT CDB fields	218
A.5 LOG SELECT save options	219
A.6 LOG SELECT controller parameter values	220
A.7 Log Parameter Control Byte saving definitions	221
A.9 Logging exception conditions	222
A.8 Log Parameter Control Byte updating definitions	222
B.1 SBC direct access commands that are allowed in the presence of various reservations.....	225
B.2 SBC optical memory commands that are allowed in the presence of various reservations	226
B.3 SBC write-once commands that are allowed in the presence of various reservations	227
B.4 SMC commands that are allowed in the presence of various reservations	228
C.1 ASC and ASCQ assignments.....	230
C.2 Operation Codes	242
C.3 Log Page Codes.....	248
C.4 Mode Page Codes.....	249
C.5 Version descriptor assignments	251
C.6 Standard code value guidelines	255
C.7 Revision code value guidelines	257
C.8 Variable Length CDB Service Action Code Ranges.....	258
C.9 Variable Length CDB Service Action Codes Used by All Device Types	258
D.1 Vendor identification list	259

Figures

	Page
1 SCSI document relationships.....	14
2 Device server interpretation of PREEMPT service action.....	46
3 Power conditions flowchart	202