

ISO/IEC 14543-3-2 :2006-09 (E)

Information technology - Home Electronic Systems (HES) Architecture - Part 3-2: Communication layers - Transport, network and general parts of data link layer for network based control of HES Class 1

CONTENTS

- FOREWORD.....5
- INTRODUCTION.....6
- 1 Scope.....7
- 2 Normative references.....7
- 3 Terms, definitions and abbreviations.....7
 - 3.1 Terms and definitions7
 - 3.2 Abbreviations.....9
- 4 Conformance.....9
- 5 Requirements for the physical layer and independent data link layer.....9
 - 5.1 Functions of the data link layer9
 - 5.2 Possible media and their impact on layer-2 10
 - 5.3 Data link layer services 11
 - 5.3.1 Data link layer modes 11
 - 5.3.2 L_Data service..... 11
 - 5.3.3 L_SystemBroadcast service 15
 - 5.3.4 L_Poll_Data service and protocol 16
 - 5.3.5 L_Busmon service 17
 - 5.3.6 L_Service_Information service 17
 - 5.4 Data link layer protocol 18
 - 5.4.1 Protocol..... 18
 - 5.4.2 Recommendations for duplication prevention 18
 - 5.5 Parameters of layer-2 18
 - 5.6 Specific devices..... 19
 - 5.6.1 Layer-2 of a bridge..... 19
 - 5.6.2 Layer-2 of a router 19
- 6 Requirements for the network layer..... 19
 - 6.1 Functions of the network layer 19
 - 6.2 Network layer services and protocol..... 21
 - 6.2.1 Network layer protocol data unit (NPDU) 21
 - 6.2.2 Network layer services 21
 - 6.3 Parameters of the network layer..... 27
 - 6.4 Network layer state machines 27
 - 6.4.1 Overview 27
 - 6.4.2 State machine of network layer for normal devices 27
 - 6.4.3 State machine of network layer for bridges 27
 - 6.4.4 State machine of network layer for routers 28
- 7 Requirements for the transport layer 30
 - 7.1 Functionality of the transport layer 30
 - 7.2 Transport layer Protocol Data Unit (TPDU)..... 30
 - 7.3 Overview communication modes 31
 - 7.3.1 Point-to-multipoint, connection-less (multicast) communication mode 31
 - 7.3.2 Point-to-domain, connection-less (broadcast) communication mode 32
 - 7.3.3 Point-to-all-points, connection-less (SystemBroadcast) communication mode 32
 - 7.3.4 Point-to-point, connection-less communication mode 32

7.3.5	Point-to-point, connection-oriented communication mode	32
7.3.6	Algorithm for the identifier of communication	33
7.4	Transport layer services.....	33
7.4.1	General	33
7.4.2	T_Data_Group service	33
7.4.3	T_Data_Tag_Group service	34
7.4.4	T_Data_Broadcast service	36
7.4.5	T_Data_SystemBroadcast service.....	37
7.4.6	T_Data_Individual service	38
7.4.7	T_Connect service	39
7.4.8	T_Disconnect service.....	40
7.4.9	T_Data_Connected service	41
7.5	Parameters of transport layer.....	42
7.6	State machine of connection-oriented communication mode.....	43
7.6.1	General	43
7.6.2	States.....	43
7.6.3	Required actions.....	44
7.6.4	Transition table of the connection oriented transport layer state machine.....	46
7.6.5	State diagrams	53
Annex A (informative)	Examples of transport layer connection oriented state machine state diagrams	54
A.1	Connect and disconnect.....	54
A.1.1	Connect from a remote device	54
A.1.2	Connect from a remote device during an existing connection.....	54
A.1.3	Disconnect from a remote device	55
A.1.4	Connect from the local user to an existing device.....	55
A.1.5	Connect from the local user to a non existing device	55
A.1.6	Connect from the local user during an existing connection	56
A.1.7	Disconnect from the local user	56
A.1.8	Disconnect from the local user without an existing connection.....	56
A.1.9	Connection timeout.....	57
A.2	Reception of data	57
A.2.1	Reception of a correct N_Data_Individual.....	57
A.2.2	Reception of a repeated N_Data_Individual.....	58
A.2.3	Reception of data N_Data_Individual with wrong sequence number.....	58
A.2.4	Reception of data N_Data_Individual with wrong source address.....	58
A.3	Transmission of data	59
A.3.1	T_DATA-Request from the local user.....	59
A.3.2	Reception of a T_ACK_PDU with wrong sequence number.....	59
A.3.3	Reception of T_ACK_PDU with wrong connection address	60
A.3.4	Reception of T_NACK_PDU with wrong sequence number	60
A.3.5	Reception of T_NACK_PDU with correct sequence number.....	60
A.3.6	Reception of T_NACK_PDU and maximum number of repetitions is reached.....	61
A.3.7	Reception of T_NACK_PDU with wrong connection address.....	61
Bibliography	62

Figure 1 – Individual address.....	8
Figure 2 – Group address.....	8
Figure 3 – Interaction of the data link layer	10
Figure 4 – Exchange of primitives for the L_Data-Service	11
Figure 5 – Frame_format Parameter.....	14
Figure 6 – Coding of Extended Frame Format	14
Figure 7 – Interaction of the network layer (not for Bridges or Routers)	20
Figure 8 – General functionality of a router or a bridge.....	20
Figure 9 – Format of the NPDU (Example).....	21
Figure 10 – Interaction of the transport layer.....	30
Figure 11 – Format of the TPDU (Example)	31
Figure 12 – Transport control field.....	31
Table 1 – Usage of priority	13
Table 2 – Actions of the connection oriented state machine	44
Table 3 – Transition table – Style 1	46
Table 4 – Transition table – Style 1-rationalized.....	48
Table 5 – Transition table – Style 2	50
Table 6 – Transition table – Style 3	52