

ISO/IEC 14776-412 :2006-10 (E)

Information technology_ - Small Computer System Interface (SCSI)_ - Part_412: Architecture Model_-2 (SAM-2)

Contents

	Page
1 General.....	11
1.1 Scope	11
1.2 Precedence requirements	11
2 Normative reference	12
3 Definitions, symbols, abbreviations, and conventions	13
3.1 Definitions.....	13
3.2 Acronyms.....	23
3.3 Keywords.....	23
3.4 Editorial conventions	24
3.5 Numeric conventions	25
3.6 Notation conventions	25
3.6.1 Hierarchy diagram conventions	25
3.6.2 Notation for procedures and functions.....	26
3.6.3 Notation for state diagrams	27
4 SCSI Architecture Model.....	28
4.1 Introduction.....	28
4.2 The SCSI distributed service model	29
4.3 The SCSI client-server model.....	30
4.4 The SCSI structural model	31
4.5 SCSI domain	33
4.6 The service delivery subsystem	33
4.6.1 The service delivery subsystem object.....	33
4.6.2 Synchronizing client and server states	34
4.6.3 Request/Response ordering.....	34
4.7 SCSI devices	35
4.7.1 SCSI initiator device	35
4.7.2 SCSI target device.....	35
4.7.3 SCSI target/initiator device	37
4.7.4 SCSI port identifier	37
4.7.5 SCSI task router	37
4.7.6 SCSI device name.....	38
4.7.7 SCSI port name	38
4.8 Logical units.....	39
4.9 Logical unit numbers	40
4.9.1 Logical unit numbers overview	40
4.9.2 LUN 0 address.....	40
4.9.3 Single level logical unit number structure	40
4.9.4 Eight byte logical unit number structure	42
4.9.5 Logical unit addressing method.....	44
4.9.6 Peripheral device addressing method	44
4.9.7 Flat space addressing method	45
4.9.8 Extended logical unit addressing.....	45
4.9.9 Well known logical unit addressing.....	47
4.10 Tasks.....	48
4.10.1 The task object	48
4.10.2 Task tags	48
4.11 The nexus object	49

4.12 SCSI ports	50
4.12.1 SCSI port configurations.....	50
4.12.2 SCSI devices with multiple ports	50
4.12.3 Multiple port target SCSI device structure	51
4.12.4 Multiple port initiator SCSI device structure.....	52
4.12.5 Multiple port target/initiator SCSI device structure	53
4.12.6 SCSI initiator device view of a multiple port SCSI target device	53
4.12.7 SCSI target device view of a multiple port SCSI initiator device	55
4.13 Model for dependent logical units.....	56
4.14 The SCSI model for distributed communications	58
5 SCSI Command Model	61
5.1 The Execute Command remote procedure	61
5.2 Command descriptor block (CDB).....	62
5.2.1 CDB format.....	62
5.2.2 OPERATION CODE byte.....	63
5.2.3 CONTROL byte.....	64
5.3 Status	65
5.3.1 Status codes.....	65
5.3.2 Status precedence.....	66
5.4 SCSI transport protocol services in support of Execute Command.....	67
5.4.1 Overview.....	67
5.4.2 Execute Command request/confirmation SCSI transport protocol services	67
5.4.3 Data transfer SCSI transport protocol services	69
5.4.3.1 Introduction.....	69
5.4.3.2 Data-In delivery service	70
5.4.3.3 Data-Out delivery service	70
5.5 Task and command lifetimes.....	71
5.6 Task management function lifetime.....	72
5.7 Aborting tasks.....	72
5.7.1 Mechanisms that cause tasks to be aborted	72
5.7.2 When a SCSI initiator port aborts its own tasks	72
5.7.3 When a SCSI initiator port aborts tasks from other SCSI initiator ports	73
5.8 Command processing examples	73
5.8.1 Unlinked command example	73
5.8.2 Linked command example.....	74
5.9 Command processing considerations and exception conditions.....	75
5.9.1 Contingent allegiance (CA) and auto contingent allegiance (ACA).....	75
5.9.1.1 Overview.....	75
5.9.1.2 Establishing a CA or ACA.....	75
5.9.1.3 Handling tasks when neither CA or ACA is in effect.....	77
5.9.1.4 Handling new tasks from the faulted initiator port when CA or ACA is in effect	77
5.9.1.5 Handling new tasks from non-faulted initiator ports when CA or ACA is in effect	78
5.9.1.5.1 Commands permitted from non-faulted initiator ports during CA or ACA.....	78
5.9.1.5.2 Handling new tasks from non-faulted initiator ports when CA or ACA is in effect	79
5.9.1.6 Clearing a CA condition.....	81
5.9.1.7 Clearing an ACA condition	81
5.9.2 Overlapped commands	81
5.9.3 Incorrect logical unit selection	82
5.9.4 Sense data	82
5.9.4.1 Sense data introduction.....	82
5.9.4.2 Asynchronous event reporting.....	83
5.9.4.3 Autosense.....	83
5.9.5 Unit Attention condition.....	84
5.9.6 Hard reset.....	85
5.9.7 Logical unit reset	85

6 Task management functions	86
6.1 Introduction	86
6.2 ABORT TASK	87
6.3 ABORT TASK SET	87
6.4 CLEAR ACA	88
6.5 CLEAR TASK SET	88
6.6 LOGICAL UNIT RESET	89
6.7 TARGET RESET	89
6.8 WAKEUP	89
6.9 Task management SCSI transport protocol services	90
6.10 Task management function example	91
7 Task Set Management	92
7.1 Introduction to task set management	92
7.2 Controlling task set management	92
7.3 Task management events	93
7.4 Task states	93
7.4.1 Overview	93
7.4.1.1 Task state nomenclature	93
7.4.1.2 Suspended information	93
7.4.2 Enabled task state	93
7.4.3 Blocked task state	94
7.4.4 Dormant task state	94
7.4.5 Ended task state	94
7.4.6 Task states and task lifetimes	94
7.5 Task attributes	95
7.5.1 Simple task	95
7.5.2 Ordered task	95
7.5.3 Head of queue task	95
7.5.4 ACA task	95
7.6 Task state transitions	96
7.7 Task set management examples	97
7.7.1 Introduction	97
7.7.2 Head of queue tasks	98
7.7.3 Ordered tasks	99
7.7.4 ACA task	100
Annex A (informative)	
Identifiers and names for objects	101
A.1 Identifiers and names overview	101
A.2 Identifiers and names	101
A.3 SCSI transport protocol acronyms and bibliography	103
Annex B (informative)	
Terminology mapping	105
Bibliography	106

Tables

1 Single level logical unit number structure for 256 or fewer logical units.....	40
2 Single level logical unit number structure for 257 to 16 384 logical units.....	41
3 Eight byte logical unit number structure adjustments	42
4 Eight Byte logical unit number structure	43
5 Format of addressing fields.....	43
6 ADDRESS METHOD field values.....	43
7 Logical unit addressing	44
8 Peripheral device addressing.....	44
9 Flat space addressing.....	45
10 Extended logical unit addressing	46
11 LENGTH field values	46
12 Two byte extended logical unit addressing format	46
13 Four byte extended logical unit addressing format	46
14 Six byte extended logical unit addressing format.....	46
15 Eight byte extended logical unit addressing format	46
16 Logical unit extended address methods	47
17 Well known logical unit extended address format.....	47
18 Mapping nexus to SAM-2 identifiers	49
19 Command Descriptor Block (CDB) Format	63
20 OPERATION CODE byte	63
21 Group Code values	63
22 CONTROL byte	64
23 Status codes	65
24 Autosense, CA, and ACA Interactions	75
25 Blocking and aborting tasks when a CA or ACA is established	76
26 Task handling when neither CA nor ACA is in effect	77
27 Handling for new tasks from a faulted initiator port during CA.....	77
28 Handling for new tasks from a faulted initiator port during ACA.....	78
29 Handling for new tasks from non-faulted initiator ports during CA.....	79
30 Handling for new tasks from non-faulted initiator ports during ACA.....	80
31 Task Management Functions.....	86
32 Task State Nomenclature	93
33 Task attribute and state indications in examples	97
34 Dormant task blocking boundary requirements	99
A.1 Object size and support requirements.....	101
A.2 Object identifier size for each SCSI transport protocol.....	102
A.3 Object identifier format for each SCSI transport protocol.....	102
A.4 Object name size for each SCSI transport protocol	103
A.5 Object name format for each SCSI transport protocol.....	103
B.1 SAM-2 to SAM terminology mapping	105

Figures

	Page
0 SCSI document structure	9
1 Requirements precedence	11
2 Example hierarchy diagram	25
3 Example state diagram	27
4 Client-Server model	29
5 SCSI client-server model	30
6 SCSI I/O system and domain model	31
7 Overall SCSI domain model	32
8 SCSI domain model	33
9 Service delivery subsystem model	33
10 SCSI initiator device model	35
11 SCSI target device model	36
12 SCSI target/initiator device model	37
13 Logical unit model	39
14 Eight Byte logical unit number structure adjustments	42
15 SCSI device functional models	50
16 Multiple port target SCSI device structure model	51
17 Multiple port SCSI initiator device structure model	52
18 Multiple port target/initiator SCSI device structure model	53
19 SCSI target device configured in a single SCSI domain	54
20 SCSI target device configured in multiple SCSI domains	54
21 SCSI target device and SCSI initiator device configured in a single SCSI domain	55
22 Dependent logical unit model	56
23 Example of hierarchical system diagram	57
24 Protocol service reference model	58
25 Protocol service model	59
26 Request-Response ULP transaction and related LLP services	60
27 Model for Data-In and Data-Out data transfers	69
28 Command processing events	73
29 Linked command processing events	74
30 Task management processing events	91
31 Example of Dormant state task behavior	94
32 Task states	96
33 Head of queue tasks and blocking boundaries (example 1)	98
34 Head of queue tasks and blocking boundaries (example 2)	98
35 Ordered tasks and blocking boundaries	99
36 ACA task example	100