ISO/IEC 14776-412 :2006-10 (E)

Information technology_- Small Computer System Interface (SCSI)_- Part_412: Architecture Model_-2 (SAM-2)

Contents

Page

1 General 11
1.1 Scope 11
1.2 Precedence requirements 11

2 Normative reference 12

3 Definitions, symbols, abbreviations, and conventions 13
3.1 Definitions 13
3.2 Acronyms 23
3.3 Keywords 23
3.4 Editorial conventions 24
3.5 Numeric conventions 25
3.6 Notation conventions 25
3.6.1 Hierarchy diagram conventions 25
3.6.2 Notation for procedures and functions 26
3.6.3 Notation for state diagrams 27

4 SCSI Architecture Model 28
4.1 Introduction 28
4.2 The SCSI distributed service model 29
4.3 The SCSI client-server model 30
4.4 The SCSI structural model 31
4.5 SCSI domain 33
4.6 The service delivery subsystem 33
4.6.1 The service delivery subsystem object 33
4.6.2 Synchronizing client and server states 34
4.6.3 Request/Response ordering 34
4.7 SCSI devices 35
4.7.1 SCSI initiator device 35
4.7.2 SCSI target device 35
4.7.3 SCSI target/initiator device 37
4.7.4 SCSI port identifier 37
4.7.5 SCSI task router 37
4.7.6 SCSI device name 38
4.7.7 SCSI port name 38
4.8 Logical units 39
4.9 Logical unit numbers 40
4.9.1 Logical unit numbers overview 40
4.9.2 LUN 0 address 40
4.9.3 Single level logical unit number structure 40
4.9.4 Eight byte logical unit number structure 42
4.9.5 Logical unit addressing method 44
4.9.6 Peripheral device addressing method 44
4.9.7 Flat space addressing method 45
4.9.8 Extended logical unit addressing 45
4.9.9 Well known logical unit addressing 47
4.10 Tasks 48
4.10.1 The task object 48
4.10.2 Task tags 48
4.11 The nexus object 49

4.12 SCSI ports 50
4.12.1 SCSI port configurations 50
4.12.2 SCSI devices with multiple ports 50
4.12.3 Multiple port target SCSI device structure 51
4.12.4 Multiple port initiator SCSI device structure 52
4.12.5 Multiple port target/initiator SCSI device structure 53
4.12.6 SCSI initiator device view of a multiple port SCSI target device 53
4.12.7 SCSI target device view of a multiple port SCSI initiator device 55
4.13 Model for dependent logical units 56
4.14 The SCSI model for distributed communications 58

5 SCSI Command Model 61
5.1 The Execute Command remote procedure 61
5.2 Command descriptor block (CDB) 62
5.2.1 CDB format 62
5.2.2 OPERATION CODE byte 63
5.2.3 CONTROL byte 64
5.3 Status 65
5.3.1 Status codes 65
5.3.2 Status precedence 66
5.4 SCSI transport protocol services in support of Execute Command 67
5.4.1 Overview 67
5.4.2 Execute Command request/confirmation SCSI transport protocol services 67
5.4.3 Data transfer SCSI transport protocol services 69
5.4.3.1 Introduction 69
5.4.3.2 Data-In delivery service 70
5.4.3.3 Data-Out delivery service 70
5.5 Task and command lifetimes 71
5.6 Task management function lifetime 72
5.7 Aborting tasks 72
5.7.1 Mechanisms that cause tasks to be aborted 72
5.7.2 When a SCSI initiator port aborts its own tasks 72
5.7.3 When a SCSI initiator port aborts tasks from other SCSI initiator ports 73
5.8 Command processing examples 73
5.8.1 Unlinked command example 73
5.8.2 Linked command example 74
5.9 Command processing considerations and exception conditions 75
5.9.1 Contingent allegiance (CA) and auto contingent allegiance (ACA) 75
5.9.1.1 Overview 75
5.9.1.2 Establishing a CA or ACA 75
5.9.1.3 Handling tasks when neither CA or ACA is in effect 77
5.9.1.4 Handling new tasks from the faulted initiator port when CA or ACA is in effect 77
5.9.1.5 Handling new tasks from non-faulted initiator ports when CA or ACA is in effect 78
5.9.1.5.1 Commands permitted from non-faulted initiator ports during CA or ACA 78
5.9.1.5.2 Handling new tasks from non-faulted initiator ports when CA or ACA is in effect 79
5.9.1.6 Clearing a CA condition 81
5.9.1.7 Clearing an ACA condition 81
5.9.2 Overlapped commands 81
5.9.3 Incorrect logical unit selection 82
5.9.4 Sense data 82
5.9.4.1 Sense data introduction 82
5.9.4.2 Asynchronous event reporting 83
5.9.4.3 Autosense 83
5.9.5 Unit Attention condition 84
5.9.6 Hard reset 85
5.9.7 Logical unit reset 85

6 Task management functions 86
6.1 Introduction 86
6.2 ABORT TASK 87
6.3 ABORT TASK SET 87
6.4 CLEAR ACA 88
6.5 CLEAR TASK SET 88
6.6 LOGICAL UNIT RESET 89
6.7 TARGET RESET 89
6.8 WAKEUP 89
6.9 Task management SCSI transport protocol services 90
6.10 Task management function example 91

7 Task Set Management 92
7.1 Introduction to task set management 92
7.2 Controlling task set management 92
7.3 Task management events 93
7.4 Task states 93
7.4.1 Overview 93
7.4.1.1 Task state nomenclature 93
7.4.1.2 Suspended information 93
7.4.2 Enabled task state 93
7.4.3 Blocked task state 94
7.4.4 Dormant task state 94
7.4.5 Ended task state 94
7.4.6 Task states and task lifetimes 94
7.5 Task attributes 95
7.5.1 Simple task 95
7.5.2 Ordered task 95
7.5.3 Head of queue task 95
7.5.4 ACA task 95
7.6 Task state transitions 96
7.7 Task set management examples 97
7.7.1 Introduction 97
7.7.2 Head of queue tasks 98
7.7.3 Ordered tasks 99
7.7.4 ACA task 100

Annex A (informative)
Identifiers and names for objects 101
A.1 Identifiers and names overview 101
A.2 Identifiers and names 101
A.3 SCSI transport protocol acronyms and bibliography 103

Annex B (informative)
Terminology mapping 105

Bibliography 106

Tables

1 Single level logical unit number structure for 256 or fewer logical units 40
2 Single level logical unit number structure for 257 to 16 384 logical units 41
3 Eight byte logical unit number structure adjustments 42
4 Eight Byte logical unit number structure 43
5 Format of addressing fields 43
6 ADDRESS METHOD field values 43
7 Logical unit addressing 44
8 Peripheral device addressing 44
9 Flat space addressing 45
10 Extended logical unit addressing 46
11 LENGTH field values 46
12 Two byte extended logical unit addressing format 46
13 Four byte extended logical unit addressing format 46
14 Six byte extended logical unit addressing format 46
15 Eight byte extended logical unit addressing format 46
16 Logical unit extended address methods 47
17 Well known logical unit extended address format 47
18 Mapping nexus to SAM-2 identifiers 49
19 Command Descriptor Block (CDB) Format 63
20 OPERATION CODE byte 63
21 Group Code values 63
22 CONTROL byte 64
23 Status codes 65
24 Autosense, CA, and ACA Interactions 75
25 Blocking and aborting tasks when a CA or ACA is established 76
26 Task handling when neither CA nor ACA is in effect 77
27 Handling for new tasks from a faulted initiator port during CA 77
28 Handling for new tasks from a faulted initiator port during ACA 78
29 Handling for new tasks from non-faulted initiator ports during CA 79
30 Handling for new tasks from non-faulted initiator ports during ACA 80
31 Task Management Functions 86
32 Task State Nomenclature 93
33 Task attribute and state indications in examples 97
34 Dormant task blocking boundary requirements 99
A.1 Object size and support requirements 101
A.2 Object identifier size for each SCSI transport protocol 102
A.3 Object identifier format for each SCSI transport protocol 102
A.4 Object name size for each SCSI transport protocol 103
A.5 Object name format for each SCSI transport protocol 103
B.1 SAM-2 to SAM terminology mapping 105

Figures

Page
0 SCSI document structure 9
1 Requirements precedence 11
2 Example hierarchy diagram 25
3 Example state diagram 27
4 Client-Server model 29
5 SCSI client-server model 30
6 SCSI I/O system and domain model 31
7 Overall SCSI domain model 32
8 SCSI domain model 33
9 Service delivery subsystem model 33
10 SCSI initiator device model 35
11 SCSI target device model 36
12 SCSI target/initiator device model 37
13 Logical unit model 39
14 Eight Byte logical unit number structure adjustments 42
15 SCSI device functional models 50
16 Multiple port target SCSI device structure model 51
17 Multiple port SCSI initiator device structure model 52
18 Multiple port target/initiator SCSI device structure model 53
19 SCSI target device configured in a single SCSI domain 54
20 SCSI target device configured in multiple SCSI domains 54
21 SCSI target device and SCSI initiator device configured in a single SCSI domain 55
22 Dependent logical unit model 56
23 Example of hierarchical system diagram 57
24 Protocol service reference model 58
25 Protocol service model 59
26 Request-Response ULP transaction and related LLP services 60
27 Model for Data-In and Data-Out data transfers 69
28 Command processing events 73
29 Linked command processing events 74
30 Task management processing events 91
31 Example of Dormant state task behavior 94
32 Task states 96
33 Head of queue tasks and blocking boundaries (example 1) 98
34 Head of queue tasks and blocking boundaries (example 2) 98
35 Ordered tasks and blocking boundaries 99
36 ACA task example 100