

# ISO/IEC 14776-412 :2006-10 (E)

## Information technology\_ - Small Computer System Interface (SCSI)\_ - Part\_412: Architecture Model\_-2 (SAM-2)

---

### Contents

	Page
1 General.....	11
1.1 Scope .....	11
1.2 Precedence requirements .....	11
2 Normative reference .....	12
3 Definitions, symbols, abbreviations, and conventions .....	13
3.1 Definitions.....	13
3.2 Acronyms.....	23
3.3 Keywords.....	23
3.4 Editorial conventions .....	24
3.5 Numeric conventions .....	25
3.6 Notation conventions .....	25
3.6.1 Hierarchy diagram conventions .....	25
3.6.2 Notation for procedures and functions.....	26
3.6.3 Notation for state diagrams .....	27
4 SCSI Architecture Model.....	28
4.1 Introduction.....	28
4.2 The SCSI distributed service model.....	29
4.3 The SCSI client-server model.....	30
4.4 The SCSI structural model .....	31
4.5 SCSI domain .....	33
4.6 The service delivery subsystem .....	33
4.6.1 The service delivery subsystem object.....	33
4.6.2 Synchronizing client and server states .....	34
4.6.3 Request/Response ordering.....	34
4.7 SCSI devices.....	35
4.7.1 SCSI initiator device .....	35
4.7.2 SCSI target device.....	35
4.7.3 SCSI target/initiator device .....	37
4.7.4 SCSI port identifier .....	37
4.7.5 SCSI task router .....	37
4.7.6 SCSI device name.....	38
4.7.7 SCSI port name .....	38
4.8 Logical units.....	39
4.9 Logical unit numbers .....	40
4.9.1 Logical unit numbers overview .....	40
4.9.2 LUN 0 address.....	40
4.9.3 Single level logical unit number structure .....	40
4.9.4 Eight byte logical unit number structure .....	42
4.9.5 Logical unit addressing method.....	44
4.9.6 Peripheral device addressing method .....	44
4.9.7 Flat space addressing method .....	45
4.9.8 Extended logical unit addressing.....	45
4.9.9 Well known logical unit addressing.....	47
4.10 Tasks.....	48
4.10.1 The task object .....	48
4.10.2 Task tags .....	48
4.11 The nexus object .....	49

4.12 SCSI ports .....	50
4.12.1 SCSI port configurations.....	50
4.12.2 SCSI devices with multiple ports .....	50
4.12.3 Multiple port target SCSI device structure .....	51
4.12.4 Multiple port initiator SCSI device structure.....	52
4.12.5 Multiple port target/initiator SCSI device structure .....	53
4.12.6 SCSI initiator device view of a multiple port SCSI target device .....	53
4.12.7 SCSI target device view of a multiple port SCSI initiator device .....	55
4.13 Model for dependent logical units.....	56
4.14 The SCSI model for distributed communications .....	58
5 SCSI Command Model .....	61
5.1 The Execute Command remote procedure .....	61
5.2 Command descriptor block (CDB).....	62
5.2.1 CDB format.....	62
5.2.2 OPERATION CODE byte.....	63
5.2.3 CONTROL byte.....	64
5.3 Status .....	65
5.3.1 Status codes.....	65
5.3.2 Status precedence.....	66
5.4 SCSI transport protocol services in support of Execute Command.....	67
5.4.1 Overview.....	67
5.4.2 Execute Command request/confirmation SCSI transport protocol services .....	67
5.4.3 Data transfer SCSI transport protocol services .....	69
5.4.3.1 Introduction.....	69
5.4.3.2 Data-In delivery service .....	70
5.4.3.3 Data-Out delivery service .....	70
5.5 Task and command lifetimes.....	71
5.6 Task management function lifetime.....	72
5.7 Aborting tasks.....	72
5.7.1 Mechanisms that cause tasks to be aborted .....	72
5.7.2 When a SCSI initiator port aborts its own tasks .....	72
5.7.3 When a SCSI initiator port aborts tasks from other SCSI initiator ports .....	73
5.8 Command processing examples .....	73
5.8.1 Unlinked command example .....	73
5.8.2 Linked command example.....	74
5.9 Command processing considerations and exception conditions.....	75
5.9.1 Contingent allegiance (CA) and auto contingent allegiance (ACA).....	75
5.9.1.1 Overview.....	75
5.9.1.2 Establishing a CA or ACA.....	75
5.9.1.3 Handling tasks when neither CA or ACA is in effect.....	77
5.9.1.4 Handling new tasks from the faulted initiator port when CA or ACA is in effect .....	77
5.9.1.5 Handling new tasks from non-faulted initiator ports when CA or ACA is in effect .....	78
5.9.1.5.1 Commands permitted from non-faulted initiator ports during CA or ACA.....	78
5.9.1.5.2 Handling new tasks from non-faulted initiator ports when CA or ACA is in effect .....	79
5.9.1.6 Clearing a CA condition.....	81
5.9.1.7 Clearing an ACA condition .....	81
5.9.2 Overlapped commands .....	81
5.9.3 Incorrect logical unit selection .....	82
5.9.4 Sense data .....	82
5.9.4.1 Sense data introduction.....	82
5.9.4.2 Asynchronous event reporting.....	83
5.9.4.3 Autosense.....	83
5.9.5 Unit Attention condition.....	84
5.9.6 Hard reset.....	85
5.9.7 Logical unit reset .....	85

6 Task management functions .....	86
6.1 Introduction .....	86
6.2 ABORT TASK .....	87
6.3 ABORT TASK SET .....	87
6.4 CLEAR ACA .....	88
6.5 CLEAR TASK SET .....	88
6.6 LOGICAL UNIT RESET .....	89
6.7 TARGET RESET .....	89
6.8 WAKEUP .....	89
6.9 Task management SCSI transport protocol services .....	90
6.10 Task management function example .....	91
7 Task Set Management .....	92
7.1 Introduction to task set management .....	92
7.2 Controlling task set management .....	92
7.3 Task management events .....	93
7.4 Task states .....	93
7.4.1 Overview .....	93
7.4.1.1 Task state nomenclature .....	93
7.4.1.2 Suspended information .....	93
7.4.2 Enabled task state .....	93
7.4.3 Blocked task state .....	94
7.4.4 Dormant task state .....	94
7.4.5 Ended task state .....	94
7.4.6 Task states and task lifetimes .....	94
7.5 Task attributes .....	95
7.5.1 Simple task .....	95
7.5.2 Ordered task .....	95
7.5.3 Head of queue task .....	95
7.5.4 ACA task .....	95
7.6 Task state transitions .....	96
7.7 Task set management examples .....	97
7.7.1 Introduction .....	97
7.7.2 Head of queue tasks .....	98
7.7.3 Ordered tasks .....	99
7.7.4 ACA task .....	100
Annex A (informative)	
Identifiers and names for objects .....	101
A.1 Identifiers and names overview .....	101
A.2 Identifiers and names .....	101
A.3 SCSI transport protocol acronyms and bibliography .....	103
Annex B (informative)	
Terminology mapping .....	105
Bibliography .....	106

## Tables

1 Single level logical unit number structure for 256 or fewer logical units.....	40
2 Single level logical unit number structure for 257 to 16 384 logical units.....	41
3 Eight byte logical unit number structure adjustments .....	42
4 Eight Byte logical unit number structure .....	43
5 Format of addressing fields.....	43
6 ADDRESS METHOD field values.....	43
7 Logical unit addressing .....	44
8 Peripheral device addressing.....	44
9 Flat space addressing.....	45
10 Extended logical unit addressing .....	46
11 LENGTH field values .....	46
12 Two byte extended logical unit addressing format .....	46
13 Four byte extended logical unit addressing format .....	46
14 Six byte extended logical unit addressing format.....	46
15 Eight byte extended logical unit addressing format .....	46
16 Logical unit extended address methods .....	47
17 Well known logical unit extended address format.....	47
18 Mapping nexus to SAM-2 identifiers .....	49
19 Command Descriptor Block (CDB) Format .....	63
20 OPERATION CODE byte .....	63
21 Group Code values .....	63
22 CONTROL byte .....	64
23 Status codes .....	65
24 Autosense, CA, and ACA Interactions .....	75
25 Blocking and aborting tasks when a CA or ACA is established .....	76
26 Task handling when neither CA nor ACA is in effect .....	77
27 Handling for new tasks from a faulted initiator port during CA.....	77
28 Handling for new tasks from a faulted initiator port during ACA.....	78
29 Handling for new tasks from non-faulted initiator ports during CA.....	79
30 Handling for new tasks from non-faulted initiator ports during ACA.....	80
31 Task Management Functions.....	86
32 Task State Nomenclature .....	93
33 Task attribute and state indications in examples .....	97
34 Dormant task blocking boundary requirements .....	99
A.1 Object size and support requirements.....	101
A.2 Object identifier size for each SCSI transport protocol.....	102
A.3 Object identifier format for each SCSI transport protocol.....	102
A.4 Object name size for each SCSI transport protocol .....	103
A.5 Object name format for each SCSI transport protocol.....	103
B.1 SAM-2 to SAM terminology mapping .....	105

## Figures

	Page
0 SCSI document structure .....	9
1 Requirements precedence .....	11
2 Example hierarchy diagram .....	25
3 Example state diagram .....	27
4 Client-Server model .....	29
5 SCSI client-server model .....	30
6 SCSI I/O system and domain model .....	31
7 Overall SCSI domain model .....	32
8 SCSI domain model .....	33
9 Service delivery subsystem model .....	33
10 SCSI initiator device model .....	35
11 SCSI target device model .....	36
12 SCSI target/initiator device model .....	37
13 Logical unit model .....	39
14 Eight Byte logical unit number structure adjustments .....	42
15 SCSI device functional models .....	50
16 Multiple port target SCSI device structure model .....	51
17 Multiple port SCSI initiator device structure model .....	52
18 Multiple port target/initiator SCSI device structure model .....	53
19 SCSI target device configured in a single SCSI domain .....	54
20 SCSI target device configured in multiple SCSI domains .....	54
21 SCSI target device and SCSI initiator device configured in a single SCSI domain .....	55
22 Dependent logical unit model .....	56
23 Example of hierarchical system diagram .....	57
24 Protocol service reference model .....	58
25 Protocol service model .....	59
26 Request-Response ULP transaction and related LLP services .....	60
27 Model for Data-In and Data-Out data transfers .....	69
28 Command processing events .....	73
29 Linked command processing events .....	74
30 Task management processing events .....	91
31 Example of Dormant state task behavior .....	94
32 Task states .....	96
33 Head of queue tasks and blocking boundaries (example 1) .....	98
34 Head of queue tasks and blocking boundaries (example 2) .....	98
35 Ordered tasks and blocking boundaries .....	99
36 ACA task example .....	100