

ISO 9364:2017-11 (E)

Steel sheet, 55 % aluminium-zinc alloy-coated by the continuous hot-dip process, of commercial, drawing and structural qualities

| Contents | | Page |
|-----------------|--|-------------|
| Foreword | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Dimensions | 2 |
| 5 | Conditions of manufacture | 3 |
| 5.1 | Steelmaking | 3 |
| 5.2 | Chemical composition | 3 |
| 5.3 | Chemical analysis | 3 |
| 5.3.1 | Heat analysis | 3 |
| 5.3.2 | Product analysis | 3 |
| 5.4 | Mechanical properties | 4 |
| 5.4.1 | Commercial and drawing quality | 4 |
| 5.4.2 | Structural quality | 5 |
| 5.5 | Coating | 6 |
| 5.5.1 | Coating mass | 6 |
| 5.5.2 | Coating adherence | 7 |
| 5.6 | Weldability | 7 |
| 5.7 | Painting | 7 |
| 5.8 | Coating finish condition | 7 |
| 5.9 | Surface treatment | 8 |
| 5.9.1 | Mill passivation | 8 |
| 5.9.2 | Oiling | 8 |
| 5.10 | Coated coil joining | 8 |
| 5.11 | Dimensional and shape tolerances | 8 |
| 6 | Sampling | 8 |
| 6.1 | Tensile test | 8 |
| 6.2 | Coating tests | 8 |
| 6.2.1 | Coating mass | 8 |
| 6.2.2 | Triple-spot test | 8 |
| 6.2.3 | Single-spot test | 9 |
| 6.2.4 | Coating adherence | 9 |
| 7 | Test methods | 9 |
| 7.1 | Tensile test | 9 |
| 7.2 | Coating properties | 9 |
| 7.2.1 | Coating mass | 9 |
| 7.2.2 | Coating adherence | 9 |
| 8 | Designation system | 9 |
| 8.1 | General | 9 |
| 8.2 | Coating designation | 9 |
| 8.3 | Coating mass | 10 |
| 8.4 | Coating finish condition | 10 |
| 8.5 | Surface treatment | 10 |

| | | |
|-----|---|----|
| 8.6 | Base-metal quality | 10 |
| 8.7 | Examples | 10 |
| 9 | Retests | 11 |
| 9.1 | Machining and flaws | 11 |
| 9.2 | Elongation | 11 |
| 9.3 | Additional tests | 11 |
| 10 | Resubmission | 11 |
| 11 | Workmanship | 12 |
| 12 | Inspection and acceptance | 12 |
| 13 | Coil size | 12 |
| 14 | Marking | 12 |
| 15 | Information to be supplied by the purchaser | 13 |
| | Annex A (normative) Orders requiring base-metal thickness | 14 |
| | Bibliography | 15 |