

DIN EN ISO 683-3:2019-04 (E)

Heat-treatable steels, alloy steels and free-cutting steels - Part 3: Case-hardening steels (ISO 683-3:2019)

Contents		Page
European foreword		4
Foreword		5
1	Scope	6
2	Normative references	6
3	Terms and definitions	7
4	Classification and designation	8
4.1	Classification	8
4.2	Designation	8
5	Information to be supplied by the purchaser	8
5.1	Mandatory information	8
5.2	Options and/or supplementary or special requirements	8
5.3	Ordering example	9
6	Manufacturing process	9
6.1	General	9
6.2	Deoxidation	9
6.3	Heat-treatment condition and surface condition at delivery	9
6.3.1	Normal condition at delivery	9
6.3.2	Particular heat-treatment condition	9
6.3.3	Particular surface conditions	9
6.4	Traceability of the cast	9
7	Requirements	10
7.1	Chemical composition, hardness and hardenability	10
7.1.1	General	10
7.1.2	Hardenability	10
7.1.3	Chemical composition	10
7.2	Machinability	10
7.3	Cold shearability	10
7.4	Grain size	10
7.5	Non-metallic inclusions	11
7.5.1	Microscopic inclusions	11
7.5.2	Macroscopic inclusions	11
7.6	Internal soundness	11
7.7	Surface condition	11
7.8	Shape, dimensions and tolerances	11
8	Inspection	12
8.1	Testing procedures and types of documents	12
8.2	Frequency of testing	12
8.3	Tests to be carried out for specific inspection	12
8.3.1	General	12
8.3.2	Visual and dimensional inspection	12
9	Test methods	12

9.1	Chemical analysis	12
9.2	Hardness and hardenability tests	13
9.2.1	Verification of hardness	13
9.2.2	Verification of hardenability	13
9.3	Retests	13
10	Marking	13
Annex A (normative) Supplementary or special requirements		35
A.1	Fine grain steel	35
A.2	Non-destructive tests	35
A.3	Product analysis	35
A.4	Reduction ratio and deformation ratio	35
A.5	Special agreements for marking	36
Annex B (informative) Designation of steels given in this document and of comparable grades covered in various designation systems		37
Annex C (informative) Dimensional standards applicable to products complying with this document		39
Annex D (informative) Classification of steel grades according to minimum tensile strength as a function of diameter after hardening and tempering at 200 °C		40
Bibliography		41