

# ISO 5000:2019 (E)

## Steel sheet, aluminium-silicon alloy-coated by the continuous hot-dip process, of commercial and drawing qualities

---

### Contents

	Foreword
1	Scope
2	Normative references
3	Terms and definitions
4	Dimensions
5	Conditions of manufacture
5.1	Steelmaking
5.2	Chemical composition
5.3	Chemical analysis
5.3.1	Heat analysis
5.3.2	Product analysis
5.4	Mechanical properties
5.4.1	Ordering conditions
5.4.2	Fabrication qualities
5.4.3	Interstitial free steel
5.5	Coating
5.5.1	Silicon content
5.5.2	Coating mass
5.5.3	Coating adherence
5.6	Weldability
5.7	Coating finish condition
5.8	Surface treatment
5.8.1	Mill passivation
5.8.2	Oiling
5.9	Coated coil joining
5.10	Dimensional and shape tolerances
6	Sampling
6.1	Tensile test
6.2	Coating tests
6.2.1	Coating mass
6.2.2	Triple-spot test
6.2.3	Single-spot test
6.2.4	Coating adherence
7	Test methods
7.1	Tensile test
7.2	Coating properties
7.2.1	Coating mass
7.2.2	Coating adherence
8	Designation system
8.1	General
8.2	Coating designation
8.3	Coating mass
8.4	Coating finish condition
8.5	Surface treatment
8.6	Base-metal quality

8.7	Examples
9	Retests
9.1	Machining and flaws
9.2	Elongation
9.3	Additional tests
10	Resubmission
11	Workmanship
12	Inspection and acceptance
13	Coil size
14	Marking
15	Information to be supplied by the purchaser
Annex A	(normative) Orders requiring base-metal thickness
Annex B	(normative) Determination of mass of coating on aluminium-silicon alloy-coated steel sheet
B.1	General
B.2	Procedure A: stripping with hydrochloric acid
B.2.1	Apparatus
B.2.2	Reagents
B.2.3	Sampling
B.2.4	Procedure
B.2.5	Expression of results
B.3	Procedure B: stripping with inhibited hydrochloric acid
B.3.1	Principle
B.3.2	Apparatus
B.3.3	Reagents
B.3.4	Sampling
B.3.5	Procedure
B.3.6	Expression of results

Page count: 16