

# ISO 4992-2:2020-03 (E)

## Steel castings - Ultrasonic testing - Part 2: Steel castings for highly stressed components

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>4</b>	<b>Requirements .....</b>	<b>3</b>
4.1	Order information .....	3
4.2	Extent of testing .....	3
4.3	Maximum acceptable size of discontinuities .....	3
4.3.1	General .....	3
4.3.2	Indications without measurable dimensions .....	3
4.3.3	Indications with measurable dimensions .....	3
4.4	Qualification of personnel .....	5
4.5	Wall-section zones .....	5
4.6	Classes .....	5
<b>5</b>	<b>Testing .....</b>	<b>5</b>
5.1	Principles .....	5
5.2	Material .....	5
5.3	Test equipment, coupling fluid, test sensitivity and resolution of detection .....	6
5.3.1	Ultrasonic instrument .....	6
5.3.2	Probes and transducer frequencies .....	6
5.3.3	Checking of the ultrasonic test equipment .....	6
5.3.4	Coupling fluid .....	6
5.3.5	Test sensitivity and resolution of detection .....	7
5.4	Preparation of casting surfaces for testing .....	7
5.5	Test procedure .....	7
5.5.1	General .....	7
5.5.2	Range setting .....	8
5.5.3	Sensitivity setting .....	8
5.5.4	Consideration of various types of indications .....	9
5.5.5	Recording and recording limits .....	9
5.5.6	Assessment of indications to be recorded .....	9
5.5.7	Characterization and sizing of discontinuities .....	10
5.6	Test report .....	10
Annex A (normative) Resolution of detection of the instrument-probe combination .....		18
Annex B (informative) Sound-beam diameters .....		19
Annex C (informative) Types of indications generated by typical discontinuities .....		21
Bibliography .....		33