

# DIN 488-6:2024-09 (E)

## Reinforcing steel - Part 6: Assessment of conformity

---

| <b>Contents</b>   |  | <b>Page</b> |
|---|--|-------------|
| Foreword .....  |  | 5           |
| <b>1</b> <b>Scope</b> .....   |  | <b>6</b>    |
| <b>2</b> <b>Normative references</b> .....  |  | <b>6</b>    |
| <b>3</b> <b>Terms and definitions</b> .....   |  | <b>6</b>    |
| <b>4</b> <b>Symbols</b> .....   |  | <b>7</b>    |
| <b>5</b> <b>Assessment of conformity</b> .....  |  | <b>8</b>    |
| 5.1 <b>General</b> .....  |  | <b>8</b>    |
| 5.2 <b>Factory production control (FPC)</b> .....   |  | <b>8</b>    |
| 5.2.1 <b>General</b> .....  |  | <b>8</b>    |
| 5.2.2 <b>Sampling and testing of finished products</b> .....  |  | <b>9</b>    |
| 5.2.3 <b>Assessment of test results</b> .....   |  | <b>12</b>   |
| 5.2.4 <b>Traceability</b> .....   |  | <b>14</b>   |
| 5.2.5 <b>Determination of long-term quality level</b> .....   |  | <b>15</b>   |
| 5.3 <b>Initial type testing</b> .....   |  | <b>16</b>   |
| 5.3.1 <b>General</b> .....  |  | <b>16</b>   |
| 5.3.2 <b>Test scope (standard properties and fatigue strength)</b> .....  |  | <b>16</b>   |
| 5.3.3 <b>Performing fatigue tests</b> .....   |  | <b>19</b>   |
| 5.3.4 <b>Assessment, reporting and measures</b> .....   |  | <b>20</b>   |
| 5.4 <b>Third-party inspection of factory production control and random testing</b> .....  |  | <b>23</b>   |
| 5.4.1 <b>General</b> .....  |  | <b>23</b>   |
| 5.4.2 <b>Random testing of test specimens taken in the works</b> .....  |  | <b>23</b>   |
| 5.4.3 <b>Assessment, reporting and measures</b> .....   |  | <b>29</b>   |
| <b>6</b> <b>Test methods</b> .....  |  | <b>30</b>   |
| 6.1 <b>Test conditions</b> .....  |  | <b>30</b>   |
| 6.2 <b>Bars, coils, reinforcing wire and decoiled products</b> .....  |  | <b>30</b>   |
| 6.3 <b>Welded fabric</b> .....  |  | <b>30</b>   |
| 6.4 <b>Lattice girders</b> .....  |  | <b>31</b>   |
| <b>7</b> <b>Certification</b> .....   |  | <b>31</b>   |
| <b>Annex A</b> (normative) <b>Requirements for copper contents <math>0,60 \% &lt; Cu \leq 0,80 \%</math> according to the cast analysis (in connection with DIN 488-1:2009-08, Table 2)</b> ..... |  | <b>32</b>   |
| <b>Annex B</b> (normative) <b>Method for measurement of shear force of welded joints in lattice girders — Shear test on welded intersections</b> .....  |  | <b>34</b>   |
| B.1 <b>General</b> .....  |  | <b>34</b>   |
| B.2 <b>Method 1</b> .....   |  | <b>34</b>   |
| B.3 <b>Method 2</b> .....   |  | <b>35</b>   |
| <b>Annex C</b> (normative) <b>Method for determining the corrected relative rib area in the case of decoiled products</b> .....   |  | <b>36</b>   |
| C.1 <b>General</b> .....  |  | <b>36</b>   |
| C.2 <b>Calculated value of the corrected relative rib area</b> .....  |  | <b>36</b>   |
| C.2.1 <b>General</b> .....  |  | <b>36</b>   |
| C.2.2 <b>Condition for using the corrected relative rib area</b> .....  |  | <b>36</b>   |
| C.2.3 <b>Determining the calculated value of the corrected relative rib area</b> .....  |  | <b>37</b>   |
| <b>Annex D</b> (normative) <b>Tables for determining the acceptance constant <math>k</math></b> .....   |  | <b>39</b>   |
| <b>Bibliography</b> .....   |  | <b>46</b>   |

## Figures

|   |    |
|---|----|
| Figure B.1 — Principle of the shear test using method 1 ..... | 34 |
| Figure B.2 — Principle of the shear test using method 2 ..... | 35 |

## Tables

|  |    |
|--|----|
| Table 1 — Symbols .....  | 7  |
| Table 2 — Assignment of the tasks for assessing the conformity of the reinforcing steel with the requirements of this standard.....  | 8  |
| Table 3 — Number of test specimens for welded fabrics.....   | 10 |
| Table 4 — Number of test specimens for lattice girders.....  | 11 |
| Table 5 — Type and number of tests for the initial type testing of bars, coils and reinforcing wire coils and bars .....   | 16 |
| Table 6 — Number of samples for the standard properties of bars, coils, reinforcing wire coils and bars and decoiled products in the initial type testing.....   | 17 |
| Table 7 — Type and number of tests for the initial type testing of welded fabric.....  | 18 |
| Table 8 — Number of samples for the standard properties of welded fabric in the initial type testing.....  | 18 |
| Table 9 — Number of samples for the standard properties of lattice girders in initial type testing....   | 19 |
| Table 10 — Type and number of tests for the third-party inspection of bars, coils and reinforcing wire bars and coils .....  | 24 |
| Table 11 — Testing of the standard properties of bars, coils and reinforcing wire bars and coils in the third-party inspection.....  | 24 |
| Table 12 — Number of samples for the standard properties of decoiled products in the third-party inspection .....  | 25 |
| Table 13 — Type and number of tests for the third-party inspection of welded fabric.....   | 26 |
| Table 14 — Testing of the standard properties of welded fabric in the third-party inspection .....   | 27 |
| Table 15 — Testing the standard properties of lattice girders in the third-party inspection .....  | 28 |
| Table 16 — Conditions for determining the mechanical properties.....   | 30 |
| Table A.1 — Additional test rules to be applied in the factory production control for reinforcing steels with a copper content between $0,60 \% < Cu \leq 0,80 \%$ according to the cast analysis..... | 32 |

|  |           |
|--|-----------|
| <b>Table D.1 — Acceptance constant <math>k</math> for <math>R_e</math>, <math>F_s</math>, <math>F_j</math>, <math>\Delta_{An}</math> and <math>f_R</math> and as a function of the number (<math>n</math>) of test results in the case of unknown standard deviation (for a permitted percentage of rejects of 5 % [<math>p = 0,95</math>] at a probability of 90 %) .....</b>   | <b>39</b> |
| <b>Table D.2 — Acceptance constant <math>k</math> for <math>A_{gtv} R_{e,ist}/R_{e,nenn}</math> and <math>R_m/R_e</math> and as a function of the number (<math>n</math>) of test results in the case of unknown standard deviation (for a permitted percentage of rejects of 10 % [<math>p = 0,90</math>] at a probability of 90 %) .....</b>   | <b>40</b> |
| <b>Table D.3 — Acceptance constant <math>k</math> for <math>R_e</math>, <math>F_s</math>, <math>F_j</math>, <math>\Delta_{An}</math> and <math>f_R</math> and as a function of the number (<math>n</math>) of test results in the case of known standard deviation (for a permitted percentage of rejects of 10 % [<math>p = 0,90</math>] at a probability of 90 %) .....</b>  | <b>41</b> |
| <b>Table D.4 — Acceptance constant <math>k</math> for <math>A_{gtv} R_{e,ist}/R_{e,nenn}</math> and <math>R_m/R_e</math> and as a function of the number (<math>n</math>) of test results in the case of known standard deviation (for a permitted percentage of rejects of 5 % [<math>p = 0,95</math>] at a probability of 90 %) .....</b>  | <b>42</b> |
| <b>Table D.5 — Acceptance constant <math>k</math> for <math>2\sigma_a</math> as a function of the number (<math>n</math>) of test results (for a permitted percentage of rejects of 5 % [<math>p = 0,95</math>] at a probability of 75 % according to ISO 12491:1997) .....</b>  | <b>43</b> |
| <b>Table D.6 — Acceptance constant <math>k</math> for <math>R_e</math>, <math>F_s</math> and <math>F_j</math> as a function of the number (<math>n</math>) of test results in the case of unknown standard deviation — valid for reinforcing steel bars, welded fabric, lattice girders and straightened reinforcing wire (for a permitted percentage of rejects of 5 % [<math>p = 0,95</math>] at a probability of 25 %) — ISO 12491:1997 .....</b>             | <b>43</b> |
| <b>Table D.7 — Acceptance constant <math>k</math> for <math>A_{gtv} R_{e,ist}/R_{e,nenn}</math> and <math>R_m/R_e</math> as a function of the number (<math>n</math>) of test results in the case of unknown standard deviation — valid for reinforcing steel bars, welded fabric, lattice girders and straightened reinforcing wire (for a permitted percentage of rejects of 10 % [<math>p = 0,90</math>] at a probability of 25 %) — ISO 12491:1997 .....</b> | <b>44</b> |
| <b>Table D.8 — Acceptance constant <math>k</math> for <math>R_e</math>, <math>F_s</math> and <math>F_j</math> as a function of the number (<math>n</math>) of test results in the case of unknown standard deviation — valid for reinforcing steel coils and reinforcing wire coils (for a permitted percentage of rejects of 5 % [<math>p = 0,95</math>] at a probability of 50 %) — ISO 12491:1997 .....</b>   | <b>44</b> |
| <b>Table D.9 — Acceptance constant <math>k</math> for <math>A_{gtv} R_{e,ist}/R_{e,nenn}</math> and <math>R_m/R_e</math> as a function of the number (<math>n</math>) of test results in the case of unknown standard deviation, valid for reinforcing steel coils and reinforcing wire coils (for a permitted percentage of rejects of 10 % [<math>p = 0,90</math>] at a probability of 50 %) — ISO 12491:1997 .....</b>  | <b>45</b> |