

ISO 6934-2:2024-12 (E)

Steel for the prestressing of concrete - Part 2: Cold-drawn wire

Contents

Page

| | |
|--|-----------|
| Foreword..... | iv |
| 1 Scope..... | 1 |
| 2 Normative references..... | 1 |
| 3 Terms and definitions..... | 1 |
| 4 Test methods..... | 1 |
| 5 Conditions of manufacture..... | 1 |
| 6 Surface configuration..... | 1 |
| 7 Properties..... | 2 |
| 7.1 General..... | 2 |
| 7.2 Dimensions and properties of mill coil wire..... | 2 |
| 7.2.1 Dimensions, masses and tensile properties..... | 2 |
| 7.2.2 Elongation and ductility..... | 2 |
| 7.2.3 Relaxation..... | 3 |
| 7.2.4 Fatigue..... | 3 |
| 7.2.5 Torsion..... | 3 |
| 7.2.6 Stress corrosion test..... | 3 |
| 7.3 Dimensions and properties of stress-relieved wire..... | 4 |
| 7.3.1 Dimensions, masses and tensile properties..... | 4 |
| 7.3.2 Elongation and ductility..... | 4 |
| 7.3.3 Relaxation..... | 5 |
| 7.3.4 Fatigue..... | 5 |
| 7.3.5 Stress corrosion test..... | 6 |
| 8 Designation..... | 6 |
| 9 Delivery conditions..... | 6 |
| 9.1 General..... | 6 |
| 9.2 Coil size..... | 6 |
| 9.3 Curvature of stress-relieved wires..... | 7 |
| Annex A (informative) Examples of indentations, crimps and spiral ribs..... | 8 |
| Annex B (informative) Recommended internal diameter of coil..... | 11 |