

DIN EN ISO 10684:2011-09 (E)

Fasteners - Hot dip galvanized coatings (ISO 10684:2004 + Cor. 1:2008)

Contents		Page
Foreword		3
1	Scope	4
2	Normative references	4
3	Terms and definitions	5
4	Materials	6
4.1	Raw material of parts	6
4.2	Zinc	6
5	Hot dip galvanizing procedures and precautions	6
5.1	Stress relief	6
5.2	Cleaning and pickling	6
5.3	Baking	6
5.4	Fluxing	6
5.5	Hot dip galvanizing	6
5.6	Spinning and quenching	7
5.7	Special requirements for nuts	7
5.8	Post-treatment	7
6	Requirements on thread tolerances and additional marking	7
6.1	General	7
6.2	Requirements and precautions in assembling hot dip galvanized threaded fasteners	7
6.3	Special requirements for marking when supplying fasteners in sealed containers	11
7	Mechanical properties of nuts tapped oversize and undersize threaded bolts, screws and studs	11
8	Coating requirements	11
8.1	Appearance of zinc coating	11
8.2	Considerations for hot dip galvanized washers	11
8.3	Zinc coating thickness	11
8.4	Adhesion of zinc coating	11
9	Lubrication	12
10	Ordering requirements	12
11	Designation	12
Annex A (normative)	Special requirements for bolts, screws and nuts with thread sizes M8 and M10	14
Annex B (normative)	Limits of sizes for hot dip galvanized internal and external screw thread M8 ...	16
Annex C (informative)	Calculation of minimum ultimate tensile loads and proof loads for bolts and screws M8 and M10 with threads undersized to tolerance class 6az	18
Annex D (informative)	Surface areas of bolts, screws and nuts	19

Annex E (normative) Adherence of hot-dip galvanized coating	22
Annex F (informative) Strength of hot dip galvanized bolt or screw and nut assemblies	23