DIN EN 14399-3:2015-04 (E)

High-strength structural bolting assemblies for preloading - Part 3: System HR - Hexagon bolt and nut assemblies

Contents

Page

Foreword 3

Introduction 4

1 Scope 6

2 Normative references 6

3 Bolts 7
3.1 Dimensions of bolts 7
3.2 Specification for bolts and reference standard 11
3.3 Marking of bolts 11

4 Nuts 12
4.1 Dimensions of nuts 12
4.2 Specification for nuts and reference standards 14
4.3 Proof load values of nuts 15
4.4 Decarburization of the nut thread 15
4.5 Marking of nuts 15

5 Designation of the bolt/nut assemblies 16

6 Associated washers 16

7 Functional characteristics of the bolt/nut/washer(s) assembly 16
7.1 General 16
7.2 Maximum individual value of the bolt force during fitness for purpose test ($F_{bi,max}$) 17
7.3 Values of angle $\Delta\theta_1$ 17
7.4 Values of angle $\Delta\theta_2$ 17
7.5 Individual values of the k-factor (k_i), mean value of the k-factor (k_m) and coefficient of variation of the k-factor (V_k) 17
7.5.1 Individual values of the k-factor (k_i) for k-class K1 17
7.5.2 Mean value of the k-factor (k_m) and coefficient of variation of the k-factor (V_k) for k-class K2 18

Annex A (normative) Clamp lengths and grip lengths 19
A.1 Clamp lengths for bolting assemblies with one or two washers 19
A.2 Grip lengths for bolting assemblies with one or two washers 22

Bibliography 28