

DIN EN 14399-4:2015-04 (E)

High-strength structural bolting assemblies for preloading - Part 4: System HV - Hexagon bolt and nut assemblies

Contents		Page
Foreword		3
Introduction		4
1	Scope	6
2	Normative references	6
3	Bolts	7
3.1	Dimensions of bolts	7
3.2	Specifications for bolts and reference standards	10
3.3	Marking of bolts	10
4	Nuts	11
4.1	Dimensions of nuts	11
4.2	Specification for nuts and reference standards	13
4.3	Decarburization of the nut thread	13
4.4	Marking of nuts	13
5	Designation of the bolt/nut assemblies	14
6	Associated washers	14
7	Functional characteristics of the bolt/nut/washers assembly	14
7.1	General	14
7.2	Maximum individual value of the bolt force during fitness for purpose test ($F_{bi,max}$)	15
7.3	Values of angle 1	15
7.4	Values of angle 2	15
7.5	Individual values of the k-factor (k_i), mean value of the k-factor (k_m) and coefficient of variation of the k-factor (V_k)	16
7.5.1	Individual values of the k-factor (k_i) for k-class K1	16
7.5.2	Mean value of the k-factor (k_m) and coefficient of variation of the k-factor (V_k) for k-class K2	16
Annex A (normative)	Clamp lengths and Grip lengths	17
Bibliography		20