

DIN EN 14399-4:2015-04 (E)

High-strength structural bolting assemblies for preloading - Part 4: System HV - Hexagon bolt and nut assemblies

| Contents | | Page |
|----------------------------|--|-------------|
| Foreword | | 3 |
| Introduction | | 4 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Bolts | 7 |
| 3.1 | Dimensions of bolts | 7 |
| 3.2 | Specifications for bolts and reference standards | 10 |
| 3.3 | Marking of bolts | 10 |
| 4 | Nuts | 11 |
| 4.1 | Dimensions of nuts | 11 |
| 4.2 | Specification for nuts and reference standards | 13 |
| 4.3 | Decarburization of the nut thread | 13 |
| 4.4 | Marking of nuts | 13 |
| 5 | Designation of the bolt/nut assemblies | 14 |
| 6 | Associated washers | 14 |
| 7 | Functional characteristics of the bolt/nut/washers assembly | 14 |
| 7.1 | General | 14 |
| 7.2 | Maximum individual value of the bolt force during fitness for purpose test ($F_{bi,max}$) | 15 |
| 7.3 | Values of angle 1 | 15 |
| 7.4 | Values of angle 2 | 15 |
| 7.5 | Individual values of the k-factor (k_i), mean value of the k-factor (k_m) and coefficient of variation of the k-factor (V_k) | 16 |
| 7.5.1 | Individual values of the k-factor (k_i) for k-class K1 | 16 |
| 7.5.2 | Mean value of the k-factor (k_m) and coefficient of variation of the k-factor (V_k) for k-class K2 | 16 |
| Annex A (normative) | Clamp lengths and Grip lengths | 17 |
| Bibliography | | 20 |