DIN EN 14399-8:2019-06 (E)

High-strength structural bolting assemblies for preloading - Part 8: System HV - Hexagon fit bolt and nut assemblies

Contents

Page

European foreword 3

Introduction 4

1 Scope 6

2 Normative references 6

3 Fit bolts 7
3.1 Dimensions of fit bolts 7
3.2 Specifications for fit bolts and reference standards 10
3.3 Marking of fit bolts 11

4 Nuts 11
4.1 Dimensions of nuts 11
4.2 Specification for nuts and reference standards 13
4.3 Decarburization of the nut thread 13
4.4 Marking of nuts 13

5 Designation of the bolt/nut assemblies 14

6 Associated washers 14

7 Functional characteristics of the bolt/nut/washers assembly 14
7.1 General 14
7.2 Maximum individual value of the bolt force during fitness for purpose test (Fbi max) 15
7.3 Values of angle 1 15
7.4 Values of angle 2 15
7.5 Individual values of the k-factor (ki), mean value of the k-factor (km) and coefficient of variation of the k-factor (Vk) 15
7.5.1 Individual values of the k-factor (ki) for k-class K1 15
7.5.2 Mean value of the k-factor (km) and coefficient of variation of the k-factor (Vk) for k-class K2 16

Annex A (normative) Clamp lengths and grip lengths 17

Bibliography 20