

DIN EN 14399-9:2019-06 (E)

High-strength structural bolting assemblies for preloading - Part 9: System HR or HV - Direct tension indicators for bolt and nut assemblies

Contents		Page
European foreword		3
Introduction		5
1	Scope	7
2	Normative references	7
3	Direct tension indicators	8
3.1	General	8
3.2	Dimensions	8
3.3	Specifications and reference standards for direct tension indicators	10
3.4	Functional test of direct tension indicators	11
3.5	Test method for measuring compression loads (all finishes) on direct tension indicators	12
3.5.1	General	12
3.5.2	Testing apparatus	12
3.5.3	Support blocks	13
3.5.4	Bearing blocks	14
3.5.5	Calibration	14
3.5.6	Test procedure	14
3.6	Marking of the direct tension indicator	17
3.7	Designation of the direct tension indicator	17
4	Nut face washers (HN) and bolt face washers (HB)	17
4.1	Dimensions	17
4.2	Specifications and reference standards for nut face washers (HN) and bolt face washers (HB)	19
4.3	Marking	20
4.3.1	Nut face washers (HN)	20
4.3.2	Bolt face washers (HB)	20
4.4	Designation of nut face washers (HN) and bolt face washers (HB)	21
5	Functional characteristics	21
5.1	Bolting assemblies	21
5.2	Functional characteristics of direct tension indicators in the assembly	22
5.3	Functional characteristics of bolting assemblies with direct tension indicator	23
5.3.1	General	23
5.3.2	Suitability test procedures	23
Annex A (informative) Use of structural bolting assemblies for preloading with direct tension indicators		25
A.1	General	25
A.2	Bolting assembly configurations	25
A.3	Checking	26
Bibliography		29