

ISO 4042:2018 (E)

Fasteners — Electroplated coating systems

Contents

| | |
|-------|--|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | General characteristics of the coating |
| 4.1 | Coating metals or alloys and main purposes |
| 4.2 | Build-up of basic electroplated coating systems |
| 4.3 | Coating systems and coating processes |
| 4.4 | Internal hydrogen embrittlement |
| 4.4.1 | General |
| 4.4.2 | Fasteners with hardness below 360 HV |
| 4.4.3 | Fasteners with hardness equal to and above 360 HV and up to 390 HV |
| 4.4.4 | Fasteners with hardness above 390 HV |
| 4.4.5 | Fasteners in accordance with ISO 898-1, ISO 898-2 and ISO 898-3 |
| 4.4.6 | Baking and test requirements for case-hardened and tempered screws |
| 4.4.7 | Work-hardened fasteners |
| 4.4.8 | Fasteners with bainitic structure |
| 4.5 | Baking |
| 5 | Corrosion protection and testing |
| 5.1 | General |
| 5.2 | Neutral salt spray test (NSS) for zinc based coating systems |
| 5.3 | Sulfur dioxide test (Kesternich test) |
| 5.4 | Bulk handling, automatic processes such as feeding and/or sorting, storage and transport |
| 6 | Dimensional requirements and testing |
| 6.1 | General |
| 6.2 | Fasteners with ISO metric thread |
| 6.2.1 | Coating thickness |
| 6.2.2 | Gaugeability and assemblability |
| 6.3 | Other fasteners |
| 6.4 | Test methods for thickness determination |
| 7 | Mechanical and physical properties and testing |
| 7.1 | General |
| 7.2 | Appearance |
| 7.3 | Corrosion resistance related to temperature |
| 7.4 | Torque/clamp force relationship |
| 7.5 | Determination of hexavalent chromium |
| 8 | Applicability of tests |
| 8.1 | General |
| 8.2 | Tests mandatory for each lot |
| 8.3 | Tests for in-process control |
| 8.4 | Tests to be performed when specified by the purchaser |
| 9 | Designation system |

- 9.1 General
- 9.2 Designation of electroplated coating systems for the order
- 9.3 Examples of designation of hexavalent chromium free electroplated coating systems for fasteners
- 9.4 Designation of fasteners with electroplated coating systems for labelling
- 10 Ordering requirements for electroplating
- 11 Storage conditions

Annex A (informative) Design aspects and assembly of coated fasteners

- A.1 Design
 - A.1.1 General
 - A.1.2 Coating process
 - A.1.3 Sealants and top coats
 - A.1.4 Possible effects of coating corrosion on appearance
 - A.1.4.1 General
 - A.1.4.2 White haze
 - A.1.4.3 White corrosion
 - A.1.4.4 Black spots
- A.2 Functional properties
 - A.2.1 Assemblability and mountability
 - A.2.2 Other properties of coated fasteners and assemblies
 - A.2.2.1 Chemical resistance
 - A.2.2.2 Electrical conductivity
 - A.2.2.3 Galvanic corrosion
 - A.2.2.4 Cleanliness
- A.3 Particular issues related to fasteners and coating processes
 - A.3.1 General
 - A.3.2 Fasteners with ISO metric thread
 - A.3.3 Fasteners with captive washer
 - A.3.4 Washers and similar fasteners
 - A.3.5 Fasteners with adhesive or patch
 - A.3.6 Prevailing torque nuts
 - A.3.7 Fasteners with recess, internal drive, cavity or hole
 - A.3.8 Screws which form their own mating thread
 - A.3.9 Clips and retaining rings
- A.4 Storage of coated fasteners

Annex B (informative) Hydrogen embrittlement consideration

- B.1 General
- B.2 Conditions for hydrogen embrittlement failure
- B.3 Electroplating and Internal Hydrogen Embrittlement (IHE)
- B.4 Baking
- B.5 Stress relief
- B.6 Hydrogen embrittlement test methods

Annex C (informative) Corrosion protection related to zinc coatings with chromate conversion coatings

Annex D (informative) Coating thickness and thread clearance for ISO metric screw threads

- D.1 General
- D.2 Geometrical relationship between coating thickness and pitch diameter
- D.3 Coating thickness on externally threaded fasteners
- D.4 Coating thickness on internal threads
- D.5 Clearance for coating thickness
 - D.5.1 Fasteners with external thread
 - D.5.2 Fasteners with internal thread
- D.6 Compatibility between corrosion resistance and clearance

Annex E (informative) Coating systems tested in accordance with ISO 9227, NSS — Evaluation of cabinet corrosivity for the neutral salt spray test

- E.1 Introduction
- E.2 Purpose
- E.3 Frequency of controls

- E.4 Operating conditions
 - E.4.1 Parameters
 - E.4.2 Reference panels
 - E.4.3 Preparation of the reference panels
 - E.4.3.1 Degreasing procedure
 - E.4.3.2 Panel protection
 - E.4.3.3 Position of reference panels and collectors
 - E.4.3.4 Filling of the cabinet
 - E.4.4 Control mask
 - E.4.5 Determination of the corroded surface
 - E.4.6 Quantification of corrosivity
- E.5 Corrosivity results
- E.6 Example of report format for annual control and monthly monitoring of the cabinet
 - E.6.1 Annual control and monthly monitoring of the cabinet corrosivity level
 - E.6.2 Condensate check
 - E.6.3 Determination of the corrosivity level
 - E.6.4 Conclusion for the corrosivity of the cabinet
 - E.6.5 Example for the determination of the corrosivity level

Annex F (informative) Obsolete designation codes for electroplated coating systems on fasteners according to ISO 4042:1999

- F.1 Obsolete code system
- F.2 Example of obsolete designation

Page count: 55