

# ISO 7240-27:2009-04 (E)

Fire detection and alarm systems - Part 27: Point-type fire detectors using a scattered-light, transmitted-light or ionization smoke sensor, an electrochemical-cell carbon-monoxide sensor and a heat sensor

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vii
1	Scope .....	1
2	Normative references .....	1
3	Definitions .....	2
4	General requirements .....	2
4.1	Compliance .....	2
4.2	Individual alarm indication .....	2
4.3	Connection of ancillary devices .....	3
4.4	Monitoring of detachable detectors .....	3
4.5	Manufacturer's adjustments .....	3
4.6	On-site adjustment of response behaviour .....	3
4.7	Protection against the ingress of foreign bodies .....	3
4.8	Rate-sensitive CO response behaviour .....	3
4.9	Smoke response to slowly developing fires .....	4
4.10	Marking .....	4
4.11	Data .....	5
4.12	Requirements for software controlled detectors .....	5
5	Tests .....	6
5.1	General .....	6
5.2	Repeatability of smoke response .....	11
5.3	Repeatability of CO response .....	11
5.4	Directional dependence of smoke response .....	11
5.5	Directional dependence of CO response .....	12
5.6	Directional dependence of heat response (optional function) .....	12
5.7	Lower limit of heat response (optional function) .....	13
5.8	Reproducibility of smoke response .....	13
5.9	Reproducibility of CO response .....	14
5.10	Reproducibility of heat response (optional function) .....	14
5.11	Exposure to chemical agents at environmental concentrations .....	15
5.12	Long-term stability of CO response .....	16
5.13	Saturation .....	16
5.14	Exposure to chemical agents associated with a fire .....	17
5.15	Variation in supply parameters .....	18
5.16	Air movement .....	19
5.17	Dazzling .....	20
5.18	Dry heat (operational) .....	20
5.19	Cold (operational), smoke .....	21
5.20	Cold (operational), CO .....	23
5.21	Damp heat cyclic (operational) .....	24
5.22	Damp heat, steady state (endurance) .....	25
5.23	Low humidity, steady state (endurance) .....	26
5.24	Sulfur dioxide SO <sub>2</sub> corrosion (endurance) .....	27

5.25	Shock (operational) .....	28
5.26	Impact (operational) .....	29
5.27	Vibration, sinusoidal (operational) .....	30
5.28	Vibration, sinusoidal (endurance) .....	32
5.29	Electromagnetic compatibility (EMC) immunity tests (operational) .....	33
5.30	Fire sensitivity .....	34
6	Test report .....	36
Annex A (normative) Gas test chamber for response threshold value and cross sensitivity measurements .....		37
Annex B (informative) Construction of the heat tunnel .....		38
Annex C (normative) Apparatus for impact test .....		41
Annex D (normative) Fire test room .....		43
Annex E (normative) Smouldering (pyrolysis) wood fire (TF2) .....		45
Annex F (normative) Glowing, smouldering cotton fire (TF3) .....		48
Annex G (normative) Open plastics (polyurethane) fire (TF4) .....		51
Annex H (normative) Liquid (heptane) fire (TF5) .....		53
Annex I (normative) Low-temperature, black-smoke (decalin) liquid fire (TF8) .....		55
Annex J (informative) Information concerning the construction of the gas test chamber .....		57